


TA7
W34
No. M-70-4
Comp. 2




1

TECHNICAL REPORT M-70-4 ✓

RELATIVE OFF-ROAD MOBILITY PERFORMANCE OF SIX WHEELED AND FOUR TRACKED VEHICLES IN SELECTED TERRAIN

by

J. K. Stoll, D. D. Randolph, A. A. Rula



March 1970

Sponsored by U. S. Army Materiel Command

Conducted by U. S. Army Engineer Waterways Experiment Station, Vicksburg, Mississippi

DISTRIBUTION STATEMENT A

Approved for public release;
Distribution Unlimited

Statement A per ch/MESL, WES 11/15/71

DDC
JUN 8 1971
RESERVED
D

Destroy this report when it is no longer needed.
Do not return it to the originator.

The findings in this report are not to be construed as an official
Department of the Army position unless so designated
by other authorized documents.

AD-A040125



TECHNICAL REPORT M-70-4 ✓

RELATIVE OFF-ROAD MOBILITY PERFORMANCE OF SIX WHEELED AND
FOUR TRACKED VEHICLES IN SELECTED TERRAIN

by

J. K. Stoll
D. D. Randolph
A. A. Rula

D R A F T

| | |
|------------------------------|---|
| STANDARD FORM 104 | |
| DTIC | DTIC Status <input checked="" type="checkbox"/> |
| DDC | DDC Status <input type="checkbox"/> |
| CLASSIFIED | <input type="checkbox"/> |
| JUSTIFICATION | |
| EXEMPTION/AVAILABILITY CODES | |
| MAIL, RUC, OR SPECIAL | |
| A | |



March 1970

DDC
RECEIVED
JUN 6 1971
D

Sponsored by U. S. Army Materiel Command

Conducted by U. S. Army Engineer Waterways Experiment Station, Vicksburg, Mississippi ✓

ARMY-MRC VICKSBURG, MISS.

This document
is for
prior approval

DISTRIBUTION STATEMENT A

Approved for public release;
Distribution Unlimited

ch transmittal
only with
ent Station.

11/15/71

Statement A for ch/MES, WES

FOREWORD

This report is a consolidation of three draft reports submitted in 1967 and 1968 to the U. S. Army Tank-Automotive Command in connection with a cost-effectiveness study authorized by the U. S. Army Materiel Command. The study herein was performed at the U. S. Army Engineer Waterways Experiment Station (WES) in April-May 1967, September-October 1967, and May-June 1968 by personnel of the Obstacle-Vehicle Studies Section, Mobility and Environmental Division. General supervision was provided by Messrs. W. J. Turnbull, W. G. Shockley, A. A. Rula, and J. K. Stoll. The report was prepared by Messrs. Stoll, Rula, and D. D. Randolph.

Acknowledgment is made for vehicle data provided by the U. S. Army Tank-Automotive Command; Office, Chief of Engineers; U. S. Army Ordnance Corps; Military Research and Development Center, Thailand; Pacific Car and Foundry; and Aberdeen Proving Ground.

COL John R. Oswalt, Jr., CE, and COL Levi A. Brown, CE, were Directors of WES during the conduct of this study and preparation of this report. Mr. J. B. Tiffany and Mr. F. R. Brown were Technical Directors.

CONTENTS

| | <u>Page</u> |
|--|-------------|
| FOREWORD | iii |
| CONVERSION FACTORS, BRITISH TO METRIC UNITS OF MEASUREMENT | vii |
| SUMMARY. | ix |
| PART I: INTRODUCTION | 1 |
| Background | 1 |
| Purpose | 2 |
| Scope | 2 |
| Definitions | 3 |
| PART II: TERRAIN AND PERFORMANCE EVALUATION DATA USED IN THE STUDY | 6 |
| The Computer Program | 6 |
| Terrain Data | 6 |
| Performance Evaluation Data | 19 |
| PART III: EVALUATION OF VEHICLES | 45 |
| Selection of Traverses and Preparation of Speed Maps | 45 |
| Performance in Various Terrain Types | 46 |
| Speed Performance | 47 |
| Fuel Consumption | 62 |
| Cargo Delivery Rate | 63 |
| Summary of Vehicle Evaluations | 63 |
| PART IV: CONCLUSIONS AND RECOMMENDATIONS | 65 |
| Conclusions | 65 |
| Recommendations | 65 |
| LITERATURE CITED | 66 |
| TABLES 1-4 | |
| PLATES 1-19 | |
| APPENDIX A: WES ANALYTICAL MODEL FOR PREDICTING OFF-ROAD GROUND VEHICLE PERFORMANCE | A1 |
| TABLES A1 and A2 | |
| APPENDIX B: EVALUATION OF DYNAMIC RESPONSE OF M706 | B1 |
| APPENDIX C: EFFECT OF SOIL STRENGTH ON VEHICLE PERFORMANCE. . . | C1 |
| TABLE C1 | |

CONVERSION FACTORS, BRITISH TO METRIC UNITS OF MEASUREMENT

British units of measurement used in this report can be converted to metric units as follows:

| <u>Multiply</u> | <u>By</u> | <u>To Obtain</u> |
|------------------------|------------|---------------------------------|
| inches | 2.54 | centimeters |
| square inches | 6.4516 | square centimeters |
| feet | 0.3048 | meters |
| cubic feet | 0.0283168 | cubic meters |
| pounds | 0.45359237 | kilograms |
| pounds per square inch | 0.070307 | kilograms per square centimeter |
| pounds per cubic foot | 16.0185 | kilograms per cubic meter |
| tons | 907.185 | kilograms |
| miles | 1.609344 | kilometers |
| miles per hour | 1.609344 | kilometers per hour |
| square miles | 2.58999 | square kilometers |

SUMMARY

The U. S. Army Engineer Waterways Experiment Station analytical model for predicting off-road ground mobility was used to evaluate the performance of six wheeled vehicles (M656, M54A2, M520, M37B1, M561, and M706) and four tracked vehicles (M548, M113A1, M116, and M571) over a selected traverse in Thailand. Maps were prepared to exhibit the terrain in terms of surface composition (soil consistency), surface geometry (slopes, rice-field dikes, etc.), vegetation, and hydrologic geometry (rivers and streams). The performance of each vehicle was evaluated in terms of average speed over the traverse and the center line, average fuel consumed over the traverse, and center-line cargo delivery rate.

The vehicles were "run" over the traverse under dry-season conditions (60 or 40 rating cone index) and wet-season conditions (60 or 35 rating cone index). Four of the vehicles (M656, M54A2, M520, and M548) were tested also under wet-season conditions of 60 or 40 rating cone index. Wet-season conditions usually reduced vehicle performance. However, soil strength was not as significant as other terrain factors in evaluating the vehicles over the selected traverse because the soil strengths used were higher than the vehicle cone indexes of all the vehicles; so no vehicles were immobilized because of soft soils.

No one vehicle provided optimum mobility for all the terrain conditions encountered on the traverse over which predictions were made. Further, neither wheels nor tracks appeared to consistently give better performance. The M113A1 had the highest average traverse and center-line speeds in the dry season, and the M571 had the highest speeds in the wet. The M54A2 had the lowest traverse and center-line speeds in both seasons. The M571 consumed less fuel on the average in the dry season, and the M561 and M571 consumed the least in the wet. The M548 consumed the most in the dry season and the 60 or 40 rating cone index wet season; the M520 the most in the 60 or 35 rating cone index wet season. The M520 had the highest delivery rate in both seasons and the M37B1 the lowest.

A recommendation was made that the mission environment for any new vehicle be defined in quantitative terms before the new vehicle is developed.

Appendix A describes the WES analytical model in an abbreviated form; Appendix B, the evaluation of the dynamic response of the M706; and Appendix C, some additional general analyses of the effects of soil strength on vehicle performance.

RELATIVE OFF-ROAD MOBILITY PERFORMANCE OF
SIX WHEELED AND FOUR TRACKED VEHICLES
IN SELECTED TERRAIN

PART I: INTRODUCTION

Background

1. In November 1966, responsibility was delegated by the U. S. Army Materiel Command (AMC) to the U. S. Army Tank-Automotive Command (TACOM) to conduct a cost-effectiveness study for the Department of the Army (DA), in which the performance of the new M656 truck was to be compared with the performance of selected standard vehicles. Following a limited 17-day study by TACOM, in which a terrain model was used, DA requested further investigation and suggested the use of the more sophisticated Waterways Experiment Station (WES) analytical model for predicting off-road ground mobility performance.

2. In April 1967, the WES undertook the requested study and reported its findings to TACOM in May 1967 in a draft report entitled "Relative Off-Road Mobility Performance of the M656, M54A2, M520, and M548 in Selected Terrain." This WES report was made a part of the TACOM final report entitled "Cost/Performance Analysis of the M656, M520, M54A2, and M548 Vehicles."

3. In September 1967, the Materiel Studies Review Committee met at AMC to review the TACOM final report. As a result of that review, the WES was asked to perform an analysis of the effects of wet-season conditions on vehicle performance. The results of that analysis were submitted to TACOM in October 1967 in a supplement to the first WES report. The supplement was titled "Relative Off-Road Mobility Performance of the M656, M54A2, M520, and M548 in Selected Terrain; Supplement No. 1, Evaluation of Vehicles in the Wet Season."

4. The study by WES was later extended to cover an additional group of vehicles, and a draft report was submitted to TACOM in June 1968. That report was titled "Relative Off-Road Mobility Performance of the M113A1, M571, M116, M561, M706, and M37B1 in a Selected Terrain."

5. The same analytical model, the same terrain, and basically the same evaluation procedures were used throughout the WES investigations. This report, then, is a consolidation of the information contained in the three draft reports submitted to TACOM and named in the preceding paragraphs.

Purpose

6. The purpose of this study was to evaluate by use of the WES analytical model the relative off-road mobility performances over a selected route of 10 vehicles, 6 wheeled and 4 tracked, in terms of average speed (mph),* fuel consumption (gal/miles), and cargo delivery rate (ton-miles/hr).

Scope

7. The scope of the study was governed by the AMC work directive, availability of terrain and vehicle data in a form amenable to computer usage, restrictions imposed by time deadlines, and limitations of the analytical model. The model is described in detail in a report now in preparation¹ and in an abbreviated form in Appendix A. Specific conditions pertaining to the study are discussed in the following paragraphs.

Terrain data

8. The performances of the vehicles were analyzed over one strip of Thailand terrain for which data were already compiled² and ready for immediate input to the WES computer. The analyses included the effects of soil strength, vegetation, surface geometry, and hydrologic geometry on vehicle performance. The effects of vegetation in obscuring driver vision and subsequent effect on vehicle speed were not evaluated.

9. Average soil strength values for the dry season and the wet (high-moisture condition) season were used.

Vehicle data

10. The following vehicles were included in the study:

* A table of factors for converting British units of measurement to metric units is presented on page vii.

Wheeled

M656, truck, cargo, 5-ton, 8x8
M54A2, truck, cargo, 5-ton, 6x6
M520, truck, cargo, 8-ton, 4x4 (GOER)
M37B1, truck, cargo, 3/4-ton, 4x4
M561, truck, cargo, 1-1/2-ton, 6x6
M706, car, armored, light, 4x4

Tracked

M548, carrier, cargo, 6-ton
M113A1, carrier, personnel, full-tracked, armored
M116, carrier, cargo, amphibious, 1-1/2-ton
M571, carrier, utility, articulated, full-tracked, 1-ton

11. The evaluation considered the use of winches, where needed, for all vehicles except the M113A1, which was assumed to be equipped with capstans and anchors of the type being used for self-recovery of this vehicle in South Vietnam. Pitch articulation of the M561 and yaw and pitch articulation of the M571 were considered in their evaluations. The wheeled vehicles were evaluated at a selected tire deflection of 25 percent. Since no test data were available pertinent to the ability of the M706 to cross vertical obstacles, the use of vehicle dynamics modeling techniques was necessary in computing the performance limits of this vehicle.

12. The effects of special vehicle characteristics such as duck walking and positive traction were not included in the study because appropriate quantitative relations were not available. Qualitative statements, however, are included to explain advantages to be gained from these characteristics.

13. Comparative performance values were obtained from selected traverses of straight-line segments of terrain that permitted each vehicle to travel at its highest rate of speed. An upper-limit speed of 40 mph was imposed on all vehicles.

Definitions

14. Certain special terms used in this study are defined as follows:

Soil terms

Cone index (CI). An index of the shearing resistance of soil obtained with a cone penetrometer.

Remolding index (RI). A ratio that expresses the change of strength that may occur under the traffic of a vehicle.

Rating cone index (RCI). The product of the measured cone index and the remolding index for the same layer of soil.

Terrain terms

Terrain factor. A specific attribute of the terrain that can be adequately described by a single quantitative description, e.g. slope.

Terrain factor value. A quantity defining a specific point on the scale of all possible values of a terrain factor, e. g. a 5-degree slope

Terrain factor class. A category within the total range of values exhibited by a terrain factor, defined in terms of a specific range of factor values, e. g. slope class 1, 0 to 1.5 degrees.

Terrain factor family. A group of related terrain factors that either alone or in concert tend to produce a characteristic effect on vehicle performance, e. g. slope, obstacle spacing, terrain approach angle, and step height.

Areal terrain factor complex. An areal unit throughout which a specific assemblage of factor classes occurs.

Linear terrain factor complex. An elongated unit throughout which a specific assemblage of factor classes occurs.

Surface geometry. The three-dimensional configuration of the surface on which ground-contact vehicles operate.

Macrogeometry feature. A smooth, sloping surface whose area is greater than the contact surface of the vehicle operating thereon.

Microgeometry feature. A surface whose area is less than the contact surface of the vehicle operating thereon.

Vehicle contact surface. The surface generated by a plane passing through the points of contact between the vehicle and the surface on which it is resting.

Terrain approach angle. The acute angle formed by the intersection of two ground surface planes (see sketch, page 5).

Hydrologic features. Streams, lakes, and other water bodies with water depths greater than 3 ft.

Vehicle-soil system terms

Tractive force (T_f). The total thrust developed by the vehicle's traction elements in propelling a vehicle on a level, smooth surface.


Propelling force (P_f). The sum of all forces acting to propel the vehicle.

Motion resistance. The force required to tow a vehicle under given conditions.

Maximum drawbar pull. The largest sustained towing force produced by a self-propelled vehicle at its drawbar under given conditions.

Slip. The percentage of wheel or track movement ineffective in thrusting a vehicle forward.

Vehicle approach angle. The acute angle formed by a line drawn tangent to the vehicle traction components and a line tangent to the leading edge of the vehicle and the leading edge of the front traction component (see sketch below).



Vehicle departure angle. The acute angle formed by a line drawn tangent to the vehicle traction components and a line tangent to the trailing edge of the vehicle and the trailing edge of the traction component (see sketch above).

Vehicle cone index (VCI). The minimum rating cone index (RCI) that will permit a vehicle to complete a specified number of passes; thus, VCI_{50} means the minimum RCI necessary to complete 50 passes, and VCI_1 means the minimum RCI necessary to complete one pass.

Mobility index (MI). A dimensionless number that results from a consideration of certain vehicle characteristics.

PART II: TERRAIN AND PERFORMANCE EVALUATION DATA
USED IN THE STUDY

The Computer Program

Early phases of the study

15. In general, the procedures discussed in Appendix A of this report were followed in predicting cross-country performance of the four vehicles evaluated in the early phases of the study; however, some exceptions were necessary because certain data were lacking.

16. A computer was used to make the computations and approximations necessary to predict the average tractive force requirement, average speed, and fuel consumption for each vehicle in each areal terrain unit. The computer program consisted of 11 overlays stored on magnetic tape; they are called and executed as required to produce the desired output for a given set of terrain and vehicle data. Data from one overlay needed to perform the computations on the next are retained in memory storage for all 11 overlays. Total size of the program is approximately 35,000 words. At the time of the early phases of the study, the computer program did not include overlays for predicting vehicle performance in hydrologic geometry features or in rice fields. Neither were overlays available for predicting performance as related to the effects of vegetation obscuration on the driver's vision or obstacle-vehicle geometry interference and maximum tractive force required in crossing microgeometry features. The effects of these elements on vehicle performance were determined graphically or mathematically and integrated with the results of the computer program.

Later phases

17. Computer programs were prepared to predict vehicle performance in rice fields and to estimate fuel consumption. These programs were used in conjunction with the basic program used in the early phases of the study.

Terrain Data

18. Because time for this study was limited, an area around Khon Kaen,

Thailand (fig. 1), for which terrain data were immediately available, was selected for the vehicle evaluations. The specific route is designated as Route 1 in plate 1. (Instructions for preparing a map of this type are given in WES Technical Report No. 3-726³.) The route was a strip approximately 40 miles long and 1 mile wide. Aerial views of segments, at a scale of 1:15,000, are shown in figs. 2-7; the locations shown in these photographs are identified in plate 2.

19. The area in which Route 1 is located is classified as tropical savanna and has a very pronounced seasonal distribution of rainfall. The rainy season coincides with the southwest monsoon which occurs between May and October and accounts for about 85 percent of the yearly rainfall. The typhoons of the South China seas that pass over the area normally combine with the southwest monsoon in producing torrential rains. The long-term yearly average rainfall is 42.1 in. The humidity is highest during the rainy season; the yearly average is about 71.1 percent. The yearly average temperature is approximately 26.5 C., with April the warmest month (30 C.).

Physiography and soils

20. The geomorphologic features of Route 1 are determined mainly by the tremendous alluvial deposits of the Mekong River and its tributaries. Several well-separated phases of sedimentation and their associated cycles of erosion can be recognized throughout this complex system, such as alluvial plains, low terraces, middle terraces, and high terraces.

21. The main features of the alluvial plains are the rather prominent natural levees and basins or backswamps. Sediments are mainly clayey, but lighter-textured materials are found on the levees. Narrow valleys of creeks and drainageways have no natural levees, and the recent alluvial sediments are mostly lighter in texture and are usually similar to the sandy materials widespread in the adjacent areas. The low terraces are relatively higher than the alluvial plains. In slightly higher parts, the low terraces are composed mainly of medium- to light-textured sediments; in the lower parts, medium- to heavy-textured deposits dominate the surface layers.

22. The middle terrace formations are of undulating to rolling relief with diverse formations that differ from those of the low terraces




Fig. 2. Aerial photograph of segment of Route 1;
Position on route is shown in plate 2, area 1.



Fig. 3. Aerial photograph of segment of Route 1;
Position on route is shown in plate 2, area 2




Fig. 4. Aerial photograph of segment of Route 1;
Position on route is shown in plate 2, area 3.



Fig. 5. Aerial photograph of segment of Route 1;
Position on route is shown in plate 2, area 4.



Fig. 6. Aerial photograph of segment of Route 1;
Position on route is shown in plate 2, area 5.




Fig. 7. Aerial Photograph of Segment of Route 1;
Position on route is shown in plate 2, area 6.

and the alluvial plains. They show two distinctly different kinds of sediments in the geological succession, clayey lower strata and sandy upper ones. Only small areas of high terrace formations occur. Erosion through the years has left small islands higher than and surrounded by the younger terrace formations, one of which is along the route near Kho. Kaen. The material of the islands is generally red sandy clay.

Vegetation and land use

23. The natural vegetation in the areas included in Route 1 is classified as dry monsoon forest, consisting of trees, shrubs, bamboo, and grasses. Weeds are widespread throughout the area except in very dry, sandy parts. In the plains and on terrace formations, trees in forest stands are generally small and sparse; however, isolated areas of large trees closely spaced may be found. In low spots, marshy vegetation is normally found. Shifting cultivation is common in the area. Kenaf, a plant cultivated for its fiber, is grown everywhere except in the lower land, which is used mainly for rice cultivation. The areas in and around villages are normally used for garden crops.

Hydrologic features

24. The main rivers in the area of Route 1 contain water the year around. River valleys are broad, with a relatively high ground water level. Gradients of the rivers are extremely low, and extensive flooding occurs in the lowlands in the rainy season. Many creeks are intermittent.

Terrain types

25. Ground-level views of several terrain types are shown in figs. 8-11. Terrain-factor maps for the area in which the route was selected had been prepared for another study.² The area mapped was approximately 40 miles long and 11 miles wide. Mapping classes were established from 80 soil consistency samples, 300 surface geometry samples, 76 vegetation samples, and 133 hydrologic geometry samples. Wet-season conditions produced a difference in two terrain factors--soil strength and stream stages; thus both "areal" and "linear" terrain-type maps prepared for the dry season (plates 1 and 2) were revised to reflect seasonal differences (plates 3 and 4). None of the areal terrain types appearing on the dry-season map (plate 1) was entirely eliminated by the revisions made for the wet-season condition (plate 3).




Fig. 8. Ground-level view of terrain
types 10 and 15



Fig. 9. Ground-level view of terrain
type 18



Fig. 10. Ground-level view of terrain type 13



Fig. 11. Ground-level view of hydrologic geometry
type 27/3 (water depth > 3 ft)

26. Areal terrain types. The surface composition maps used in this study contained four mapping classes of soil strength in terms of rating cone index (RCI): 10-25, 25-60, 60-100, and greater than 100. The 10-25 class did not occur in the areas mapped in the wet season nor the dry season. Also, since an RCI of 60 or greater did not significantly affect vehicle performance, classes 60-100 and greater than 100 were grouped as one class, i.e. greater than 60 RCI. Thus the two soil strength classes involved in the study were 25-60 and greater than 60 RCI. The total area of terrain types with RCI's in the 25-60 range increased in the wet season, and the area of terrain types with RCI's greater than 60 decreased correspondingly. The location and extent of these changes are indicated in plate 5. When the surface composition factor map portraying soil strength in the wet season was overlaid on the surface geometry and vegetation factor maps, 11 new terrain types were created. These new types are identified in plate 3 by a number and the letter "A."

27. For both dry-season and wet-season conditions, an RCI of 40, the approximate midpoint of the RCI soil strength class 25-60, and an RCI of 60 for the second class were used in the analysis. Since the vehicle cone indexes (VCI's) of all the vehicles were less than 40 (see table 1), none of the vehicles was expected to be immobilized because of soil strength. (Actually, even when wet-season soil strengths were considered in combination with slope and vegetation, there were no impassable areal terrain types.)

28. Because the terrain selected was situated on a regional topographic high (Korat Plateau), wet-season conditions were assumed to cause only moderate changes in soil strength, not great enough to change the relative ranking of the vehicles. However, since there was greater uncertainty as to what the net effects of vehicle performance would be for these still lower soil strengths, the soil strength was reduced to 35 RCI in all terrain types having a 40 RCI in the wet season, and another analysis was performed. The value of 35 RCI was selected because it was within the 25-60 class range and above the minimum soil strength requirements to permit one pass of all the vehicles. This second analysis (35 RCI) is applicable to slightly wetter-than-average soil conditions in the wet season. The location and extent of all terrain types with a wet-season soil strength of 40 RCI (first

analysis) and 35 RCI (second analysis) are indicated in plate 6 as shaded area.

29. Linear terrain types. The most pronounced effect of wet-season conditions was manifested in the time penalties imposed for stream crossings included in the optimum route selected. At 17 locations, the wet-season water depth increased from less than 3.0 ft to greater than 3.0 ft. As noted in plate 4, streams with water depths of less than 3.0 ft are analyzed as surface geometry features rather than as hydrologic geometry features. Some bank configurations that were negotiable when a vehicle was fording the streams became more critical when the vehicle was in the swimming mode. In other cases, however, the reverse situation was true, since maximum slopes that occurred on the lower portions of the banks were avoided as the amphibious swimming vehicles contacted the banks at higher elevations.


30. New routes were selected for the wet-season evaluations in an attempt to reduce the number of streams to be crossed, and thus to avoid as many immobilizations as possible. In certain cases, however, more streams were crossed, but the time lost was reduced; in other cases, the vehicles had to be rerouted completely, even to crossing a bridge some distance away.

Performance Evaluation Data


31. The vehicle characteristics and performance data for the wheeled and tracked vehicles used in this study are summarized in tables 1 and 2, respectively; figs. 12 and 13 are photographs of the wheeled and tracked vehicles, respectively.

Maximum performance on paved, level surface

32. Relations of tractive force versus speed on a paved level surface for all the vehicles of interest (fig. 14) were derived from data published by the Development and Proof Services (DPS), Aberdeen Proving Ground, Maryland^{4,5}. The curves in fig. 14 were terminated at 40 mph, which was the upper-limit speed imposed for cross-country travel in this study.



a. XM656 Truck, Cargo, 5 Ton, 8x8 (GPV)



b. M54A2 Truck, Cargo, 5 Ton, 6x6

Fig. 12. Wheeled vehicles used in study (1 of 3 sheets)



c. M520, Truck, Cargo, 8 Ton, 4x4 (GOER)




d. M37B1, Truck, Cargo, 3/4 Ton, 4x4

Fig. 12 (2 of 3 sheets)




e. M561, Truck, Cargo, 1-1/2 Ton, 6x6




f. M706, Car, Armored, Light, 4x4

Fig. 12 (3 of 3 sheets)




a. XM548, Carrier, Cargo, 5 Ton, Tracked



b. M113A1, Carrier, Personnel, Full-Tracked, Armored

Fig. 13. Tracked vehicles used in study (1 of 2 sheets)




c. M116 Carrier, Cargo, Amphibious




d. M571, Carrier, Utility, Articulated, Full-Track


Fig. 13 (2 of 2 sheets)




a. XM561, M37, XM706



b. XM520, M54A2, XM656



c. XM571, M116



d. XM548, M113A1

Fig. 14. Maximum tractive force versus speed on level pavement

Effects of soil consistency on speed

33. Data reported by DPS for the drawbar pull-speed relations on a paved surface were accounted for in computing tractive force-speed relations for 60, 40, and 35 RCI soil strength values. Computer programs were used to compute tractive force-speed curves and motion resistance for all vehicles and soil strengths. Input consisted of data derived from the tractive force-speed curves for pavement (fig. 14), and drawbar pull-soil strength curves (fig. 15), motion resistance-soil strength curves (fig. 16) and tractive force-slip curves for the specific soil strengths used in this study. The drawbar pull-RCI relation for the M548 was established by using field test data for the M113 and adjusting for the difference in the weights of the two vehicles.

34. Since tractive force-slip relations were not available for the vehicles and soil strengths considered in this analysis, the following assumptions were made:

- a. The maximum tractive force the vehicles could develop in soil occurred at 20% slip.
- b. The percentage of slip decreased with traction in a linear manner from 20% at the maximum tractive-force value to 0% at the tractive-force value required to overcome motion resistance.

Effects of surface geometry on performance

35. Except for several special conditions discussed below, the procedures described in table 1, Appendix A, were used to obtain input data for determining the effects of surface geometry on vehicle performance. For example, the relations of percentage of area denied versus speed for all the vehicles in the study are presented in fig. 17.

36. Macrogeometry. Slope class ranges shown on the terrain map (plate 1) were assumed to occur in equal proportions positive and negative to the direction of vehicle travel. If the net tractive force ($T_f - R_g$) acting up the slope is greater than the force of the vehicle acting down the slope ($W \sin \theta$), the vehicle could operate up the slope unassisted. If it could not operate up the slope, a driver probably could




Fig. 15. Drawbar-pull and slope-climbing performance curve for tracked vehicles in fine-grained soils




Fig. 16. Motion resistance performance curve for tracked vehicles in fine-grained soils






Fig. 17. Area denied-speed relations

not control the vehicle if it went down the same slope; thus, an assumption was made that the vehicle should not travel on such slopes unassisted regardless of the direction of travel with respect to the slope. If slopes too steep for the vehicle to negotiate unassisted existed in the terrain segment, the vehicle was routed around the entire segment, if possible; if it could not be routed around, a time penalty was imposed equal to the estimated time required for the vehicle to winch itself up or down the slope. Since the direction of a slope was assumed always in the direction of travel, performance on side slopes (parallel to slopes) was not considered. To predict performance in terms of actual slope position would be possible by using a contour map overlay for the terrain map. This refinement in the evaluation procedure is essential for tactical purposes; but is beyond the capability of the present model.


37. Microgeometry. The roughness of the terrain and its effect on the vehicle driver must be assessed if the effects of microgeometry on performance are to be determined. Curves were established relating the speeds at which the various vehicles could cross obstacles of various heights without exceeding a vertical acceleration of 2.5 g's at the driver's seat (considered to be the maximum tolerable). Data from tests at WES or DPS were used to develop such relations (fig. 18) for all the vehicles. The relations determined at WES for a 5-ton XM520 were adjusted for the 8-ton M520; those from WES tests with an M113 were adjusted for the M548. Only limited test data were available for the tracked vehicles as a group, and to distinguish any significant differences in their performance from these data was impossible. Therefore, the same performance curve was used for all the tracked vehicles.

38. The dynamic-response model developed by FMC Corporation⁶, which considers three degrees of freedom (pitch, roll, and bounce), was modified by WES to incorporate a representation of tire compliance⁷ and was used to determine an obstacle height-speed relation for the M706. The vehicle characteristics and development of the dynamic model of the M706 are given in Appendix B. In the application of the FMC model, the terrain was described in terms of x-y coordinates.


39. The M706 was "run" at selected speeds over single, trapezoidal,



a. Wheeled Vehicles



b. Wheeled Vehicles




c. Tracked Vehicles

Fig. 18. Vehicle performance as limited by driver's response to vertical acceleration

obstacle cross sections of varying heights. The dimensions assigned to the cross section were (a) 45 deg for approach and departure angles, representing the approximate midpoint of the mapping class range 30-55 deg; (b) a 12-in. crest width, based on field observations and measurements made in Thailand; and (c) a single height within the range of 4 to 20 in. Only one obstacle was traversed during a run, and the selected speed was held constant. The obstacle was assumed to be rigid and fixed on a smooth, level, firm surface. The impact forces transmitted through the tire⁷ and suspension system⁶ were used to compute vertical displacements at the body center of gravity (C.G.). These displacements were corrected by both translation and rotation through pitch and roll to show actual displacements at the driver's seat. Vertical acceleration at the driver's seat was predicted by taking the second derivative of vertical displacement with respect to time. These data were used to establish a basic relation between vertical acceleration at the driver's seat and speed for each obstacle height. From these basic curves, the relation of obstacle height and speed for 2.5-g acceleration at the driver's seat was derived for the M706, and is shown in fig. 18.

40. In the early phases of this study, the following special procedures were used to predict vehicle performance in rice fields with dikes 10-18 in. or 18-30 in. high. Maximum speed versus obstacle step height was plotted, and the resulting curves were used to determine the maximum speed at which each vehicle could negotiate dikes (fig. 19). An illustrative example of the way in which average speed in rice fields was determined for each vehicle is given for an arbitrarily chosen dike spacing in fig. 20. The vehicle was assumed to travel a distance equal to the base width of the dike (assumed to be 4.0 ft in all cases) plus the wheelbase of the vehicle, at the maximum speed indicated by the limiting dynamic response of the vehicle. Beyond this distance, the vehicle was assumed to accelerate in accordance with the curve derived from a plot of tractive force versus speed in a soil of similar consistency and motion resistance. The period of acceleration is from 15 to 135 ft on the performance curve in fig. 20. The driver stopped accelerating the vehicle at 35 ft and the vehicle was assumed to travel at the maximum speed during the reaction time wherein he anticipated crossing the next dike. The driver reaction time of 0.5 sec was set arbitrarily;



NOTE: M113 curve (established from WES test data) substituted for M548.

M520 curve established from testing XM520 (WES).

M656 and M54 curve established from Aberdeen Proving Ground data. Vehicle maximum speed for crossing 12-in. bump given.

Fig. 19. Relation between obstacle step height and speed which is controlled by driver tolerance (approximately 2.5 g)




Fig. 20. A graphical method for predicting vehicle performance in rice fields

the distance (ft) traveled during the driver reaction time was 9 ft. When the driver began to apply the brakes (44 ft), the negative acceleration of the vehicle was assumed equivalent to the maximum positive acceleration. The four segments were analyzed by integrating the total area under the performance envelope and dividing the result (ft^2/sec) by the dike spacing (ft) and the average speed predicted.

41. In rice fields with dike heights greater than the clearance of the vehicle, a 20-min time penalty was imposed for each dike; the average speed attained between dikes was discounted since the time was insignificant compared to the penalty time involved. Consequently, the average speed in rice fields in Route 1 with dikes of sufficient height to cause immobilization was computed to be 0.1 mph.

42. As stated in paragraph 17, a computer program was prepared during the later phases of this study and used for predicting speed in rice fields. This program was used for only the six vehicles evaluated and reported upon in the last draft report (see paragraph 4). Input consisted of:

- a. Spacing of rice-field dikes
- b. Height of dikes
- c. Base width of dikes
- d. Motion resistance of vehicle in paddy soil
- e. Tractive force-speed curve for paddy soil strength
- f. Braking rate (deceleration)
- g. Braking reaction time
- h. Obstacle height-speed curve (fig. 18)
- i. Wheelbase, or track length, in contact with the ground

The program computed the total time required for a vehicle to cross a dike, accelerate in the paddy, and then decelerate, if necessary, before crossing the next dike. The distance traveled in crossing one dike and one paddy was divided by the elapsed time to obtain the average speed performance.

Effects of vegetation on performance

43. Data needed to analyze the effects of vegetation screening on the ability of the driver to see were lacking so no speed limitations were imposed for poor visibility. This omission was not considered significant for two reasons: (a) approximately 70 percent of the vehicle travel time

was spent in rice fields where visibility is seldom a problem, and (b) the field of vision from the driver's position is approximately the same for each vehicle.

44. Rather than declaring areas of heavy vegetation impassable, a time penalty of 5 min was assessed for every 11 ft of travel, based on the time needed to cut down one large tree (10 in. in diameter) to permit passage.

Effects of hydrologic geometry
on performance

45. Special conditions imposed in the early phases of the study because of hydrologic features were:

- a. Entry into all streams and lakes was assumed possible for all vehicles.
- b. To determine stream widths accurately was impossible because of the small map scale. A 75-ft width was assumed arbitrarily and the time required for each crossing (swimming or fording) was based on an assumed speed of 3.0 mph. This combination of width and speed was assumed to include entry, crossing, and exit. When the rated water speeds (table 1) were obtained later in the study, the error involved in the assumption for speed was seen to be insignificant. Therefore, in only one instance, where the M520 had to swim a lake 600 ft across, the rated water speed of 3.3 mph and the measured width of the lake were used.
- c. When immobilization was predicted, a time penalty of 20 min was assessed. The 20-min time penalty was based on a report from the Army Concept Team in Vietnam, which stated that a well-trained crew could cross a canal with an M113 armored personnel carrier in 15-20 min when using the capstan-anchor method of self-recovery. Only one immobilization per crossing was imposed.

46. The above-listed special conditions were imposed also in the study reported in June 1968 (see paragraph 4). In addition, certain other modifications were made to the procedures described in reference 1. These modifications are discussed in the following paragraphs.

47. Stream crossing. Performance at stream crossings was restricted to the vehicle's ability to exit. To predict stream exit performance, determination was made as to whether the vehicle could negotiate the exiting stream bank unassisted, assisted by winching, or not at all. For amphibious vehicles, zero traction was assumed for all traction elements in the floating mode. If a nonamphibious vehicle could not cross a stream because the water depth was greater than the fording depth, the vehicle was rerouted.


48. If assistance was not required, the total time to cross the stream was computed without a time penalty. Based on the 3.0-mph average speed assumed for each crossing and the 75-ft width assumed for each stream (see paragraph 45b), the time to cross any stream without penalty was 17 sec. If assistance was required, a time penalty was assessed and was considered to be the total elapsed time to cross the stream. This time was 1200 sec (see paragraph 45c). The procedure used to predict the total elapsed time is illustrated in fig. 21.

49. Bank-vehicle geometry interference. A two-dimensional scale model of the vehicle and a profile of the stream channel were used to determine whether interference between the vehicle and exit bank would occur. If any part of the vehicle, other than its tracks or wheels, contacted the profile while exiting, the vehicle was considered immobilized and a penalty was assessed (fig. 21).

50. Tractive force required to climb stream banks. The tractive force that a vehicle could develop on a slope (T_d) and the tractive force required (T_r) beyond that needed to propel a vehicle on level ground were computed using input values obtained with the bank-vehicle geometry scale model (paragraph 49). Predictions were made on a go-no go basis (fig. 21).

51. The tractive force that a wheeled vehicle, regardless of the number of axles, could develop on a slope was computed by the following equation:

$$T_{dw} = \frac{W_1}{W} DBP \cos \theta_m + \sum_{x=2}^n \left[\left(\frac{W_x}{W} DBP \cos \theta_x - W_x \sin \theta_x \right) \cos (\theta_m - \theta_x) \right]$$



Where:

T_d = Tractive force that can be developed by a vehicle on a slope
 T_r = Tractive force required beyond that needed to propel the vehicle on level ground

Fig. 21. Procedure for predicting performance of vehicles in crossing streams

and the tractive force required (T_{rw}), beyond that needed to propel the vehicle on level ground, for the wheeled vehicles (M37B1, M561, and M706) to exit from a stream was computed by:

$$T_{rw} = W_1 \sin \theta_m$$

where

- T_{dw} = tractive force a wheeled vehicle can develop on a slope, lb
- W_1 = maximum axle load, lb
- W = total vehicle weight, lb
- DBP = drawbar pull on a level surface, lb
- θ_m = maximum bank angle, deg
- n = total number of axles
- W_x = axle load, lb, for any axle from 2 to n
- θ_x = angle of the bank slope in contact with the wheels of a given axle, deg
- T_{rw} = tractive force required to lift the maximum axle load up the maximum bank slope, lb

In computing T_{rw} , the weight on each axle was computed by taking the sum of the moments about the wheel ground contact points for different positions of the vehicle on the bank. By these successive solutions, the most critical conditions for exiting were defined and used in predicting performance.

52. The tractive force that a single-unit tracked vehicle could develop on a bank slope was computed by the following equation:

$$T_{dt} = DBP \cos \alpha$$

and the tractive force required for the single-unit tracked vehicles (M113A1 and M116) to exit from a stream was computed by:

$$T_{rt} = W \sin \alpha$$

where

- T_{dt} = tractive force a tracked vehicle can develop on a slope, lb
- DBP = total drawbar pull on a level surface, lb
- α = maximum attitude angle the vehicle will attain in climbing a bank, deg
- T_{rt} = tractive force required for a tracked vehicle, lb
- W = total vehicle weight, lb

53. To analyze the ability of the articulated M571 to exit from streams, values of T_{dt} and T_{rt} were determined separately for the front and rear units. These separate values were added to obtain the total T_{dt} and T_{rt} values.

54. In all cases, T_d and T_r values computed were compared, and if $T_d - T_r > 0$, a go condition was predicted, or if $T_d - T_r < 0$, a no-go condition was predicted (fig. 21).

Effects of special vehicle characteristics

55. The effects of special vehicle characteristics, such as articulation, duck walking, and positive traction, were not evaluated because appropriate quantitative relations are not available (see paragraph 12). In this study it was assumed that equal traction was available at all times for all the traction elements. Articulated vehicles have a distinct advantage over rigid-frame vehicles when operating on a terrain surface in which microrelief is of paramount importance. Traction elements of articulated vehicles conform to most surface irregularities; therefore, more traction surface is available for developing tractive force and usually responses are less, producing a better ride quality. Duck-walking capability is an advantage to a vehicle when it becomes immobilized in soft soil underlain by firm soil. By simultaneously applying power to the wheels and turning the front of the vehicle from left to right, the driver may extricate the vehicle from localized soft spots.

Prediction of fuel consumption

56. Fuel consumption-speed relations for all the vehicles were computed from fuel consumption-engine rpm performance curves obtained from DP's reports^{4,5}. The specific relations used as input to the prediction model for this study are shown in fig. 22. These relations are obtained when the vehicle is assumed to be performing at its maximum traction, regardless of the surface conditions or gear selections. Under these conditions, the engine rpm vary within a narrow range, and therefore fuel consumption remains fairly constant.

57. In the early phase of the study, the only special consideration involved stream crossings. To compute fuel consumption, a vehicle was assumed to operate at maximum horsepower output for 10 min for each 20-min

time penalty assessed for immobilization caused by bank configuration as the vehicle tried to exit; for stream crossings without imposed penalties, a vehicle was assumed to operate at maximum gross horsepower for the total crossing time.

58. In the 1968 study, separate procedures were used to predict fuel consumption for areal and for linear terrain types. For areal types the procedures were as follows:

- a. A fuel consumption rate (gal/hr) was determined for each predicted speed from the relations shown in fig. 22.
- b. The fuel consumption rate (gal/hr) was divided by the predicted speed (mph) to give a fuel consumption rate in gal/mile. Examples of the resulting relations for the M561, M706, M37B1, M116, M571, and M113A1 are shown in fig. 23.
- c. The total distance traveled in a terrain type was scaled from the terrain-type map and multiplied by the fuel consumption rate (gal/mile) to obtain the total amount of fuel consumed.

59. The amount of fuel consumed in crossing linear terrain types (streams) was considered insignificant unless the vehicle was immobilized. The following procedures were used to predict the consumption at those streams where immobilization occurred:

- a. A fuel consumption rate (gal/hr) was determined for a speed of 1.0 mph from the relations shown in fig. 22.
- b. One-half of the time penalty assessed was multiplied by the fuel consumption rate (gal/hr) to obtain the total amount of fuel consumed.

Determination of delivery rate

60. In any given terrain situation, the performance values for any two vehicles may be different. For example, vehicle A may have a high speed, high fuel consumption, and low cargo capacity; while vehicle B may have a lower speed, lower fuel consumption, but a larger cargo capacity. The evaluation of relative performance then rests on which performance measure is deemed most important. Since such a decision is often impractical, combining all performance values derived in a given terrain situation into





Fig. 22. Full load fuel consumption (gal/hr)-speed relations





Fig. 23. Full-load fuel consumption (gal/mile)-speed relations

a single performance value is useful. Cargo capacity can be multiplied by average speed made good to obtain a delivery rate in ton-miles/hr. To compute average speed made good, the following expression is used:

$$\text{Average speed made good} = \frac{\text{Straight-line distance}}{\text{Total elapsed time}}$$

To compute delivery rate, the following expression is used:

$$\text{Delivery rate (ton-miles/hr)} = \text{Cargo capacity (tons)} \times \text{Average speed made good (miles/hr)}$$

PART III: EVALUATION OF VEHICLES

61. The WES analytical model (Appendix A) was used to predict vehicle performance for the dry season and the wet season, in terms of speed and fuel consumption. Cargo delivery rate was calculated from the values of average speed and payload. In the first study (see paragraph 2), in which performance was evaluated for the dry season, a soil strength of 60 or 40 RCI was used (paragraph 27). In the supplemental study (paragraph 3) for the wet season, two traverses were used, one with terrain types of either 60 or 40 RCI, and the other with terrain types of either 60 or 35 RCI (paragraph 28). In the 1968 study (paragraph 4), performance was evaluated for both the dry season and the wet season; soil strengths of either 60 or 40 RCI was used for the dry season, and either 60 or 35 RCI for the wet.

Selection of Traverses and Preparation of Speed Maps

62. The predicted performances of all the vehicles used in this study, for both the dry-season and wet-season conditions, are summarized in table 3. The predictions were made in terms of average speed, fuel consumption, and delivery rate, for all terrain types in the Khon Kaen study area. The terrain types that allowed the vehicle the highest average speed were traversed along straight-line paths, which were connected to form a continuous route. The traverse starting at Ban Meng and ending at Ban Sang Kao represents the optimum path within the 1.2-mile-wide limits of the route selected.

63. Because in all cases the evaluation criterion was speed, traverses were selected that would yield the highest speed. (If the traverses had been selected for other than speed, e.g. for fuel consumption or rate of delivery, they may have been different.)

64. The average speed of each vehicle was determined for the terrain factor complexes along route 1 and mobility maps were prepared. Only some of the mobility maps along with the traverse over which predictions were

made are included in this report. Those that are included are identified in the following table:

| <u>Vehicle</u> | <u>Plate No.</u> | <u>Season</u> |
|----------------|------------------|---------------|
| M556 | 7 | Dry |
| | 8 | Average wet |
| | 9 | Maximum wet |
| M54A2 | 10 | Dry |
| | 11 | Average wet |
| | 12 | Maximum wet |
| M520 | 13 | Dry |
| | 14 | Average wet |
| | 15 | Maximum wet |
| M548 | 16 | Dry |
| | 17 | Average wet |
| | 18 | Maximum wet |
| M113 | 19 | Dry season |

65. Average speed for a total traverse was obtained by dividing the traverse length by the time spent in traveling over it. If a vehicle had to cross a water body in a particular terrain type, the time required to complete the crossing (time penalty) was added to the time required to traverse that terrain type. Performance data can be obtained by referencing terrain type and vehicle identification in table 3.

Performance in Various Terrain Types

66. The performances predicted for each vehicle in each terrain type successfully traversed along the route are tabulated in table 4. The terrain types are listed in the order in which they were traversed. The distances listed were measured along straight lines on the cross-country mobility routes. (When a change of direction occurs within a terrain type, distances are given for each segment.) In the column marked "Penalty," 17 sec denotes that a vehicle crossed a stream without assistance, and 1200 sec that assistance was required. Multiples of 17 indicate more than one stream was crossed, and multiples of 1200 indicate that more than one immobilization occurred in the same terrain type. It should be noted that the penalties listed in this column occurred only in linear terrain types. The time and fuel required for each vehicle to traverse each terrain type include those required for stream crossings.

Speed Performance

Effect of terrain type on speed

67. The maximum and minimum speed performance for all the vehicles and the terrain types in which they occurred are shown in the following table.

| Vehicle | Dry-season Condition (60 or 40 RCI) | | | Wet-season Condition (60 or 40 RCI) | | | Wet-season Condition (60 or 35 RCI) | | |
|------------------|--|-----|----------------------|--|-----|-----------------|--|-----|-------------------|
| | Avg Speed | | Terrain Type | Avg Speed | | Terrain Type | Avg Speed | | Terrain Type |
| | Mph | | | Mph | | | Mph | | |
| | Max | Min | | Max | Min | | Max | Min | |
| Wheeled Vehicles | | | | | | | | | |
| M656 | 27.2 | | 19 | 27.2 | | 19 | 27.2 | | 19 |
| | | 0.1 | 13 | | 0.1 | 13,30 | | 0.1 | 13,30 |
| M54A2 | 23.5 | | 19 | 16.4 | | 23 | 16.4 | | 23 |
| | | 0.1 | 13,30,32 | | 0.1 | 13,30,32 | | 0.1 | 13,30,32 |
| M520 | 15.0 | | 19 | 15.0 | | 19 | 15.0 | | 19 |
| | | 3.6 | 13 | | 3.6 | 13 | | 1.6 | 36A |
| M37B1 | 31.0 | | 3,17,28, 31,37,52 | | | | 31.0 | | 3,17,28, 31,37 |
| | | 0.1 | 30,32 | | | | | 0.1 | 30,32 |
| M561 | 40.0 | | 3,31,37 | | | | 40.0 | | 3,17,28, 31,37 |
| | | 0.1 | 30,32 | | | | | 0.1 | 30,32 |
| M706 | 38.3 | | 3,31,37 | | | | 38.3 | | 3,31,37 |
| | | 0.1 | 30,32 | | | | | 0.1 | 30,32 |
| Tracked Vehicles | | | | | | | | | |
| M548 | 10.6 | | 23 | 10.6 | | 23 | 10.6 | | 23 |
| | | 0.1 | 13 | | 0.1 | 13 | | 0.1 | 13 |
| M113A1 | 39.0 | | 3,17,28, 31,37 | | | | 39.0 | | 3,17,28, 31,37 |
| | | 1.3 | 13 | | | | | 1.3 | 13 |

| Vehicle | Dry-season Condition (60 or 40 RCI) | | | Wet-season Condition (60 or 40 RCI) | | | Wet-season Condition (60 or 35 RCI) | | |
|---------|--|-----|-----------------|--|-----|-----------------|--|-----|-----------------------------|
| | Avg Speed | | Terrain Type | Avg Speed | | Terrain Type | Avg Speed | | Terrain Type |
| | Mph | | | Mph | | | Mph | | |
| | Max | Min | | Max | Min | | Max | Min | |
| M116 | 32.1 | | 3,17,31, 37 | | | | 32.1 | | 3,10,17, 22,28,31, 37 |
| | | 0.1 | 13 | | | | | 0.1 | 13 |
| M571 | 27.4 | | 3,17,31, 37 | | | | 27.4 | | 3,17,28, 31,37 |
| | | 2.2 | 13 | | | | | 2.2 | 13 |

The M561 had the highest speed of the wheeled vehicles in both dry- and wet-season conditions, and the M113A1 had the highest speed of the tracked vehicles in both conditions. The M520 and the M548 had the lowest maximum speed in both seasons. Except for the M54A2, each vehicle was able to travel at its same maximum speed regardless of seasonal conditions. Except for the M520, each traveled at its same minimum speed in both seasons; the wet-season condition with 60 or 35 RCI caused the M520 to travel at a lower speed than in the other two seasonal conditions.

68. Terrain type 19 allowed maximum speed for three vehicles in the dry season and for two of the three in the wet season. Types 3, 31, and 37 allowed maximum speed in both seasons for six vehicles; some of the same vehicles also attained maximum speed in types 17 (four vehicles in both seasons), 28 (two vehicles in the dry season and four in the wet), 52 (one vehicle in the dry season), and 22 and 10 (one vehicle in the wet season for both types). Seven vehicles traveled at minimum speed in terrain type 13 in both seasonal conditions. Type 30 was traversed at minimum speed by one of the seven in the wet season and by another of the seven and three additional vehicles in both seasons. Type 32 was traversed at minimum speed by the same four latter vehicles above in both seasons.

69. Seven vehicles, five wheeled and two tracked, had the same minimum speed in one or more of the same terrain types. While terrain type

appeared to be the major factor affecting vehicle speed, seasonal conditions and soil strength apparently did not significantly affect either maximum or minimum speeds, at least for the soil strengths tested in this study. In the wet-season analysis of the first four vehicles tested (see paragraph 3), a special study was made to provide a more comprehensive treatment of the effects of soil strength on performance. The discussions deal with speed, delivery rate, one-pass vehicle cone index, and overall trafficability in the United States and Thailand, and can be found in Appendix C.

Speed within terrain classes

70. The terrain types were grouped into three qualitative classes: vegetation, rice fields, and streams.

71. Vegetation. Vegetation was divided into three sub-classes, based on the percentage of maximum tractive force required to traverse vegetated areas. The sub-classes were: (a) light, 0-25% tractive force required; (b) medium, 26-50%; and (c) heavy, 51-100%. No vegetation in the medium sub-class occurred in the terrain selected for this study.

72. The time expended in traversing areas of light vegetation and the average speed attained were computed for the four vehicles in the first study (fig. 24); there were no immobilizations. The time and speed were not computed in the 1968 study. The speed of the M656 (12.6 mph) and the M54A2 (12.4 mph) was approximately twice that of the M520 (6.6 mph) and the M548 (7.9 mph) because of greater power available beyond 10 mph (see figs. 25a and 25b). The performance of the M520 did not exceed that of the M548 because the M520 is 11 in. wider, and so encountered more vegetation while traversing the terrain; this, in turn, increased the average force requirement. This greater force requirement canceled the advantage of greater available power, so that the speed of the M520 was below that of the M548.

73. Only one terrain type (type 13) was classified as containing heavy vegetation. Again, the time expended in traversing this type and the average speed attained were computed for the four vehicles in the first study (fig. 24). In the 1968 study, they were computed for the M116, the only vehicle tested at that time that became immobilized in heavy vegetation; the other five vehicles could either circumvent or override it. The following tabulation presents the data derived for the vehicles that were




Fig. 24. Comparison of average speed performance and elapsed time for groups of terrain types




Fig. 25a. Net horsepower-speed performance relations for M656 and M54A2




Fig. 25b. Net horsepower-speed performance relations for M520 and M548

immobilized (i.e. suffered time penalties):

| <u>Vehicle</u> | <u>Total Distance Ft</u> | <u>No. 5-Min Penalties (See par 44)</u> | <u>Total Time Hr</u> | <u>Avg Speed Mph</u> | <u>Terrain Type Speed*</u> |
|-----------------------------------|----------------------------------|---|------------------------------|------------------------------|------------------------------------|
| <u>Dry Season (60 or 40 RCI)</u> | | | | | |
| M656 | 3200 | 204 | 17.0 | 0.04 | 0.1 |
| M54A2 | 3300 | 213 | 17.8 | 0.03 | 0.1 |
| M548 | 3000 | 210 | 17.5 | 0.03 | 0.1 |
| M116 | 3200 | 174 | 14.5 | 0.04 | 0.1 |
| <u>Wet Season (60 and 35 RCI)</u> | | | | | |
| M656 | 3300 | 210 | 17.5 | 0.04 | 0.1 |
| M54A2 | 3000 | 194 | 16.2 | 0.04 | 0.1 |
| M548 | 3000 | 210 | 17.5 | 0.03 | 0.1 |
| M116 | 3200 | 174 | 14.5 | 0.04 | 0.1 |

*Predicted speed in each areal terrain type was rounded to nearest tenth of a mile per hour to: (a) avoid vehicle immobilization and (b) be consistent with other predicted speeds.

74. The M520 was not immobilized in heavy vegetation and so could maintain a 3.6-mph speed, as opposed to 0.1-mph speed for the other vehicles. This superior performance was due in part to greater available power in the 0-3 mph range. Also significant was the higher leading edge (50 in.) of the vehicle, which reduced the average force required for vegetation override. The leading edge of the M520 can withstand an impact force 1.5 times larger than that of the M656 and the M54A2, and 3 times larger than that of the M548 (see tables 1 and 2). The M520 weighs approximately 1.3 times more than the M54A2, and 1.6 times more than the M656 and the M548. This added weight provided a substantially greater kinetic energy that could be utilized in overcoming peak force demands.

75. The M548 tracked vehicle would be superior to the M520 (see fig. 26a) if it were not for the heavy vegetation, which covered 3200-3900 ft, or 1.3-1.6 percent of the total distance traversed. This fact emphasizes that the distribution of critical terrain conditions can be extremely significant to cross-country vehicle travel, although it is often overlooked because a

particular terrain feature that occurs infrequently can easily go unnoticed on small-scale maps unless each terrain-vehicle interaction is examined in detail.

76. Rice fields. Approximately 70 percent of the travel time on the route was spent in rice fields (paragraph 43). The time required to traverse rice fields and the average speed attained were computed only for the four vehicles in the first study (fig. 24) and for the vehicles in the 1968 study that became immobilized. The following tabulation presents the data derived for the vehicles that were immobilized:

| <u>Vehicle</u> | <u>Dike Spacing Ft</u> | <u>Total Distance Ft</u> | <u>No. 20-Min Penalties (See par 41)</u> | <u>Total Time Hr</u> | <u>Avg Speed Mph</u> | <u>Terrain Type Speed*</u> |
|----------------------------------|--------------------------------|----------------------------------|--|------------------------------|------------------------------|------------------------------------|
| <u>Dry Season (60 or 40 RCI)</u> | | | | | | |
| M656 | 100 | 3700 | 37 | 12.3 | 0.06 | 0.1 |
| M54A2 | 100 | 3300 | 33 | 11.0 | 0.06 | 0.1 |
| M37B1 | 100 | 3800 | 38 | 12.7 | 0.06 | 0.1 |
| M561 | 100 | 3300 | 33 | 11.0 | 0.06 | 0.1 |
| M706 | 100 | 3400 | 34 | 11.3 | 0.06 | 0.1 |
| <u>Wet Season (60 or 35 RCI)</u> | | | | | | |
| M656 | 100 | 5000 | 50 | 16.7 | 0.06 | 0.1 |
| M54A2 | 100 | 7900 | 79 | 26.3 | 0.06 | 0.1 |
| M37B1 | 100 | 5500 | 55 | 18.3 | 0.06 | 0.1 |
| M561 | 100 | 3100 | 31 | 10.3 | 0.06 | 0.1 |
| M706 | 100 | 3700 | 37 | 12.3 | 0.06 | 0.1 |

*Predicted speed in each areal terrain type was rounded to nearest positive tenth of a mile per hour to: (a) avoid vehicle immobilization and (b) be consistent with other predicted speeds.

77. The performance of the wheeled vehicles in rice fields could be judged almost entirely on undercarriage clearance. This was particularly significant for those terrains characterized by dikes 18-30 in. high. Undercarriage clearance was not a consideration for the tracked vehicles, and these vehicles were not immobilized; their better performance was due in part to their superior dynamic response characteristics.

78. The M520 was the only wheeled vehicle that was not immobilized. Its larger diameter tires (71.1 in.) provided it with a 30-in. under-carriage clearance, compared to 20 in. for the M656, 21 in. for the M54A2, 16 in. for the M37B1, 15 in. for the M561, and 23 in. for the M706. The M520 was designed, however, with no suspension system, and induced vibratory motions are compensated only within the limits of the spring and damping properties of its pneumatic tires. So, in spite of its large power output, the M520 was unable to perform as well as the tracked vehicles.

79. Streams. The number of streams crossed and the time penalties assessed for all the vehicles are shown in the following tabulation:

| Vehicle | Dry Season (60 or 40 RCI) | | | | Wet Season (60 or 35 RCI) | | | |
|---------|---------------------------|---------------|----------|------------------------|---------------------------|---------------|----------|------------------------|
| | No. Streams Crossed | No. Penalties | | Total Penalty Time Sec | No. Streams Crossed | No. Penalties | | Total Penalty Time Sec |
| | | 17-Sec | 1200-Sec | | | 17-Sec | 1200-Sec | |
| M656 | 11 | 3 | 8 | 9651 | 10 | 3 | 7 | 8451 |
| M54A2 | 11 | 2 | 9 | 10834 | 9 | 1 | 8 | 9617 |
| M520 | 10 | 5 | 5 | 6085 | 9 | 1 | 8 | 9617 |
| M37B1 | 8 | 4 | 4 | 4868 | 8 | 2 | 6 | 7234 |
| M561 | 9 | 5 | 4 | 4885 | 8 | 3 | 5 | 6051 |
| M706 | 8 | 2 | 6 | 7234 | 8 | 2 | 6 | 7234 |
| M548 | 8 | 3 | 5 | 6051 | 9 | 2 | 7 | 8434 |
| M113A1 | 8 | 4 | 4 | 4868 | 8 | 2 | 6 | 7234 |
| M116 | 9 | 6 | 3 | 3702 | 9 | 6 | 3 | 3702 |
| M571 | 9 | 7 | 2 | 2519 | 9 | 7 | 2 | 2519 |

80. As stated in paragraph 30, new routes were chosen for all vehicles in the wet season in an attempt to reduce the number of 1200-sec penalties for crossing streams; however, reductions in the number of penalties only occurred for a few vehicles. The number of streams crossed in the wet season was reduced for the M656, M54A2, M520 and M561; no change occurred for the M37B1, M706, M113A1, M116, and M571; and the number was increased for the M548. The number of 17-sec penalties assigned in the wet season decreased over the dry season for the M54A2, M520, M37B1, M548, M113A1, and M561, and no change occurred for the M656, M706, M116, and M571. There was a decrease in the number of 1200-sec penalties assigned in the wet season for the M656, M54A2; no change

in the number of penalties for the M706, M116, and M571; and the number of penalties increased for the M520, M37B1, M548, M113A1, and M561.

81. Summary. While penalties were a major factor in determining the performance of the vehicles within terrain classes, no relations were established between the number of penalties assessed in particular terrain classes and the average speed the vehicles could attain in crossing them. Other factors had to be considered, e.g. the time involved when a vehicle was routed over a longer segment of the route, or the ability of some vehicles to maneuver in certain terrain classes better than other vehicles could.

Average traverse speed for route

82. The traverse distances and the average speed of each vehicle listed below were taken from table 4. The path elongations were computed in each case by dividing the traverse distance by the center-line distance (44.8 miles for all vehicles in all seasonal conditions).

| Vehicle | Dry Season (60 or 40 RCI) | | | Wet Season (60 or 40 RCI) | | | Wet Season (60 or 35 RCI) | | |
|---------|---------------------------|-------------------------|-------------------|---------------------------|-------------------------|-------------------|---------------------------|-------------------------|-------------------|
| | Traverse Distance miles | Path Elongation ga-tion | Average Speed mph | Traverse Distance miles | Path Elongation ga-tion | Average Speed mph | Traverse Distance miles | Path Elongation ga-tion | Average Speed mph |
| M656 | 44.9 | 1.00 | 2.4 | 47.4 | 1.06 | 2.2 | 47.4 | 1.06 | 2.2 |
| M54A2 | 46.0 | 1.03 | 2.2 | 48.6 | 1.08 | 1.7 | 48.6 | 1.08 | 1.7 |
| M520 | 44.9 | 1.00 | 5.5 | 44.6 | 1.00 | 4.8 | 44.6 | 1.00 | 3.9 |
| M37B1 | 46.7 | 1.04 | 3.1 | | | | 47.7 | 1.06 | 2.5 |
| M561 | 46.3 | 1.03 | 4.2 | | | | 45.7 | 1.02 | 4.2 |
| M706 | 46.3 | 1.03 | 3.9 | | | | 46.1 | 1.03 | 3.7 |
| M548 | 45.4 | 1.01 | 3.7 | 45.6 | 1.02 | 3.5 | 45.6 | 1.02 | 3.4 |
| M113A1 | 46.3 | 1.03 | 9.0 | | | | 45.4 | 1.01 | 7.3 |
| M116 | 45.8 | 1.02 | 4.6 | | | | 45.9 | 1.02 | 4.2 |
| M571 | 46.0 | 1.03 | 8.7 | | | | 46.9 | 1.05 | 8.5 |

83. The maximum difference in traverse distances in the dry season was 1.7 miles; in the wet season the maximum difference was 4.0 miles, regardless of the soil strength combinations considered.

84. The comparative traverse performances for all the vehicles are portrayed in figs. 26a and 26b in terms of cumulative time. Examples of




Fig. 26a. Cumulative time-distance (dry season) for M54A2, M656, M548, and M520




Fig. 26b. Cumulative time-distance (dry season) for M37Bl, M706, M561, M116, M571, and M113Al

similar comparative traverse performances for the M37B1, M706, M561, M116, M113A1, and M571 are portrayed in fig. 26c for the wet-season condition. The short vertical discontinuities in each line represent stream crossings where time penalties were imposed because of immobilization. The longer vertical discontinuities represent time penalties assessed in rice fields where dikes were 18-30 in. high. A steady increase in time between approximately 16 and 38 miles reflects the better performance of all vehicles in light vegetation and rice fields characterized by dikes less than 18 in. high. The sharp increase in time accumulation by the M656, M54A2, M37B1, M548, and M116 at mile 38-39 was due to time penalties imposed for negotiating heavy vegetation.

85. All the vehicles had higher speeds in the dry season than in the wet, except the M561 with the same speed in both seasons. Of the wheeled vehicles tested, the M520 had the best average speed for both seasons, and the M54A2 the worst. Of the tracked vehicles, the M113A1 had the best dry-season average speed and the M571 the best wet-season average speed; the M548 had the lowest for both seasons. The greatest reduction in average traverse speeds from the dry to the wet seasons occurred for the M113A1 (9.0 to 7.3 mph). Significantly, the M116 had the fastest speed over the first 38 miles in both seasons.

86. Since the one-pass vehicle cone index (VCI_1) for each vehicle was less than 35 (see table 1), none of the vehicles were immobilized because of insufficient soil strength. In the predictions for the two strength combinations for the wet season, the M656 and the M54A2 had the same average speed for both conditions; the M548 was only 0.1 mph slower on the lower soil strength; and the M520 had the greatest reduction (4.8 to 3.9 mph). The reduction in the speed of this latter vehicle is related to the comparatively larger increase in motion resistance that occurs as soil strength is reduced, as shown by the following tabulation. Only four vehicles are listed because they were the only ones tested in both wet-season conditions.




Fig. 26c. Cumulative time-distance (wet season) for M37B1, M706, M561, M116, M571, and M113A1

| Vehicle | Motion Resistance, lb | |
|---------|-----------------------|--------|
| | 40 RCI | 35 RCI |
| M656 | 2760 | 3450 |
| M54A2 | 2800 | 3100 |
| M520 | 4077 | 8561 |
| M548 | 2800 | 3100 |

Average center-line speed for the route

87. As previously stated, the center-line distance for all the vehicles in all seasonal conditions was 44.8 miles. This center-line distance was divided by the total time required to traverse it to obtain the average center-line speed for each vehicle. The following table presents the data for all the vehicles:

| Vehicle | Dry Season (60 or 40 RCI) | | Wet Season (60 or 40 RCI) | | Wet Season (60 or 35 RCI) | |
|---------|---------------------------|-------------------------|---------------------------|-------------------------|---------------------------|-------------------------|
| | Total Time | Average | Total Time | Average | Total Time | Average |
| | to Complete Center-Line | to Complete Center-Line | to Complete Center-Line | to Complete Center-Line | to Complete Center-Line | to Complete Center-Line |
| | Traverse, hr | Speed, mph | Traverse, hr | Speed, mph | Traverse, hr | Speed, mph |
| M656 | 18.7 | 2.4 | 21.6 | 2.1 | 21.8 | 2.1 |
| M54A2 | 21.0 | 2.1 | 29.1 | 1.5 | 29.3 | 1.5 |
| M520 | 8.2 | 5.4 | 9.4 | 4.8 | 11.3 | 4.0 |
| M37B1 | 14.9 | 3.0 | | | 19.1 | 2.3 |
| M561 | 11.0 | 4.1 | | | 11.0 | 4.1 |
| M706 | 11.8 | 3.8 | | | 12.4 | 3.6 |
| M548 | 12.6 | 3.7 | 12.9 | 3.6 | 13.3 | 3.4 |
| M113A1 | 5.2 | 8.7 | | | 6.2 | 7.2 |
| M116 | 10.0 | 4.5 | | | 10.8 | 4.1 |
| M571 | 5.3 | 8.5 | | | 5.6 | 8.1 |

88. The total time required for each vehicle to complete the traverse in the wet season exceeded the time required for the dry season, except for the M561, whose time was the same for both seasons. Again, of all the wheeled vehicles, the M520 had the highest average speed for both seasons, and the M54A2 the worst. Also, of the tracked vehicles, the M113A1 again had the highest dry-season average speed and the M571 the highest wet-season average speed; the M548 had the lowest speed for both seasons.

Fuel Consumption

89. The average rate and volume of fuel consumed by each vehicle in crossing each terrain type in the route are presented in table 4. The total fuel consumed and the average consumed in dry- and wet-season conditions were as follows:

| Vehicle | Dry Season (60 or 40 RCI) | | | Wet Season (60 or 40 RCI) | | | Wet Season (60 or 35 RCI) | | |
|---------|---------------------------|-------------------------|--------------------------------|---------------------------|-------------------------|--------------------------------|---------------------------|-------------------------|--------------------------------|
| | Traverse Distance Miles | Total Fuel Consumed Gal | Average Fuel Consumed Gal/mile | Traverse Distance Miles | Total Fuel Consumed Gal | Average Fuel Consumed Gal/mile | Traverse Distance Miles | Total Fuel Consumed Gal | Average Fuel Consumed Gal/mile |
| | | | | | | | | | |
| M656 | 44.9 | 58.5 | 1.3 | 47.4 | 63.8 | 1.4 | 47.4 | 65.3 | 1.4 |
| M54A2 | 46.0 | 84.4 | 1.8 | 48.6 | 88.1 | 1.8 | 48.6 | 89.2 | 1.8 |
| M520 | 44.9 | 82.3 | 1.8 | 44.6 | 87.1 | 2.0 | 44.6 | 101.4 | 2.3 |
| M37B1 | 46.7 | 38.6 | 0.8 | | | | 47.7 | 43.9 | 0.9 |
| M561 | 46.3 | 35.0 | 0.8 | | | | 45.7 | 31.4 | 0.7 |
| M706 | 46.3 | 65.0 | 1.4 | | | | 46.1 | 61.0 | 1.3 |
| M548 | 45.4 | 91.3 | 2.0 | 45.6 | 102.0 | 2.2 | 45.6 | 102.4 | 2.2 |
| M113A1 | 46.3 | 48.4 | 1.0 | | | | 45.4 | 55.6 | 1.2 |
| M116 | 45.8 | 59.2 | 1.3 | | | | 45.9 | 62.5 | 1.4 |
| M571 | 46.0 | 29.7 | 0.6 | | | | 46.9 | 31.0 | 0.7 |

90. In the dry-season analysis, the M571 tracked vehicles had the lowest average fuel consumption, and the M548 tracked vehicle the highest. In the wet season, the M561 wheeled vehicle and the M571 tracked vehicle had the same average fuel consumption, which was also the lowest of all the vehicles; the M548 tracked vehicle and the M520 wheeled vehicle had the highest for the two wet-season conditions, respectively. Significantly, this lowest average was also on the lowest soil strength. The M520 wheeled vehicle had the highest average fuel consumption in the wet season in both strength conditions, even though its traverse distance was the shortest of all the vehicles in both wet-season conditions. The fuel consumption rates for the M656, M520, M37B1, M548, M113A1, M116, and M571 were lower in the dry season, those of the M561 and M706 were lower in the wet season, and those of the M54A2 were the same in both seasons.

Cargo Delivery Rate

91. The cargo delivery rate was obtained by multiplying the average center-line speed and the cargo capacity (payload); the values obtained are given below.

| Vehicle | Pay-load Tons | Dry Season (60 or 40 RCI) | | Wet Season (60 or 40 RCI) | | Wet Season (60 or 35 RCI) | |
|---------|------------------|-------------------------------------|------------------|-------------------------------------|------------------|-------------------------------------|------------------|
| | | Average Center- line Speed | Delivery Rate | Average Center- line Speed | Delivery Rate | Average Center- line Speed | Delivery Rate |
| | | Mph | Ton-miles/hr | Mph | Ton-miles/hr | Mph | Ton-miles/hr |
| M656 | 5.00 | 2.4 | 12.0 | 2.1 | 10.5 | 2.1 | 10.5 |
| M54A2 | 5.00 | 2.1 | 10.5 | 1.5 | 7.5 | 1.5 | 7.5 |
| M520 | 8.00 | 5.4 | 43.2 | 4.8 | 38.4 | 4.0 | 32.0 |
| M37B1 | 0.75 | 3.0 | 2.2 | | | 2.3 | 1.7 |
| M561 | 1.25 | 4.1 | 5.1 | | | 4.1 | 5.1 |
| M706 | 1.00 | 3.8 | 3.8 | | | 3.6 | 3.6 |
| M548 | 6.00 | 3.7 | 22.2 | 3.6 | 21.6 | 3.4 | 20.6 |
| M113A1 | 1.93 | 8.7 | 16.8 | | | 7.2 | 13.9 |
| M116 | 1.50 | 4.5 | 6.8 | | | 4.1 | 6.2 |
| M571 | 1.00 | 8.5 | 8.5 | | | 8.1 | 8.1 |

92. As would be expected, the M520 with the largest cargo capacity and fastest center-line speed had the highest delivery rate in all conditions, and the M37B1 with the smallest capacity and less than average speed (of all the vehicles) had the lowest delivery rate in both dry- and wet-season conditions. Both are wheeled vehicles. Of the tracked vehicles, the M548 had the highest cargo delivery rate and the M116 the lowest in both seasons. All the vehicles had higher delivery rates in the dry season than in the wet, except the M561, whose delivery rate was the same in both seasons.

Summary of Vehicle Evaluations

93. The performance of each vehicle was evaluated in terms of average

speed over the traverse and the center line, average fuel consumed over the traverse, and center-line cargo delivery rate. Values of these criteria are summarized below.

| <u>Vehicle</u> | <u>Average Traverse Speed mph</u> | <u>Average Center-line Speed, mph</u> | <u>Average Fuel Consumed Over Traverse gal/mile</u> | <u>Center-line Delivery Rate ton-miles/hr</u> |
|----------------------------------|---|---|---|---|
| <u>Dry Season (60 or 40 RCI)</u> | | | | |
| M656 | 2.4 | 2.4 | 1.3 | 12.0 |
| M54A2 | 2.2 | 2.1 | 1.8 | 10.5 |
| M520 | 5.5 | 5.4 | 1.8 | 43.2 |
| M37B1 | 3.1 | 3.0 | 0.8 | 2.2 |
| M561 | 4.2 | 4.1 | 0.8 | 5.1 |
| M706 | 3.9 | 3.8 | 1.4 | 33.8 |
| M548 | 3.7 | 3.7 | 2.0 | 22.2 |
| M113A1 | 9.0 | 8.7 | 1.0 | 16.8 |
| M116 | 4.6 | 4.5 | 1.3 | 6.8 |
| M571 | 8.7 | 8.5 | 0.6 | 8.5 |
| <u>Wet Season (60 or 40 RCI)</u> | | | | |
| M656 | 2.2 | 2.1 | 1.4 | 10.5 |
| M54A2 | 1.7 | 1.5 | 1.8 | 7.5 |
| M520 | 4.8 | 4.8 | 2.0 | 38.4 |
| M548 | 3.5 | 3.6 | 2.2 | 21.6 |
| <u>Wet Season (60 or 35 RCI)</u> | | | | |
| M656 | 2.2 | 2.1 | 1.4 | 10.5 |
| M54A2 | 1.7 | 1.5 | 1.8 | 7.5 |
| M520 | 3.9 | 4.0 | 2.3 | 32.0 |
| M37B1 | 2.5 | 2.3 | 0.9 | 1.7 |
| M561 | 4.2 | 4.1 | 0.7 | 5.1 |
| M706 | 3.7 | 3.6 | 1.3 | 33.6 |
| M548 | 3.4 | 3.4 | 2.2 | 20.6 |
| M113A1 | 7.3 | 7.2 | 1.2 | 13.9 |
| M116 | 4.2 | 4.1 | 1.4 | 6.2 |
| M571 | 8.5 | 8.1 | 0.7 | 8.1 |

94. The M113A1 had the highest average traverse and center-line speeds in the dry season, and the M571 had the highest speeds in the wet. The M54A2 had the lowest traverse and center-line speeds in both seasons. The M571 consumed less fuel on the average in the dry season, and the M561 and M571 consumed the least in the wet. The M548 consumed the most in the dry season and the 60 or 40 RCI wet season; the M520 the most in the 60 or 35 RCI wet season. The M520 had the highest delivery rate in both seasons and the M37B1 the lowest.

PART IV: CONCLUSIONS AND RECOMMENDATIONS

Conclusions

95. Based on the results reported herein, the following conclusions are drawn:

- a. The WES analytical model was used successfully to evaluate the off-road mobility performance of the vehicles in this study over the selected terrain.
- b. Soil strength was not as significant as other terrain factors in evaluating the vehicles over the selected terrain; no vehicles were immobilized because of soil strength.
- c. A vehicle can perform well in one set of terrain conditions, but it will suffer penalties in another; thus, no one vehicle provided optimum mobility in all ranges of terrain conditions. Further, neither wheels nor tracks appeared to result consistently in better performance; wheeled vehicles performed better in some circumstances, and tracked performed better in others.
- d. Wet-season conditions usually reduced vehicle performance, as evidenced by (1) the reduction in average traverse speed of all the vehicles, except the M561; (2) the reduction in average center-line speed of all the vehicles, except the M561; (3) the increase in average fuel consumption for all the vehicles, except the M561, M706, and M54A2; and (4) the decrease in cargo delivery rates for all the vehicles, except the M561.

Recommendations

96. It is recommended that:

- a. The WES analytical model be refined as required to make it even more useful.
- b. The mission environment for any new vehicle be defined in quantitative terms before the new vehicle is developed.

LITERATURE CITED

1. U. S. Army Engineer Waterways Experiment Station, "An Analytical Model for Predicting Cross-Country Vehicle Performance, Technical Report No. 3-783 (in preparation), Vicksburg, Miss.
2. _____, "A Plan for a Quantitative Evaluation of the Cross-Country Performance of Prototype Vehicles" (in preparation), Vicksburg, Miss.
3. Dornbusch, W. K., Jr., "Mobility Environmental Research Study; A Quantitative Method for Describing Terrain for Ground Mobility, Volume VII: Development of Factor-Complex Maps for Ground Mobility," Technical Report No. 3-726, Apr 1968, U. S. Army Engineer Waterways Experiment Station, CE, Vicksburg, Miss.
4. Aberdeen Proving Ground, "Wheeled Vehicle Performance Data Consolidation," Report No. DPS-2410, Jun 1967, Aberdeen Proving Ground, Maryland
5. _____, "Tracked Vehicle Performance Data Consolidation," Report No. DPS-1846, Dec 1965, Aberdeen Proving Ground, Maryland
6. FMC Corporation, "A Computer Analysis of Vehicle Dynamics While Traversing Hard Surface Terrain Profiles," Contract Report No. 3-155, Feb 1966, U. S. Army Engineer Waterways Experiment Station, CE, Vicksburg, Miss.
7. Lessem, A. S., "Dynamics of Wheeled Vehicles, A Mathematical Model for Traversal of Rigid Obstacles by a Pneumatic Tire," Technical Report No. M-68-1, Report 1, May 1968, U. S. Army Engineer Waterways Experiment Station, CE, Vicksburg, Miss.

Table 1
Summary of Vehicle Characteristics and Performance Data for Wheeled Vehicles

| Characteristics | Source of Data | | Source of Data | | Source of Data | | Source of Data | | Source of Data | |
|--|----------------|----|----------------|----|----------------|----|----------------|----|----------------|----|
| | M556 | 23 | M542 | 27 | M520 | 30 | M578 | 24 | M561 | 17 |
| 1. Vehicle crew index (man-pass) | | | | | | | | | | |
| 2. Cross-country gross weight, fully equipped plus payload and personnel | | | | | | | | | | |
| a. Axle loads (front to rear), lb | | | | | | | | | | |
| (1) No. 1 | | | | | | | | | | |
| (2) No. 2 | | | | | | | | | | |
| (3) No. 3 | | | | | | | | | | |
| b. Total gross weight, lb | | | | | | | | | | |
| c. Payload, tons | | | | | | | | | | |
| 3. Dimensions, in. | | | | | | | | | | |
| a. Overall length (including winch if available) | | | | | | | | | | |
| b. Wheelbase | | | | | | | | | | |
| c. Height of leading edge | | | | | | | | | | |
| d. Width | | | | | | | | | | |
| e. Distance between wheel center lines | | | | | | | | | | |
| f. Distance between axles (front to rear) | | | | | | | | | | |
| (1) No. 1 - No. 2 | | | | | | | | | | |
| (2) No. 2 - No. 3 | | | | | | | | | | |
| (3) No. 3 - No. 4 | | | | | | | | | | |
| 4. Vehicle approach angle, deg | | | | | | | | | | |
| 5. Vehicle departure angle, deg | | | | | | | | | | |
| 6. Undercarriage clearance, in. | | | | | | | | | | |
| a. Axle | | | | | | | | | | |
| b. Interior | | | | | | | | | | |
| 7. Force leading edge can withstand, lb | | | | | | | | | | |
| 8. Winch capacity, lb | | | | | | | | | | |
| 9. Water performance characteristics | | | | | | | | | | |
| a. Fording depth, in. | | | | | | | | | | |
| (1) Normal fording depth | | | | | | | | | | |
| (2) Fording depth with fording kit | | | | | | | | | | |
| (3) Fording depth with snorkel kit | | | | | | | | | | |
| b. Water speed, mph | | | | | | | | | | |
| c. Depth below water line when loaded, in. | | | | | | | | | | |

(Continued)

* TACOM - US Army Tank-Automotive Command
 WES - US Army Engineer Waterways Experiment Station
 MA - Not applicable
 AFG - Aberdeen Proving Ground
 MEDC - Military Research and Development Center

Table 1 (Continued)

| Characteristics | | Source of Data | M56 | M542 | Source of Data | M520 | Source of Data | M751 | Source of Data | M561 | Source of Data | M706 | Source of Data |
|--|--|----------------|-----|----------------|----------------|----------------|----------------|---------------|----------------|-------|----------------|--------------|----------------|
| 10. Engine | | | | | | | | | | | | | |
| a. Make | | Continental | | Chrysler | | Caterpillar | | Dodge | | WES | | APC | Chrysler |
| b. Model | | LDS-465-1 | | LDS-465 | | E333TA | | T-245 | | APC | | WES | APC |
| c. Fuel type | | Cite | | Diesel | | Diesel | | Gasoline | | WES | | Cite | APC |
| d. Brake (BHP) or net (WHP) horsepower | | 198 BHP | | 210 BHP | | 176 BHP | | 77 BHP | | WES | | 103 BHP | APC |
| e. Maximum torque, lb-ft | | | | | | | | 188 | | TACOM | | -- | -- |
| f. Engine RPM at maximum torque | | | | | | | | 1200 | | TACOM | | -- | -- |
| g. Engine RPM at brake (BHP) or net (WHP) horsepower | | 2800 BHP | | 2800 BHP | | 2290 BHP | | 3000 BHP | | TACOM | | 2800 BHP | APC |
| 11. Transmission | | | | | | | | | | | | | |
| a. Type or model | | TX200-6 | | 6352 | | Caterpillar | | T-245-3995 | | OGE | | Chevrolet | APC |
| b. Gear ratios | | | | | | | | | | | | | |
| (1) 1st | | 5.296:1 | | 7.31:1 | | 4.274:1 | | 6.40:1 | | WES | | 7.06:1 | APC |
| (2) 2d | | 3.810:1 | | 4.09:1 | | 2.463:1 | | 3.09:1 | | WES | | 4.33:1 | APC |
| (3) 3d | | 2.691:1 | | 2.41:1 | | 1.885:1 | | 1.69:1 | | WES | | 2.61:1 | APC |
| (4) 4th | | 1.936:1 | | 1.44:1 | | 1.418:1 | | 1.00:1 | | WES | | 1.00:1 | APC |
| (5) 5th | | 1.390:1 | | 1.00:1 | | 1.087:1 | | -- | | -- | | -- | APC |
| (6) 6th | | 1.00:1 | | MA | | 0.818:1 | | -- | | -- | | -- | APC |
| 12. Transfer case | | | | | | | | | | | | | |
| a. Make or model | | DANA | | MA | | Caterpillar | | Titan | | TACOM | | Rockwell std | APC |
| b. Gear ratios | | | | | | | | | | | | | |
| (1) High | | 1.036:1 | | 1.000:1 | | -- | | 1.00:1 | | WES | | 1.00:1 | APC |
| (2) Low | | 1.036:1 | | 2.024:1 | | 1.222:1 | | 1.96:1 | | WES | | 1.79:1 | APC |
| 13. Axles | | | | | | | | | | | | | |
| a. Make or model | | Rockwell std | | MA | | Caterpillar | | T-245 | | TACOM | | Rockwell std | APC |
| b. Gear ratios | | | | | | | | | | | | | |
| (1) 1st axle | | 6.40:1 | | 6.443:1 | | 14.69:1 | | -- | | -- | | -- | APC |
| (2) 2d axle | | | | | | | | 5.83:1 | | TACOM | | 6.72:1 | APC |
| 14. Tire data | | | | | | | | | | | | | |
| a. Type | | Wide base | | Military | | CC | | Mad and snow | | APC | | Military | APC |
| b. Size | | 16:00x20 | | TACOM 11:00x20 | | TACOM 18:00x33 | | TACOM 9:00x16 | | APC | | 11:00x18 | APC |
| c. Ply | | 10 | | TACOM 12 | | TACOM 10 | | TACOM 8 | | APC | | APC | APC |
| d. Tread design | | ***HDC | | HDC | | Mod tra | | ***HMS | | APC | | HDC | APC |
| e. Tread depth, in. | | 15.4 | | 11.8 | | 21.2 | | 1 | | WES | | 1 | APC |

* OGE - Office Chief of Engineers
 CG - Cadillac Gage
 ** HMS - Nondirectional mad and snow
 ***HDC - Nondirectional cross-country

Table 1 (Continued)

| Characteristics | Source # | | Source of Data | | Source of Data | | Source of Data | |
|--|----------|-------|----------------|-------|----------------|--------------|----------------|--|
| | M56 | M542 | M520 | M57B1 | M561 | M706 | | |
| f. Unloaded diameter (including tread), in. | 43.6 | 43.6 | 71.1 | 35.8 | TACOM 40.0 | TACOM 49.5 | TACOM | |
| g. Unloaded width, in. ✓ | | | | 10.2 | TACOM 12.0 | 14.75 | TACOM | |
| h. No. of tires | 8 | 10 | 4 | 4 | TACOM 6 | 4 | TACOM | |
| i. No. of wheels (duals as one) | 8 | 6 | 4 | 0 | TACOM 6 | 4 | TACOM | |
| j. Cross-country inflation pressure (CCP), psi | 10-15 | 15 | 25 | 14 | WES 12 | APC -- | -- | |
| k. Cross-country tire deflection, % | 27 | 25 | 25 | 25 | TACOM 25 | WES 25 | WES | |
| l. Highway inflation pressure, psi | | | | 40 | OC 22 | APC 45 | TACOM | |
| 15. Steering data | | | | | | | | |
| a. Turning radius (curb to curb), ft | -- | -- | 25.2 | 25 | OC 35.24 | APC 24.5 | APC | |
| b. Maximum steering angle, deg | 29.0 | 29.0 | 60.0 | NA | NA 13.55 | WES NA | NA | |
| c. Time required to steer from straight ahead position to full lock turn, sec | 2.8 | 2.8 | 2.8 | 3 | WES 2.3 | WES 3 | WES | |
| d. Distance from front wheel steering pivot (hub) pivot to front of vehicle, in. | | | | 35.62 | WES 19.7 | WES 4.96 | WES | |
| e. Distance from front wheel steering pivot (hub) to outside of vehicle, in. | | | | 10.0 | WES 12.7 | WES 0.65 | WES | |
| 16. Articulated characteristics | | | | | | | | |
| a. Distance from leading edge to articulated joint, in. | -- | -- | 45.0 | NA | NA 118 | APC NA | NA | |
| b. Maximum pitch angle, deg | -- | -- | -- | NA | NA 40 | APC NA | NA | |
| c. Maximum roll angle, deg | -- | -- | -- | NA | NA 30 | APC NA | NA | |
| d. Maximum yaw angle, deg | -- | -- | 60.0 | NA | NA -- | NA -- | NA | |
| 17. Center of gravity location, in. | | | | | | | | |
| a. Horizontal distance from front axle | 82.0 | 135.0 | 81.2 | 63 | TACOM 90.1 | TACOM 57.75 | APC | |
| b. Vertical distance above ground at full load static position | 36.0 | 54.0 | 46.5 | 34 | TACOM 36.2 | TACOM 41.875 | APC | |

Table 2

Summary of Vehicle Characteristics and Performance Data for Tracked Vehicles

| Characteristics | Source of Data | | Source of Data | | Source of Data | |
|--|----------------|--------|----------------|--------|----------------|-------|
| | M548 | ML13A1 | ML16 | M571 | | |
| 1. Vehicle cone index (one-pass) | 25 | 20 | 12 | 11 | WES | WES |
| 2. Cross-country gross weight, fully equipped plus payload and personnel | | | | | | |
| a. Track | | | | | | |
| (1) Left 1st unit, lb | | 11,900 | 5,300 | 2063.5 | WES | WES |
| 2d Unit, lb | | -- | -- | 2063.5 | -- | WES |
| (2) Right 1st unit, lb | | 11,900 | 5,300 | 1936.5 | WES | WES |
| 2d Unit, lb | | -- | -- | 1936.5 | -- | WES |
| b. Total gross weight, lb | 27,041 | 23,800 | 10,600 | 8,000 | TACOM | TACOM |
| c. Cross-country payload, ton | 6.00 | 1.93 | 1.5 | 1 | -- | TACOM |
| 3. Dimensions | | | | | | |
| a. Overall length, in. | 226.5 | 191.5 | 181.0 | 234.0 | TACOM | TACOM |
| b. Height of leading edge, in. | 40 | 23.0 | 60.0 | 26.0 | PCFC | TACOM |
| c. Width of vehicle, in. | 105.5 | 105.75 | 82.0 | 64.5 | PCFC | TACOM |
| d. Horizontal distance from leading edge to front sprocket of vehicle, in. | 25.0 | 14.0 | 15.5 | 5.0 | PCFC | TACOM |

* WES - U.S. Army Engineer Waterways Experiment Station
 APG - Aberdeen Proving Ground

TACOM - U. S. Army Tank-Automotive Command
 PCFC - Pacific Car and Foundry

Table 2 (Continued)

| Characteristics | Source of Data | | Source of Data | | Source of Data | | Source of Data | |
|--|----------------|--------------|----------------|------------|----------------|------------|----------------|------------|
| | M548 | M113A1 | M116 | M571 | M116 | M571 | M116 | M571 |
| 4. Approach angle, deg | 57.0 | 70 | 75.0 | 78.0 | 75.0 | 78.0 | 75.0 | 78.0 |
| 5. Departure angle, deg | 35.0 | 40 | 60.0 | 41.0 | 60.0 | 41.0 | 60.0 | 41.0 |
| 6. Ground clearance of hull between tracks, in. | 16.0 | 16 | 14.0 | 12.0 | 14.0 | 12.0 | 14.0 | 12.0 |
| 7. Force leading edge can withstand, lb | 10,000 | no limit | 5,000 | 3,000 | 5,000 | 3,000 | 5,000 | 3,000 |
| 8. Winch capacity, lb | -- | NA* | 5,000 | 3,200 | 5,000 | 3,200 | 5,000 | 3,200 |
| 9. Water performance characteristics | | | | | | | | |
| a. Fording depth, normal fording, in. | no limit | amphibious | amphibious | amphibious | amphibious | amphibious | amphibious | amphibious |
| b. Water speed, mph | 3.5 | 3.0 | 4.2 | 1.7 | 4.2 | 1.7 | 4.2 | 1.7 |
| c. Depth below water line when loaded, in. | 66 | 54.0 16.0 | 56.0 | 45.0 | 56.0 | 45.0 | 56.0 | 45.0 |
| 10. Engine | | | | | | | | |
| a. Make | GM Diesel | GM Diesel | Chevrolet | Chevrolet | Chevrolet | Chevrolet | Chevrolet | Chevrolet |
| b. Model | 6V-M3 | 6V-53 | 2B3V8 | Corvair | 2B3V8 | Corvair | 2B3V8 | Corvair |
| c. Fuel type | Diesel | Diesel | Gas | Gas | Gas | Gas | Gas | Gas |
| d. Brake (BHP) or net (NHP) horsepower | 202 NHP | 202 NHP | 160 BHP | 86.0 BHP | 160 BHP | 86.0 BHP | 160 BHP | 86.0 BHP |
| e. Engine RPM at brake (BHP) or net (NHP) horsepower | 2800 NHP | 2800 NHP | 4600 BHP | 3600 BHP | 4600 BHP | 3600 BHP | 4600 BHP | 3600 BHP |

(Continued)

* NA - Not applicable

(2 of 5 sheets)

Table 2 (Continued)

| Characteristics | | M548 | Source of Data | M113A1 | Source of Data | M116 | Source of Data | M571 | Source of Data |
|--|--|----------|----------------------|----------|----------------------|-------------|----------------------|--------|----------------------|
| 11. Transmission | | | | | | | | | |
| a. Model | | -- | -- | TX-100-1 | TACOM | 305MC | TACOM | D1MA | TACOM |
| b. Ratios | | | | | | | | | |
| (1) 1st | | 3.81:1 | | 3.81:1 | APG | 4.09:1 | TACOM | 3.79:1 | TACOM |
| (2) 2d | | 1.93:1 | | 1.93:1 | APG | 2.63:1 | TACOM | 2.21:1 | TACOM |
| (3) 3d | | 1.00:1 | | 1.00:1 | APG | 1.55:1 | TACOM | 1.35:1 | TACOM |
| (4) 4th | | -- | -- | -- | -- | 1.00:1 | TACOM | 1.07:1 | TACOM |
| (5) 5th | | -- | -- | -- | -- | -- | -- | -- | -- |
| (6) 6th | | -- | -- | -- | -- | -- | -- | -- | -- |
| 12. Transfer case | | | | | | | | | |
| a. Model | | TX-100-1 | | -- | -- | -- | -- | -- | -- |
| b. Ratios | | | | | | | | | |
| (1) High | | 1:1 | | 0.778:1 | APG | 1.52:1 | TACOM | 3.04:1 | APG |
| (2) Low | | 13.31:1 | | -- | -- | NA | NA | 1.00:1 | APG |
| 13. Final drive | | | | | | | | | |
| a. Type | | -- | -- | -- | -- | WG/GS-100-1 | TACOM | -- | -- |
| b. Ratio | | 4.31:1 | | 3.93:1 | TACOM | 4.17:1 | TACOM | 3.89:1 | TACOM |
| 14. Track data | | | | | | | | | |
| a. Length of track in contact with ground, in. | | | | | | | | | |
| (1) 1st unit | | 111.0 | | 105.0 | APG | 103.0 | APG | 52.0 | APG |
| (2) 2d unit | | -- | -- | -- | -- | NA | NA | 52.0 | APG |

(Continued)

(3 of 5 sheets)

Table 2 (Continued)

| Characteristics | Source of Data | | Source of Data | | Source of Data | | Source of Data | |
|--|----------------|--------|----------------|------|----------------|------|----------------|------|
| | M548 | M113A1 | M116 | M571 | M571 | M571 | M571 | M571 |
| b. Width of track, in | 15.0 | 15.0 | 20.0 | 18.0 | 18.0 | 18.0 | 18.0 | 18.0 |
| c. Grouser height, in. | <1.5 | <1.5 | <1.5 | <1.5 | <1.5 | <1.5 | <1.5 | <1.5 |
| d. Total number of bogies in contact with ground | 10 | 10 | 10 | 16 | 16 | 16 | 16 | 16 |
| e. Area of one track shoe, sq in. | 90.0 | 90.0 | 80.0 | 85.5 | 85.5 | 85.5 | 85.5 | 85.5 |
| f. No. of tracks | 2 | 2 | 2 | 4 | 4 | 4 | 4 | 4 |
| 15. Steering data | | | | | | | | |
| a. Turning radius at a forward speed determined from point at center of outside track, ft | 14.0 | 12.7 | 11.0 | 40.1 | 40.1 | 40.1 | 40.1 | 40.1 |
| b. Horizontal distance from leading edge of vehicle to midpoint of track in contact with ground, in. | 107.4 | 92.25 | 91.0 | 57.0 | 57.0 | 57.0 | 57.0 | 57.0 |
| c. Width of track, in. | 15.0 | 15.0 | 20.0 | 18.0 | 18.0 | 18.0 | 18.0 | 18.0 |
| 16. Articulated characteristics | | | | | | | | |
| a. Distance from leading edge of vehicle to articulated joint, in. | -- | NA | NA | NA | NA | NA | NA | NA |
| b. Maximum pitch angle, deg | -- | NA | NA | NA | NA | NA | NA | NA |
| c. Maximum roll angle, deg | -- | NA | NA | NA | NA | NA | NA | NA |
| d. Maximum yaw angle, deg | -- | NA | NA | NA | NA | NA | NA | NA |

(Continued)

(4 of 5 sheets)

Table 2 (Concluded)

| Characteristics | Source of Data | ML13A1 | Source of Data | ML16 | Source of Data | M571 | Source of Data |
|---|----------------|--------|----------------|-------|----------------|------|----------------|
| 17. Center of gravity location | | | | | | | |
| a. Horizontal distance from front sprocket, in. | | | | | | | |
| Front unit | 67.0 | 78 | TACOM | 78.25 | TACOM | 51.0 | APG |
| Rear Unit | | -- | -- | -- | -- | 49.5 | APG |
| b. Vertical distance above bottom of track, in. | | | | | | | |
| Front | 29.0 | 39 | TACOM | 31.25 | TACOM | 28.2 | APG |
| Rear | | -- | -- | -- | -- | 19.1 | APG |

Table 3
Predicted Vehicle Performance in Km. on Actual Terrain Types

| Type | Speed km/h | Wheeled Vehicle | | | | Tracked Vehicle | | | |
|------|---------------|-----------------|----------------------------|--------------|--------------------------|-----------------|----------------------------|--------------|--------------------------|
| | | Fuel Con- | sump- tion gall/mile | Speed mph | Deliv- ery ton-mph | Fuel Con- | sump- tion gall/mile | Speed mph | Deliv- ery ton-mph |
| 1 | 9.1 | 1.3 | 1.5 | 6.5 | 36.0 | 1.1 | 1.1 | 6.6 | 6.6 |
| 2 | 12.6 | 1.0 | 1.3 | 9.7 | 52.0 | 1.0 | 1.0 | 9.7 | 9.7 |
| 3 | 15.3 | 0.7 | 1.1 | 12.7 | 57.6 | 0.8 | 0.8 | 12.7 | 12.7 |
| 4 | 18.1 | 0.9 | 1.5 | 15.3 | 60.8 | 1.1 | 1.1 | 15.3 | 15.3 |
| 5 | 23.2 | 0.4 | 1.0 | 18.1 | 60.8 | 0.7 | 0.7 | 18.1 | 18.1 |
| 6 | 13.2 | 1.0 | 1.4 | 6.8 | 54.4 | 0.8 | 0.8 | 6.8 | 6.8 |
| 7 | 11.1 | 1.3 | 1.5 | 5.1 | 44.4 | 0.5 | 0.5 | 5.1 | 5.1 |
| 8 | 27.2 | 0.2 | 0.6 | 23.2 | 120.0 | 0.2 | 0.2 | 23.2 | 23.2 |
| 9 | 21.1 | 0.3 | 0.7 | 18.1 | 120.0 | 0.3 | 0.3 | 18.1 | 18.1 |
| 10 | 16.2 | 0.8 | 1.0 | 13.2 | 120.0 | 0.7 | 0.7 | 13.2 | 13.2 |
| 11 | 9.4 | 1.2 | 1.5 | 6.8 | 120.0 | 0.8 | 0.8 | 6.8 | 6.8 |
| 12 | 11.1 | 1.3 | 1.5 | 5.1 | 120.0 | 0.5 | 0.5 | 5.1 | 5.1 |
| 13 | 11.1 | 1.3 | 1.5 | 5.1 | 120.0 | 0.5 | 0.5 | 5.1 | 5.1 |
| 14 | 9.1 | 1.3 | 1.5 | 5.1 | 120.0 | 0.5 | 0.5 | 5.1 | 5.1 |
| 15 | 9.1 | 1.3 | 1.5 | 5.1 | 120.0 | 0.5 | 0.5 | 5.1 | 5.1 |
| 16 | 9.1 | 1.3 | 1.5 | 5.1 | 120.0 | 0.5 | 0.5 | 5.1 | 5.1 |
| 17 | 12.6 | 0.8 | 1.1 | 10.5 | 120.0 | 0.8 | 0.8 | 10.5 | 10.5 |
| 18 | 12.6 | 0.8 | 1.1 | 10.5 | 120.0 | 0.8 | 0.8 | 10.5 | 10.5 |
| 19 | 27.2 | 0.2 | 0.6 | 23.2 | 120.0 | 0.2 | 0.2 | 23.2 | 23.2 |
| 20 | 23.2 | 0.2 | 0.6 | 20.0 | 120.0 | 0.2 | 0.2 | 20.0 | 20.0 |
| 21 | 16.2 | 0.8 | 1.0 | 13.2 | 120.0 | 0.7 | 0.7 | 13.2 | 13.2 |
| 22 | 9.1 | 1.3 | 1.5 | 5.1 | 120.0 | 0.5 | 0.5 | 5.1 | 5.1 |
| 23 | 27.2 | 0.2 | 0.6 | 23.2 | 120.0 | 0.2 | 0.2 | 23.2 | 23.2 |
| 24 | 9.0 | 1.4 | 1.5 | 7.5 | 120.0 | 0.7 | 0.7 | 7.5 | 7.5 |
| 25 | 13.2 | 1.0 | 1.4 | 10.5 | 120.0 | 0.8 | 0.8 | 10.5 | 10.5 |
| 26 | 18.3 | 0.7 | 1.0 | 15.3 | 120.0 | 0.6 | 0.6 | 15.3 | 15.3 |
| 27 | 12.6 | 0.8 | 1.1 | 10.5 | 120.0 | 0.8 | 0.8 | 10.5 | 10.5 |
| 28 | 12.6 | 0.8 | 1.1 | 10.5 | 120.0 | 0.8 | 0.8 | 10.5 | 10.5 |
| 29 | 27.2 | 0.2 | 0.6 | 23.2 | 120.0 | 0.2 | 0.2 | 23.2 | 23.2 |
| 30 | 27.2 | 0.2 | 0.6 | 23.2 | 120.0 | 0.2 | 0.2 | 23.2 | 23.2 |
| 31 | 18.3 | 0.7 | 1.0 | 15.3 | 120.0 | 0.6 | 0.6 | 15.3 | 15.3 |
| 32 | 12.6 | 0.8 | 1.1 | 10.5 | 120.0 | 0.8 | 0.8 | 10.5 | 10.5 |
| 33 | 12.6 | 0.8 | 1.1 | 10.5 | 120.0 | 0.8 | 0.8 | 10.5 | 10.5 |
| 34 | 12.6 | 0.8 | 1.1 | 10.5 | 120.0 | 0.8 | 0.8 | 10.5 | 10.5 |
| 35 | 18.3 | 0.7 | 1.0 | 15.3 | 120.0 | 0.6 | 0.6 | 15.3 | 15.3 |
| 36 | 12.6 | 0.8 | 1.1 | 10.5 | 120.0 | 0.8 | 0.8 | 10.5 | 10.5 |
| 37 | 12.6 | 0.8 | 1.1 | 10.5 | 120.0 | 0.8 | 0.8 | 10.5 | 10.5 |
| 38 | 12.6 | 0.8 | 1.1 | 10.5 | 120.0 | 0.8 | 0.8 | 10.5 | 10.5 |
| 39 | 12.6 | 0.8 | 1.1 | 10.5 | 120.0 | 0.8 | 0.8 | 10.5 | 10.5 |
| 40 | 12.6 | 0.8 | 1.1 | 10.5 | 120.0 | 0.8 | 0.8 | 10.5 | 10.5 |
| 41 | 12.6 | 0.8 | 1.1 | 10.5 | 120.0 | 0.8 | 0.8 | 10.5 | 10.5 |
| 42 | 12.6 | 0.8 | 1.1 | 10.5 | 120.0 | 0.8 | 0.8 | 10.5 | 10.5 |
| 43 | 12.6 | 0.8 | 1.1 | 10.5 | 120.0 | 0.8 | 0.8 | 10.5 | 10.5 |
| 44 | 12.6 | 0.8 | 1.1 | 10.5 | 120.0 | 0.8 | 0.8 | 10.5 | 10.5 |
| 45 | 12.6 | 0.8 | 1.1 | 10.5 | 120.0 | 0.8 | 0.8 | 10.5 | 10.5 |

The vehicle was immobilized on each rice dike. A 20-minute penalty was assessed for each immobilized and included in the speed calculation.
The size and density of trees required that some trees be cut in order for the vehicle to negotiate the terrain. The speed was computed using a 5-minute penalty for that needed to be cut.

[illegible]

The vehicle was immobilized on each rice dike. A 20-minute penalty was assessed for each immobilization and included in the speed calculation. The driver's penalty points were assessed for each immobilization and included in the speed calculation. The driver's penalty points were assessed for each immobilization and included in the speed calculation. The driver's penalty points were assessed for each immobilization and included in the speed calculation.

Table 3 (Continued)

| Per- tain Type | Wheeled Vehicles | | | | | | | | | | Tracked Vehicles | | | | | | | | | | | | | | | | | | | | |
|---------------------------|------------------|-----------------------------------|--------------------------|--------------|-----------------------------------|--------------------------|--------------|-----------------------------------|--------------------------|--------------|-----------------------------------|--------------------------|--------------|-----------------------------------|--------------------------|--------------|-----------------------------------|--------------------------|--------------|-----------------------------------|--------------------------|--------------|-----------------------------------|--------------------------|--------------|-----------------------------------|--------------------------|--------------|-----------------------------------|-------|------|
| | M551 | | | | | M551 | | | | | M551 | | | | | M551 | | | | | M551 | | | | | | | | | | |
| Deliv- ery ton-mph | Speed mph | Con- sump- tion gal/mile | Deliv- ery ton-mph | Speed mph | Con- sump- tion gal/mile | Deliv- ery ton-mph | Speed mph | Con- sump- tion gal/mile | Deliv- ery ton-mph | Speed mph | Con- sump- tion gal/mile | Deliv- ery ton-mph | Speed mph | Con- sump- tion gal/mile | Deliv- ery ton-mph | Speed mph | Con- sump- tion gal/mile | Deliv- ery ton-mph | Speed mph | Con- sump- tion gal/mile | Deliv- ery ton-mph | Speed mph | Con- sump- tion gal/mile | Deliv- ery ton-mph | Speed mph | Con- sump- tion gal/mile | Deliv- ery ton-mph | Speed mph | Con- sump- tion gal/mile | | |
| 91 | 9.1 | 1.3 | 45.5 | 7.2 | 1.5 | 36.0 | 6.5 | 1.8 | 52.0 | 9.0 | 0.8 | 6.8 | 14.7 | 0.5 | 18.4 | 10.5 | 1.2 | 20.5 | 9.2 | 1.9 | 55.2 | 11.2 | 0.5 | 11.2 | 0.5 | 11.2 | 0.5 | 11.2 | 0.5 | 11.2 | |
| 92 | 18.8 | 1.6 | 94.0 | 14.8 | 1.8 | 74.0 | 11.8 | 2.0 | 94.4 | 11.6 | 0.6 | 8.7 | 36.5 | 0.2 | 45.6 | 12.2 | 1.0 | 12.2 | 14.3 | 2.8 | 56.4 | 14.2 | 0.9 | 22.4 | 0.3 | 22.4 | 0.3 | 22.4 | 0.3 | 22.4 | |
| 93 | 0.1** | 3.3 | 0.5 | 0.1** | 2.8 | 36.5 | 3.5 | 1.8 | 36.5 | 0.2 | 8.0 | 0.8 | 2.5 | 3.0 | 3.3 | 2.1 | 5.8 | 2.1 | 0.1** | 1.2 | 60.0 | 2.2 | 3.0 | 2.2 | 3.0 | 2.2 | 3.0 | 2.2 | 3.0 | 2.2 | |
| 94 | 9.1 | 1.3 | 45.5 | 7.2 | 1.5 | 36.0 | 6.5 | 1.8 | 52.0 | 9.0 | 0.8 | 6.8 | 14.7 | 0.5 | 18.4 | 10.5 | 1.2 | 20.5 | 9.2 | 1.9 | 55.2 | 11.2 | 0.5 | 11.2 | 0.5 | 11.2 | 0.5 | 11.2 | 0.5 | 11.2 | |
| 95 | 9.4 | 1.3 | 47.0 | 8.0 | 1.5 | 40.0 | 5.8 | 2.0 | 46.4 | 8.0 | 0.8 | 6.7 | 8.8 | 0.8 | 11.0 | 11.0 | 1.1 | 11.1 | 8.1 | 2.4 | 50.4 | 10.6 | 1.3 | 15.9 | 1.1 | 15.9 | 1.1 | 15.9 | 1.1 | 15.9 | |
| 96 | 16.2 | 0.8 | 81.0 | 11.0 | 1.1 | 75.0 | 8.2 | 1.6 | 65.6 | 10.8 | 0.7 | 8.1 | 9.6 | 0.8 | 12.0 | 10.4 | 1.2 | 10.4 | 10.5 | 1.2 | 63.0 | 10.7 | 0.8 | 19.7 | 11.1 | 1.3 | 16.7 | 9.9 | 0.6 | 9.9 | |
| 97 | 18.7 | 0.8 | 93.5 | 15.6 | 1.1 | 78.0 | 8.2 | 1.6 | 65.6 | 16.0 | 0.4 | 12.0 | 24.6 | 0.3 | 30.8 | 27.4 | 0.4 | 27.4 | 10.5 | 1.2 | 63.0 | 24.8 | 0.8 | 41.7 | 20.8 | 0.7 | 31.2 | 14.8 | 0.4 | 14.8 | |
| 98 | 12.6 | 1.0 | 63.0 | 9.7 | 1.3 | 48.5 | 7.0 | 1.7 | 56.0 | 10.8 | 0.7 | 8.1 | 13.2 | 0.5 | 16.5 | 13.2 | 0.9 | 13.2 | 9.4 | 1.8 | 56.4 | 12.1 | 1.1 | 23.9 | 11.4 | 1.2 | 17.1 | 12.0 | 0.5 | 17.0 | |
| Net Season (60 or 40 MCI) | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 1 | 9.1 | 1.3 | 45.5 | 7.2 | 1.5 | 36.0 | 6.5 | 1.8 | 52.0 | 9.0 | 0.8 | 6.8 | 14.7 | 0.5 | 18.4 | 10.5 | 1.2 | 20.5 | 9.2 | 1.9 | 55.2 | 11.2 | 0.5 | 11.2 | 0.5 | 11.2 | 0.5 | 11.2 | 0.5 | 11.2 | |
| 2 | 12.6 | 1.0 | 63.0 | 9.7 | 1.3 | 48.5 | 7.0 | 1.7 | 56.0 | 10.8 | 0.7 | 8.1 | 13.2 | 0.5 | 16.5 | 13.2 | 0.9 | 13.2 | 9.4 | 1.8 | 56.4 | 12.1 | 1.1 | 23.9 | 11.4 | 1.2 | 17.1 | 12.0 | 0.5 | 17.0 | |
| 3 | 18.3 | 0.7 | 91.5 | 10.0 | 1.3 | 50.0 | 7.2 | 1.6 | 57.6 | 11.6 | 0.6 | 8.7 | 36.5 | 0.2 | 45.6 | 12.2 | 1.0 | 12.2 | 10.0 | 1.5 | 60.0 | 10.0 | 1.5 | 60.0 | 10.0 | 1.5 | 60.0 | 10.0 | 1.5 | 60.0 | |
| 4 | 14.1 | 0.9 | 70.5 | 7.8 | 1.5 | 39.0 | 6.5 | 1.8 | 52.0 | 8.0 | 0.8 | 6.8 | 14.7 | 0.5 | 18.4 | 10.5 | 1.2 | 20.5 | 10.0 | 1.5 | 60.0 | 10.0 | 1.5 | 60.0 | 10.0 | 1.5 | 60.0 | 10.0 | 1.5 | 60.0 | |
| 5 | 25.2 | 0.4 | 126.0 | 16.3 | 1.0 | 81.5 | 7.6 | 1.5 | 60.8 | 14.4 | 0.8 | 14.0 | 6.8 | 1.8 | 20.8 | 14.4 | 0.8 | 14.4 | 8.4 | 2.4 | 50.4 | 10.6 | 1.3 | 15.9 | 1.1 | 15.9 | 1.1 | 15.9 | 1.1 | 15.9 | |
| 6 | 13.2 | 1.0 | 66.0 | 8.8 | 1.4 | 44.0 | 6.8 | 1.8 | 54.4 | 11.6 | 0.6 | 8.7 | 36.5 | 0.2 | 45.6 | 12.2 | 1.0 | 12.2 | 8.4 | 2.4 | 50.4 | 10.6 | 1.3 | 15.9 | 1.1 | 15.9 | 1.1 | 15.9 | 1.1 | 15.9 | |
| 7 | 8.3 | 1.5 | 41.5 | 6.6 | 1.6 | 33.0 | 5.1 | 2.0 | 48.8 | 6.8 | 0.8 | 6.7 | 8.8 | 0.8 | 11.0 | 11.0 | 1.1 | 11.1 | 5.9 | 4.1 | 31.8 | 14.2 | 0.9 | 22.4 | 0.3 | 22.4 | 0.3 | 22.4 | 0.3 | 22.4 | |
| 8 | 21.2 | 0.2 | 136.0 | 23.5 | 0.6 | 117.5 | 15.0 | 0.7 | 120.0 | 20.0 | 0.4 | 12.0 | 24.6 | 0.3 | 30.8 | 27.4 | 0.4 | 27.4 | 26.2 | 0.4 | 157.2 | 14.2 | 0.9 | 22.4 | 0.3 | 22.4 | 0.3 | 22.4 | 0.3 | 22.4 | |
| 9 | 0.1** | 3.3 | 0.5 | 0.1** | 2.8 | 36.5 | 3.5 | 1.8 | 36.5 | 0.2 | 8.0 | 0.8 | 2.5 | 3.0 | 3.3 | 2.1 | 5.8 | 2.1 | 0.1** | 1.2 | 60.0 | 2.2 | 3.0 | 2.2 | 3.0 | 2.2 | 3.0 | 2.2 | 3.0 | 2.2 | |
| 10 | 16.2 | 0.8 | 81.0 | 10.0 | 1.3 | 50.0 | 7.2 | 1.6 | 57.6 | 11.6 | 0.6 | 8.7 | 36.5 | 0.2 | 45.6 | 12.2 | 1.0 | 12.2 | 10.0 | 1.5 | 60.0 | 10.0 | 1.5 | 60.0 | 10.0 | 1.5 | 60.0 | 10.0 | 1.5 | 60.0 | |
| 11 | 9.4 | 1.3 | 47.0 | 8.0 | 1.5 | 40.0 | 5.8 | 2.0 | 46.4 | 8.0 | 0.8 | 6.7 | 8.8 | 0.8 | 11.0 | 11.0 | 1.1 | 11.1 | 8.1 | 2.4 | 50.4 | 10.6 | 1.3 | 15.9 | 1.1 | 15.9 | 1.1 | 15.9 | 1.1 | 15.9 | |
| 12 | 0.1* | 2.2 | 0.5 | 0.1* | 2.3 | 36.0 | 6.5 | 1.8 | 52.0 | 9.0 | 0.8 | 6.8 | 14.7 | 0.5 | 18.4 | 10.5 | 1.2 | 20.5 | 8.5 | 2.3 | 51.0 | 10.0 | 1.5 | 60.0 | 10.0 | 1.5 | 60.0 | 10.0 | 1.5 | 60.0 | |
| 13 | 0.1** | 3.3 | 0.5 | 0.1** | 2.8 | 36.5 | 3.5 | 1.8 | 36.5 | 0.2 | 8.0 | 0.8 | 2.5 | 3.0 | 3.3 | 2.1 | 5.8 | 2.1 | 0.1** | 1.2 | 60.0 | 2.2 | 3.0 | 2.2 | 3.0 | 2.2 | 3.0 | 2.2 | 3.0 | 2.2 | |
| 14 | 9.0 | 1.4 | 45.0 | 7.5 | 1.5 | 38.0 | 5.7 | 2.1 | 45.6 | 7.6 | 1.5 | 38.0 | 5.7 | 2.1 | 45.6 | 7.6 | 1.5 | 38.0 | 6.8 | 3.3 | 40.8 | 10.8 | 1.1 | 63.6 | 1.1 | 63.6 | 1.1 | 63.6 | 1.1 | 63.6 | |
| 15 | 1.0 | 1.3 | 37.5 | 7.2 | 1.5 | 36.0 | 6.5 | 1.8 | 52.0 | 9.0 | 0.8 | 6.8 | 14.7 | 0.5 | 18.4 | 10.5 | 1.2 | 20.5 | 6.8 | 3.3 | 40.8 | 10.8 | 1.1 | 63.6 | 1.1 | 63.6 | 1.1 | 63.6 | 1.1 | 63.6 | |
| 16 | 9.1 | 1.3 | 45.5 | 7.2 | 1.5 | 36.0 | 6.5 | 1.8 | 52.0 | 9.0 | 0.8 | 6.8 | 14.7 | 0.5 | 18.4 | 10.5 | 1.2 | 20.5 | 9.2 | 1.9 | 55.2 | 11.2 | 0.5 | 11.2 | 0.5 | 11.2 | 0.5 | 11.2 | 0.5 | 11.2 | |
| 17 | 18.7 | 0.8 | 93.5 | 15.6 | 1.1 | 78.0 | 8.2 | 1.6 | 65.6 | 16.0 | 0.4 | 12.0 | 24.6 | 0.3 | 30.8 | 27.4 | 0.4 | 27.4 | 10.5 | 1.2 | 63.0 | 24.8 | 0.8 | 41.7 | 20.8 | 0.7 | 31.2 | 14.8 | 0.4 | 14.8 | |
| 18 | 12.6 | 1.0 | 63.0 | 9.7 | 1.3 | 48.5 | 7.0 | 1.7 | 56.0 | 10.8 | 0.7 | 8.1 | 13.2 | 0.5 | 16.5 | 13.2 | 0.9 | 13.2 | 9.4 | 1.8 | 56.4 | 12.1 | 1.1 | 23.9 | 11.4 | 1.2 | 17.1 | 12.0 | 0.5 | 17.0 | |
| 19 | 27.2 | 0.2 | 136.0 | 23.5 | 0.6 | 117.5 | 15.0 | 0.7 | 120.0 | 20.0 | 0.4 | 12.0 | 24.6 | 0.3 | 30.8 | 27.4 | 0.4 | 27.4 | 18.2 | 0.7 | 109.2 | 18.2 | 0.7 | 109.2 | 18.2 | 0.7 | 109.2 | 18.2 | 0.7 | 109.2 | |
| 20 | 20.0 | 0.6 | 100.0 | 13.2 | 0.9 | 66.0 | 12.0 | 0.9 | 96.0 | 12.0 | 0.9 | 96.0 | 12.0 | 0.9 | 96.0 | 12.0 | 0.9 | 96.0 | 18.5 | 0.7 | 111.0 | 18.5 | 0.7 | 111.0 | 18.5 | 0.7 | 111.0 | 18.5 | 0.7 | 111.0 | |
| 21 | 16.2 | 0.8 | 81.0 | 10.0 | 1.3 | 50.0 | 7.2 | 1.6 | 57.6 | 11.6 | 0.6 | 8.7 | 36.5 | 0.2 | 45.6 | 12.2 | 1.0 | 12.2 | 10.0 | 1.5 | 60.0 | 10.0 | 1.5 | 60.0 | 10.0 | 1.5 | 60.0 | 10.0 | 1.5 | 60.0 | |
| 22 | 9.1 | 1.3 | 45.5 | 7.2 | 1.5 | 36.0 | 6.5 | 1.8 | 52.0 | 9.0 | 0.8 | 6.8 | 14.7 | 0.5 | 18.4 | 10.5 | 1.2 | 20.5 | 9.2 | 1.9 | 55.2 | 11.2 | 0.5 | 11.2 | 0.5 | 11.2 | 0.5 | 11.2 | 0.5 | 11.2 | |
| 23 | 25.2 | 0.4 | 126.0 | 16.3 | 1.0 | 81.5 | 7.6 | 1.5 | 60.8 | 14.4 | 0.8 | 14.0 | 6.8 | 1.8 | 20.8 | 14.4 | 0.8 | 14.4 | 10.6 | 1.1 | 63.6 | 1.1 | 63.6 | 1.1 | 63.6 | 1.1 | 63.6 | 1.1 | 63.6 | 1.1 | 63.6 |
| 24 | 9.0 | 1.4 | 45.0 | 7.6 | 1.5 | 38.0 | 5.7 | 2.1 | 45.6 | 7.6 | 1.5 | 38.0 | 5.7 | 2.1 | 45.6 | 7.6 | 1.5 | 38.0 | 10.6 | 1.1 | 63.6 | 1.1 | 63.6 | 1.1 | 63.6 | 1.1 | 63.6 | 1.1 | 63.6 | 1.1 | 63.6 |
| 25 | 19.0 | 1.0 | 62.0 | 8.8 | 1.4 | 44.0 | 6.8 | 1.8 | 54.4 | 11.6 | 0.6 | 8.7 | 36.5 | 0.2 | 45.6 | 12.2 | 1.0 | 12.2 | 8.4 | 2.4 | 50.4 | 10.6 | 1.3 | 15.9 | 1.1 | 15.9 | 1.1 | 15.9 | 1.1 | 15.9 | |
| 26 | 18.3 | 0.7 | 91.5 | 10.0 | 1.3 | 50.0 | 7.2 | 1.6 | 57.6 | 11.6 | 0.6 | 8.7 | 36.5 | 0.2 | 45.6 | 12.2 | 1.0 | 12.2 | 10.0 | 1.5 | 60.0 | 10.0 | 1.5 | 60.0 | 10.0 | 1.5 | 60.0 | 10.0 | 1.5 | 60.0 | |
| 27 | 9.1 | 1.3 | 45.5 | 7.2 | 1.5 | 36.0 | 6.5 | 1.8 | 52.0 | 9.0 | 0.8 | 6.8 | 14.7 | 0.5 | 18.4 | 10.5 | 1.2 | 20.5 | 9.2 | 1.9 | 55.2 | 11.2 | 0.5 | 11.2 | 0.5 | 11.2 | 0.5 | 11.2 | 0.5 | 11.2 | |
| 28 | 18.3 | 0.7 | 91.5 | 10.0 | 1.3 | 50.0 | 7.2 | 1.6 | 57.6 | 11.6 | 0.6 | 8.7 | 36.5 | 0.2 | 45.6 | 12.2 | 1.0 | 12.2 | 10.0 | 1.5 | 60.0 | 10.0 | 1.5 | 60.0 | 10.0 | 1.5 | 60.0 | 10.0 | 1.5 | 60.0 | |
| 29 | 9.1 | 1.3 | 45.5 | 7.2 | 1.5 | 36.0 | 6.5 | 1.8 | 52.0 | 9.0 | 0.8 | 6.8 | 14.7 | 0.5 | 18.4 | 10.5 | 1.2 | 20.5 | 9.2 | 1.9 | 55.2 | 11.2 | 0.5 | 11.2 | 0.5 | 11.2 | 0.5 | 11.2 | 0.5 | 11.2 | |
| 30 | 0.1* | 3.3 | 0.5 | 0.1* | 2.3 | 36.0 | 6.5 | 1.8 | 52.0 | 9.0 | 0.8 | 6.8 | 14.7 | 0.5 | 18.4 | 10.5 | 1.2 | 20.5 | 8.5 | 2.3 | 51.0 | 10.0 | 1.5 | 60.0 | 10.0 | 1.5 | 60.0 | 10.0 | 1.5 | 60.0 | |
| 31 | 18.3 | 0.7 | 91.5 | 10.0 | 1.3 | 50.0 | 7.2 | 1.6 | 57.6 | 11.6 | 0.6 | 8.7 | 36.5 | 0.2 | 45.6 | 12.2 | 1.0 | 12.2 | 10.0 | 1.5 | 60.0 | 10.0 | 1.5 | 60.0 | 10.0 | 1.5 | 60.0 | 10.0 | 1.5 | 60.0 | |
| 32 | 0.1* | 3.3 | 0.5 | 0.1* | 2.3 | 36.0 | 6.5 | 1.8 | 52.0 | 9.0 | 0.8 | 6.8 | 14.7 | 0.5 | 18.4 | 10.5 | 1.2 | 20.5 | 9.9 | 1.5 | 59.4 | 10.0 | 1.5 | 60.0 | 10.0 | 1.5 | 60.0 | 10.0 | 1.5 | 60.0 | |

* The vehicle was immobilized on each rise dlm. A 20-minute penalty was assessed for each immobilization and included in the speed calculation.
 ** The size and density of trees required that some trees be cut in order for the vehicle to negotiate the terrain. The speed was computed using a
 * 20-minute penalty for each tree that needed to be cut.

(Continued)

Table 3 (Continued)

| Per- centage of trees in each size class | Modelled Vehicles | | | | | | | | | | Tracked Vehicles | | | | | | | | | |
|---|---|---|-----------------|---|---|---|---|-----------------|---|---|---|---|-----------------|---|---|---|---|-----------------|---|---|
| | 1956 | | | | | 1957 | | | | | 1958 | | | | | 1959 | | | | |
| | Fuel Consumption gallons per mile | Deliv- ery rate gallons per hour | Speed m.p.h. | Deliv- ery rate gallons per hour | Fuel Consumption gallons per mile | Fuel Consumption gallons per mile | Deliv- ery rate gallons per hour | Speed m.p.h. | Deliv- ery rate gallons per hour | Fuel Consumption gallons per mile | Fuel Consumption gallons per mile | Deliv- ery rate gallons per hour | Speed m.p.h. | Deliv- ery rate gallons per hour | Fuel Consumption gallons per mile | Fuel Consumption gallons per mile | Deliv- ery rate gallons per hour | Speed m.p.h. | Deliv- ery rate gallons per hour | Fuel Consumption gallons per mile |
| 33 | 16.2 | 0.8 | 81.0 | 11.1 | 55.0 | 7.6 | 1.5 | 50.8 | 62.4 | 10.4 | 1.3 | 62.4 | 10.4 | 1.3 | 62.4 | 10.4 | 1.3 | 62.4 | 10.4 | 1.3 |
| 34 | 0.1* | 3.3 | 0.5 | 0.1* | 2.8 | 0.5 | 7.0 | 1.7 | 56.0 | 9.4 | 1.8 | 56.4 | 9.4 | 1.8 | 56.4 | 9.4 | 1.8 | 56.4 | 9.4 | 1.8 |
| 35 | 18.3 | 0.7 | 91.5 | 10.0 | 1.3 | 50.0 | 7.2 | 1.6 | 57.6 | 10.0 | 1.5 | 60.0 | 10.0 | 1.5 | 60.0 | 10.0 | 1.5 | 60.0 | 10.0 | 1.5 |
| 36 | 16.2 | 0.8 | 81.0 | 11.1 | 55.0 | 8.2 | 1.6 | 65.6 | 63.0 | 10.5 | 1.2 | 63.0 | 10.5 | 1.2 | 63.0 | 10.5 | 1.2 | 63.0 | 10.5 | 1.2 |
| 36A | 12.0 | 1.2 | 60.0 | 7.4 | 1.6 | 37.0 | 6.9 | 1.8 | 55.2 | 9.2 | 1.9 | 55.2 | 9.2 | 1.9 | 55.2 | 9.2 | 1.9 | 55.2 | 9.2 | 1.9 |
| 37 | 18.7 | 0.8 | 93.5 | 15.6 | 1.1 | 78.0 | 8.2 | 1.6 | 65.6 | 10.5 | 1.2 | 63.0 | 10.5 | 1.2 | 63.0 | 10.5 | 1.2 | 63.0 | 10.5 | 1.2 |
| 38 | 18.7 | 0.8 | 93.5 | 15.6 | 1.1 | 78.0 | 8.2 | 1.6 | 65.6 | 10.5 | 1.2 | 63.0 | 10.5 | 1.2 | 63.0 | 10.5 | 1.2 | 63.0 | 10.5 | 1.2 |
| 39 | 19.2 | 0.8 | 96.0 | 16.0 | 1.1 | 80.0 | 9.5 | 1.5 | 76.0 | 12.8 | 2.7 | 48.8 | 12.8 | 2.7 | 48.8 | 12.8 | 2.7 | 48.8 | 12.8 | 2.7 |
| 40 | 10.6 | 1.2 | 51.0 | 8.2 | 2.8 | 41.0 | 3.8 | 2.8 | 30.4 | 0.1** | 5.9 | 0.6 | 0.1** | 5.9 | 0.6 | 0.1** | 5.9 | 0.6 | 0.1** | 5.9 |
| 41 | 0.1** | 3.3 | 0.5 | 0.1** | 2.8 | 0.5 | 7.0 | 1.7 | 56.0 | 9.4 | 1.8 | 56.4 | 9.4 | 1.8 | 56.4 | 9.4 | 1.8 | 56.4 | 9.4 | 1.8 |
| 42 | 15.3 | 1.2 | 76.5 | 11.4 | 1.6 | 57.0 | 7.2 | 2.1 | 57.6 | 7.2 | 3.0 | 43.2 | 7.2 | 3.0 | 43.2 | 7.2 | 3.0 | 43.2 | 7.2 | 3.0 |
| 43 | 0.1** | 3.3 | 0.5 | 0.1** | 2.8 | 0.5 | 7.0 | 1.7 | 56.0 | 9.4 | 1.8 | 56.4 | 9.4 | 1.8 | 56.4 | 9.4 | 1.8 | 56.4 | 9.4 | 1.8 |
| 44 | 13.8 | 1.9 | 69.0 | 11.6 | 1.7 | 58.0 | 8.2 | 2.1 | 65.6 | 10.2 | 1.4 | 61.2 | 10.2 | 1.4 | 61.2 | 10.2 | 1.4 | 61.2 | 10.2 | 1.4 |
| 45 | 0.1** | 3.3 | 0.5 | 0.1** | 2.8 | 0.5 | 7.0 | 1.7 | 56.0 | 9.4 | 1.8 | 56.4 | 9.4 | 1.8 | 56.4 | 9.4 | 1.8 | 56.4 | 9.4 | 1.8 |
| 46 | 0.1** | 3.3 | 0.5 | 0.1** | 2.8 | 0.5 | 7.0 | 1.7 | 56.0 | 9.4 | 1.8 | 56.4 | 9.4 | 1.8 | 56.4 | 9.4 | 1.8 | 56.4 | 9.4 | 1.8 |
| 47 | 0.1* | 3.3 | 0.5 | 0.1* | 2.8 | 0.5 | 7.0 | 1.7 | 56.0 | 9.4 | 1.8 | 56.4 | 9.4 | 1.8 | 56.4 | 9.4 | 1.8 | 56.4 | 9.4 | 1.8 |
| 48 | 9.0 | 1.4 | 45.0 | 7.6 | 1.5 | 38.0 | 5.7 | 2.1 | 45.6 | 8.8 | 3.3 | 40.8 | 8.8 | 3.3 | 40.8 | 8.8 | 3.3 | 40.8 | 8.8 | 3.3 |
| 49 | 13.2 | 1.1 | 66.0 | 11.6 | 1.2 | 58.0 | 7.4 | 1.7 | 59.2 | 8.6 | 2.3 | 51.6 | 8.6 | 2.3 | 51.6 | 8.6 | 2.3 | 51.6 | 8.6 | 2.3 |
| 50 | 13.2 | 1.1 | 66.0 | 11.6 | 1.2 | 58.0 | 7.4 | 1.7 | 59.2 | 8.6 | 2.3 | 51.6 | 8.6 | 2.3 | 51.6 | 8.6 | 2.3 | 51.6 | 8.6 | 2.3 |
| 51 | 17.3 | 1.1 | 68.5 | 14.6 | 1.5 | 73.0 | 9.2 | 1.7 | 73.6 | 9.8 | 1.6 | 58.8 | 9.8 | 1.6 | 58.8 | 9.8 | 1.6 | 58.8 | 9.8 | 1.6 |
| 52 | 18.3 | 0.7 | 91.5 | 10.0 | 1.3 | 50.0 | 7.2 | 1.6 | 57.6 | 10.0 | 1.5 | 60.0 | 10.0 | 1.5 | 60.0 | 10.0 | 1.5 | 60.0 | 10.0 | 1.5 |
| 53 | 12.6 | 1.0 | 63.0 | 9.7 | 1.3 | 48.5 | 7.0 | 1.7 | 56.0 | 9.4 | 1.8 | 56.4 | 9.4 | 1.8 | 56.4 | 9.4 | 1.8 | 56.4 | 9.4 | 1.8 |
| 54 | 16.2 | 0.8 | 81.0 | 11.1 | 55.0 | 7.2 | 1.6 | 57.6 | 63.0 | 10.5 | 1.2 | 63.0 | 10.5 | 1.2 | 63.0 | 10.5 | 1.2 | 63.0 | 10.5 | 1.2 |
| 55 | 16.2 | 0.8 | 81.0 | 11.1 | 55.0 | 7.2 | 1.6 | 57.6 | 63.0 | 10.5 | 1.2 | 63.0 | 10.5 | 1.2 | 63.0 | 10.5 | 1.2 | 63.0 | 10.5 | 1.2 |
| 56 | 13.2 | 1.0 | 66.0 | 8.8 | 1.4 | 44.0 | 6.8 | 1.8 | 54.4 | 8.4 | 2.4 | 50.4 | 8.4 | 2.4 | 50.4 | 8.4 | 2.4 | 50.4 | 8.4 | 2.4 |
| 56A | 8.3 | 1.5 | 41.5 | 6.6 | 1.6 | 33.0 | 6.1 | 2.0 | 40.8 | 8.0 | 2.6 | 48.0 | 8.0 | 2.6 | 48.0 | 8.0 | 2.6 | 48.0 | 8.0 | 2.6 |
| 57 | 13.3 | 1.0 | 66.5 | 9.0 | 1.3 | 45.0 | 6.8 | 1.8 | 54.4 | 7.8 | 2.7 | 46.8 | 7.8 | 2.7 | 46.8 | 7.8 | 2.7 | 46.8 | 7.8 | 2.7 |
| 58 | 0.1** | 3.3 | 0.5 | 0.1** | 2.8 | 0.5 | 7.0 | 1.7 | 56.0 | 9.4 | 1.8 | 56.4 | 9.4 | 1.8 | 56.4 | 9.4 | 1.8 | 56.4 | 9.4 | 1.8 |
| 59 | 0.1* | 3.3 | 0.5 | 0.1* | 2.8 | 0.5 | 7.0 | 1.7 | 56.0 | 9.4 | 1.8 | 56.4 | 9.4 | 1.8 | 56.4 | 9.4 | 1.8 | 56.4 | 9.4 | 1.8 |
| 60 | 17.6 | 1.0 | 68.0 | 14.8 | 1.3 | 74.0 | 10.2 | 1.6 | 81.6 | 12.4 | 0.9 | 74.4 | 12.4 | 0.9 | 74.4 | 12.4 | 0.9 | 74.4 | 12.4 | 0.9 |
| 61 | 18.7 | 0.8 | 93.5 | 15.6 | 1.1 | 78.0 | 8.2 | 1.6 | 65.6 | 10.5 | 1.2 | 63.0 | 10.5 | 1.2 | 63.0 | 10.5 | 1.2 | 63.0 | 10.5 | 1.2 |
| 62 | 13.2 | 1.1 | 66.0 | 11.6 | 1.2 | 58.0 | 7.4 | 1.7 | 59.2 | 8.6 | 2.3 | 51.6 | 8.6 | 2.3 | 51.6 | 8.6 | 2.3 | 51.6 | 8.6 | 2.3 |
| 63 | 13.2 | 1.0 | 66.0 | 8.8 | 1.4 | 44.0 | 6.8 | 1.8 | 54.4 | 8.4 | 2.4 | 50.4 | 8.4 | 2.4 | 50.4 | 8.4 | 2.4 | 50.4 | 8.4 | 2.4 |
| 64 | 25.2 | 0.4 | 126.0 | 16.4 | 1.0 | 82.0 | 7.8 | 1.5 | 62.4 | 10.6 | 1.1 | 61.6 | 10.6 | 1.1 | 61.6 | 10.6 | 1.1 | 61.6 | 10.6 | 1.1 |
| 65 | 12.6 | 1.0 | 63.0 | 9.7 | 1.3 | 48.5 | 7.0 | 1.7 | 56.0 | 9.4 | 1.8 | 56.4 | 9.4 | 1.8 | 56.4 | 9.4 | 1.8 | 56.4 | 9.4 | 1.8 |
| 66 | 9.1 | 1.3 | 45.5 | 7.2 | 1.5 | 36.0 | 6.5 | 1.8 | 52.0 | 9.2 | 1.9 | 55.2 | 9.2 | 1.9 | 55.2 | 9.2 | 1.9 | 55.2 | 9.2 | 1.9 |
| 67 | 9.3 | 1.4 | 46.5 | 7.8 | 1.6 | 39.0 | 5.8 | 2.0 | 46.4 | 8.6 | 2.3 | 51.6 | 8.6 | 2.3 | 51.6 | 8.6 | 2.3 | 51.6 | 8.6 | 2.3 |
| 68 | 0.1** | 3.3 | 0.5 | 0.1** | 2.8 | 0.5 | 7.0 | 1.7 | 56.0 | 9.4 | 1.8 | 56.4 | 9.4 | 1.8 | 56.4 | 9.4 | 1.8 | 56.4 | 9.4 | 1.8 |
| 69 | 12.6 | 1.0 | 63.0 | 9.7 | 1.3 | 48.5 | 7.0 | 1.7 | 56.0 | 9.4 | 1.8 | 56.4 | 9.4 | 1.8 | 56.4 | 9.4 | 1.8 | 56.4 | 9.4 | 1.8 |
| 70 | 12.6 | 1.0 | 63.0 | 9.7 | 1.3 | 48.5 | 7.0 | 1.7 | 56.0 | 9.4 | 1.8 | 56.4 | 9.4 | 1.8 | 56.4 | 9.4 | 1.8 | 56.4 | 9.4 | 1.8 |
| 71 | 14.4 | 1.0 | 72.0 | 11.0 | 1.1 | 55.0 | 7.7 | 1.6 | 61.6 | 9.2 | 1.9 | 55.2 | 9.2 | 1.9 | 55.2 | 9.2 | 1.9 | 55.2 | 9.2 | 1.9 |
| 72 | 9.2 | 1.3 | 46.0 | 7.4 | 1.6 | 37.0 | 6.7 | 1.8 | 53.6 | 8.6 | 2.3 | 51.6 | 8.6 | 2.3 | 51.6 | 8.6 | 2.3 | 51.6 | 8.6 | 2.3 |
| 73 | 0.1 | 3.3 | 0.5 | 0.1** | 2.8 | 0.5 | 7.0 | 1.7 | 56.0 | 9.4 | 1.8 | 56.4 | 9.4 | 1.8 | 56.4 | 9.4 | 1.8 | 56.4 | 9.4 | 1.8 |
| 73A | 17.4* | 0.8 | 87.0 | 10.0 | 1.3 | 50.0 | 7.2 | 1.6 | 57.6 | 10.0 | 1.5 | 60.0 | 10.0 | 1.5 | 60.0 | 10.0 | 1.5 | 60.0 | 10.0 | 1.5 |
| 73A | 9.1 | 1.4 | 45.5 | 7.2 | 1.4 | 36.0 | 6.5 | 1.8 | 52.0 | 9.0 | 2.1 | 54.0 | 9.0 | 2.1 | 54.0 | 9.0 | 2.1 | 54.0 | 9.0 | 2.1 |

(Continued)

* The vehicle was immobilized on each tree. A 20-minute penalty was assessed for each immobilization (on 73 included in the speed calculation).
 ** The size and density of trees required that some trees be cut in order for the vehicle to negotiate the terrain. The speed was computed using a 20-minute penalty for each tree that needed to be cut.

[illegible]

* The vehicle was immobilized on each rice dike. A 30-minute penalty was assessed for each immobilization and included in the speed calculation.

** The size and density of trees required that some trees be cut in order for the vehicle to negotiate the terrain. The speed was computed using a 30-minute penalty for each tree that needed to be cut.

Table 3 (Continued)

| Ter- rain Type | M602 | | | | | | | | | | M601 | | | | | | | | | | M600 | | | | | | | | | | M599 | | | | | | | | | | M598 | | | | | | | | | | M597 | | | | | | | | | | M596 | | | | | | | | | | M595 | | | | | | | | | | M594 | | | | | | | | | | M593 | | | | | | | | | | M592 | | | | | | | | | | M591 | | | | | | | | | | M590 | | | | | | | | | | M589 | | | | | | | | | | M588 | | | | | | | | | | M587 | | | | | | | | | | M586 | | | | | | | | | | M585 | | | | | | | | | | M584 | | | | | | | | | | M583 | | | | | | | | | | M582 | | | | | | | | | | M581 | | | | | | | | | | M580 | | | | | | | | | | M579 | | | | | | | | | | M578 | | | | | | | | | | M577 | | | | | | | | | | M576 | | | | | | | | | | M575 | | | | | | | | | | M574 | | | | | | | | | | M573 | | | | | | | | | | M572 | | | | | | | | | | M571 | | | | | | | | | | M570 | | | | | | | | | | M569 | | | | | | | | | | M568 | | | | | | | | | | M567 | | | | | | | | | | M566 | | | | | | | | | | M565 | | | | | | | | | | M564 | | | | | | | | | | M563 | | | | | | | | | | M562 | | | | | | | | | | M561 | | | | | | | | | | M560 | | | | | | | | | | M559 | | | | | | | | | | M558 | | | | | | | | | | M557 | | | | | | | | | | M556 | | | | | | | | | | M555 | | | | | | | | | | M554 | | | | | | | | | | M553 | | | | | | | | | | M552 | | | | | | | | | | M551 | | | | | | | | | | M550 | | | | | | | | | | M549 | | | | | | | | | | M548 | | | | | | | | | | M547 | | | | | | | | | | M546 | | | | | | | | | | M545 | | | | | | | | | | M544 | | | | | | | | | | M543 | | | | | | | | | | M542 | | | | | | | | | | M541 | | | | | | | | | | M540 | | | | | | | | | | M539 | | | | | | | | | | M538 | | | | | | | | | | M537 | | | | | | | | | | M536 | | | | | | | | | | M535 | | | | | | | | | | M534 | | | | | | | | | | M533 | | | | | | | | | | M532 | | | | | | | | | | M531 | | | | | | | | | | M530 | | | | | | | | | | M529 | | | | | | | | | | M528 | | | | | | | | | | M527 | | | | | | | | | | M526 | | | | | | | | | | M525 | | | | | | | | | | M524 | | | | | | | | | | M523 | | | | | | | | | | M522 | | | | | | | | | | M521 | | | | | | | | | | M520 | | | | | | | | | | M519 | | | | | | | | | | M518 | | | | | | | | | | M517 | | | | | | | | | | M516 | | | | | | | | | | M515 | | | | | | | | | | M514 | | | | | | | | | | M513 | | | | | | | | | | M512 | | | | | | | | | | M511 | | | | | | | | | | M510 | | | | | | | | | | M509 | | | | | | | | | | M508 | | | | | | | | | | M507 | | | | | | | | | | M506 | | | | | | | | | | M505 | | | | | | | | | | M504 | | | | | | | | | | M503 | | | | | | | | | | M502 | | | | | | | | | | M501 | | | | | | | | | | M500 | | | | | | | | | | M499 | | | | | | | | | | M498 | | | | | | | | | | M497 | | | | | | | | | | M496 | | | | | | | | | | M495 | | | | | | | | | | M494 | | | | | | | | | | M493 | | | | | | | | | | M492 | | | | | | | | | | M491 | | | | | | | | | | M490 | | | | | | | | | | M489 | | | | | | | | | | M488 | | | | | | | | | | M487 | | | | | | | | | | M486 | | | | | | | | | | M485 | | | | | | | | | | M484 | | | | | | | | | | M483 | | | | | | | | | | M482 | | | | | | | | | | M481 | | | | | | | | | | M480 | | | | | | | | | | M479 | | | | | | | | | | M478 | | | | | | | | | | M477 | | | | | | | | | | M476 | | | | | | | | | | M475 | | | | | | | | | | M474 | | | | | | | | | | M473 | | | | | | | | | | M472 | | | | | | | | | | M471 | | | | | | | | | | M470 | | | | | | | | | | M469 | | | | | | | | | |
|----------------------|---------------|----------------------|---------------------------------|--------------------------|--------------------------|---------------|----------------------|---------------------------------|--------------------------|--------------------------|---------------|----------------------|---------------------------------|--------------------------|--------------------------|---------------|----------------------|---------------------------------|--------------------------|--------------------------|---------------|----------------------|---------------------------------|--------------------------|--------------------------|---------------|----------------------|---------------------------------|--------------------------|--------------------------|---------------|----------------------|---------------------------------|--------------------------|--------------------------|---------------|----------------------|---------------------------------|--------------------------|--------------------------|---------------|----------------------|---------------------------------|--------------------------|--------------------------|---------------|----------------------|---------------------------------|--------------------------|--------------------------|---------------|----------------------|---------------------------------|--------------------------|--------------------------|---------------|----------------------|---------------------------------|--------------------------|--------------------------|---------------|----------------------|---------------------------------|--------------------------|--------------------------|---------------|----------------------|---------------------------------|--------------------------|--------------------------|---------------|----------------------|---------------------------------|--------------------------|--------------------------|---------------|----------------------|---------------------------------|--------------------------|--------------------------|---------------|----------------------|---------------------------------|--------------------------|--------------------------|---------------|----------------------|---------------------------------|--------------------------|--------------------------|---------------|----------------------|---------------------------------|--------------------------|--------------------------|---------------|----------------------|---------------------------------|--------------------------|--------------------------|---------------|----------------------|---------------------------------|--------------------------|--------------------------|---------------|----------------------|---------------------------------|--------------------------|--------------------------|---------------|----------------------|---------------------------------|--------------------------|--------------------------|---------------|----------------------|---------------------------------|--------------------------|--------------------------|---------------|----------------------|---------------------------------|--------------------------|--------------------------|---------------|----------------------|---------------------------------|--------------------------|--------------------------|---------------|----------------------|---------------------------------|--------------------------|--------------------------|---------------|----------------------|---------------------------------|--------------------------|--------------------------|---------------|----------------------|---------------------------------|--------------------------|--------------------------|---------------|----------------------|---------------------------------|--------------------------|--------------------------|---------------|----------------------|---------------------------------|--------------------------|--------------------------|---------------|----------------------|---------------------------------|--------------------------|--------------------------|---------------|----------------------|---------------------------------|--------------------------|--------------------------|---------------|----------------------|---------------------------------|--------------------------|--------------------------|---------------|----------------------|---------------------------------|--------------------------|--------------------------|---------------|----------------------|---------------------------------|--------------------------|--------------------------|---------------|----------------------|---------------------------------|--------------------------|--------------------------|---------------|----------------------|---------------------------------|--------------------------|--------------------------|---------------|----------------------|---------------------------------|--------------------------|--------------------------|---------------|----------------------|---------------------------------|--------------------------|--------------------------|---------------|----------------------|---------------------------------|--------------------------|--------------------------|---------------|----------------------|---------------------------------|--------------------------|--------------------------|---------------|----------------------|---------------------------------|--------------------------|--------------------------|---------------|----------------------|---------------------------------|--------------------------|--------------------------|---------------|----------------------|---------------------------------|--------------------------|--------------------------|---------------|----------------------|---------------------------------|--------------------------|--------------------------|---------------|----------------------|---------------------------------|--------------------------|--------------------------|---------------|----------------------|---------------------------------|--------------------------|--------------------------|---------------|----------------------|---------------------------------|--------------------------|--------------------------|---------------|----------------------|---------------------------------|--------------------------|--------------------------|---------------|----------------------|---------------------------------|--------------------------|--------------------------|---------------|----------------------|---------------------------------|--------------------------|--------------------------|---------------|----------------------|---------------------------------|--|--|--|--|--|--|--|------|--|--|--|--|--|--|--|--|--|------|--|--|--|--|--|--|--|--|--|------|--|--|--|--|--|--|--|--|--|------|--|--|--|--|--|--|--|--|--|------|--|--|--|--|--|--|--|--|--|------|--|--|--|--|--|--|--|--|--|------|--|--|--|--|--|--|--|--|--|------|--|--|--|--|--|--|--|--|--|------|--|--|--|--|--|--|--|--|--|------|--|--|--|--|--|--|--|--|--|------|--|--|--|--|--|--|--|--|--|------|--|--|--|--|--|--|--|--|--|------|--|--|--|--|--|--|--|--|--|------|--|--|--|--|--|--|--|--|--|------|--|--|--|--|--|--|--|--|--|------|--|--|--|--|--|--|--|--|--|------|--|--|--|--|--|--|--|--|--|------|--|--|--|--|--|--|--|--|--|------|--|--|--|--|--|--|--|--|--|------|--|--|--|--|--|--|--|--|--|------|--|--|--|--|--|--|--|--|--|------|--|--|--|--|--|--|--|--|--|------|--|--|--|--|--|--|--|--|--|------|--|--|--|--|--|--|--|--|--|------|--|--|--|--|--|--|--|--|--|------|--|--|--|--|--|--|--|--|--|------|--|--|--|--|--|--|--|--|--|------|--|--|--|--|--|--|--|--|--|------|--|--|--|--|--|--|--|--|--|------|--|--|--|--|--|--|--|--|--|------|--|--|--|--|--|--|--|--|--|------|--|--|--|--|--|--|--|--|--|------|--|--|--|--|--|--|--|--|--|------|--|--|--|--|--|--|--|--|--|------|--|--|--|--|--|--|--|--|--|------|--|--|--|--|--|--|--|--|--|------|--|--|--|--|--|--|--|--|--|------|--|--|--|--|--|--|--|--|--|------|--|--|--|--|--|--|--|--|--|------|--|--|--|--|--|--|--|--|--|------|--|--|--|--|--|--|--|--|--|------|--|--|--|--|--|--|--|--|--|------|--|--|--|--|--|--|--|--|--|------|--|--|--|--|--|--|--|--|--|------|--|--|--|--|--|--|--|--|--|------|--|--|--|--|--|--|--|--|--|------|--|--|--|--|--|--|--|--|--|------|--|--|--|--|--|--|--|--|--|------|--|--|--|--|--|--|--|--|--|------|--|--|--|--|--|--|--|--|--|------|--|--|--|--|--|--|--|--|--|------|--|--|--|--|--|--|--|--|--|------|--|--|--|--|--|--|--|--|--|------|--|--|--|--|--|--|--|--|--|------|--|--|--|--|--|--|--|--|--|------|--|--|--|--|--|--|--|--|--|------|--|--|--|--|--|--|--|--|--|------|--|--|--|--|--|--|--|--|--|------|--|--|--|--|--|--|--|--|--|------|--|--|--|--|--|--|--|--|--|------|--|--|--|--|--|--|--|--|--|------|--|--|--|--|--|--|--|--|--|------|--|--|--|--|--|--|--|--|--|------|--|--|--|--|--|--|--|--|--|------|--|--|--|--|--|--|--|--|--|------|--|--|--|--|--|--|--|--|--|------|--|--|--|--|--|--|--|--|--|------|--|--|--|--|--|--|--|--|--|------|--|--|--|--|--|--|--|--|--|------|--|--|--|--|--|--|--|--|--|------|--|--|--|--|--|--|--|--|--|------|--|--|--|--|--|--|--|--|--|------|--|--|--|--|--|--|--|--|--|------|--|--|--|--|--|--|--|--|--|------|--|--|--|--|--|--|--|--|--|------|--|--|--|--|--|--|--|--|--|------|--|--|--|--|--|--|--|--|--|------|--|--|--|--|--|--|--|--|--|------|--|--|--|--|--|--|--|--|--|------|--|--|--|--|--|--|--|--|--|------|--|--|--|--|--|--|--|--|--|------|--|--|--|--|--|--|--|--|--|------|--|--|--|--|--|--|--|--|--|------|--|--|--|--|--|--|--|--|--|------|--|--|--|--|--|--|--|--|--|------|--|--|--|--|--|--|--|--|--|------|--|--|--|--|--|--|--|--|--|------|--|--|--|--|--|--|--|--|--|------|--|--|--|--|--|--|--|--|--|------|--|--|--|--|--|--|--|--|--|------|--|--|--|--|--|--|--|--|--|------|--|--|--|--|--|--|--|--|--|------|--|--|--|--|--|--|--|--|--|------|--|--|--|--|--|--|--|--|--|------|--|--|--|--|--|--|--|--|--|------|--|--|--|--|--|--|--|--|--|------|--|--|--|--|--|--|--|--|--|------|--|--|--|--|--|--|--|--|--|------|--|--|--|--|--|--|--|--|--|------|--|--|--|--|--|--|--|--|--|------|--|--|--|--|--|--|--|--|--|------|--|--|--|--|--|--|--|--|--|------|--|--|--|--|--|--|--|--|--|------|--|--|--|--|--|--|--|--|--|------|--|--|--|--|--|--|--|--|--|------|--|--|--|--|--|--|--|--|--|------|--|--|--|--|--|--|--|--|--|
| | Speed mi/h | Comp- time min | Con- sump- tion gal/mi | Deliv- ery ton-mph | Deliv- ery ton-mph | Speed mi/h | Comp- time min | Con- sump- tion gal/mi | Deliv- ery ton-mph | Deliv- ery ton-mph | Speed mi/h | Comp- time min | Con- sump- tion gal/mi | Deliv- ery ton-mph | Deliv- ery ton-mph | Speed mi/h | Comp- time min | Con- sump- tion gal/mi | Deliv- ery ton-mph | Deliv- ery ton-mph | Speed mi/h | Comp- time min | Con- sump- tion gal/mi | Deliv- ery ton-mph | Deliv- ery ton-mph | Speed mi/h | Comp- time min | Con- sump- tion gal/mi | Deliv- ery ton-mph | Deliv- ery ton-mph | Speed mi/h | Comp- time min | Con- sump- tion gal/mi | Deliv- ery ton-mph | Deliv- ery ton-mph | Speed mi/h | Comp- time min | Con- sump- tion gal/mi | Deliv- ery ton-mph | Deliv- ery ton-mph | Speed mi/h | Comp- time min | Con- sump- tion gal/mi | Deliv- ery ton-mph | Deliv- ery ton-mph | Speed mi/h | Comp- time min | Con- sump- tion gal/mi | Deliv- ery ton-mph | Deliv- ery ton-mph | Speed mi/h | Comp- time min | Con- sump- tion gal/mi | Deliv- ery ton-mph | Deliv- ery ton-mph | Speed mi/h | Comp- time min | Con- sump- tion gal/mi | Deliv- ery ton-mph | Deliv- ery ton-mph | Speed mi/h | Comp- time min | Con- sump- tion gal/mi | Deliv- ery ton-mph | Deliv- ery ton-mph | Speed mi/h | Comp- time min | Con- sump- tion gal/mi | Deliv- ery ton-mph | Deliv- ery ton-mph | Speed mi/h | Comp- time min | Con- sump- tion gal/mi | Deliv- ery ton-mph | Deliv- ery ton-mph | Speed mi/h | Comp- time min | Con- sump- tion gal/mi | Deliv- ery ton-mph | Deliv- ery ton-mph | Speed mi/h | Comp- time min | Con- sump- tion gal/mi | Deliv- ery ton-mph | Deliv- ery ton-mph | Speed mi/h | Comp- time min | Con- sump- tion gal/mi | Deliv- ery ton-mph | Deliv- ery ton-mph | Speed mi/h | Comp- time min | Con- sump- tion gal/mi | Deliv- ery ton-mph | Deliv- ery ton-mph | Speed mi/h | Comp- time min | Con- sump- tion gal/mi | Deliv- ery ton-mph | Deliv- ery ton-mph | Speed mi/h | Comp- time min | Con- sump- tion gal/mi | Deliv- ery ton-mph | Deliv- ery ton-mph | Speed mi/h | Comp- time min | Con- sump- tion gal/mi | Deliv- ery ton-mph | Deliv- ery ton-mph | Speed mi/h | Comp- time min | Con- sump- tion gal/mi | Deliv- ery ton-mph | Deliv- ery ton-mph | Speed mi/h | Comp- time min | Con- sump- tion gal/mi | Deliv- ery ton-mph | Deliv- ery ton-mph | Speed mi/h | Comp- time min | Con- sump- tion gal/mi | Deliv- ery ton-mph | Deliv- ery ton-mph | Speed mi/h | Comp- time min | Con- sump- tion gal/mi | Deliv- ery ton-mph | Deliv- ery ton-mph | Speed mi/h | Comp- time min | Con- sump- tion gal/mi | Deliv- ery ton-mph | Deliv- ery ton-mph | Speed mi/h | Comp- time min | Con- sump- tion gal/mi | Deliv- ery ton-mph | Deliv- ery ton-mph | Speed mi/h | Comp- time min | Con- sump- tion gal/mi | Deliv- ery ton-mph | Deliv- ery ton-mph | Speed mi/h | Comp- time min | Con- sump- tion gal/mi | Deliv- ery ton-mph | Deliv- ery ton-mph | Speed mi/h | Comp- time min | Con- sump- tion gal/mi | Deliv- ery ton-mph | Deliv- ery ton-mph | Speed mi/h | Comp- time min | Con- sump- tion gal/mi | Deliv- ery ton-mph | Deliv- ery ton-mph | Speed mi/h | Comp- time min | Con- sump- tion gal/mi | Deliv- ery ton-mph | Deliv- ery ton-mph | Speed mi/h | Comp- time min | Con- sump- tion gal/mi | Deliv- ery ton-mph | Deliv- ery ton-mph | Speed mi/h | Comp- time min | Con- sump- tion gal/mi | Deliv- ery ton-mph | Deliv- ery ton-mph | Speed mi/h | Comp- time min | Con- sump- tion gal/mi | Deliv- ery ton-mph | Deliv- ery ton-mph | Speed mi/h | Comp- time min | Con- sump- tion gal/mi | Deliv- ery ton-mph | Deliv- ery ton-mph | Speed mi/h | Comp- time min | Con- sump- tion gal/mi | Deliv- ery ton-mph | Deliv- ery ton-mph | Speed mi/h | Comp- time min | Con- sump- tion gal/mi | Deliv- ery ton-mph | Deliv- ery ton-mph | Speed mi/h | Comp- time min | Con- sump- tion gal/mi | Deliv- ery ton-mph | Deliv- ery ton-mph | Speed mi/h | Comp- time min | Con- sump- tion gal/mi | Deliv- ery ton-mph | Deliv- ery ton-mph | Speed mi/h | Comp- time min | Con- sump- tion gal/mi | Deliv- ery ton-mph | Deliv- ery ton-mph | Speed mi/h | Comp- time min | Con- sump- tion gal/mi | Deliv- ery ton-mph | Deliv- ery ton-mph | Speed mi/h | Comp- time min | Con- sump- tion gal/mi | Deliv- ery ton-mph | Deliv- ery ton-mph | Speed mi/h | Comp- time min | Con- sump- tion gal/mi | Deliv- ery ton-mph | Deliv- ery ton-mph | Speed mi/h | Comp- time min | Con- sump- tion gal/mi | Deliv- ery ton-mph | Deliv- ery ton-mph | Speed mi/h | Comp- time min | Con- sump- tion gal/mi | Deliv- ery ton-mph | Deliv- ery ton-mph | Speed mi/h | Comp- time min | Con- sump- tion gal/mi | Deliv- ery ton-mph | Deliv- ery ton-mph | Speed mi/h | Comp- time min | Con- sump- tion gal/mi | Deliv- ery ton-mph | Deliv- ery ton-mph | Speed mi/h | Comp- time min | Con- sump- tion gal/mi | Deliv- ery ton-mph | Deliv- ery ton-mph | Speed mi/h | Comp- time min | Con- sump- tion gal/mi | Deliv- ery ton-mph | Deliv- ery ton-mph | Speed mi/h | Comp- time min | Con- sump- tion gal/mi | Deliv- ery ton-mph | Deliv- ery ton-mph | Speed mi/h | Comp- time min | Con- sump- tion gal/mi | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |

[illegible]

(Continued)

* The vehicle was immobilized on each rice dike. A 20-minute penalty was assessed for each immobilization and included in the speed calculation.

22 The size and density of trees required that some trees be cut in order for the vehicle to negotiate the terrain. The speed was computed using a 5-minute penalty for each tree that needed to be cut.

5-adjusts penalty for each tree that needed to be cut.

Table 3 (Concluded)

| Per-centage of Total Trucks | Speeded Vehicles | | | | | | | | | | Tracked Vehicles | | | | | | | | | | | | | | | | | | |
|--------------------------------------|--|--------------------------|--------------|--------------------------|--|--|--------------------------|--------------|--------------------------|--|--|--------------------------|--------------|--------------------------|--|--|--------------------------|--------------|--------------------------|--|--|--------------------------|--------------|--------------------------|--|--|--------------------------|--------------|--------------------------|
| | 1950 | | | | | 1955 | | | | | 1960 | | | | | 1965 | | | | | | | | | | | | | |
| | Fuel Con- sump- tion gal./ ton-mile | Deliv- ery ton-mph | Speed mph | Deliv- ery ton-mph | Fuel Con- sump- tion gal./ ton-mile | Fuel Con- sump- tion gal./ ton-mile | Deliv- ery ton-mph | Speed mph | Deliv- ery ton-mph | Fuel Con- sump- tion gal./ ton-mile | Fuel Con- sump- tion gal./ ton-mile | Deliv- ery ton-mph | Speed mph | Deliv- ery ton-mph | Fuel Con- sump- tion gal./ ton-mile | Fuel Con- sump- tion gal./ ton-mile | Deliv- ery ton-mph | Speed mph | Deliv- ery ton-mph | Fuel Con- sump- tion gal./ ton-mile | Fuel Con- sump- tion gal./ ton-mile | Deliv- ery ton-mph | Speed mph | Deliv- ery ton-mph | Fuel Con- sump- tion gal./ ton-mile | Fuel Con- sump- tion gal./ ton-mile | Deliv- ery ton-mph | Speed mph | Deliv- ery ton-mph |
| 96A | 8.0 | 1.5 | 40.0 | 2.6 | 2.1 | 13.0 | 1.6 | 3.0 | 12.8 | 9.5 | 0.8 | 7.1 | 9.2 | 0.8 | 11.5 | 9.2 | 1.3 | 9.2 | 9.3 | 1.7 | 95.8 | 10.3 | 0.8 | 18.5 | 10.9 | 1.3 | 16.4 | 9.7 | 0.6 |
| 96B | 18.7 | 0.8 | 93.5 | 15.6 | 1.1 | 78.0 | 8.2 | 1.6 | 65.6 | 16.0 | 0.4 | 12.0 | 28.5 | 0.4 | 30.8 | 27.4 | 0.4 | 27.4 | 10.5 | 1.2 | 61.0 | 28.8 | 0.8 | 41.7 | 20.8 | 0.7 | 31.2 | 14.6 | 0.4 |
| 96C | 15.7 | 0.8 | 93.5 | 15.6 | 1.1 | 78.0 | 8.2 | 1.6 | 65.6 | 16.0 | 0.4 | 12.0 | 28.5 | 0.4 | 30.8 | 27.4 | 0.4 | 27.4 | 10.5 | 1.2 | 61.0 | 28.8 | 0.8 | 41.7 | 20.8 | 0.7 | 31.2 | 14.6 | 0.4 |
| 96D | 8.5 | 1.4 | 42.5 | 5.9 | 1.8 | 29.5 | 3.1 | 2.6 | 56.8 | 8.1 | 0.9 | 8.1 | 13.2 | 0.5 | 16.5 | 13.2 | 0.9 | 13.2 | 9.4 | 1.8 | 75.5 | 11.1 | 1.2 | 19.7 | 19.4 | 0.9 | 29.1 | 11.4 | 0.6 |
| 96E | 12.6 | 1.0 | 63.0 | 9.7 | 1.3 | 48.5 | 7.0 | 1.7 | 56.0 | 10.8 | 0.7 | 8.1 | 13.2 | 0.5 | 16.5 | 13.2 | 0.9 | 13.2 | 9.4 | 1.8 | 75.5 | 11.1 | 1.2 | 19.7 | 19.4 | 0.9 | 29.1 | 11.4 | 0.5 |

Table 4
Predicted Vehicle Performance on Selected Terrain

| Vehi- cle | Ter- rain | Dry Season (60 or 40 RPT) | | | | | Wet Season (60 or 40 RPT) | | | | | Wet Season (60 or 35 RPT) | | | | | Fuel gal/ mile |
|--------------|--------------|---------------------------|-------------|---------------------|----------------------|--------------|---------------------------|-------------|---------------------|----------------------|--------------|---------------------------|-------------|---------------------|----------------------|-----|----------------------|
| | | Distance feet | Time sec | Avg Speed mph | Fuel gal/ mile | Ter- rain | Distance feet | Time sec | Avg Speed mph | Fuel gal/ mile | Ter- rain | Distance feet | Time sec | Avg Speed mph | Fuel gal/ mile | | |
| M656 | 2 | 900 | 0.17 | 99 | 12.6 | 2 | 1,500 | 0.28 | 81 | 12.6 | 2 | 1,500 | 0.28 | 81 | 12.6 | 1.0 | |
| | 10 | 200 | 0.04 | 8 | 16.2 | 0.03 | 0.8 | 10 | 300 | 0.06 | 13 | 16.2 | 0.05 | 0.8 | 0.8 | | |
| | 52 | 2,700 | 0.51 | 101 | 18.3 | 0.36 | 0.7 | 52 | 2,500 | 0.47 | 93 | 18.3 | 0.36 | 0.7 | 0.7 | | |
| | 10 | 2,700 | 0.51 | 114 | 16.2 | 0.41 | 0.8 | 10 | 2,400 | 0.45 | 105 | 16.2 | 0.38 | 0.8 | 0.8 | | |
| | 3 | 300 | 0.06 | 11 | 18.3 | 0.04 | 0.7 | 3 | 800 | 0.15 | 30 | 18.3 | 0.10 | 0.7 | 0.7 | | |
| | 10 | 2,300 | 0.44 | 97 | 16.2 | 0.35 | 0.8 | 10 | 5,400 | 1.02 | 227 | 16.2 | 0.82 | 0.8 | 0.8 | | |
| | 6 | 600 | 0.11 | 31 | 13.2 | 0.11 | 1.0 | 15 | 800 | 0.15 | 60 | 9.1 | 0.20 | 1.3 | 1.5 | | |
| | 10 | 6,500 | 1.23 | 274 | 16.2 | 0.38 | 0.8 | 10 | 960 | 0.17 | 38 | 16.2 | 0.14 | 0.8 | 0.8 | | |
| | 6 | 400 | 0.08 | 21 | 13.2 | 0.08 | 1.0 | 6 | 2,000 | 0.38 | 100 | 13.6 | 0.38 | 1.0 | 1.0 | | |
| | 10 | 800 | 0.15 | 34 | 16.2 | 0.12 | 0.8 | 15 | 1,100 | 0.21 | 1200 | 9.1 | 2.40 | 1.3 | 1.5 | | |
| | 10 | 2,700 | 0.51 | 131 | 16.2 | 0.41 | 0.8 | 6 | 700 | 0.13 | 36 | 13.2 | 0.13 | 1.0 | 1.0 | | |
| | 14 | 500 | 0.09 | 36 | 9.0 | 0.13 | 1.4 | 15 | 300 | 0.06 | 22 | 9.1 | 0.08 | 1.3 | 1.5 | | |
| | 10 | 600 | 0.11 | 25 | 16.2 | 0.09 | 0.8 | 6 | 1,900 | 0.36 | 98 | 13.2 | 0.36 | 1.0 | 1.5 | | |
| | 6 | 800 | 0.15 | 41 | 13.2 | 0.15 | 1.0 | 15 | 900 | 0.17 | 67 | 9.1 | 0.22 | 1.3 | 1.5 | | |
| | 6 | 1,300 | 0.25 | 67 | 13.2 | 0.25 | 1.0 | 10 | 300 | 0.06 | 13 | 16.2 | 0.05 | 0.8 | 0.8 | | |
| | 10 | 1,200 | 0.23 | 51 | 16.2 | 0.18 | 0.8 | 6 | 2,100 | 0.40 | 108 | 13.2 | 0.40 | 1.0 | 1.0 | | |
| | 6 | 600 | 0.11 | 31 | 13.2 | 0.11 | 1.0 | 6 | 1,000 | 0.19 | 42 | 16.2 | 0.15 | 0.8 | 0.8 | | |
| | 10 | 2,500 | 0.47 | 105 | 16.2 | 0.38 | 0.8 | 6 | 600 | 0.11 | 31 | 13.2 | 0.11 | 1.0 | 1.5 | | |
| | 3 | 2,100 | 0.40 | 78 | 18.3 | 0.28 | 0.7 | 15 | 2,400 | 0.45 | 180 | 9.1 | 0.37 | 1.3 | 1.5 | | |
| | 3 | 600 | 0.11 | 22 | 18.3 | 0.08 | 0.7 | 3 | 2,800 | 0.53 | 104 | 18.3 | 0.53 | 0.7 | 0.7 | | |
| | 10 | 2,300 | 0.44 | 2400 | 16.2 | 4.61 | 0.8 | 15 | 2,300 | 0.43 | 2400 | 9.1 | 4.82 | 1.3 | 1.5 | | |
| | 3 | 1,300 | 0.25 | 48 | 18.3 | 0.17 | 0.7 | 3 | 1,100 | 0.21 | 41 | 18.3 | 0.15 | 0.7 | 1.5 | | |
| | 10 | 2,500 | 0.47 | 105 | 16.2 | 0.36 | 0.8 | 15 | 4,100 | 0.77 | 377 | 9.1 | 1.00 | 1.3 | 1.5 | | |
| | 6 | 700 | 0.13 | 27 | 17.4 | 0.11 | 0.8 | 10 | 300 | 0.06 | 13 | 16.2 | 0.05 | 0.8 | 0.8 | | |
| | 85 | 400 | 0.08 | 17 | 17.4 | 0.11 | 0.8 | 15 | 900 | 0.17 | 67 | 9.1 | 0.22 | 1.3 | 1.5 | | |
| | 10 | 1,900 | 0.36 | 97 | 16.2 | 0.29 | 0.8 | 10 | 200 | 0.04 | 8 | 16.2 | 0.03 | 0.8 | 0.8 | | |
| | 28 | 300 | 0.06 | 11 | 18.3 | 0.04 | 0.7 | 49 | 1,100 | 0.21 | 57 | 13.2 | 0.23 | 1.1 | 1.0 | | |
| | 28 | 5,000 | 0.95 | 186 | 18.3 | 0.66 | 0.7 | 6 | 700 | 0.13 | 36 | 13.2 | 0.13 | 1.0 | 1.0 | | |
| | 88 | 400 | 0.08 | 15 | 19.7 | 0.06 | 0.8 | 28 | 1,400 | 0.26 | 52 | 18.3 | 0.18 | 0.7 | 0.7 | | |
| | 88 | 900 | 0.17 | 33 | 18.7 | 0.14 | 0.8 | 6 | 2,300 | 0.43 | 119 | 13.2 | 0.43 | 1.0 | 1.0 | | |
| | 6 | 2,400 | 0.45 | 124 | 13.2 | 0.45 | 1.0 | 89 | 700 | 0.13 | 35 | 6.7 | 0.20 | 1.5 | 1.5 | | |
| | 37 | 600 | 0.11 | 1,222 | 18.7 | 2.22 | 0.8 | 6 | 4,800 | 0.91 | 248 | 13.2 | 0.91 | 1.0 | 1.0 | | |
| | 3 | 1,200 | 0.23 | 8,184 | 0.1 | 0.75 | 3.3 | 30 | 1,000 | 0.19 | 6,835 | 0.1 | 0.63 | 3.3 | 3.3 | | |
| | 3 | 1,600 | 0.30 | 63 | 18.3 | 0.21 | 0.7 | 30 | 1,600 | 0.30 | 60 | 18.3 | 0.21 | 0.7 | 0.7 | | |
| | 3 | 1,700 | 0.32 | 63 | 18.3 | 0.22 | 0.7 | 30 | 1,200 | 0.23 | 17 | 8.182 | 0.1 | 0.76 | 3.3 | | |
| | 37 | 900 | 0.17 | 33 | 18.7 | 0.14 | 0.8 | 37 | 4,600 | 0.87 | 168 | 18.7 | 0.70 | 0.8 | 0.8 | | |
| | 17 | 200 | 0.04 | 7 | 18.7 | 0.03 | 0.8 | 82 | 1,000 | 0.19 | 114 | 9.0 | 0.27 | 1.4 | 1.4 | | |
| | 14 | 1,700 | 0.32 | 129 | 9.0 | 0.45 | 1.4 | 14 | 1,500 | 0.28 | 114 | 9.0 | 0.39 | 1.4 | 1.4 | | |
| | 10 | 2,000 | 0.23 | 91 | 9.0 | 0.32 | 1.4 | 15 | 300 | 0.06 | 22 | 9.1 | 0.08 | 1.3 | 1.5 | | |
| | 14 | 1,200 | 0.38 | 84 | 16.2 | 0.30 | 0.8 | 10 | 1,700 | 0.32 | 72 | 16.2 | 0.26 | 0.8 | 0.8 | | |
| | 14 | 800 | 0.15 | 61 | 9.0 | 0.21 | 1.4 | 14 | 400 | 0.08 | 30 | 9.0 | 0.11 | 1.4 | 1.4 | | |
| | 82 | 1,900 | 0.36 | 139 | 9.3 | 0.50 | 1.4 | 15 | 1,400 | 0.08 | 30 | 9.0 | 0.12 | 1.5 | 1.5 | | |
| | 14 | 300 | 0.06 | 23 | 9.0 | 0.06 | 1.4 | 82 | 1,900 | 0.36 | 139 | 9.3 | 0.50 | 1.4 | 1.4 | | |
| | 10 | 700 | 0.13 | 23 | 16.2 | 0.11 | 0.8 | 14 | 300 | 0.06 | 23 | 9.0 | 0.08 | 1.4 | 1.4 | | |
| | 3 | 1,000 | 0.19 | 37 | 18.3 | 0.13 | 0.7 | 15 | 700 | 0.13 | 52 | 9.1 | 0.17 | 1.3 | 1.5 | | |
| | 10 | 4,300 | 0.81 | 181 | 16.2 | 0.65 | 0.8 | 3 | 1,000 | 0.19 | 37 | 18.3 | 0.13 | 0.7 | 0.7 | | |
| | 23 | 1,500 | 0.24 | 51 | 25.2 | 0.14 | 0.4 | 15 | 4,400 | 0.83 | 330 | 9.1 | 1.08 | 1.3 | 1.5 | | |
| | 3 | 700 | 0.13 | 26 | 13.3 | 0.09 | 0.7 | 23 | 1,700 | 0.32 | 46 | 25.2 | 0.13 | 0.4 | 0.4 | | |
| | 57 | 700 | 0.13 | 36 | 13.3 | 0.13 | 1.0 | 16 | 600 | 0.11 | 45 | 9.1 | 0.14 | 1.3 | 1.4 | | |
| | 57 | 700 | 0.13 | 36 | 13.3 | 0.13 | 1.0 | 57 | 7,400 | 1.40 | 379 | 13.3 | 1.40 | 1.0 | 1.0 | | |

Continued

(Continued)

Table 4 (Continued)

| Vehi- cle | Tr- ain | Dry Season (60 or 80 Mph) | | | | | Wet Season (60 or 80 Mph) | | | | | Wet Season (60 or 80 Mph) | | | | |
|--------------|------------|---------------------------|-------------|--------------|-------------|--------------|---------------------------|-------------|--------------|-------------|--------------|---------------------------|-------------|--------------|-------------|--------------|
| | | Distance feet | Time sec | Speed mph | Fuel gal | Fuel mile | Distance feet | Time sec | Speed mph | Fuel gal | Fuel mile | Distance feet | Time sec | Speed mph | Fuel gal | Fuel mile |
| 32 | 3 | 400 | 0.08 | 2,728 | 0.1 | 0.25 | 30 | 500 | 0.09 | 1,200 | 4,609 | 0.1 | 2.43 | 3.3 | 3.3 | 3.3 |
| 16 | 16 | 500 | 0.09 | 49 | 12.6 | 0.17 | 2 | 800 | 0.15 | 43 | 12.6 | 0.15 | 1.0 | 1.0 | 1.0 | 1.0 |
| 30 | 30 | 200 | 0.04 | 1,364 | 0.1 | 0.12 | 16 | 500 | 0.09 | 37 | 9.1 | 0.12 | 1.3 | 1.3 | 1.3 | 1.3 |
| 3 | 3 | 700 | 0.13 | 26 | 18.3 | 0.09 | 30 | 400 | 0.08 | 2,727 | 0.1 | 0.26 | 3.3 | 3.3 | 3.3 | 3.3 |
| 2 | 2 | 1,100 | 0.21 | 60 | 12.6 | 0.21 | 2 | 1,100 | 0.21 | 60 | 12.6 | 0.21 | 1.0 | 1.0 | 1.0 | 1.0 |
| 32 | 32 | 1,500 | 0.36 | 14,158 | 19 | 18.3 | 30 | 1,500 | 0.36 | 12,994 | 0.1 | 1.19 | 3.3 | 3.3 | 3.3 | 3.3 |
| 3 | 3 | 500 | 0.09 | 19 | 18.3 | 0.09 | 3 | 600 | 0.11 | 22 | 18.3 | 0.08 | 0.7 | 0.7 | 0.7 | 0.7 |
| 2 | 2 | 700 | 0.13 | 38 | 12.6 | 0.13 | 2 | 800 | 0.15 | 43 | 12.6 | 0.15 | 1.0 | 1.0 | 1.0 | 1.0 |
| 3 | 3 | 2,100 | 0.40 | 78 | 18.3 | 0.28 | 3 | 2,100 | 0.40 | 78 | 18.3 | 0.28 | 0.7 | 0.7 | 0.7 | 0.7 |
| 5 | 5 | 700 | 0.13 | 19 | 25.2 | 0.05 | 5 | 4,300 | 0.81 | 116 | 25.2 | 0.32 | 0.4 | 0.4 | 0.4 | 0.4 |
| 73 | 73 | 800 | 0.15 | 31 | 17.4 | 0.12 | 73A | 900 | 0.17 | 67 | 9.1 | 0.24 | 1.4 | 1.4 | 1.4 | 1.4 |
| 3 | 3 | 1,300 | 0.25 | 48 | 18.3 | 0.17 | 3 | 7,000 | 1.32 | 261 | 18.3 | 0.92 | 0.7 | 0.7 | 0.7 | 0.7 |
| 3 | 3 | 4,400 | 0.83 | 154 | 18.3 | 0.58 | 15 | 5,200 | 0.98 | 390 | 9.1 | 1.27 | 1.3 | 1.3 | 1.3 | 1.3 |
| 3 | 3 | 1,200 | 0.23 | 45 | 18.3 | 0.16 | 10 | 500 | 0.09 | 21 | 16.2 | 0.07 | 0.8 | 0.8 | 0.8 | 0.8 |
| 10 | 10 | 700 | 0.13 | 29 | 16.2 | 0.11 | 15 | 3,700 | 0.70 | 277 | 9.1 | 0.81 | 1.3 | 1.3 | 1.3 | 1.3 |
| 10 | 10 | 1,700 | 0.32 | 72 | 16.2 | 0.26 | 3 | 2,400 | 0.45 | 118 | 16.2 | 0.42 | 0.8 | 0.8 | 0.8 | 0.8 |
| 10 | 10 | 3,100 | 0.59 | 131 | 16.2 | 0.47 | 69 | 100 | 0.02 | 89 | 18.3 | 0.22 | 0.7 | 0.7 | 0.7 | 0.7 |
| 15 | 15 | 3,800 | 0.72 | 285 | 9.1 | 0.93 | 94 | 400 | 0.08 | 30 | 9.1 | 0.10 | 1.3 | 1.3 | 1.3 | 1.3 |
| 10 | 10 | 2,600 | 0.49 | 109 | 16.2 | 0.32 | 81 | 1,500 | 0.28 | 77 | 13.2 | 0.28 | 1.0 | 1.0 | 1.0 | 1.0 |
| 3 | 3 | 2,700 | 0.51 | 101 | 18.3 | 0.36 | 69 | 1,200 | 0.23 | 50 | 16.2 | 0.18 | 0.8 | 0.8 | 0.8 | 0.8 |
| 69 | 69 | 500 | 0.09 | 21 | 16.2 | 0.08 | 17 | 100 | 0.02 | 4 | 18.7 | 0.02 | 0.8 | 0.8 | 0.8 | 0.8 |
| 81 | 81 | 1,500 | 0.28 | 78 | 13.2 | 0.28 | 69 | 800 | 0.15 | 34 | 16.2 | 0.12 | 0.8 | 0.8 | 0.8 | 0.8 |
| 69 | 69 | 900 | 0.17 | 38 | 16.2 | 0.14 | 17 | 300 | 0.06 | 11 | 18.7 | 0.05 | 0.8 | 0.8 | 0.8 | 0.8 |
| 69 | 69 | 300 | 0.06 | 13 | 16.2 | 0.05 | 25 | 800 | 0.15 | 41 | 13.2 | 0.15 | 1.0 | 1.0 | 1.0 | 1.0 |
| 17 | 17 | 300 | 0.06 | 11 | 18.7 | 0.05 | 81 | 900 | 0.17 | 46 | 13.2 | 0.17 | 1.0 | 1.0 | 1.0 | 1.0 |
| 69 | 69 | 200 | 0.04 | 8 | 16.2 | 0.03 | 25 | 700 | 0.13 | 36 | 13.2 | 0.13 | 1.0 | 1.0 | 1.0 | 1.0 |
| 17 | 17 | 300 | 0.06 | 11 | 18.7 | 0.05 | 15 | 1,300 | 0.25 | 97 | 9.1 | 0.32 | 1.3 | 1.3 | 1.3 | 1.3 |
| 25 | 25 | 800 | 0.15 | 41 | 13.2 | 0.15 | 6 | 100 | 0.02 | 5 | 13.2 | 0.02 | 1.0 | 1.0 | 1.0 | 1.0 |
| 61 | 61 | 700 | 0.13 | 36 | 13.2 | 0.13 | 62 | 6,700 | 1.27 | 346 | 13.2 | 1.40 | 1.1 | 1.1 | 1.1 | 1.1 |
| 25 | 25 | 1,000 | 0.19 | 52 | 13.2 | 0.19 | 364 | 300 | 0.06 | 17 | 12.0 | 0.07 | 1.2 | 1.2 | 1.2 | 1.2 |
| 10 | 10 | 1,800 | 0.43 | 51 | 16.2 | 0.18 | 15 | 600 | 0.11 | 45 | 9.1 | 0.14 | 1.3 | 1.3 | 1.3 | 1.3 |
| 62 | 62 | 7,000 | 1.52 | 362 | 13.2 | 1.46 | 63 | 300 | 0.06 | 15 | 13.2 | 0.06 | 1.0 | 1.0 | 1.0 | 1.0 |
| 36 | 36 | 200 | 0.04 | 8 | 16.2 | 0.03 | 62 | 1,100 | 0.21 | 57 | 13.2 | 0.23 | 1.1 | 1.1 | 1.1 | 1.1 |
| 10 | 10 | 600 | 0.11 | 25 | 16.2 | 0.09 | 63 | 1,000 | 0.19 | 52 | 13.2 | 0.19 | 1.0 | 1.0 | 1.0 | 1.0 |
| 63 | 63 | 400 | 0.08 | 21 | 13.2 | 0.08 | 62 | 1,000 | 0.19 | 52 | 13.2 | 0.21 | 1.1 | 1.1 | 1.1 | 1.1 |
| 62 | 62 | 1,100 | 0.21 | 57 | 13.2 | 0.23 | 63 | 4,600 | 0.87 | 238 | 13.2 | 0.87 | 1.0 | 1.0 | 1.0 | 1.0 |
| 63 | 63 | 1,000 | 0.19 | 52 | 13.2 | 0.19 | 80 | 1,400 | 0.26 | 105 | 9.1 | 0.34 | 1.3 | 1.3 | 1.3 | 1.3 |
| 62 | 62 | 900 | 0.17 | 47 | 13.2 | 0.19 | 31 | 600 | 0.11 | 22 | 18.3 | 0.07 | 0.7 | 0.7 | 0.7 | 0.7 |
| 63 | 63 | 4,600 | 0.87 | 238 | 13.2 | 0.87 | 80 | 1,400 | 0.26 | 105 | 9.1 | 0.34 | 1.3 | 1.3 | 1.3 | 1.3 |
| 55 | 55 | 2,800 | 0.62 | 134 | 18.3 | 0.18 | 31 | 3,900 | 0.66 | 130 | 18.3 | 0.46 | 0.7 | 0.7 | 0.7 | 0.7 |
| 31 | 31 | 800 | 0.15 | 30 | 18.3 | 0.11 | 15 | 400 | 0.08 | 30 | 9.1 | 0.10 | 1.3 | 1.3 | 1.3 | 1.3 |
| 55 | 55 | 1,000 | 0.19 | 42 | 16.2 | 0.15 | 31 | 2,100 | 0.40 | 78 | 18.3 | 0.28 | 0.7 | 0.7 | 0.7 | 0.7 |
| 31 | 31 | 3,600 | 0.68 | 134 | 18.3 | 0.46 | 10 | 1,700 | 0.32 | 72 | 16.2 | 0.26 | 0.8 | 0.8 | 0.8 | 0.8 |
| 10 | 10 | 1,600 | 0.30 | 67 | 16.2 | 0.24 | 19 | 3,900 | 0.74 | 98 | 27.2 | 0.15 | 0.2 | 0.2 | 0.2 | 0.2 |
| 31 | 31 | 600 | 0.11 | 22 | 18.3 | 0.08 | 10 | 1,800 | 0.34 | 76 | 16.2 | 0.27 | 0.8 | 0.8 | 0.8 | 0.8 |
| 10 | 10 | 2,200 | 0.42 | 93 | 16.2 | 0.33 | 15 | 1,100 | 0.21 | 1200 | 1,262 | 9.1 | 2.40 | 1.3 | 1.3 | 1.3 |

(Continued)

(2 of 32 sheets)

Table 4. (Continued)

| Vehi- cle | Dry Season (60 or 40 Mph) | | | | | | Wet Season (60 or 40 Mph) | | | | | | Wet Season (60 or 35 Mph) | | | | | | |
|--------------|---------------------------|------------------|-------------|---------------------|--------------------|----------------|---------------------------|------------------|-------------|---------------------|--------------------|----------------|---------------------------|------------------|-------------|---------------------|--------------------|----------------|------|
| | Per- son | Distance feet | Time sec | Avg Speed mph | Fuel gal/ mi | Fuel mi/gal | Per- son | Distance feet | Time sec | Avg Speed mph | Fuel gal/ mi | Fuel mi/gal | Per- son | Distance feet | Time sec | Avg Speed mph | Fuel gal/ mi | Fuel mi/gal | |
| 10 | 19 | 1,100 | 0.21 | 46 | 16.2 | 0.17 | 0.8 | 10 | 2,900 | 0.55 | 122 | 16.2 | 0.44 | 10 | 2,900 | 0.55 | 122 | 16.2 | 0.44 |
| 19 | 19 | 3,600 | 0.68 | 90 | 27.2 | 0.14 | 0.2 | 15 | 600 | 0.11 | 42 | 9.1 | 0.14 | 15 | 600 | 0.11 | 42 | 9.1 | 0.14 |
| 19 | 19 | 200 | 0.04 | 5 | 27.2 | 0.01 | 0.2 | 3 | 2,300 | 0.43 | 86 | 18.3 | 0.30 | 3 | 2,300 | 0.43 | 86 | 18.3 | 0.30 |
| 10 | 19 | 1,700 | 0.32 | 72 | 16.2 | 0.26 | 0.8 | 21 | 600 | 0.11 | 25 | 16.2 | 0.09 | 21 | 600 | 0.11 | 25 | 16.2 | 0.09 |
| 15 | 15 | 200 | 0.04 | 1200 | 1.215 | 9.1 | 2.18 | 1.3 | 3 | 4,100 | 0.77 | 153 | 18.3 | 0.54 | 3 | 4,100 | 0.77 | 153 | 18.3 |
| 15 | 15 | 900 | 0.17 | 67 | 9.1 | 0.22 | 1.3 | 21 | 600 | 0.11 | 25 | 16.2 | 0.09 | 21 | 600 | 0.11 | 25 | 16.2 | 0.09 |
| 10 | 3 | 3,400 | 0.64 | 143 | 16.2 | 0.51 | 0.8 | 22 | 1,500 | 0.28 | 112 | 9.1 | 0.36 | 22 | 1,500 | 0.28 | 112 | 9.1 | 0.36 |
| 3 | 3 | 800 | 0.15 | 30 | 18.3 | 0.11 | 0.7 | 21 | 500 | 0.09 | 21 | 16.2 | 0.07 | 21 | 500 | 0.09 | 21 | 16.2 | 0.07 |
| 3 | 3 | 1,300 | 0.25 | 48 | 18.3 | 0.17 | 0.7 | 22 | 1,300 | 0.25 | 47 | 9.1 | 0.32 | 22 | 1,300 | 0.25 | 47 | 9.1 | 0.32 |
| 3 | 3 | 900 | 0.17 | 34 | 18.3 | 0.12 | 0.7 | 21 | 500 | 0.09 | 21 | 16.2 | 0.07 | 21 | 500 | 0.09 | 21 | 16.2 | 0.07 |
| 21 | 21 | 500 | 0.09 | 21 | 16.2 | 0.08 | 0.8 | 22 | 2,000 | 0.38 | 150 | 9.1 | 0.49 | 22 | 2,000 | 0.38 | 150 | 9.1 | 0.49 |
| 3 | 4,200 | 0.73 | 177 | 18.3 | 0.66 | 0.6 | 0.8 | 2 | 300 | 0.06 | 16 | 12.6 | 0.06 | 2 | 300 | 0.06 | 16 | 12.6 | 0.06 |
| 21 | 21 | 400 | 0.08 | 17 | 16.2 | 0.06 | 0.8 | 28 | 600 | 0.11 | 45 | 9.1 | 0.14 | 28 | 600 | 0.11 | 45 | 9.1 | 0.14 |
| 22 | 22 | 1,500 | 0.28 | 112 | 9.1 | 0.37 | 1.3 | 28 | 3,000 | 0.57 | 1200 | 13.2 | 2.53 | 28 | 3,000 | 0.57 | 1200 | 13.2 | 2.53 |
| 21 | 21 | 500 | 0.09 | 21 | 16.2 | 0.08 | 0.8 | 3 | 2,300 | 0.43 | 66 | 18.3 | 0.30 | 3 | 2,300 | 0.43 | 66 | 18.3 | 0.30 |
| 22 | 22 | 1,300 | 0.25 | 97 | 9.1 | 0.32 | 1.3 | 21 | 300 | 0.06 | 13 | 16.2 | 0.05 | 21 | 300 | 0.06 | 13 | 16.2 | 0.05 |
| 21 | 21 | 500 | 0.09 | 21 | 16.2 | 0.08 | 0.8 | 3 | 1,000 | 0.19 | 37 | 18.3 | 0.13 | 3 | 1,000 | 0.19 | 37 | 18.3 | 0.13 |
| 22 | 22 | 1,000 | 0.36 | 142 | 9.1 | 0.47 | 1.3 | 10 | 2,300 | 0.43 | 97 | 18.2 | 0.34 | 10 | 2,300 | 0.43 | 97 | 18.2 | 0.34 |
| 2 | 2 | 500 | 0.09 | 27 | 12.6 | 0.09 | 1.0 | 3 | 800 | 0.15 | 30 | 18.3 | 0.10 | 3 | 800 | 0.15 | 30 | 18.3 | 0.10 |
| 15 | 15 | 600 | 0.11 | 45 | 9.1 | 0.15 | 1.3 | 10 | 800 | 0.15 | 34 | 18.2 | 0.12 | 10 | 800 | 0.15 | 34 | 18.2 | 0.12 |
| 28 | 28 | 1,400 | 0.26 | 1252 | 18.3 | 2.32 | 0.7 | 3 | 1,000 | 0.19 | 37 | 18.3 | 0.13 | 3 | 1,000 | 0.19 | 37 | 18.3 | 0.13 |
| 28 | 28 | 1,300 | 0.25 | 148 | 18.3 | 0.17 | 0.7 | 10 | 2,100 | 0.40 | 68 | 16.2 | 0.32 | 10 | 2,100 | 0.40 | 68 | 16.2 | 0.32 |
| 3 | 3 | 3,500 | 0.74 | 145 | 18.3 | 0.52 | 0.7 | 15 | 5,000 | 0.94 | 375 | 9.1 | 1.22 | 15 | 5,000 | 0.94 | 426 | 8.0 | 1.41 |
| 10 | 10 | 2,200 | 0.42 | 59 | 16.2 | 0.33 | 0.8 | 3 | 400 | 0.08 | 15 | 18.3 | 0.06 | 3 | 400 | 0.08 | 15 | 18.3 | 0.06 |
| 3 | 3 | 800 | 0.15 | 30 | 18.3 | 0.11 | 0.7 | 10 | 100 | 0.02 | 4 | 16.2 | 0.02 | 10 | 100 | 0.02 | 4 | 16.2 | 0.02 |
| 10 | 10 | 800 | 0.15 | 34 | 16.2 | 0.12 | 0.8 | 10 | 400 | 0.08 | 17 | 16.2 | 0.06 | 10 | 400 | 0.08 | 17 | 16.2 | 0.06 |
| 3 | 3 | 1,100 | 0.21 | 41 | 18.3 | 0.15 | 0.7 | 3 | 900 | 0.17 | 34 | 18.3 | 0.12 | 3 | 900 | 0.17 | 34 | 18.3 | 0.12 |
| 10 | 10 | 200 | 0.04 | 8 | 16.2 | 0.03 | 0.8 | 10 | 500 | 0.09 | 21 | 16.2 | 0.07 | 10 | 500 | 0.09 | 21 | 16.2 | 0.07 |
| 10 | 10 | 700 | 0.13 | 29 | 16.2 | 0.11 | 0.8 | 3 | 500 | 0.09 | 19 | 18.3 | 0.06 | 3 | 500 | 0.09 | 19 | 18.3 | 0.06 |
| 15 | 15 | 5,000 | 0.95 | 392 | 9.1 | 1.23 | 1.3 | 10 | 300 | 0.06 | 13 | 16.2 | 0.05 | 10 | 300 | 0.06 | 13 | 16.2 | 0.05 |
| 3 | 3 | 500 | 0.09 | 19 | 18.3 | 0.07 | 0.7 | 15 | 300 | 0.06 | 22 | 9.1 | 0.08 | 15 | 300 | 0.06 | 22 | 9.1 | 0.08 |
| 10 | 10 | 200 | 0.04 | 8 | 16.2 | 0.03 | 0.8 | 10 | 100 | 0.02 | 4 | 16.2 | 0.02 | 10 | 100 | 0.02 | 4 | 16.2 | 0.02 |
| 3 | 3 | 1,800 | 0.34 | 67 | 18.3 | 0.24 | 0.7 | 3 | 7,600 | 1.44 | 317 | 18.3 | 1.01 | 3 | 7,600 | 1.44 | 317 | 18.3 | 1.01 |
| 3 | 3 | 160 | 0.02 | 4 | 18.3 | 0.01 | 0.7 | 15 | 400 | 0.08 | 30 | 9.1 | 0.10 | 15 | 400 | 0.08 | 30 | 9.1 | 0.10 |
| 10 | 10 | 500 | 0.09 | 21 | 16.2 | 0.08 | 0.8 | 3 | 1,900 | 0.36 | 71 | 18.3 | 0.25 | 3 | 1,900 | 0.36 | 71 | 18.3 | 0.25 |
| 15 | 15 | 1,000 | 0.19 | 75 | 9.1 | 0.25 | 1.3 | 94 | 500 | 0.09 | 37 | 9.1 | 0.12 | 94 | 500 | 0.09 | 43 | 8.0 | 0.15 |
| 16 | 16 | 1,400 | 0.26 | 125 | 16.2 | 0.25 | 0.8 | 69 | 1,400 | 0.26 | 59 | 16.2 | 0.21 | 69 | 1,400 | 0.26 | 59 | 16.2 | 0.21 |
| 16 | 16 | 300 | 0.09 | 17 | 9.1 | 0.12 | 1.3 | 13 | 3,000 | 0.57 | 20,154 | 0.1 | 1.88 | 13 | 3,000 | 0.57 | 20,154 | 0.1 | 1.88 |
| 3 | 3 | 700 | 0.13 | 31 | 18.3 | 0.22 | 0.7 | 10 | 1,000 | 0.19 | 7 | 18.3 | 0.03 | 10 | 1,000 | 0.19 | 7 | 18.3 | 0.03 |
| 3 | 3 | 5,500 | 1.04 | 205 | 18.3 | 0.73 | 0.7 | 3 | 200 | 0.04 | 4 | 16.2 | 0.03 | 3 | 200 | 0.04 | 4 | 16.2 | 0.03 |
| 69 | 69 | 1,700 | 0.32 | 72 | 16.2 | 0.26 | 0.8 | 15 | 1,800 | 0.34 | 135 | 9.1 | 0.44 | 15 | 1,800 | 0.34 | 135 | 9.0 | 0.15 |
| 69 | 69 | 1,000 | 0.22 | 4 | 16.2 | 0.02 | 0.8 | 1 | 1,300 | 0.25 | 97 | 9.1 | 0.32 | 1 | 1,300 | 0.25 | 97 | 9.0 | 0.15 |
| 13 | 13 | 2,900 | 0.55 | 19,778 | 0.1 | 1.81 | 3.3 | 14 | 3,500 | 0.66 | 265 | 9.0 | 0.42 | 14 | 3,500 | 0.66 | 265 | 9.0 | 0.42 |
| 10 | 10 | 600 | 0.11 | 25 | 16.2 | 0.09 | 0.8 | 1 | 7,400 | 1.40 | 554 | 9.1 | 1.62 | 1 | 7,400 | 1.40 | 631 | 8.0 | 2.10 |
| 3 | 3 | 700 | 0.13 | 26 | 18.3 | 0.09 | 0.7 | 1 | 2,600 | 0.53 | 104 | 18.3 | 0.37 | 1 | 2,600 | 0.53 | 104 | 18.3 | 0.37 |
| 10 | 10 | 2,000 | 0.38 | 84 | 16.2 | 0.30 | 0.8 | 3 | 2,800 | 0.53 | 104 | 18.3 | 0.37 | 3 | 2,800 | 0.53 | 104 | 18.3 | 0.37 |
| 14 | 14 | 1,300 | 0.25 | 63 | 14.1 | 0.22 | 0.9 | 16 | 700 | 0.13 | 52 | 9.1 | 0.17 | 16 | 700 | 0.13 | 52 | 9.0 | 0.17 |
| 14 | 14 | 3,500 | 0.66 | 265 | 9.0 | 0.42 | 0.9 | 3 | 200 | 0.04 | 7 | 18.3 | 0.03 | 3 | 200 | 0.04 | 7 | 18.3 | 0.03 |
| 4 | 4 | 1,700 | 0.32 | 72 | 16.2 | 0.26 | 0.8 | 1 | 4,800 | 0.91 | 1,560 | 9.1 | 3.31 | 1 | 4,800 | 0.91 | 1,560 | 9.0 | 3.49 |
| 4 | 4 | 600 | 0.11 | 25 | 16.2 | 0.09 | 0.8 | 13 | 300 | 0.06 | 2,045 | 0.1 | 0.20 | 13 | 300 | 0.06 | 2,045 | 0.1 | 0.20 |
| 4 | 4 | 4,600 | 0.87 | 222 | 14.1 | 0.76 | 0.9 | 3 | 8,100 | 1.53 | 302 | 18.3 | 1.07 | 3 | 8,100 | 1.53 | 302 | 18.3 | 1.07 |
| 4 | 4 | 1,200 | 0.23 | 58 | 14.1 | 0.20 | 0.9 | 1 | 1,200 | 0.23 | 58 | 14.1 | 0.21 | 1 | 1,200 | 0.23 | 58 | 14.1 | 0.21 |
| 3 | 3 | 800 | 0.15 | 30 | 18.3 | 0.11 | 0.7 | 1 | 500 | 0.09 | 37 | 9.1 | 0.12 | 1 | 500 | 0.09 | 43 | 8.0 | 0.15 |
| 3 | 3 | 3,000 | 0.57 | 112 | 18.3 | 0.40 | 0.7 | 2 | 100 | 0.02 | 7 | 9.1 | 0.01 | 2 | 100 | 0.02 | 7 | 9.0 | 0.01 |
| 3 | 3 | 4,000 | 0.71 | 140 | 18.3 | 0.50 | 0.8 | 2 | 500 | 0.09 | 27 | 12.6 | 0.09 | 2 | 500 | 0.09 | 27 | 12.6 | 0.09 |

(Continued)

(3 of 32 sheets)

Table 4 (Continued)

| Vehi- Cis | Type | Dry Season (60 or 70 MI) | | | | | Wet Season (60 or 70 MI) | | | | | Wet Season (60 or 70 MI) | | | | | Wet Season (60 or 70 MI) | | | | | | | | |
|--------------|------|--------------------------|------------------|-------------|---------------------|----------------------|--------------------------|------------------|-------------|---------------------|----------------------|--------------------------|------------------|-------------|---------------------|----------------------|--------------------------|------------------|-------------|---------------------|----------------------|--------|-------|------|------|
| | | Per- min | Distance feet | Time sec | Avg Speed mph | Fuel gal/ mile | Per- min | Distance feet | Time sec | Avg Speed mph | Fuel gal/ mile | Per- min | Distance feet | Time sec | Avg Speed mph | Fuel gal/ mile | Per- min | Distance feet | Time sec | Avg Speed mph | Fuel gal/ mile | | | | |
| 13 | 3 | 300 | 0.06 | 2,066 | 0.1 | 0.19 | 3-3 | 300 | 0.06 | 2,066 | 0.1 | 0.19 | 3-3 | 300 | 0.06 | 2,066 | 0.1 | 0.19 | 3-3 | 300 | 0.06 | 2,066 | 0.1 | 0.19 | 3-3 |
| 3 | 3 | 4,500 | 0.85 | 168 | 18.3 | 0.60 | 0.7 | 4,500 | 0.85 | 168 | 18.3 | 0.60 | 0.7 | 4,500 | 0.85 | 168 | 18.3 | 0.60 | 0.7 | 4,500 | 0.85 | 168 | 18.3 | 0.60 | 0.7 |
| 3 | 3 | 2,100 | 0.40 | 78 | 18.3 | 0.28 | 0.7 | 2,100 | 0.40 | 78 | 18.3 | 0.28 | 0.7 | 2,100 | 0.40 | 78 | 18.3 | 0.28 | 0.7 | 2,100 | 0.40 | 78 | 18.3 | 0.28 | 0.7 |
| 4 | 4 | 3,700 | 0.70 | 179 | 14.1 | 0.63 | 0.9 | 3,700 | 0.70 | 179 | 14.1 | 0.63 | 0.9 | 3,700 | 0.70 | 179 | 14.1 | 0.63 | 0.9 | 3,700 | 0.70 | 179 | 14.1 | 0.63 | 0.9 |
| 2 | 2 | 400 | 0.06 | 22 | 12.6 | 0.08 | 1.0 | 400 | 0.06 | 22 | 12.6 | 0.08 | 1.0 | 400 | 0.06 | 22 | 12.6 | 0.08 | 1.0 | 400 | 0.06 | 22 | 12.6 | 0.08 | 1.0 |
| Totals | | 237,400 | 44.91 | 67,210 | 58.52 | | | 237,400 | 44.91 | 67,210 | 58.52 | | | 237,400 | 44.91 | 67,210 | 58.52 | | | 237,400 | 44.91 | 67,210 | 58.52 | | |
| 10442 | 2 | 500 | 0.09 | 35 | 9.7 | 0.12 | 1.3 | 500 | 0.09 | 35 | 9.7 | 0.12 | 1.3 | 500 | 0.09 | 35 | 9.7 | 0.12 | 1.3 | 500 | 0.09 | 35 | 9.7 | 0.12 | 1.3 |
| 10 | 10 | 700 | 0.13 | 17 | 10.0 | 0.17 | 1.3 | 700 | 0.13 | 17 | 10.0 | 0.17 | 1.3 | 700 | 0.13 | 17 | 10.0 | 0.17 | 1.3 | 700 | 0.13 | 17 | 10.0 | 0.17 | 1.3 |
| 52 | 52 | 2,600 | 0.49 | 177 | 10.0 | 0.68 | 1.8 | 2,600 | 0.49 | 177 | 10.0 | 0.68 | 1.8 | 2,600 | 0.49 | 177 | 10.0 | 0.68 | 1.8 | 2,600 | 0.49 | 177 | 10.0 | 0.68 | 1.8 |
| 10 | 10 | 200 | 0.06 | 14 | 10.0 | 0.09 | 1.3 | 200 | 0.06 | 14 | 10.0 | 0.09 | 1.3 | 200 | 0.06 | 14 | 10.0 | 0.09 | 1.3 | 200 | 0.06 | 14 | 10.0 | 0.09 | 1.3 |
| 10 | 10 | 2,700 | 0.51 | 184 | 10.0 | 0.62 | 1.3 | 2,700 | 0.51 | 184 | 10.0 | 0.62 | 1.3 | 2,700 | 0.51 | 184 | 10.0 | 0.62 | 1.3 | 2,700 | 0.51 | 184 | 10.0 | 0.62 | 1.3 |
| 3 | 3 | 300 | 0.06 | 20 | 10.0 | 0.07 | 1.3 | 300 | 0.06 | 20 | 10.0 | 0.07 | 1.3 | 300 | 0.06 | 20 | 10.0 | 0.07 | 1.3 | 300 | 0.06 | 20 | 10.0 | 0.07 | 1.3 |
| 10 | 10 | 2,300 | 0.43 | 157 | 10.0 | 0.57 | 1.3 | 2,300 | 0.43 | 157 | 10.0 | 0.57 | 1.3 | 2,300 | 0.43 | 157 | 10.0 | 0.57 | 1.3 | 2,300 | 0.43 | 157 | 10.0 | 0.57 | 1.3 |
| 6 | 6 | 500 | 0.09 | 56 | 8.8 | 0.13 | 1.4 | 500 | 0.09 | 56 | 8.8 | 0.13 | 1.4 | 500 | 0.09 | 56 | 8.8 | 0.13 | 1.4 | 500 | 0.09 | 56 | 8.8 | 0.13 | 1.4 |
| 10 | 10 | 6,000 | 1.25 | 450 | 10.0 | 1.62 | 1.3 | 6,000 | 1.25 | 450 | 10.0 | 1.62 | 1.3 | 6,000 | 1.25 | 450 | 10.0 | 1.62 | 1.3 | 6,000 | 1.25 | 450 | 10.0 | 1.62 | 1.3 |
| 6 | 6 | 400 | 0.08 | 31 | 8.8 | 0.11 | 1.4 | 400 | 0.08 | 31 | 8.8 | 0.11 | 1.4 | 400 | 0.08 | 31 | 8.8 | 0.11 | 1.4 | 400 | 0.08 | 31 | 8.8 | 0.11 | 1.4 |
| 10 | 10 | 700 | 0.13 | 18 | 10.0 | 0.17 | 1.3 | 700 | 0.13 | 18 | 10.0 | 0.17 | 1.3 | 700 | 0.13 | 18 | 10.0 | 0.17 | 1.3 | 700 | 0.13 | 18 | 10.0 | 0.17 | 1.3 |
| 10 | 10 | 2,700 | 0.51 | 184 | 10.0 | 0.62 | 1.3 | 2,700 | 0.51 | 184 | 10.0 | 0.62 | 1.3 | 2,700 | 0.51 | 184 | 10.0 | 0.62 | 1.3 | 2,700 | 0.51 | 184 | 10.0 | 0.62 | 1.3 |
| 10 | 10 | 700 | 0.13 | 18 | 10.0 | 0.17 | 1.3 | 700 | 0.13 | 18 | 10.0 | 0.17 | 1.3 | 700 | 0.13 | 18 | 10.0 | 0.17 | 1.3 | 700 | 0.13 | 18 | 10.0 | 0.17 | 1.3 |
| 6 | 6 | 1,400 | 0.26 | 109 | 8.8 | 0.37 | 1.4 | 1,400 | 0.26 | 109 | 8.8 | 0.37 | 1.4 | 1,400 | 0.26 | 109 | 8.8 | 0.37 | 1.4 | 1,400 | 0.26 | 109 | 8.8 | 0.37 | 1.4 |
| 10 | 10 | 1,100 | 0.21 | 75 | 10.0 | 0.27 | 1.3 | 1,100 | 0.21 | 75 | 10.0 | 0.27 | 1.3 | 1,100 | 0.21 | 75 | 10.0 | 0.27 | 1.3 | 1,100 | 0.21 | 75 | 10.0 | 0.27 | 1.3 |
| 6 | 6 | 700 | 0.13 | 54 | 8.8 | 0.18 | 1.4 | 700 | 0.13 | 54 | 8.8 | 0.18 | 1.4 | 700 | 0.13 | 54 | 8.8 | 0.18 | 1.4 | 700 | 0.13 | 54 | 8.8 | 0.18 | 1.4 |
| 10 | 10 | 2,400 | 0.45 | 164 | 10.0 | 0.59 | 1.3 | 2,400 | 0.45 | 164 | 10.0 | 0.59 | 1.3 | 2,400 | 0.45 | 164 | 10.0 | 0.59 | 1.3 | 2,400 | 0.45 | 164 | 10.0 | 0.59 | 1.3 |
| 6 | 6 | 2,800 | 0.42 | 150 | 10.0 | 0.54 | 1.3 | 2,800 | 0.42 | 150 | 10.0 | 0.54 | 1.3 | 2,800 | 0.42 | 150 | 10.0 | 0.54 | 1.3 | 2,800 | 0.42 | 150 | 10.0 | 0.54 | 1.3 |
| 3 | 3 | 500 | 0.09 | 34 | 10.0 | 0.12 | 1.3 | 500 | 0.09 | 34 | 10.0 | 0.12 | 1.3 | 500 | 0.09 | 34 | 10.0 | 0.12 | 1.3 | 500 | 0.09 | 34 | 10.0 | 0.12 | 1.3 |
| 10 | 10 | 2,300 | 0.43 | 157 | 10.0 | 0.57 | 1.3 | 2,300 | 0.43 | 157 | 10.0 | 0.57 | 1.3 | 2,300 | 0.43 | 157 | 10.0 | 0.57 | 1.3 | 2,300 | 0.43 | 157 | 10.0 | 0.57 | 1.3 |
| 3 | 3 | 400 | 0.08 | 27 | 10.0 | 0.10 | 1.3 | 400 | 0.08 | 27 | 10.0 | 0.10 | 1.3 | 400 | 0.08 | 27 | 10.0 | 0.10 | 1.3 | 400 | 0.08 | 27 | 10.0 | 0.10 | 1.3 |
| 10 | 10 | 2,700 | 0.51 | 184 | 10.0 | 0.62 | 1.3 | 2,700 | 0.51 | 184 | 10.0 | 0.62 | 1.3 | 2,700 | 0.51 | 184 | 10.0 | 0.62 | 1.3 | 2,700 | 0.51 | 184 | 10.0 | 0.62 | 1.3 |
| 21 | 21 | 300 | 0.06 | 2400 | 10.0 | 0.79 | 1.3 | 300 | 0.06 | 2400 | 10.0 | 0.79 | 1.3 | 300 | 0.06 | 2400 | 10.0 | 0.79 | 1.3 | 300 | 0.06 | 2400 | 10.0 | 0.79 | 1.3 |
| 65 | 65 | 700 | 0.13 | 18 | 10.0 | 0.17 | 1.3 | 700 | 0.13 | 18 | 10.0 | 0.17 | 1.3 | 700 | 0.13 | 18 | 10.0 | 0.17 | 1.3 | 700 | 0.13 | 18 | 10.0 | 0.17 | 1.3 |
| 10 | 10 | 1,900 | 0.34 | 137 | 10.0 | 0.47 | 1.3 | 1,900 | 0.34 | 137 | 10.0 | 0.47 | 1.3 | 1,900 | 0.34 | 137 | 10.0 | 0.47 | 1.3 | 1,900 | 0.34 | 137 | 10.0 | 0.47 | 1.3 |
| 28 | 28 | 200 | 0.04 | 34 | 10.0 | 0.05 | 1.3 | 200 | 0.04 | 34 | 10.0 | 0.05 | 1.3 | 200 | 0.04 | 34 | 10.0 | 0.05 | 1.3 | 200 | 0.04 | 34 | 10.0 | 0.05 | 1.3 |
| 28 | 28 | 5,100 | 0.96 | 340 | 10.0 | 1.28 | 1.3 | 5,100 | 0.96 | 340 | 10.0 | 1.28 | 1.3 | 5,100 | 0.96 | 340 | 10.0 | 1.28 | 1.3 | 5,100 | 0.96 | 340 | 10.0 | 1.28 | 1.3 |
| 88 | 88 | 600 | 0.11 | 26 | 15.6 | 0.12 | 1.1 | 600 | 0.11 | 26 | 15.6 | 0.12 | 1.1 | 600 | 0.11 | 26 | 15.6 | 0.12 | 1.1 | 600 | 0.11 | 26 | 15.6 | 0.12 | 1.1 |
| 88 | 88 | 800 | 0.15 | 35 | 15.6 | 0.17 | 1.1 | 800 | 0.15 | 35 | 15.6 | 0.17 | 1.1 | 800 | 0.15 | 35 | 15.6 | 0.17 | 1.1 | 800 | 0.15 | 35 | 15.6 | 0.17 | 1.1 |
| 6 | 6 | 2,000 | 0.42 | 171 | 8.8 | 0.58 | 1.4 | 2,000 | 0.42 | 171 | 8.8 | 0.58 | 1.4 | 2,000 | 0.42 | 171 | 8.8 | 0.58 | 1.4 | 2,000 | 0.42 | 171 | 8.8 | 0.58 | 1.4 |
| 6 | 6 | 200 | 0.04 | 16 | 8.8 | 0.05 | 1.4 | 200 | 0.04 | 16 | 8.8 | 0.05 | 1.4 | 200 | 0.04 | 16 | 8.8 | 0.05 | 1.4 | 200 | 0.04 | 16 | 8.8 | 0.05 | 1.4 |
| 37 | 37 | 700 | 0.13 | 31 | 15.6 | 0.18 | 1.1 | 700 | 0.13 | 31 | 15.6 | 0.18 | 1.1 | 700 | 0.13 | 31 | 15.6 | 0.18 | 1.1 | 700 | 0.13 | 31 | 15.6 | 0.18 | 1.1 |
| 38 | 38 | 1,200 | 0.23 | 1200 | 10.0 | 0.31 | 2.61 | 1,200 | 0.23 | 1200 | 10.0 | 0.31 | 2.61 | 1,200 | 0.23 | 1200 | 10.0 | 0.31 | 2.61 | 1,200 | 0.23 | 1200 | 10.0 | 0.31 | 2.61 |
| 3 | 3 | 1,500 | 0.28 | 102 | 10.0 | 0.37 | 1.3 | 1,500 | 0.28 | 102 | 10.0 | 0.37 | 1.3 | 1,500 | 0.28 | 102 | 10.0 | 0.37 | 1.3 | 1,500 | 0.28 | 102 | 10.0 | 0.37 | 1.3 |
| 3 | 3 | 1,700 | 0.32 | 116 | 10.0 | 0.42 | 1.3 | 1,700 | 0.32 | 116 | 10.0 | 0.42 | 1.3 | 1,700 | 0.32 | 116 | 10.0 | 0.42 | 1.3 | 1,700 | 0.32 | 116 | 10.0 | 0.42 | 1.3 |
| 3 | 3 | 1,900 | 0.37 | 81 | 7.6 | 0.29 | 1.7 | 1,900 | 0.37 | 81 | 7.6 | 0.29 | 1.7 | 1,900 | 0.37 | 81 | 7.6 | 0.29 | 1.7 | 1,900 | 0.37 | 81 | 7.6 | 0.29 | 1.7 |
| 63 | 63 | 200 | 0.04 | 18 | 7.6 | 0.06 | 1.7 | 200 | 0.04 | 18 | 7.6 | 0.06 | 1.7 | 200 | 0.04 | 18 | 7.6 | 0.06 | 1.7 | 200 | 0.04 | 18 | 7.6 | 0.06 | 1.7 |
| 11 | 11 | 1,400 | 0.26 | 126 | 7.6 | 0.40 | 1.5 | 1,400 | 0.26 | 126 | 7.6 | 0.40 | 1.5 | 1,400 | 0.26 | 126 | 7.6 | 0.40 | 1.5 | 1,400 | 0.26 | 126 | 7.6 | 0.40 | 1.5 |
| 11 | 11 | 1,500 | 0.28 | 135 | 7.6 | 0.43 | 1.5 | 1,500 | 0.28 | 135 | 7.6 | 0.43 | 1.5 | 1,500 | 0.28 | 135 | 7.6 | 0.43 | 1.5 | 1,500 | 0.28 | 135 | 7.6 | 0.43 | 1.5 |
| 11 | 11 | 1,900 | 0.36 | 130 | 10.0 | 0.47 | 1.3 | 1,900 | 0.36 | 130 | 10.0 | 0.47 | 1.3 | 1,900 | 0.36 | 130 | 10.0 | 0.47 | 1.3 | 1,900 | 0.36 | 130 | 10.0 | 0.47 | 1.3 |
| 11 | 11 | 900 | 0.17 | 81 | 7.6 | 0.26 | 1.5 | 900 | 0.17 | 81 | 7.6 | 0.26 | 1.5 | 900 | 0.17 | 81 | 7.6 | 0.26 | 1.5 | 900 | 0.17 | 81 | 7.6 | 0.26 | 1.5 |
| 62 | 62 | 1,900 | 0.36 | 166 | 7.6 | 0.57 | 1.6 | 1,900 | 0.36 | 166 | 7.6 | 0.57 | 1.6 | 1,900 | 0.36 | 166 | 7.6 | 0.57 | 1.6 | 1,900 | 0.36 | 166 | 7.6 | 0.57 | 1.6 |

(Continued)

(1 of 3 sheets)

Table 4 (Continued)

| Vehi- cle | By Season (60 or 50 Mph) | | | | | Net Season (60 or 50 Mph) | | | | | By Season (60 or 50 Mph) | | | | | Net Season (60 or 50 Mph) | | | | | By Season (60 or 50 Mph) | | | | | Net Season (60 or 50 Mph) | | | | | | | | | | | | | | | |
|--------------|--------------------------|------------------|-------------|--------------|----------------------|---------------------------|------------------|-------------|--------------|----------------------|--------------------------|------------------|-------------|--------------|----------------------|---------------------------|------------------|-------------|--------------|----------------------|--------------------------|------------------|-------------|--------------|----------------------|---------------------------|------------------|-------------|--------------|----------------------|-----|-------|------|-------|-------|-------|------|-----|------|------|-----|
| | Rein Type | Distance feet | Time sec | Speed mph | Fuel gal/ mile | Rein Type | Distance feet | Time sec | Speed mph | Fuel gal/ mile | Rein Type | Distance feet | Time sec | Speed mph | Fuel gal/ mile | Rein Type | Distance feet | Time sec | Speed mph | Fuel gal/ mile | Rein Type | Distance feet | Time sec | Speed mph | Fuel gal/ mile | Rein Type | Distance feet | Time sec | Speed mph | Fuel gal/ mile | | | | | | | | | | | |
| 14 | 200 | 0.04 | 18 | 7.6 | 0.06 | 1.5 | 82 | 1,900 | 0.36 | 166 | 7.8 | 0.58 | 1.6 | 82 | 1,900 | 0.36 | 166 | 7.8 | 0.58 | 1.6 | 82 | 1,900 | 0.36 | 166 | 7.8 | 0.58 | 1.6 | 82 | 1,900 | 0.36 | 166 | 7.8 | 0.58 | 1.6 | | | | | | | |
| 10 | 700 | 0.13 | 48 | 10.0 | 0.17 | 1.3 | 14 | 800 | 0.06 | 27 | 7.6 | 0.09 | 1.5 | 15 | 800 | 0.06 | 27 | 7.6 | 0.09 | 1.5 | 15 | 800 | 0.06 | 27 | 7.6 | 0.09 | 1.5 | 15 | 800 | 0.06 | 27 | 7.6 | 0.09 | 1.5 | | | | | | | |
| 3 | 1,000 | 0.19 | 68 | 10.0 | 0.25 | 1.3 | 15 | 800 | 0.15 | 76 | 7.2 | 0.22 | 1.5 | 15 | 800 | 0.15 | 76 | 7.2 | 0.22 | 1.5 | 15 | 800 | 0.15 | 76 | 7.2 | 0.22 | 1.5 | 15 | 800 | 0.15 | 76 | 7.2 | 0.22 | 1.5 | | | | | | | |
| 10 | 2,500 | 0.49 | 177 | 10.0 | 0.64 | 1.3 | 10 | 800 | 0.15 | 55 | 10.0 | 0.20 | 1.3 | 10 | 800 | 0.15 | 55 | 10.0 | 0.20 | 1.3 | 10 | 800 | 0.15 | 55 | 10.0 | 0.20 | 1.3 | 10 | 800 | 0.15 | 55 | 10.0 | 0.20 | 1.3 | | | | | | | |
| 23 | 3,500 | 0.68 | 150 | 16.4 | 0.68 | 1.0 | 15 | 4,300 | 0.81 | 407 | 7.2 | 1.22 | 1.5 | 15 | 4,300 | 0.81 | 407 | 7.2 | 1.22 | 1.5 | 15 | 4,300 | 0.81 | 407 | 7.2 | 1.22 | 1.5 | 15 | 4,300 | 0.81 | 407 | 7.2 | 1.22 | 1.5 | | | | | | | |
| 3 | 700 | 0.13 | 48 | 10.0 | 0.17 | 1.3 | 23 | 5,400 | 1.02 | 224 | 16.4 | 1.02 | 1.0 | 23 | 5,400 | 1.02 | 224 | 16.4 | 1.02 | 1.0 | 23 | 5,400 | 1.02 | 224 | 16.4 | 1.02 | 1.0 | 23 | 5,400 | 1.02 | 224 | 16.4 | 1.02 | 1.0 | | | | | | | |
| 57 | 6,500 | 1.23 | 493 | 9.0 | 1.60 | 1.3 | 3 | 300 | 0.06 | 20 | 10.0 | 0.08 | 1.3 | 3 | 300 | 0.06 | 20 | 10.0 | 0.08 | 1.3 | 3 | 300 | 0.06 | 20 | 10.0 | 0.08 | 1.3 | 3 | 300 | 0.06 | 20 | 10.0 | 0.08 | 1.3 | | | | | | | |
| 27 | 500 | 0.17 | 68 | 9.0 | 0.22 | 1.3 | 23 | 600 | 0.11 | 25 | 16.4 | 0.11 | 1.0 | 23 | 600 | 0.11 | 25 | 16.4 | 0.11 | 1.0 | 23 | 600 | 0.11 | 25 | 16.4 | 0.11 | 1.0 | 23 | 600 | 0.11 | 25 | 16.4 | 0.11 | 1.0 | | | | | | | |
| 32 | 400 | 0.08 | 2,728 | 0.1 | 0.21 | 2.8 | 3 | 600 | 0.11 | 41 | 10.0 | 0.14 | 1.3 | 3 | 600 | 0.11 | 41 | 10.0 | 0.14 | 1.3 | 3 | 600 | 0.11 | 41 | 10.0 | 0.14 | 1.3 | 3 | 600 | 0.11 | 41 | 10.0 | 0.14 | 1.3 | | | | | | | |
| 2 | 900 | 0.17 | 63 | 9.7 | 0.22 | 1.3 | 57 | 5,000 | 0.94 | 379 | 9.0 | 1.22 | 1.3 | 57 | 5,000 | 0.94 | 379 | 9.0 | 1.22 | 1.3 | 57 | 5,000 | 0.94 | 379 | 9.0 | 1.22 | 1.3 | 57 | 5,000 | 0.94 | 379 | 9.0 | 1.22 | 1.3 | | | | | | | |
| 16 | 500 | 0.09 | 47 | 7.2 | 0.14 | 1.5 | 2 | 1,600 | 0.30 | 112 | 9.7 | 0.39 | 1.3 | 2 | 1,600 | 0.30 | 112 | 9.7 | 0.39 | 1.3 | 2 | 1,600 | 0.30 | 112 | 9.7 | 0.39 | 1.3 | 2 | 1,600 | 0.30 | 112 | 9.7 | 0.39 | 1.3 | | | | | | | |
| 30 | 200 | 0.04 | 1,304 | 0.1 | 0.10 | 2.8 | 30 | 6,200 | 1.17 | 2,400 | 46.72 | 0.1 | 8.00 | 2.8 | 30 | 6,200 | 1.17 | 2,400 | 46.72 | 0.1 | 8.00 | 2.8 | 30 | 6,200 | 1.17 | 2,400 | 46.72 | 0.1 | 8.00 | 2.8 | 30 | 6,200 | 1.17 | 2,400 | 46.72 | 0.1 | 8.00 | 2.8 | | | |
| 3 | 700 | 0.13 | 48 | 10.0 | 0.17 | 1.3 | 3 | 500 | 0.09 | 34 | 10.0 | 0.12 | 1.3 | 3 | 500 | 0.09 | 34 | 10.0 | 0.12 | 1.3 | 3 | 500 | 0.09 | 34 | 10.0 | 0.12 | 1.3 | 3 | 500 | 0.09 | 34 | 10.0 | 0.12 | 1.3 | 3 | 500 | 0.09 | 34 | 10.0 | 0.12 | 1.3 |
| 2 | 1,100 | 0.21 | 77 | 9.7 | 0.27 | 1.3 | 2 | 700 | 0.13 | 49 | 9.7 | 0.17 | 1.3 | 2 | 700 | 0.13 | 49 | 9.7 | 0.17 | 1.3 | 2 | 700 | 0.13 | 49 | 9.7 | 0.17 | 1.3 | 2 | 700 | 0.13 | 49 | 9.7 | 0.17 | 1.3 | 2 | 700 | 0.13 | 49 | 9.7 | 0.17 | 1.3 |
| 3 | 500 | 0.09 | 34 | 10.0 | 0.12 | 1.3 | 3 | 2,100 | 0.40 | 143 | 10.0 | 0.52 | 1.3 | 3 | 2,100 | 0.40 | 143 | 10.0 | 0.52 | 1.3 | 3 | 2,100 | 0.40 | 143 | 10.0 | 0.52 | 1.3 | 3 | 2,100 | 0.40 | 143 | 10.0 | 0.52 | 1.3 | 3 | 2,100 | 0.40 | 143 | 10.0 | 0.52 | 1.3 |
| 32 | 1,900 | 0.36 | 1,458 | 0.1 | 3.37 | 2.8 | 5 | 4,300 | 0.81 | 180 | 16.3 | 0.81 | 1.0 | 5 | 4,300 | 0.81 | 180 | 16.3 | 0.81 | 1.0 | 5 | 4,300 | 0.81 | 180 | 16.3 | 0.81 | 1.0 | 5 | 4,300 | 0.81 | 180 | 16.3 | 0.81 | 1.0 | 5 | 4,300 | 0.81 | 180 | 16.3 | 0.81 | 1.0 |
| 3 | 500 | 0.09 | 34 | 10.0 | 0.12 | 1.3 | 734 | 83 | 6.6 | 0.21 | 1.4 | 734 | 83 | 6.6 | 0.21 | 1.4 | 734 | 83 | 6.6 | 0.21 | 1.4 | 734 | 83 | 6.6 | 0.21 | 1.4 | 734 | 83 | 6.6 | 0.21 | 1.4 | 734 | 83 | 6.6 | 0.21 | 1.4 | 734 | 83 | 6.6 | 0.21 | 1.4 |
| 2 | 300 | 0.08 | 21 | 9.7 | 0.07 | 1.3 | 3 | 6,700 | 1.27 | 497 | 10.0 | 1.05 | 1.3 | 3 | 6,700 | 1.27 | 497 | 10.0 | 1.05 | 1.3 | 3 | 6,700 | 1.27 | 497 | 10.0 | 1.05 | 1.3 | 3 | 6,700 | 1.27 | 497 | 10.0 | 1.05 | 1.3 | 3 | 6,700 | 1.27 | 497 | 10.0 | 1.05 | 1.3 |
| 2 | 400 | 0.08 | 28 | 9.7 | 0.10 | 1.3 | 15 | 6,100 | 1.15 | 578 | 7.2 | 1.72 | 1.5 | 15 | 6,100 | 1.15 | 578 | 7.2 | 1.72 | 1.5 | 15 | 6,100 | 1.15 | 578 | 7.2 | 1.72 | 1.5 | 15 | 6,100 | 1.15 | 578 | 7.2 | 1.72 | 1.5 | 15 | 6,100 | 1.15 | 578 | 7.2 | 1.72 | 1.5 |
| 3 | 2,200 | 0.42 | 150 | 10.0 | 0.54 | 1.3 | 10 | 400 | 0.08 | 27 | 10.0 | 0.10 | 1.3 | 10 | 400 | 0.08 | 27 | 10.0 | 0.10 | 1.3 | 10 | 400 | 0.08 | 27 | 10.0 | 0.10 | 1.3 | 10 | 400 | 0.08 | 27 | 10.0 | 0.10 | 1.3 | 10 | 400 | 0.08 | 27 | 10.0 | 0.10 | 1.3 |
| 5 | 600 | 0.11 | 25 | 16.3 | 0.11 | 1.0 | 15 | 3,700 | 0.70 | 350 | 7.2 | 1.05 | 1.5 | 15 | 3,700 | 0.70 | 350 | 7.2 | 1.05 | 1.5 | 15 | 3,700 | 0.70 | 350 | 7.2 | 1.05 | 1.5 | 15 | 3,700 | 0.70 | 350 | 7.2 | 1.05 | 1.5 | 15 | 3,700 | 0.70 | 350 | 7.2 | 1.05 | 1.5 |
| 5 | 3,800 | 0.72 | 159 | 16.3 | 0.72 | 1.0 | 10 | 2,800 | 0.53 | 101 | 10.0 | 0.69 | 1.3 | 10 | 2,800 | 0.53 | 101 | 10.0 | 0.69 | 1.3 | 10 | 2,800 | 0.53 | 101 | 10.0 | 0.69 | 1.3 | 10 | 2,800 | 0.53 | 101 | 10.0 | 0.69 | 1.3 | 10 | 2,800 | 0.53 | 101 | 10.0 | 0.69 | 1.3 |
| 73 | 700 | 0.13 | 48 | 10.0 | 0.17 | 1.3 | 3 | 2,500 | 0.47 | 170 | 10.0 | 0.61 | 1.3 | 3 | 2,500 | 0.47 | 170 | 10.0 | 0.61 | 1.3 | 3 | 2,500 | 0.47 | 170 | 10.0 | 0.61 | 1.3 | 3 | 2,500 | 0.47 | 170 | 10.0 | 0.61 | 1.3 | 3 | 2,500 | 0.47 | 170 | 10.0 | 0.61 | 1.3 |
| 3 | 1,200 | 0.23 | 82 | 10.0 | 0.30 | 1.3 | 69 | 300 | 0.06 | 28 | 7.2 | 0.09 | 1.5 | 69 | 300 | 0.06 | 28 | 7.2 | 0.09 | 1.5 | 69 | 300 | 0.06 | 28 | 7.2 | 0.09 | 1.5 | 69 | 300 | 0.06 | 28 | 7.2 | 0.09 | 1.5 | 69 | 300 | 0.06 | 28 | 7.2 | 0.09 | 1.5 |
| 3 | 4,600 | 0.87 | 314 | 10.0 | 1.13 | 1.3 | 94 | 300 | 0.06 | 28 | 7.2 | 0.09 | 1.5 | 94 | 300 | 0.06 | 28 | 7.2 | 0.09 | 1.5 | 94 | 300 | 0.06 | 28 | 7.2 | 0.09 | 1.5 | 94 | 300 | 0.06 | 28 | 7.2 | 0.09 | 1.5 | 94 | 300 | 0.06 | 28 | 7.2 | 0.09 | 1.5 |
| 3 | 1,200 | 0.23 | 82 | 10.0 | 0.30 | 1.3 | 81 | 1,400 | 0.26 | 108 | 8.8 | 0.36 | 1.4 | 81 | 1,400 | 0.26 | 108 | 8.8 | 0.36 | 1.4 | 81 | 1,400 | 0.26 | 108 | 8.8 | 0.36 | 1.4 | 81 | 1,400 | 0.26 | 108 | 8.8 | 0.36 | 1.4 | 81 | 1,400 | 0.26 | 108 | 8.8 | 0.36 | 1.4 |
| 10 | 800 | 0.15 | 55 | 10.0 | 0.44 | 1.3 | 69 | 400 | 0.08 | 70 | 10.0 | 0.10 | 1.3 | 69 | 400 | 0.08 | 70 | 10.0 | 0.10 | 1.3 | 69 | 400 | 0.08 | 70 | 10.0 | 0.10 | 1.3 | 69 | 400 | 0.08 | 70 | 10.0 | 0.10 | 1.3 | 69 | 400 | 0.08 | 70 | 10.0 | 0.10 | 1.3 |
| 10 | 1,800 | 0.34 | 123 | 10.0 | 0.44 | 1.3 | 81 | 900 | 0.17 | 70 | 8.8 | 0.24 | 1.4 | 81 | 900 | 0.17 | 70 | 8.8 | 0.24 | 1.4 | 81 | 900 | 0.17 | 70 | 8.8 | 0.24 | 1.4 | 81 | 900 | 0.17 | 70 | 8.8 | 0.24 | 1.4 | 81 | 900 | 0.17 | 70 | 8.8 | 0.24 | 1.4 |
| 10 | 3,000 | 0.57 | 207 | 10.0 | 0.74 | 1.3 | 69 | 300 | 0.06 | 20 | 10.0 | 0.08 | 1.3 | 69 | 300 | 0.06 | 20 | 10.0 | 0.08 | 1.3 | 69 | 300 | 0.06 | 20 | 10.0 | 0.08 | 1.3 | 69 | 300 | 0.06 | 20 | 10.0 | 0.08 | 1.3 | 69 | 300 | 0.06 | 20 | 10.0 | 0.08 | 1.3 |
| 15 | 3,700 | 0.70 | 351 | 7.2 | 1.05 | 1.3 | 17 | 400 | 0.08 | 17 | 15.6 | 0.09 | 1.1 | 17 | 400 | 0.08 | 17 | 15.6 | 0.09 | 1.1 | 17 | 400 | 0.08 | 17 | 15.6 | 0.09 | 1.1 | 17 | 400 | 0.08 | 17 | 15.6 | 0.09 | 1.1 | 17 | 400 | 0.08 | 17 | 15.6 | 0.09 | 1.1 |
| 10 | 1,200 | 0.23 | 82 | 10.0 | 0.30 | 1.3 | 25 | 1,000 | 0.19 | 77 | 8.8 | 0.27 | 1.4 | 25 | 1,000 | 0.19 | 77 | 8.8 | 0.27 | 1.4 | 25 | 1,000 | 0.19 | 77 | 8.8 | 0.27 | 1.4 | 25 | 1,000 | 0.19 | 77 | 8.8 | 0.27 | 1.4 | 25 | 1,000 | 0.19 | 77 | 8.8 | 0.27 | 1.4 |
| 57 | 600 | 0.11 | 45 | 9.0 | 0.15 | 1.3 | 81 | 800 | 0.15 | 62 | 8.8 | 0.21 | 1.4 | 81 | 800 | 0.15 | 62 | 8.8 | 0.21 | 1.4 | 81 | 800 | 0.15 | 62 | 8.8 | 0.21 | 1.4 | 81 | 800 | 0.15 | 62 | 8.8 | 0.21 | 1.4 | 81 | 800 | 0.15 | 62 | 8.8 | 0.21 | 1.4 |
| 10 | 700 | 0.13 | 48 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |

Table 4 (Continued)

| Week- end date | Dry Season (60 or 80 MCI) | | | | | | Wet Season (60 or 80 MCI) | | | | | | Wet Season (60 or 80 MCI) | | | | | | Fuel gal/ mi. | | | | | |
|----------------------|---------------------------|---------------------|-----------------------|---------------------|-------------|---------------------|---------------------------|---------------------|-----------------------|---------------------|-------------|---------------------|---------------------------|---------------------|-----------------------|---------------------|-------------|---------------------|---------------------|------|--------|-----|------|-----|
| | Ver- tain type | Re- tain type | Dis- tance feet | Avg Speed mph | Time sec | Fuel gal/ mi. | Ver- tain type | Re- tain type | Dis- tance feet | Avg Speed mph | Time sec | Fuel gal/ mi. | Ver- tain type | Re- tain type | Dis- tance feet | Avg Speed mph | Time sec | Fuel gal/ mi. | | | | | | |
| 55 | 3 | 300 | 0.06 | 20 | 10.0 | 0.07 | 1.3 | 15 | 500 | 0.09 | 47 | 7.2 | 0.14 | 1.5 | 15 | 500 | 0.09 | 55 | 6.2 | 0.14 | 1.6 | | | |
| 56 | 3 | 300 | 0.15 | 55 | 10.0 | 0.20 | 1.3 | 3 | 3,100 | 0.59 | 211 | 10.0 | 0.77 | 1.3 | 3 | 3,100 | 0.59 | 211 | 10.0 | 0.77 | 1.3 | | | |
| 57 | 3 | 300 | 0.29 | 68 | 10.0 | 0.25 | 1.3 | 21 | 3,100 | 0.09 | 34 | 10.0 | 0.12 | 1.3 | 21 | 3,100 | 0.09 | 34 | 10.0 | 0.12 | 1.3 | | | |
| 58 | 3 | 3,600 | 0.68 | 246 | 10.0 | 0.86 | 1.3 | 3 | 1,400 | 0.26 | 95 | 10.0 | 0.34 | 1.3 | 3 | 1,400 | 0.26 | 95 | 10.0 | 0.34 | 1.3 | | | |
| 59 | 3 | 1,700 | 0.32 | 116 | 10.0 | 0.42 | 1.3 | 28 | 900 | 0.17 | 61 | 10.0 | 0.22 | 1.3 | 28 | 900 | 0.17 | 61 | 10.0 | 0.22 | 1.3 | | | |
| 31 | 2,200 | 0.42 | 150 | 10.0 | 0.54 | 1.3 | 3 | 2,100 | 0.40 | 143 | 10.0 | 0.52 | 1.3 | 3 | 2,100 | 0.40 | 143 | 10.0 | 0.52 | 1.3 | | | | |
| 10 | 1,400 | 0.08 | 27 | 10.0 | 0.10 | 1.3 | 15 | 1,400 | 0.08 | 38 | 7.2 | 0.12 | 1.5 | 15 | 1,400 | 0.08 | 38 | 7.2 | 0.12 | 1.5 | | | | |
| 10 | 1,100 | 0.21 | 75 | 10.0 | 0.27 | 1.3 | 22 | 6,700 | 1.27 | 634 | 7.2 | 1.90 | 1.5 | 22 | 6,700 | 1.27 | 634 | 7.2 | 1.90 | 1.5 | | | | |
| 19 | 3,600 | 0.68 | 104 | 23.5 | 0.41 | 0.6 | 21 | 7,400 | 1.40 | 595 | 10.0 | 0.82 | 1.3 | 21 | 7,400 | 1.40 | 595 | 10.0 | 0.82 | 1.3 | | | | |
| 19 | 200 | 0.04 | 6 | 23.5 | 0.02 | 0.6 | 3 | 1,900 | 0.36 | 130 | 10.0 | 0.47 | 1.3 | 3 | 1,900 | 0.36 | 130 | 10.0 | 0.47 | 1.3 | | | | |
| 10 | 1,700 | 0.32 | 116 | 10.0 | 0.42 | 1.3 | 10 | 1,500 | 0.28 | 102 | 10.0 | 0.36 | 1.3 | 10 | 1,500 | 0.28 | 102 | 10.0 | 0.36 | 1.3 | | | | |
| 15 | 1,800 | 0.15 | 1200 | 7.2 | 0.23 | 1.5 | 3 | 1,200 | 0.23 | 68 | 10.0 | 0.30 | 1.3 | 3 | 1,200 | 0.23 | 68 | 10.0 | 0.30 | 1.3 | | | | |
| 15 | 1,800 | 0.15 | 249 | 10.0 | 0.86 | 1.3 | 10 | 1,000 | 0.19 | 68 | 10.0 | 0.25 | 1.3 | 10 | 1,000 | 0.19 | 68 | 10.0 | 0.25 | 1.3 | | | | |
| 3 | 3 | 600 | 0.11 | 41 | 10.0 | 0.15 | 1.3 | 10 | 1,300 | 0.25 | 89 | 10.0 | 0.32 | 1.3 | 10 | 1,300 | 0.25 | 89 | 10.0 | 0.32 | 1.3 | | | |
| 3 | 1,700 | 0.32 | 116 | 10.0 | 0.42 | 1.3 | 15 | 5,000 | 0.94 | 473 | 7.2 | 1.41 | 1.5 | 15 | 5,000 | 0.94 | 473 | 7.2 | 1.41 | 1.5 | | | | |
| 3 | 3,800 | 0.15 | 55 | 10.0 | 0.20 | 1.3 | 3 | 3,500 | 0.09 | 34 | 10.0 | 0.12 | 1.3 | 3 | 3,500 | 0.09 | 34 | 10.0 | 0.12 | 1.3 | | | | |
| 21 | 3 | 4,300 | 0.08 | 293 | 10.0 | 1.06 | 1.3 | 3 | 1,800 | 0.34 | 123 | 10.0 | 0.44 | 1.3 | 3 | 1,800 | 0.34 | 123 | 10.0 | 0.44 | 1.3 | | | |
| 10 | 300 | 0.06 | 20 | 10.0 | 0.07 | 1.3 | 15 | 300 | 0.08 | 20 | 10.0 | 0.08 | 1.3 | 15 | 300 | 0.08 | 20 | 10.0 | 0.08 | 1.3 | | | | |
| 22 | 1,600 | 0.30 | 132 | 7.2 | 0.46 | 1.5 | 15 | 400 | 0.08 | 38 | 7.2 | 0.12 | 1.5 | 15 | 400 | 0.08 | 38 | 7.2 | 0.12 | 1.5 | | | | |
| 22 | 1,400 | 0.08 | 27 | 10.0 | 0.10 | 1.3 | 7 | 100 | 0.02 | 7 | 10.0 | 0.03 | 1.3 | 7 | 100 | 0.02 | 7 | 10.0 | 0.03 | 1.3 | | | | |
| 22 | 1,400 | 0.08 | 123 | 7.2 | 0.51 | 1.5 | 15 | 5,100 | 0.96 | 1948 | 10.0 | 3.61 | 1.3 | 15 | 5,100 | 0.96 | 1948 | 10.0 | 3.61 | 1.3 | | | | |
| 22 | 1,400 | 0.08 | 130 | 7.2 | 0.51 | 1.5 | 15 | 400 | 0.08 | 38 | 7.2 | 0.12 | 1.5 | 15 | 400 | 0.08 | 38 | 7.2 | 0.12 | 1.5 | | | | |
| 22 | 1,900 | 0.36 | 180 | 7.2 | 0.54 | 1.5 | 15 | 1,800 | 0.34 | 123 | 10.0 | 0.44 | 1.3 | 15 | 1,800 | 0.34 | 123 | 10.0 | 0.44 | 1.3 | | | | |
| 2 | 500 | 0.09 | 35 | 9.7 | 0.12 | 1.3 | 64 | 700 | 0.13 | 66 | 7.2 | 0.20 | 1.5 | 64 | 700 | 0.13 | 77 | 6.2 | 0.20 | 1.6 | | | | |
| 15 | 600 | 0.11 | 57 | 7.2 | 0.17 | 1.5 | 69 | 1,000 | 0.23 | 82 | 10.0 | 0.30 | 1.3 | 69 | 1,000 | 0.23 | 82 | 10.0 | 0.30 | 1.3 | | | | |
| 15 | 600 | 0.11 | 1200 | 1.99 | 10.0 | 2.70 | 1.3 | 10 | 3,500 | 0.57 | 2034 | 10.0 | 1.60 | 2.8 | 10 | 3,500 | 0.57 | 2034 | 10.0 | 1.60 | 2.8 | | | |
| 28 | 1,400 | 0.28 | 95 | 10.0 | 0.34 | 1.3 | 3 | 700 | 0.13 | 48 | 10.0 | 0.17 | 1.3 | 3 | 700 | 0.13 | 48 | 10.0 | 0.17 | 1.3 | | | | |
| 3 | 3,800 | 0.72 | 259 | 10.0 | 0.94 | 1.3 | 35 | 1,900 | 0.36 | 180 | 7.2 | 0.44 | 1.5 | 35 | 1,900 | 0.36 | 209 | 6.2 | 0.44 | 1.6 | | | | |
| 10 | 1,700 | 0.32 | 116 | 10.0 | 0.42 | 1.3 | 15 | 1,600 | 0.30 | 132 | 7.2 | 0.45 | 1.5 | 15 | 1,600 | 0.30 | 176 | 6.2 | 0.45 | 1.6 | | | | |
| 3 | 1,200 | 0.23 | 82 | 10.0 | 0.29 | 1.3 | 14 | 9,000 | 1.70 | 807 | 7.6 | 2.95 | 1.5 | 14 | 9,000 | 1.70 | 807 | 7.6 | 2.95 | 1.5 | | | | |
| 10 | 1,400 | 0.08 | 27 | 10.0 | 0.10 | 1.3 | 14 | 800 | 0.15 | 76 | 7.2 | 0.20 | 1.5 | 14 | 800 | 0.15 | 88 | 6.2 | 0.20 | 1.6 | | | | |
| 3 | 1,200 | 0.23 | 82 | 10.0 | 0.30 | 1.3 | 3 | 2,800 | 0.53 | 191 | 7.2 | 0.69 | 1.3 | 3 | 2,800 | 0.53 | 191 | 7.2 | 0.69 | 1.3 | | | | |
| 15 | 1,700 | 0.32 | 161 | 7.2 | 0.48 | 1.5 | 16 | 200 | 0.04 | 19 | 7.2 | 0.06 | 1.5 | 16 | 200 | 0.04 | 22 | 6.2 | 0.06 | 1.6 | | | | |
| 15 | 3,400 | 0.66 | 332 | 7.2 | 0.99 | 1.5 | 3 | 1,400 | 0.26 | 1200 | 10.0 | 2.46 | 1.3 | 3 | 1,400 | 0.26 | 1271 | 10.0 | 2.46 | 1.3 | | | | |
| 3 | 300 | 0.09 | 44 | 10.0 | 0.12 | 1.3 | 1 | 2,000 | 0.38 | 169 | 7.2 | 0.57 | 1.3 | 1 | 2,000 | 0.38 | 176 | 6.2 | 0.57 | 1.3 | | | | |
| 3 | 600 | 0.08 | 41 | 10.0 | 0.10 | 1.3 | 1 | 1,400 | 0.26 | 95 | 10.0 | 0.34 | 1.3 | 1 | 1,400 | 0.26 | 95 | 10.0 | 0.34 | 1.3 | | | | |
| 3 | 600 | 0.11 | 41 | 10.0 | 0.15 | 1.3 | 1 | 2,300 | 0.43 | 218 | 7.2 | 0.64 | 1.5 | 1 | 2,300 | 0.43 | 253 | 6.2 | 0.64 | 1.6 | | | | |
| 3 | 1,000 | 0.19 | 68 | 10.0 | 0.25 | 1.3 | 5 | 1,500 | 0.28 | 63 | 16.3 | 0.28 | 1.0 | 5 | 1,500 | 0.28 | 63 | 16.3 | 0.28 | 1.0 | | | | |
| 3 | 400 | 0.08 | 27 | 10.0 | 0.10 | 1.3 | 3 | 5,100 | 0.96 | 348 | 10.0 | 1.25 | 1.3 | 3 | 5,100 | 0.96 | 348 | 10.0 | 1.25 | 1.3 | | | | |
| 10 | 200 | 0.05 | 20 | 10.0 | 0.07 | 1.3 | 4 | 1,600 | 0.30 | 140 | 7.8 | 0.45 | 1.5 | 4 | 1,600 | 0.30 | 140 | 7.8 | 0.45 | 1.5 | | | | |
| 15 | 1,400 | 0.11 | 57 | 7.2 | 0.17 | 1.5 | 2 | 1,400 | 0.28 | 133 | 7.2 | 0.39 | 1.5 | 2 | 1,400 | 0.28 | 154 | 6.2 | 0.39 | 1.6 | | | | |
| 15 | 1,400 | 0.28 | 133 | 7.2 | 0.40 | 1.5 | 2 | 1,400 | 0.28 | 98 | 9.7 | 0.34 | 1.3 | 2 | 1,400 | 0.28 | 98 | 9.7 | 0.34 | 1.3 | | | | |
| 3 | 300 | 0.06 | 2400 | 10.0 | 0.10 | 1.3 | 3 | 300 | 0.06 | 2400 | 10.0 | 0.10 | 1.3 | 3 | 300 | 0.06 | 2400 | 10.0 | 0.10 | 1.3 | | | | |
| 10 | 600 | 0.11 | 41 | 10.0 | 0.15 | 1.3 | 11 | 1,100 | 0.20 | 101 | 10.0 | 0.31 | 1.3 | 11 | 1,100 | 0.20 | 101 | 10.0 | 0.31 | 1.3 | | | | |
| 3 | 3,900 | 0.74 | 266 | 10.0 | 0.96 | 1.3 | 3 | 3,900 | 0.74 | 266 | 10.0 | 0.96 | 1.3 | 3 | 3,900 | 0.74 | 266 | 10.0 | 0.96 | 1.3 | | | | |
| 69 | 2,100 | 0.40 | 183 | 10.0 | 0.58 | 1.3 | 13 | 1,300 | 0.28 | 103 | 10.0 | 0.32 | 1.3 | 13 | 1,300 | 0.28 | 103 | 10.0 | 0.32 | 1.3 | | | | |
| 13 | 3,000 | 0.57 | 20,460 | 0.1 | 1.59 | 2.8 | 20,460 | 0.57 | 20,460 | 0.1 | 1.59 | 2.8 | 20,460 | 0.57 | 20,460 | 0.1 | 1.59 | 2.8 | 20,460 | 0.57 | 20,460 | 0.1 | 1.59 | 2.8 |
| 10 | 1,400 | 0.08 | 27 | 10.0 | 0.10 | 1.3 | 3 | 1,400 | 0.08 | 27 | 10.0 | 0.10 | 1.3 | 3 | 1,400 | 0.08 | 27 | 10.0 | 0.10 | 1.3 | | | | |
| 3 | 800 | 0.15 | 55 | 10.0 | 0.20 | 1.3 | 10 | 1,800 | 0.34 | 122 | 7.8 | 0.40 | 1.5 | 10 | 1,800 | 0.34 | 122 | 7.8 | 0.40 | 1.5 | | | | |
| 10 | 1,800 | 0.34 | 122 | 7.8 | 0.40 | 1.5 | 10 | 1,800 | 0.34 | 122 | 7.8 | 0.40 | 1.5 | 10 | 1,800 | 0.34 | 122 | 7.8 | 0.40 | 1.5 | | | | |
| 14 | 3,400 | 0.64 | 305 | 7.6 | 0.96 | 1.5 | 14 | 3,400 | 0.64 | 305 | 7.6 | 0.96 | 1.5 | 14 | 3,400 | 0.64 | 305 | 7.6 | 0.96 | 1.5 | | | | |

(Continued)

(15) 20 9)

Table 4 (Continued)

| Vehi- cle | Ter- rain TYPE | Dry Season (60 or 45 RCI) | | | | | Wet Season (60 or 40 RCI) | | | | | Wet Season (60 or 35 RCI) | | | | |
|--------------|----------------------|---------------------------|---------------------|-------------|---------------------|----------------------|---------------------------|---------------------|-------------|---------------------|----------------------|---------------------------|---------------------|-------------|---------------------|----------------------|
| | | Distance feet | Pen- alty sec | Time sec | Avg Speed mph | Fuel gal/ mile | Distance feet | Pen- alty sec | Time sec | Avg Speed mph | Fuel gal/ mile | Distance feet | Pen- alty sec | Time sec | Avg Speed mph | Fuel gal/ mile |
| M520 | 1 | 800 | 0.15 | 76 | 7.2 | 0.23 | 1.5 | | | | | | | | | |
| | 4 | 700 | 0.13 | 61 | 7.8 | 0.20 | 1.5 | | | | | | | | | |
| | 4 | 4,600 | 0.87 | 402 | 7.8 | 1.31 | 1.5 | | | | | | | | | |
| | 4 | 1,300 | 0.25 | 114 | 7.8 | 0.37 | 1.5 | | | | | | | | | |
| | 3 | 700 | 0.15 | 55 | 10.0 | 0.20 | 1.3 | | | | | | | | | |
| | 3 | 2,900 | 0.55 | 198 | 10.0 | 0.71 | 1.3 | | | | | | | | | |
| | 3 | 4,700 | 0.89 | 1,611 | 7.8 | 3.70 | 1.5 | | | | | | | | | |
| | 13 | 300 | 0.08 | 2,046 | 0.1 | 0.16 | 2.8 | | | | | | | | | |
| | 3 | 4,600 | 0.87 | 314 | 10.0 | 1.13 | 1.3 | | | | | | | | | |
| | 3 | 2,100 | 0.47 | 183 | 10.0 | 0.52 | 1.3 | | | | | | | | | |
| | 4 | 3,700 | 0.70 | 324 | 7.8 | 1.05 | 1.5 | | | | | | | | | |
| | 2 | 600 | 0.11 | 42 | 9.7 | 0.15 | 1.3 | | | | | | | | | |
| Totals | | 283,600 | 46.03 | 75,473 | 84.14 | | | 257,000 | 48.57 | 104,621 | 88.07 | | 257,000 | 48.57 | 105,542 | 89.24 |
| M520 | 2 | 1,100 | 0.21 | 107 | 7.0 | 0.35 | 1.7 | | | | | | | | | |
| | 10 | 2,100 | 0.40 | 199 | 7.2 | 0.64 | 1.6 | | | | | | | | | |
| | 52 | 700 | 0.13 | 66 | 7.2 | 0.21 | 1.6 | | | | | | | | | |
| | 10 | 2,900 | 0.55 | 275 | 7.2 | 0.80 | 1.6 | | | | | | | | | |
| | 10 | 2,800 | 0.53 | 265 | 7.2 | 0.85 | 1.6 | | | | | | | | | |
| | 6 | 300 | 0.06 | 30 | 6.8 | 0.10 | 1.8 | | | | | | | | | |
| | 10 | 6,200 | 1.23 | 633 | 7.2 | 1.97 | 1.6 | | | | | | | | | |
| | 5 | 500 | 0.09 | 52 | 6.8 | 0.17 | 1.8 | | | | | | | | | |
| | 10 | 1,400 | 0.26 | 133 | 7.2 | 0.42 | 1.6 | | | | | | | | | |
| | 6 | 2,300 | 0.44 | 231 | 6.8 | 0.78 | 1.8 | | | | | | | | | |
| | 4 | 200 | 0.04 | 21 | 6.5 | 0.07 | 1.8 | | | | | | | | | |
| | 10 | 1,200 | 0.16 | 114 | 7.2 | 0.36 | 1.6 | | | | | | | | | |
| | 6 | 1,000 | 0.19 | 100 | 6.8 | 0.34 | 1.8 | | | | | | | | | |
| | 10 | 700 | 0.13 | 66 | 7.2 | 0.21 | 1.6 | | | | | | | | | |
| | 6 | 1,800 | 0.34 | 181 | 6.8 | 0.61 | 1.8 | | | | | | | | | |
| | 10 | 2,100 | 0.40 | 199 | 7.2 | 0.64 | 1.6 | | | | | | | | | |
| | 3 | 2,900 | 0.55 | 275 | 7.2 | 0.88 | 1.6 | | | | | | | | | |
| | 10 | 2,100 | 0.40 | 240 | 7.2 | 3.20 | 1.6 | | | | | | | | | |
| | 3 | 1,200 | 0.23 | 114 | 7.2 | 0.36 | 1.6 | | | | | | | | | |
| | 37 | 900 | 0.15 | 78 | 7.0 | 0.24 | 1.6 | | | | | | | | | |
| | 10 | 2,500 | 0.47 | 237 | 7.2 | 0.76 | 1.6 | | | | | | | | | |
| | 85 | 800 | 0.15 | 70 | 7.8 | 0.23 | 1.5 | | | | | | | | | |
| | 85 | 200 | 0.04 | 17 | 7.8 | 0.06 | 1.5 | | | | | | | | | |
| | 49 | 1,100 | 0.21 | 101 | 7.2 | 0.33 | 1.5 | | | | | | | | | |
| | 49 | 1,100 | 0.21 | 101 | 7.4 | 0.35 | 1.7 | | | | | | | | | |
| | 6 | 300 | 0.06 | 30 | 6.8 | 0.10 | 1.8 | | | | | | | | | |
| | 28 | 800 | 0.15 | 76 | 7.2 | 0.24 | 1.6 | | | | | | | | | |
| | 3 | 1,000 | 0.19 | 95 | 7.2 | 0.30 | 1.6 | | | | | | | | | |
| 28 | 600 | 0.11 | 57 | 7.2 | 0.18 | 1.6 | | | | | | | | | | |
| 6 | 1,700 | 0.32 | 171 | 6.8 | 0.58 | 1.8 | | | | | | | | | | |
| 28 | 900 | 0.17 | 85 | 7.2 | 0.27 | 1.6 | | | | | | | | | | |
| 32 | 3,300 | 0.62 | 330 | 7.0 | 1.00 | 1.6 | | | | | | | | | | |
| 3 | 200 | 0.04 | 19 | 7.2 | 0.06 | 1.6 | | | | | | | | | | |
| 83 | 1,300 | 0.24 | 108 | 5.7 | 0.52 | 2.1 | | | | | | | | | | |

(Continued)

(7 of 32 sheets)

Table 4 (Continued)

| Vehi- cle | Ter- rein Type | Dry Season (60 or 40 RCI) | | | | | Wet Season (60 or 40 RCI) | | | | | Wet Season (60 or 40 RCI) | | | | | Wet Season (60 or 40 RCI) | | | | | | | | |
|--------------|----------------------|---------------------------|-----------------------|-------------|---------------------|----------------------|---------------------------|-----------------------|-------------|---------------------|----------------------|---------------------------|------------------|-----------------------|-------------|---------------------|---------------------------|----------------------|------------------|-----------------------|-------------|---------------------|----------------------|------|-----|
| | | Distance feet | Pen- alty miles | Time sec | Avg Speed mph | Fuel gal/ mile | Distance feet | Pen- alty miles | Time sec | Avg Speed mph | Fuel gal/ mile | Ter- rein Type | Distance feet | Pen- alty miles | Time sec | Avg Speed mph | Fuel gal/ mile | Ter- rein Type | Distance feet | Pen- alty miles | Time sec | Avg Speed mph | Fuel gal/ mile | | |
| 83 | 82 | 700 | 0.13 | 58 | 5.7 | 0.28 | 2.1 | 0.28 | 2.1 | 0.28 | 2.1 | 3 | 100 | 0.02 | 9 | 7.2 | 0.03 | 1.6 | 0.02 | 9 | 7.2 | 0.03 | 1.6 | | |
| 82 | 82 | 1,000 | 0.19 | 120 | 5.7 | 0.38 | 2.1 | 0.38 | 2.1 | 0.38 | 2.1 | 90 | 600 | 0.11 | 59 | 7.0 | 0.19 | 1.7 | 59 | 7.0 | 0.19 | 1.7 | | | |
| 14 | 14 | 1,200 | 0.28 | 180 | 5.7 | 0.50 | 2.1 | 0.50 | 2.1 | 0.50 | 2.1 | 86 | 1,000 | 0.19 | 85 | 8.0 | 0.27 | 1.4 | 86 | 8.0 | 0.27 | 1.4 | | | |
| 10 | 10 | 2,100 | 0.40 | 199 | 7.2 | 0.64 | 1.6 | 0.64 | 1.6 | 0.64 | 1.6 | 37 | 300 | 0.06 | 25 | 8.2 | 0.10 | 1.6 | 37 | 8.2 | 0.10 | 1.6 | | | |
| 10 | 10 | 300 | 0.06 | 36 | 5.7 | 0.12 | 2.1 | 0.12 | 2.1 | 0.12 | 2.1 | 84 | 600 | 0.11 | 39 | 10.4 | 0.15 | 1.4 | 39 | 10.4 | 0.15 | 1.4 | | | |
| 10 | 10 | 500 | 0.09 | 47 | 7.2 | 0.15 | 1.6 | 0.15 | 1.6 | 0.15 | 1.6 | 37 | 300 | 0.04 | 17 | 8.2 | 0.06 | 1.6 | 37 | 8.2 | 0.06 | 1.6 | | | |
| 92 | 92 | 1,900 | 0.36 | 227 | 5.7 | 0.72 | 2.0 | 0.72 | 2.0 | 0.72 | 2.0 | 37 | 1,500 | 0.28 | 168 | 8.2 | 0.34 | 1.9 | 353 | 8.3 | 0.32 | 1.9 | | | |
| 14 | 14 | 200 | 0.04 | 24 | 7.2 | 0.08 | 2.1 | 0.08 | 2.1 | 0.08 | 2.1 | 87 | 1,600 | 0.21 | 73 | 5.6 | 0.23 | 2.1 | 87 | 5.6 | 0.23 | 2.1 | | | |
| 3 | 3 | 1,100 | 0.21 | 104 | 7.2 | 0.33 | 1.6 | 0.33 | 1.6 | 0.33 | 1.6 | 14 | 2,900 | 0.55 | 347 | 5.7 | 1.16 | 2.1 | 14 | 2,900 | 0.55 | 347 | 5.7 | 1.16 | 2.1 |
| 10 | 10 | 2,800 | 0.53 | 265 | 7.2 | 0.85 | 1.6 | 0.85 | 1.6 | 0.85 | 1.6 | 10 | 1,900 | 0.36 | 180 | 7.2 | 0.58 | 1.6 | 10 | 1,900 | 0.36 | 180 | 7.2 | 0.58 | 1.6 |
| 10 | 10 | 1,500 | 0.28 | 142 | 7.2 | 0.45 | 1.6 | 0.45 | 1.6 | 0.45 | 1.6 | 14 | 300 | 0.06 | 36 | 5.7 | 0.13 | 2.1 | 14 | 300 | 0.06 | 36 | 5.7 | 0.13 | 2.1 |
| 3 | 3 | 1,900 | 0.36 | 166 | 7.8 | 0.54 | 1.5 | 0.54 | 1.5 | 0.54 | 1.5 | 15 | 400 | 0.08 | 42 | 6.5 | 0.14 | 1.8 | 15 | 400 | 0.08 | 42 | 6.5 | 0.14 | 1.8 |
| 3 | 3 | 700 | 0.13 | 66 | 7.2 | 0.21 | 1.6 | 0.21 | 1.6 | 0.21 | 1.6 | 82 | 2,000 | 0.30 | 239 | 5.7 | 0.76 | 2.0 | 82 | 2,000 | 0.30 | 239 | 5.7 | 0.76 | 2.0 |
| 57 | 57 | 6,000 | 1.14 | 602 | 6.8 | 2.04 | 1.8 | 2.04 | 1.8 | 2.04 | 1.8 | 14 | 300 | 0.06 | 36 | 5.7 | 0.13 | 2.1 | 14 | 300 | 0.06 | 36 | 5.7 | 0.13 | 2.1 |
| 32 | 32 | 1,600 | 0.30 | 156 | 7.0 | 0.48 | 1.6 | 0.48 | 1.6 | 0.48 | 1.6 | 15 | 600 | 0.11 | 63 | 6.5 | 0.20 | 1.8 | 15 | 600 | 0.11 | 63 | 6.5 | 0.20 | 1.8 |
| 16 | 16 | 2,900 | 0.67 | 242 | 6.0 | 0.29 | 1.7 | 0.29 | 1.7 | 0.29 | 1.7 | 15 | 400 | 0.08 | 42 | 6.5 | 0.14 | 1.8 | 15 | 400 | 0.08 | 42 | 6.5 | 0.14 | 1.8 |
| 30 | 30 | 200 | 0.04 | 22 | 6.1 | 0.17 | 1.8 | 0.17 | 1.8 | 0.17 | 1.8 | 23 | 1,900 | 0.36 | 166 | 7.8 | 0.54 | 1.5 | 23 | 1,900 | 0.36 | 166 | 7.8 | 0.54 | 1.5 |
| 3 | 3 | 700 | 0.13 | 66 | 7.2 | 0.21 | 1.6 | 0.21 | 1.6 | 0.21 | 1.6 | 16 | 800 | 0.15 | 84 | 6.5 | 0.27 | 1.8 | 16 | 800 | 0.15 | 84 | 6.5 | 0.27 | 1.8 |
| 2 | 2 | 300 | 0.06 | 29 | 7.0 | 0.10 | 1.7 | 0.10 | 1.7 | 0.10 | 1.7 | 57 | 7,000 | 1.32 | 702 | 6.8 | 2.38 | 1.8 | 57 | 7,000 | 1.32 | 702 | 6.8 | 2.38 | 1.8 |
| 3 | 3 | 1,000 | 0.19 | 95 | 7.2 | 0.30 | 1.6 | 0.30 | 1.6 | 0.30 | 1.6 | 30 | 600 | 0.11 | 67 | 6.1 | 0.21 | 1.9 | 30 | 600 | 0.11 | 67 | 6.1 | 0.21 | 1.9 |
| 32 | 32 | 12,800 | 2.42 | 2,447 | 7.0 | 5.15 | 1.6 | 5.15 | 1.6 | 5.15 | 1.6 | 6 | 900 | 0.17 | 88 | 7.0 | 0.29 | 1.7 | 2 | 900 | 0.17 | 88 | 7.0 | 0.29 | 1.7 |
| 10 | 10 | 1,800 | 0.34 | 171 | 7.2 | 0.54 | 1.6 | 0.54 | 1.6 | 0.54 | 1.6 | 2 | 500 | 0.09 | 50 | 6.3 | 0.16 | 1.8 | 6 | 500 | 0.09 | 50 | 6.3 | 0.16 | 1.8 |
| 10 | 10 | 3,600 | 0.63 | 341 | 7.2 | 1.09 | 1.6 | 1.09 | 1.6 | 1.09 | 1.6 | 30 | 300 | 0.06 | 34 | 6.1 | 0.11 | 1.9 | 30 | 300 | 0.06 | 34 | 6.1 | 0.11 | 1.9 |
| 15 | 15 | 1,900 | 0.36 | 199 | 6.5 | 0.65 | 1.8 | 0.65 | 1.8 | 0.65 | 1.8 | 3 | 2,000 | 0.38 | 189 | 7.2 | 0.61 | 1.6 | 3 | 2,000 | 0.38 | 189 | 7.2 | 0.61 | 1.6 |
| 15 | 15 | 1,700 | 0.32 | 178 | 6.5 | 0.58 | 1.8 | 0.58 | 1.8 | 0.58 | 1.8 | 30 | 12,800 | 2.42 | 2,447 | 6.1 | 5.88 | 1.9 | 30 | 12,800 | 2.42 | 2,447 | 6.1 | 5.88 | 1.9 |
| 15 | 15 | 1,000 | 0.19 | 95 | 7.2 | 0.30 | 1.6 | 0.30 | 1.6 | 0.30 | 1.6 | 15 | 5,000 | 0.94 | 524 | 6.5 | 1.69 | 1.8 | 15 | 5,000 | 0.94 | 524 | 6.5 | 1.69 | 1.8 |
| 57 | 57 | 1,500 | 0.23 | 150 | 6.8 | 0.51 | 1.8 | 0.51 | 1.8 | 0.51 | 1.8 | 10 | 600 | 0.11 | 57 | 7.2 | 0.18 | 1.6 | 10 | 600 | 0.11 | 57 | 7.2 | 0.18 | 1.6 |
| 3 | 3 | 2,800 | 0.53 | 265 | 7.2 | 0.85 | 1.6 | 0.85 | 1.6 | 0.85 | 1.6 | 15 | 3,600 | 0.68 | 378 | 6.5 | 1.22 | 1.8 | 15 | 3,600 | 0.68 | 378 | 6.5 | 1.22 | 1.8 |
| 10 | 10 | 200 | 0.04 | 19 | 7.2 | 0.06 | 1.6 | 0.06 | 1.6 | 0.06 | 1.6 | 10 | 1,000 | 0.19 | 95 | 7.2 | 0.30 | 1.6 | 10 | 1,000 | 0.19 | 95 | 7.2 | 0.30 | 1.6 |
| 10 | 10 | 100 | 0.02 | 9 | 7.2 | 0.03 | 1.6 | 0.03 | 1.6 | 0.03 | 1.6 | 57 | 1,200 | 0.23 | 120 | 6.8 | 0.41 | 1.8 | 57 | 1,200 | 0.23 | 120 | 6.8 | 0.41 | 1.8 |
| 81 | 81 | 1,400 | 0.36 | 140 | 6.8 | 0.48 | 1.8 | 0.48 | 1.8 | 0.48 | 1.8 | 16 | 2,800 | 0.54 | 255 | 7.2 | 0.57 | 1.6 | 16 | 2,800 | 0.54 | 255 | 7.2 | 0.57 | 1.6 |
| 6 | 6 | 1,300 | 0.25 | 123 | 7.2 | 0.39 | 1.6 | 0.39 | 1.6 | 0.39 | 1.6 | 3 | 2,800 | 0.53 | 265 | 7.2 | 0.85 | 1.6 | 3 | 2,800 | 0.53 | 265 | 7.2 | 0.85 | 1.6 |
| 17 | 17 | 300 | 0.06 | 25 | 8.2 | 0.09 | 1.6 | 0.09 | 1.6 | 0.09 | 1.6 | 81 | 1,700 | 0.32 | 170 | 6.8 | 0.36 | 1.8 | 81 | 1,700 | 0.32 | 170 | 6.8 | 0.36 | 1.8 |
| 25 | 25 | 1,500 | 0.23 | 120 | 6.8 | 0.41 | 1.8 | 0.41 | 1.8 | 0.41 | 1.8 | 69 | 300 | 0.06 | 28 | 7.2 | 0.10 | 1.6 | 69 | 300 | 0.06 | 28 | 7.2 | 0.10 | 1.6 |
| 66 | 66 | 1,300 | 0.25 | 123 | 7.2 | 0.39 | 1.6 | 0.39 | 1.6 | 0.39 | 1.6 | 94 | 1,000 | 0.19 | 105 | 6.5 | 0.34 | 1.8 | 94 | 1,000 | 0.19 | 105 | 6.5 | 0.34 | 1.8 |
| 6 | 6 | 300 | 0.06 | 30 | 6.8 | 0.10 | 1.8 | 0.10 | 1.8 | 0.10 | 1.8 | 17 | 500 | 0.09 | 42 | 8.2 | 0.14 | 1.6 | 17 | 500 | 0.09 | 42 | 8.2 | 0.14 | 1.6 |
| 62 | 62 | 2,400 | 0.45 | 221 | 7.4 | 0.77 | 1.7 | 0.77 | 1.7 | 0.77 | 1.7 | 25 | 1,000 | 0.19 | 100 | 6.8 | 0.30 | 1.6 | 25 | 1,000 | 0.19 | 100 | 6.8 | 0.30 | 1.6 |
| 62 | 62 | 2,700 | 0.51 | 245 | 7.4 | 0.87 | 1.7 | 0.87 | 1.7 | 0.87 | 1.7 | 69 | 1,700 | 0.32 | 161 | 7.2 | 0.51 | 1.6 | 69 | 1,700 | 0.32 | 161 | 7.2 | 0.51 | 1.6 |
| 62 | 62 | 4,100 | 0.78 | 378 | 7.4 | 1.32 | 1.7 | 1.32 | 1.7 | 1.32 | 1.7 | 25 | 800 | 0.15 | 80 | 6.8 | 0.24 | 1.6 | 25 | 800 | 0.15 | 80 | 6.8 | 0.24 | 1.6 |
| 63 | 63 | 900 | 0.17 | 85 | 7.2 | 0.27 | 1.6 | 0.27 | 1.6 | 0.27 | 1.6 | 10 | 1,100 | 0.21 | 104 | 7.2 | 0.34 | 1.6 | 10 | 1,100 | 0.21 | 104 | 7.2 | 0.34 | 1.6 |
| 63 | 63 | 500 | 0.09 | 50 | 6.8 | 0.17 | 1.8 | 0.17 | 1.8 | 0.17 | 1.8 | 6 | 400 | 0.08 | 40 | 6.8 | 0.14 | 1.8 | 6 | 400 | 0.08 | 40 | 6.8 | 0.14 | 1.8 |
| 62 | 62 | 2,400 | 0.45 | 221 | 7.4 | 0.77 | 1.7 | 0.77 | 1.7 | 0.77 | 1.7 | 62 | 6,900 | 1.30 | 696 | 7.4 | 2.21 | 1.7 | 62 | 6,900 | 1.30 | 696 | 7.4 | 2.21 | 1.7 |
| 63 | 63 | 2,800 | 0.53 | 281 | 6.8 | 0.95 | 1.8 | 0.95 | 1.8 | 0.95 | 1.8 | 15 | 1,000 | 0.19 | 105 | 6.5 | 0.34 | 1.8 | 15 | 1,000 | 0.19 | 105 | 6.5 | 0.34 | 1.8 |
| 53 | 53 | 1,600 | 0.30 | 160 | 6.8 | 0.54 | 1.8 | 0.54 | 1.8 | 0.54 | 1.8 | 63 | 500 | 0.09 | 50 | 6.8 | 0.16 | 1.8 | 63 | 500 | 0.09 | 50 | 6.8 | 0.16 | 1.8 |
| 55 | 55 | 1,200 | 0.23 | 114 | 7.2 | 0.36 | 1.6 | 0.36 | 1.6 | 0.36 | 1.6 | 62 | 2,400 | 0.45 | 221 | 7.4 | 0.76 | 1.7 | 62 | 2,400 | 0.45 | 221 | 7.4 | 0.76 | 1.7 |
| 31 | 31 | 1,100 | 0.21 | 104 | 7.2 | 0.33 | 1.6 | 0.33 | 1.6 | 0.33 | 1.6 | 63 | 4,500 | 0.85 | 451 | 6.8 | 1.53 | 1.8 | 63 | 4,500 | 0.85 | 451 | 6.8 | 1.53 | 1.8 |
| 31 | 31 | 1,300 | 0.25 | 123 | 7.2 | 0.39 | 1.6 | 0.39 | 1.6 | 0.39 | 1.6 | 80 | 1,200 | 0.23 | 136 | 6.5 | 0.41 | 1.8 | 80 | 1,200 | 0.23 | 136 | 6.5 | 0.41 | 1.8 |
| 31 | 31 | 2,500 | 0.47 | 237 | 7.2 | 0.76 | 1.6 | 0.76 | 1.6 | 0.76 | 1.6 | 31 | 1,000 | 0.19 | 95 | 7.2 | 0.30 | 1.6 | 31 | 1,000 | 0.19 | 95 | 7.2 | 0.30 | 1.6 |
| 31 | 31 | 200 | 0.04 | 19 | 7.2 | 0.06 | 1.6 | 0.06 | 1.6 | 0.06 | 1.6 | 80 | 1,300 | 0.25 | 136 | 6.5 | 0.45 | 1.8 | 80 | 1,300 | 0.25 | 136 | 6.5 | 0.45 | 1.8 |
| 31 | 31 | 500 | 0.09 | 47 | 7.2 | 0.15 | 1.6 | 0.15 | 1.6 | 0.15 | 1.6 | 31 | 3,200 | 0.61 | 303 | 7.2 | 0.56 | 1.6 | 31 | 3,200 | 0.61 | 303 | 7.2 | 0.56 | 1.6 |
| 31 | 31 | 1,000 | 0.19 | 180 | 7.2 | 0.37 | 1.6 | 0.37 | 1.6 | 0.37 | 1.6 | 10 | 1,600 | 0.34 | 153 | 7.2 | 0.51 | 1.6 | 10 | 1,600 | 0.34 | 153 | 7.2 | 0.51 | 1.6 |
| 31 | 31 | 1,000 | 0.19 | 95 | 7.2 | 0.30 | 1.6 | 0.30 | 1.6 | 0.30 | 1.6 | 31 | 1,200 | 0.23 | 114 | 7.2 | 0.37 | 1.6 | 31 | 1,200 | 0.23 | 114 | 7.2 | 0.37 | 1.6 |
| 31 | 31 | 1,200 | 0.23 | 114 | 7.2 | 0.36 | 1.6 | 0.36 | 1.6 | 0.36 | 1.6 | 10 | 1,100 | 0.21 | 104 | 7.2 | 0.34 | 1.6 | 10 | 1,100 | 0.21 | 104 | 7.2 | 0.34 | 1.6 |

(Continued)

(8 of 32 sheets)

Table 4 (Continued)

| Vehi- Cte | Ter- rain Type | Dry Season (60 or 40 RCI) | | | | | Met Season (60 or 40 RCI) | | | | | Met Season (60 or 35 RCI) | | | | |
|--------------|----------------------|---------------------------|-------------------|-------------|---------------------|----------------------|---------------------------|-------------------|-------------|---------------------|----------------------|---------------------------|-------------------|-------------|---------------------|----------------------|
| | | Distance feet | Distance miles | Time sec | Avg Speed mph | Fuel gal/ mile | Distance feet | Distance miles | Time sec | Avg Speed mph | Fuel gal/ mile | Distance feet | Distance miles | Time sec | Avg Speed mph | Fuel gal/ mile |
| 31 | 10 | 200 | 0.04 | 19 | 7.2 | 0.06 | 870 | 0.15 | 76 | 7.2 | 0.24 | 800 | 0.15 | 76 | 7.2 | 0.24 |
| 10 | 10 | 500 | 0.09 | 47 | 7.2 | 0.15 | 600 | 0.11 | 57 | 7.2 | 0.14 | 600 | 0.11 | 57 | 7.2 | 0.14 |
| 31 | 10 | 200 | 0.04 | 19 | 7.2 | 0.06 | 1,700 | 0.32 | 77 | 15.0 | 0.22 | 1,700 | 0.32 | 77 | 15.0 | 0.22 |
| 10 | 10 | 400 | 0.08 | 38 | 7.2 | 0.12 | 2,400 | 0.45 | 234 | 7.0 | 0.76 | 2,400 | 0.45 | 234 | 7.0 | 0.76 |
| 19 | 10 | 1,800 | 0.34 | 82 | 15.0 | 0.24 | 300 | 0.06 | 1200 | 12.0 | 1.36 | 300 | 0.06 | 1200 | 12.0 | 1.36 |
| 2 | 10 | 2,300 | 0.44 | 224 | 7.0 | 0.74 | 10 | 0.00 | 21 | 11.5 | 0.38 | 1,100 | 0.21 | 242 | 3.1 | 0.55 |
| 10 | 10 | 500 | 0.17 | 85 | 7.2 | 0.27 | 10 | 0.00 | 21 | 11.5 | 0.38 | 1,100 | 0.21 | 242 | 3.1 | 0.55 |
| Lake | 10 | 600 | 0.11 | 17 | 14.1 | 3.3 | 3,300 | 0.68 | 47 | 6.5 | 0.14 | 3,300 | 0.68 | 47 | 6.5 | 0.14 |
| 15 | 10 | 700 | 0.13 | 73 | 6.5 | 0.24 | 2,300 | 0.43 | 218 | 7.2 | 0.69 | 2,300 | 0.43 | 218 | 7.2 | 0.69 |
| 10 | 10 | 3,400 | 0.64 | 322 | 7.2 | 1.03 | 1,200 | 0.23 | 114 | 7.2 | 0.37 | 1,200 | 0.23 | 114 | 7.2 | 0.37 |
| 3 | 10 | 2,400 | 0.45 | 227 | 7.2 | 0.73 | 4,300 | 0.81 | 407 | 7.2 | 1.30 | 4,300 | 0.81 | 407 | 7.2 | 1.30 |
| 21 | 10 | 1,700 | 0.40 | 161 | 7.2 | 0.71 | 800 | 0.19 | 184 | 6.2 | 0.34 | 800 | 0.19 | 184 | 6.2 | 0.34 |
| 22 | 10 | 3,700 | 0.70 | 381 | 7.2 | 1.12 | 1,000 | 0.08 | 105 | 6.2 | 0.34 | 1,000 | 0.08 | 105 | 6.2 | 0.34 |
| 22 | 10 | 1,800 | 0.34 | 188 | 6.5 | 0.61 | 2,000 | 0.38 | 210 | 6.5 | 0.68 | 2,000 | 0.38 | 210 | 6.5 | 0.68 |
| 21 | 10 | 400 | 0.08 | 38 | 7.2 | 0.12 | 2,000 | 0.38 | 210 | 6.5 | 0.68 | 2,000 | 0.38 | 210 | 6.5 | 0.68 |
| 22 | 10 | 400 | 0.08 | 42 | 6.5 | 0.14 | 21 | 0.00 | 19 | 7.2 | 0.06 | 21 | 0.00 | 19 | 7.2 | 0.06 |
| 22 | 10 | 1,100 | 0.21 | 115 | 6.5 | 0.37 | 2,300 | 0.43 | 241 | 6.5 | 0.77 | 2,300 | 0.43 | 241 | 6.5 | 0.77 |
| 21 | 10 | 600 | 0.11 | 57 | 7.2 | 0.18 | 1,500 | 0.09 | 1200 | 7.2 | 1.42 | 1,500 | 0.09 | 1200 | 7.2 | 1.42 |
| 21 | 10 | 2,500 | 0.47 | 262 | 6.5 | 0.85 | 3,400 | 0.57 | 284 | 7.2 | 0.91 | 3,400 | 0.57 | 284 | 7.2 | 0.91 |
| 21 | 10 | 400 | 0.08 | 17 | 55 | 7.2 | 2,300 | 0.43 | 218 | 7.2 | 0.69 | 2,300 | 0.43 | 218 | 7.2 | 0.69 |
| 3 | 10 | 800 | 0.15 | 75 | 7.2 | 0.24 | 3,100 | 0.21 | 104 | 7.2 | 0.34 | 3,100 | 0.21 | 104 | 7.2 | 0.34 |
| 28 | 10 | 800 | 0.15 | 76 | 7.2 | 0.24 | 1,800 | 0.34 | 170 | 7.2 | 0.54 | 1,800 | 0.34 | 170 | 7.2 | 0.54 |
| 21 | 10 | 3,300 | 0.44 | 123 | 7.2 | 0.70 | 800 | 0.15 | 76 | 7.2 | 0.24 | 800 | 0.15 | 76 | 7.2 | 0.24 |
| 3 | 10 | 1,000 | 0.19 | 95 | 7.2 | 0.30 | 1,100 | 0.21 | 114 | 7.2 | 0.37 | 1,100 | 0.21 | 114 | 7.2 | 0.37 |
| 10 | 10 | 1,700 | 0.32 | 161 | 7.2 | 0.51 | 1,300 | 0.23 | 104 | 7.2 | 0.37 | 1,300 | 0.23 | 104 | 7.2 | 0.37 |
| 10 | 10 | 1,000 | 0.19 | 95 | 7.2 | 0.30 | 5,200 | 0.98 | 545 | 6.5 | 1.76 | 5,200 | 0.98 | 545 | 6.5 | 1.76 |
| 10 | 10 | 1,600 | 0.11 | 57 | 7.2 | 0.18 | 1,000 | 0.19 | 95 | 7.2 | 0.30 | 1,000 | 0.19 | 95 | 7.2 | 0.30 |
| 10 | 10 | 1,200 | 0.23 | 114 | 7.2 | 0.36 | 800 | 0.15 | 76 | 7.2 | 0.24 | 800 | 0.15 | 76 | 7.2 | 0.24 |
| 10 | 10 | 1,500 | 0.28 | 142 | 7.2 | 0.45 | 700 | 0.13 | 66 | 7.2 | 0.21 | 700 | 0.13 | 66 | 7.2 | 0.21 |
| 15 | 10 | 2,900 | 0.55 | 304 | 6.5 | 0.99 | 400 | 0.08 | 38 | 7.2 | 0.13 | 400 | 0.08 | 38 | 7.2 | 0.13 |
| 15 | 10 | 2,500 | 0.47 | 262 | 6.5 | 0.86 | 300 | 0.06 | 28 | 7.2 | 0.10 | 300 | 0.06 | 28 | 7.2 | 0.10 |
| 15 | 10 | 600 | 0.11 | 57 | 7.2 | 0.18 | 100 | 0.02 | 9 | 7.2 | 0.03 | 100 | 0.02 | 9 | 7.2 | 0.03 |
| 10 | 10 | 400 | 0.08 | 38 | 7.2 | 0.12 | 4,800 | 0.91 | 1694 | 7.2 | 2.74 | 4,800 | 0.91 | 1694 | 7.2 | 2.74 |
| 3 | 10 | 1,800 | 0.34 | 171 | 7.2 | 0.54 | 700 | 0.13 | 66 | 7.2 | 0.23 | 700 | 0.13 | 66 | 7.2 | 0.23 |
| 10 | 10 | 300 | 0.06 | 28 | 7.2 | 0.09 | 2,800 | 0.53 | 265 | 7.2 | 0.85 | 2,800 | 0.53 | 265 | 7.2 | 0.85 |
| 15 | 10 | 400 | 0.08 | 42 | 6.5 | 0.14 | 1,200 | 0.23 | 126 | 6.5 | 0.41 | 1,200 | 0.23 | 126 | 6.5 | 0.41 |
| 3 | 10 | 1,000 | 0.19 | 95 | 7.2 | 0.30 | 3,000 | 0.57 | 568 | 3.6 | 1.65 | 3,000 | 0.57 | 568 | 3.6 | 1.65 |
| 3 | 10 | 7,200 | 1.36 | 1,882 | 7.2 | 3.46 | 600 | 0.11 | 57 | 7.2 | 0.18 | 600 | 0.11 | 57 | 7.2 | 0.18 |
| 69 | 10 | 1,200 | 0.23 | 114 | 7.2 | 0.36 | 700 | 0.13 | 66 | 7.2 | 0.21 | 700 | 0.13 | 66 | 7.2 | 0.21 |
| 13 | 10 | 3,100 | 0.59 | 587 | 3.6 | 1.70 | 2,000 | 0.38 | 210 | 6.5 | 0.68 | 2,000 | 0.38 | 210 | 6.5 | 0.68 |
| 10 | 10 | 500 | 0.09 | 47 | 7.2 | 0.15 | 1,800 | 0.34 | 189 | 6.5 | 0.61 | 1,800 | 0.34 | 189 | 6.5 | 0.61 |
| 3 | 10 | 500 | 0.09 | 47 | 7.2 | 0.15 | 400 | 0.04 | 21 | 6.5 | 0.07 | 400 | 0.04 | 21 | 6.5 | 0.07 |
| 3 | 10 | 1,700 | 0.32 | 161 | 7.2 | 0.51 | 5,800 | 1.10 | 684 | 5.7 | 2.31 | 5,800 | 1.10 | 684 | 5.7 | 2.31 |
| 10 | 10 | 2,100 | 0.40 | 199 | 7.2 | 0.64 | 600 | 0.11 | 63 | 6.5 | 0.20 | 600 | 0.11 | 63 | 6.5 | 0.20 |
| 4 | 10 | 1,800 | 0.34 | 189 | 6.5 | 0.61 | 1,600 | 0.30 | 191 | 5.7 | 0.63 | 1,600 | 0.30 | 191 | 5.7 | 0.63 |
| 14 | 10 | 2,700 | 0.51 | 323 | 5.7 | 1.07 | 300 | 0.06 | 31 | 6.5 | 0.11 | 300 | 0.06 | 31 | 6.5 | 0.11 |
| 14 | 10 | 3,100 | 0.59 | 371 | 5.7 | 1.23 | 2,800 | 0.53 | 265 | 7.2 | 0.85 | 2,800 | 0.53 | 265 | 7.2 | 0.85 |
| 14 | 10 | 600 | 0.11 | 63 | 6.5 | 0.20 | 1,200 | 0.23 | 126 | 6.5 | 0.41 | 1,200 | 0.23 | 126 | 6.5 | 0.41 |
| 14 | 10 | 1,600 | 0.30 | 191 | 5.7 | 0.64 | 700 | 0.13 | 66 | 7.2 | 0.21 | 700 | 0.13 | 66 | 7.2 | 0.21 |
| 4 | 10 | 400 | 0.08 | 42 | 6.5 | 0.14 | 100 | 0.02 | 10 | 6.5 | 0.04 | 100 | 0.02 | 10 | 6.5 | 0.04 |
| 14 | 10 | 1,100 | 0.21 | 132 | 5.7 | 0.44 | 300 | 0.06 | 28 | 7.2 | 0.10 | 300 | 0.06 | 28 | 7.2 | 0.10 |
| 3 | 10 | 2,800 | 0.53 | 265 | 7.2 | 0.85 | 1,800 | 0.34 | 189 | 6.5 | 0.61 | 1,800 | 0.34 | 189 | 6.5 | 0.61 |
| 4 | 10 | 2,900 | 0.55 | 1,504 | 6.5 | 2.27 | 1,300 | 0.25 | 123 | 7.2 | 0.40 | 1,300 | 0.25 | 123 | 7.2 | 0.40 |
| 3 | 10 | 1,400 | 0.26 | 133 | 7.2 | 0.42 | 2,100 | 0.40 | 220 | 6.5 | 0.72 | 2,100 | 0.40 | 220 | 6.5 | 0.72 |

(Continued)

(9 of 32 sheets)

Table 4 (Continued)

| Vehi- cle | Ter- rain Type | Dry Season (60 or 100 NCI) | | | | | Wet Season (60 or 100 NCI) | | | | | Met Season (60 or 100 NCI) | | | | | Met Season (60 or 100 NCI) | | | | | | | |
|--------------|----------------------|----------------------------|-------------------|---------------------|-------------|---------------------|----------------------------|----------------------|---------------------|----------------------|------------------|----------------------------|---------------------|-------------|---------------------|----------------------|----------------------------|-------------------|---------------------|-------------|---------------------|----------------------|--------|-----|
| | | Distance feet | Distance miles | Pen- alty sec | Time sec | Avg Speed mph | Fuel gal/ mile | Fuel gal/ mile | Avg Speed mph | Fuel gal/ mile | Distance feet | Distance miles | Pen- alty sec | Time sec | Avg Speed mph | Fuel gal/ mile | Distance feet | Distance miles | Pen- alty sec | Time sec | Avg Speed mph | Fuel gal/ mile | | |
| M37B1 | 2 | 1,600 | 0.30 | | 100 | 10.8 | 0.21 | 0.7 | | | | | | | | | 1,400 | 0.26 | | 87 | 10.8 | 0.18 | 0.7 | |
| | 10 | 1,900 | 0.36 | | 120 | 10.8 | 0.25 | 0.7 | | | | | | | | | 1,300 | 0.06 | | 20 | 10.8 | 0.04 | 0.7 | |
| | 52 | 1,000 | 0.19 | | 22 | 31.0 | 0.04 | 0.2 | | | | | | | | | 2,700 | 0.51 | | 59 | 31.0 | 0.10 | 0.2 | |
| | 10 | 1,400 | 0.26 | | 87 | 10.8 | 0.18 | 0.7 | | | | | | | | | 1,500 | 0.28 | | 93 | 10.8 | 0.20 | 0.7 | |
| | 3 | 600 | 0.11 | | 13 | 31.0 | 0.02 | 0.2 | | | | | | | | | 600 | 0.11 | | 13 | 31.0 | 0.02 | 0.2 | |
| | 10 | 3,500 | 0.66 | | 220 | 10.8 | 0.46 | 0.7 | | | | | | | | | 3,100 | 0.59 | | 197 | 10.8 | 0.41 | 0.7 | |
| | 6 | 300 | 0.06 | | 23 | 9.4 | 0.05 | 0.8 | | | | | | | | | 200 | 0.04 | | 13 | 10.8 | 0.03 | 0.7 | |
| | 10 | 4,100 | 0.77 | | 257 | 10.8 | 0.54 | 0.7 | | | | | | | | | 10 | 200 | 0.04 | 13 | 10.8 | 0.03 | 0.7 | |
| | 6 | 2,500 | 0.47 | | 180 | 9.4 | 0.38 | 0.8 | | | | | | | | | 6 | 400 | 0.08 | 31 | 9.4 | 0.06 | 0.8 | |
| | 10 | 1,200 | 0.23 | 17 | 94 | 10.8 | 0.16 | 0.7 | | | | | | | | | 10 | 2,500 | 0.47 | 57 | 10.8 | 0.33 | 0.7 | |
| M37B1 | 6 | 600 | 0.11 | | 42 | 9.4 | 0.09 | 0.8 | | | | | | | | | 15 | 700 | 0.13 | | 49 | 9.4 | 0.10 | 0.8 |
| | 10 | 800 | 0.15 | | 50 | 10.8 | 0.10 | 0.7 | | | | | | | | | 16 | 800 | 0.15 | | 50 | 10.6 | 0.10 | 0.7 |
| | 6 | 2,600 | 0.49 | | 188 | 9.4 | 0.39 | 0.8 | | | | | | | | | 6 | 2,100 | 0.40 | | 153 | 9.4 | 0.32 | 0.8 |
| | 10 | 3,000 | 0.57 | | 190 | 10.8 | 0.40 | 0.7 | | | | | | | | | 15 | 1,200 | 0.23 | 700 | 9.4 | 1.18 | 0.8 | |
| | 6 | 800 | 0.15 | | 57 | 9.4 | 0.12 | 0.8 | | | | | | | | | 6 | 500 | 0.09 | | 34 | 9.4 | 0.07 | 0.8 |
| | 10 | 1,400 | 0.26 | | 87 | 10.8 | 0.18 | 0.7 | | | | | | | | | 15 | 800 | 0.15 | | 57 | 9.4 | 0.12 | 0.8 |
| | 6 | 1,000 | 0.19 | | 73 | 9.4 | 0.15 | 0.8 | | | | | | | | | 6 | 2,500 | 0.47 | | 180 | 9.4 | 0.38 | 0.8 |
| | 10 | 1,400 | 0.26 | | 87 | 10.8 | 0.18 | 0.7 | | | | | | | | | 15 | 1,200 | 0.23 | | 87 | 9.4 | 0.18 | 0.8 |
| | 3 | 1,500 | 0.28 | | 33 | 31.0 | 0.06 | 0.2 | | | | | | | | | 10 | 1,900 | 0.36 | | 120 | 10.8 | 0.25 | 0.7 |
| | 2 | 1,000 | 0.19 | | 63 | 10.8 | 0.13 | 0.7 | | | | | | | | | 6 | 800 | 0.15 | | 57 | 9.4 | 0.12 | 0.8 |
| | 10 | 7,600 | 1.44 | 2400 | 2,880 | 10.8 | 3.01 | 0.7 | | | | | | | | | 15 | 1,200 | 0.23 | | 87 | 9.4 | 0.18 | 0.8 |
| | 49 | 700 | 0.13 | | 42 | 11.2 | 0.08 | 0.6 | | | | | | | | | 6 | 1,100 | 0.21 | | 80 | 9.4 | 0.17 | 0.8 |
| | 6 | 800 | 0.15 | | 57 | 9.4 | 0.12 | 0.8 | | | | | | | | | 15 | 1,300 | 0.25 | | 96 | 9.4 | 0.20 | 0.8 |
| | 28 | 800 | 0.15 | | 17 | 31.0 | 0.03 | 0.2 | | | | | | | | | 3 | 1,400 | 0.26 | | 30 | 31.0 | 0.05 | 0.2 |
| | 6 | 2,800 | 0.53 | | 203 | 9.4 | 0.42 | 0.8 | | | | | | | | | 2 | 900 | 0.17 | | 57 | 10.8 | 0.12 | 0.7 |
| M37B1 | 89 | 600 | 0.11 | | 51 | 7.8 | 0.11 | 1.0 | | | | | | | | | 15 | 1,700 | 0.32 | 2400 | 9.4 | 0.26 | 0.8 | |
| | 6 | 800 | 0.15 | | 57 | 9.4 | 0.12 | 0.8 | | | | | | | | | 3 | 800 | 0.17 | | 40 | 10.8 | 0.03 | 0.8 |
| | 32 | 1,000 | 0.19 | 17 | 6,897 | 0.1 | 1.14 | 6.0 | | | | | | | | | 12 | 3,000 | 0.64 | | 243 | 8.2 | 0.06 | 0.9 |
| | 37 | 600 | 0.11 | | 13 | 31.0 | 0.02 | 0.2 | | | | | | | | | 16 | 300 | 0.06 | | 26 | 8.2 | 0.06 | 0.9 |
| | 40 | 400 | 0.08 | | 33 | 8.8 | 0.06 | 0.8 | | | | | | | | | 3 | 300 | 0.06 | | 7 | 31.0 | 0.01 | 0.2 |
| | 11 | 2,000 | 0.38 | | 154 | 8.9 | 0.30 | 0.8 | | | | | | | | | 10 | 200 | 0.04 | | 13 | 10.8 | 0.03 | 0.7 |
| | 32 | 300 | 0.06 | | 2,160 | 0.1 | 0.36 | 6.0 | | | | | | | | | 15 | 700 | 0.13 | | 49 | 9.4 | 0.10 | 0.8 |
| | 87 | 1,000 | 0.19 | | 88 | 7.8 | 0.19 | 1.0 | | | | | | | | | 19 | 600 | 0.11 | | 35 | 11.2 | 0.07 | 0.6 |
| | 14 | 5,500 | 1.04 | | 576 | 6.5 | 1.25 | 1.2 | | | | | | | | | 6 | 1,000 | 0.19 | | 73 | 9.4 | 0.15 | 0.8 |
| | Totals | | 237,100 | 44.89 | | 29,591 | 82.33 | | | | | | | | | | | 236,000 | 44.64 | | 40,797 | | 101.42 | |

(Continued)

(10 of 32 sheets)

Table 4 (Continued)

| Vehi- cle | Ter- rain Type | Dry Season (60 or 40 RCI) | | | | | Wet Season (60 or 40 RCI) | | | | | Wet Season (60 or 40 RCI) | | | | | Wet Season (60 or 40 RCI) | | | | |
|--------------|----------------------|---------------------------|-------------|--------------|----------------------|----------------------|---------------------------|-------------|--------------|----------------------|----------------------|---------------------------|-------------|--------------|----------------------|----------------------|---------------------------|-------------|--------------|----------------------|----------------------|
| | | Distance feet | Time sec | Speed mph | Fuel gal/ mile | Ter- rain Type | Distance feet | Time sec | Speed mph | Fuel gal/ mile | Ter- rain Type | Distance feet | Time sec | Speed mph | Fuel gal/ mile | Ter- rain Type | Distance feet | Time sec | Speed mph | Fuel gal/ mile | Ter- rain Type |
| 62 | | 600 | 0.11 | 6.4 | 0.13 | 1.2 | 62 | 0.13 | 6.4 | 0.13 | 1.2 | 62 | 0.13 | 6.4 | 0.13 | 1.2 | 62 | 0.13 | 6.4 | 0.13 | 1.2 |
| 14 | | 300 | 0.06 | 33 | 6.5 | 0.07 | 1.2 | 33 | 6.5 | 0.07 | 1.2 | 33 | 6.5 | 0.07 | 1.2 | 33 | 6.5 | 0.07 | 1.2 | 33 | 6.5 |
| 3 | | 1,800 | 0.34 | 39 | 31.0 | 0.07 | 0.2 | 39 | 31.0 | 0.07 | 0.2 | 39 | 31.0 | 0.07 | 0.2 | 39 | 31.0 | 0.07 | 0.2 | 39 | 31.0 |
| 10 | | 600 | 0.11 | 37 | 10.8 | 0.08 | 0.7 | 37 | 10.8 | 0.08 | 0.7 | 37 | 10.8 | 0.08 | 0.7 | 37 | 10.8 | 0.08 | 0.7 | 37 | 10.8 |
| 3 | | 1,200 | 0.23 | 27 | 31.0 | 0.08 | 0.2 | 27 | 31.0 | 0.08 | 0.2 | 27 | 31.0 | 0.08 | 0.2 | 27 | 31.0 | 0.08 | 0.2 | 27 | 31.0 |
| 10 | | 3,700 | 0.70 | 233 | 10.8 | 0.49 | 0.7 | 233 | 10.8 | 0.49 | 0.7 | 233 | 10.8 | 0.49 | 0.7 | 233 | 10.8 | 0.49 | 0.7 | 233 | 10.8 |
| 23 | | 1,800 | 0.34 | 52 | 23.7 | 0.10 | 0.3 | 52 | 23.7 | 0.10 | 0.3 | 52 | 23.7 | 0.10 | 0.3 | 52 | 23.7 | 0.10 | 0.3 | 52 | 23.7 |
| 3 | | 800 | 0.15 | 17 | 31.0 | 0.03 | 0.2 | 17 | 31.0 | 0.03 | 0.2 | 17 | 31.0 | 0.03 | 0.2 | 17 | 31.0 | 0.03 | 0.2 | 17 | 31.0 |
| 57 | | 7,000 | 1.32 | 914 | 5.2 | 1.85 | 1.4 | 914 | 5.2 | 1.85 | 1.4 | 914 | 5.2 | 1.85 | 1.4 | 914 | 5.2 | 1.85 | 1.4 | 914 | 5.2 |
| 32 | | 500 | 0.09 | 3,243 | 0.1 | 0.54 | 6.0 | 3,243 | 0.1 | 0.54 | 6.0 | 3,243 | 0.1 | 0.54 | 6.0 | 3,243 | 0.1 | 0.54 | 6.0 | 3,243 | 0.1 |
| 2 | | 1,000 | 0.19 | 63 | 10.8 | 0.13 | 0.7 | 63 | 10.8 | 0.13 | 0.7 | 63 | 10.8 | 0.13 | 0.7 | 63 | 10.8 | 0.13 | 0.7 | 63 | 10.8 |
| 16 | | 400 | 0.08 | 32 | 9.0 | 0.06 | 0.8 | 32 | 9.0 | 0.06 | 0.8 | 32 | 9.0 | 0.06 | 0.8 | 32 | 9.0 | 0.06 | 0.8 | 32 | 9.0 |
| 30 | | 200 | 0.04 | 1,440 | 0.1 | 0.24 | 6.0 | 1,440 | 0.1 | 0.24 | 6.0 | 1,440 | 0.1 | 0.24 | 6.0 | 1,440 | 0.1 | 0.24 | 6.0 | 1,440 | 0.1 |
| 3 | | 800 | 0.15 | 17 | 31.0 | 0.03 | 0.2 | 17 | 31.0 | 0.03 | 0.2 | 17 | 31.0 | 0.03 | 0.2 | 17 | 31.0 | 0.03 | 0.2 | 17 | 31.0 |
| 2 | | 300 | 0.06 | 20 | 10.8 | 0.04 | 0.7 | 20 | 10.8 | 0.04 | 0.7 | 20 | 10.8 | 0.04 | 0.7 | 20 | 10.8 | 0.04 | 0.7 | 20 | 10.8 |
| 3 | | 1,200 | 0.23 | 27 | 31.0 | 0.05 | 0.2 | 27 | 31.0 | 0.05 | 0.2 | 27 | 31.0 | 0.05 | 0.2 | 27 | 31.0 | 0.05 | 0.2 | 27 | 31.0 |
| 32 | | 1,800 | 0.34 | 1,200 | 13,440 | 0.1 | 3.04 | 13,440 | 0.1 | 3.04 | 6.0 | 13,440 | 0.1 | 3.04 | 6.0 | 13,440 | 0.1 | 3.04 | 6.0 | 13,440 | 0.1 |
| 3 | | 600 | 0.11 | 43 | 31.0 | 0.02 | 0.2 | 43 | 31.0 | 0.02 | 0.2 | 43 | 31.0 | 0.02 | 0.2 | 43 | 31.0 | 0.02 | 0.2 | 43 | 31.0 |
| 2 | | 700 | 0.13 | 44 | 10.8 | 0.09 | 0.7 | 44 | 10.8 | 0.09 | 0.7 | 44 | 10.8 | 0.09 | 0.7 | 44 | 10.8 | 0.09 | 0.7 | 44 | 10.8 |
| 3 | | 2,000 | 0.38 | 44 | 31.0 | 0.08 | 0.2 | 44 | 31.0 | 0.08 | 0.2 | 44 | 31.0 | 0.08 | 0.2 | 44 | 31.0 | 0.08 | 0.2 | 44 | 31.0 |
| 5 | | 3,100 | 0.59 | 103 | 20.7 | 0.18 | 0.3 | 103 | 20.7 | 0.18 | 0.3 | 103 | 20.7 | 0.18 | 0.3 | 103 | 20.7 | 0.18 | 0.3 | 103 | 20.7 |
| 3 | | 1,700 | 0.32 | 37 | 31.0 | 0.06 | 0.2 | 37 | 31.0 | 0.06 | 0.2 | 37 | 31.0 | 0.06 | 0.2 | 37 | 31.0 | 0.06 | 0.2 | 37 | 31.0 |
| 73 | | 300 | 0.06 | 17 | 12.4 | 0.03 | 0.5 | 17 | 12.4 | 0.03 | 0.5 | 17 | 12.4 | 0.03 | 0.5 | 17 | 12.4 | 0.03 | 0.5 | 17 | 12.4 |
| 22 | | 900 | 0.17 | 62 | 9.9 | 0.14 | 0.8 | 62 | 9.9 | 0.14 | 0.8 | 62 | 9.9 | 0.14 | 0.8 | 62 | 9.9 | 0.14 | 0.8 | 62 | 9.9 |
| 16 | | 1,400 | 0.26 | 104 | 9.0 | 0.21 | 0.8 | 104 | 9.0 | 0.21 | 0.8 | 104 | 9.0 | 0.21 | 0.8 | 104 | 9.0 | 0.21 | 0.8 | 104 | 9.0 |
| 3 | | 3,900 | 0.74 | 86 | 31.0 | 0.15 | 0.2 | 86 | 31.0 | 0.15 | 0.2 | 86 | 31.0 | 0.15 | 0.2 | 86 | 31.0 | 0.15 | 0.2 | 86 | 31.0 |
| 10 | | 1,000 | 0.19 | 63 | 10.8 | 0.13 | 0.7 | 63 | 10.8 | 0.13 | 0.7 | 63 | 10.8 | 0.13 | 0.7 | 63 | 10.8 | 0.13 | 0.7 | 63 | 10.8 |
| 3 | | 300 | 0.06 | 7 | 31.0 | 0.01 | 0.2 | 7 | 31.0 | 0.01 | 0.2 | 7 | 31.0 | 0.01 | 0.2 | 7 | 31.0 | 0.01 | 0.2 | 7 | 31.0 |
| 15 | | 300 | 0.06 | 22 | 9.9 | 0.05 | 0.8 | 22 | 9.9 | 0.05 | 0.8 | 22 | 9.9 | 0.05 | 0.8 | 22 | 9.9 | 0.05 | 0.8 | 22 | 9.9 |
| 10 | | 2,500 | 0.47 | 157 | 10.8 | 0.33 | 0.7 | 157 | 10.8 | 0.33 | 0.7 | 157 | 10.8 | 0.33 | 0.7 | 157 | 10.8 | 0.33 | 0.7 | 157 | 10.8 |
| 15 | | 3,200 | 0.60 | 218 | 9.9 | 0.48 | 0.8 | 218 | 9.9 | 0.48 | 0.8 | 218 | 9.9 | 0.48 | 0.8 | 218 | 9.9 | 0.48 | 0.8 | 218 | 9.9 |
| 10 | | 1,000 | 0.19 | 63 | 10.8 | 0.13 | 0.7 | 63 | 10.8 | 0.13 | 0.7 | 63 | 10.8 | 0.13 | 0.7 | 63 | 10.8 | 0.13 | 0.7 | 63 | 10.8 |
| 2 | | 1,400 | 0.26 | 87 | 10.8 | 0.18 | 0.7 | 87 | 10.8 | 0.18 | 0.7 | 87 | 10.8 | 0.18 | 0.7 | 87 | 10.8 | 0.18 | 0.7 | 87 | 10.8 |
| 3 | | 3,000 | 0.57 | 60 | 31.0 | 0.11 | 0.2 | 60 | 31.0 | 0.11 | 0.2 | 60 | 31.0 | 0.11 | 0.2 | 60 | 31.0 | 0.11 | 0.2 | 60 | 31.0 |
| 10 | | 400 | 0.08 | 27 | 10.8 | 0.06 | 0.7 | 27 | 10.8 | 0.06 | 0.7 | 27 | 10.8 | 0.06 | 0.7 | 27 | 10.8 | 0.06 | 0.7 | 27 | 10.8 |
| 81 | | 1,300 | 0.25 | 96 | 9.4 | 0.20 | 0.8 | 96 | 9.4 | 0.20 | 0.8 | 96 | 9.4 | 0.20 | 0.8 | 96 | 9.4 | 0.20 | 0.8 | 96 | 9.4 |
| 69 | | 1,400 | 0.26 | 87 | 10.8 | 0.18 | 0.7 | 87 | 10.8 | 0.18 | 0.7 | 87 | 10.8 | 0.18 | 0.7 | 87 | 10.8 | 0.18 | 0.7 | 87 | 10.8 |
| 17 | | 1,900 | 0.36 | 42 | 31.0 | 0.07 | 0.2 | 42 | 31.0 | 0.07 | 0.2 | 42 | 31.0 | 0.07 | 0.2 | 42 | 31.0 | 0.07 | 0.2 | 42 | 31.0 |
| 69 | | 1,600 | 0.30 | 100 | 10.8 | 0.21 | 0.7 | 100 | 10.8 | 0.21 | 0.7 | 100 | 10.8 | 0.21 | 0.7 | 100 | 10.8 | 0.21 | 0.7 | 100 | 10.8 |
| 70 | | 700 | 0.13 | 43 | 10.8 | 0.09 | 0.7 | 43 | 10.8 | 0.09 | 0.7 | 43 | 10.8 | 0.09 | 0.7 | 43 | 10.8 | 0.09 | 0.7 | 43 | 10.8 |
| 69 | | 300 | 0.06 | 20 | 10.8 | 0.04 | 0.7 | 20 | 10.8 | 0.04 | 0.7 | 20 | 10.8 | 0.04 | 0.7 | 20 | 10.8 | 0.04 | 0.7 | 20 | 10.8 |
| 10 | | 800 | 0.15 | 50 | 10.8 | 0.10 | 0.7 | 50 | 10.8 | 0.10 | 0.7 | 50 | 10.8 | 0.10 | 0.7 | 50 | 10.8 | 0.10 | 0.7 | 50 | 10.8 |
| 63 | | 400 | 0.08 | 31 | 9.4 | 0.06 | 0.8 | 31 | 9.4 | 0.06 | 0.8 | 31 | 9.4 | 0.06 | 0.8 | 31 | 9.4 | 0.06 | 0.8 | 31 | 9.4 |
| 62 | | 1,900 | 0.36 | 116 | 11.2 | 0.22 | 0.6 | 116 | 11.2 | 0.22 | 0.6 | 116 | 11.2 | 0.22 | 0.6 | 116 | 11.2 | 0.22 | 0.6 | 116 | 11.2 |
| 63 | | 3,700 | 0.70 | 268 | 9.4 | 0.56 | 0.8 | 268 | 9.4 | 0.56 | 0.8 | 268 | 9.4 | 0.56 | 0.8 | 268 | 9.4 | 0.56 | 0.8 | 268 | 9.4 |
| 31 | | 4,100 | 0.77 | 89 | 1.0 | 0.15 | 0.2 | 89 | 1.0 | 0.15 | 0.2 | 89 | 1.0 | 0.15 | 0.2 | 89 | 1.0 | 0.15 | 0.2 | 89 | 1.0 |
| 55 | | 1,000 | 0.19 | 63 | 10.8 | 0.13 | 0.7 | 63 | 10.8 | 0.13 | 0.7 | 63 | 10.8 | 0.13 | 0.7 | 63 | 10.8 | 0.13 | 0.7 | 63 | 10.8 |
| 31 | | 4,900 | 0.93 | 108 | 31.0 | 0.19 | 0.2 | 108 | 31.0 | 0.19 | 0.2 | 108 | 31.0 | 0.19 | 0.2 | 108 | 31.0 | 0.19 | 0.2 | 108 | 31.0 |
| 3 | | 1,600 | 0.36 | 113 | 10.8 | 0.24 | 0.7 | 113 | 10.8 | 0.24 | 0.7 | 113 | 10.8 | 0.24 | 0.7 | 113 | 10.8 | 0.24 | 0.7 | 113 | 10.8 |
| 16 | | 400 | 0.08 | 32 | 9.0 | 0.06 | 0.8 | 32 | 9.0 | 0.06 | 0.8 | 32 | 9.0 | 0.06 | 0.8 | 32 | 9.0 | 0.06 | 0.8 | 32 | 9.0 |

(Continued)

(11 of 32 sheets)

Table 4 (Continued)

| Vehi- cle | Test run type | Dry Season (60 or 40 R/L) | | | | | Wet Season (60 or 40 R/L) | | | | | Wet Season (60 or 35 R/L) | | | | | Fuel gal/ mile |
|--------------|---------------------|---------------------------|------------------|-------------|---------------------|----------------------|---------------------------|------------------|-------------|---------------------|----------------------|---------------------------|------------------|-------------|---------------------|----------------------|----------------------|
| | | Per- cent rain | Distance feet | Time sec | Avg Speed mph | Fuel gal/ mile | Per- cent rain | Distance feet | Time sec | Avg Speed mph | Fuel gal/ mile | Per- cent rain | Distance feet | Time sec | Avg Speed mph | Fuel gal/ mile | |
| 15 | 1,700 | 3 | 1,700 | 116 | 9.9 | 0.26 | 94 | 200 | 0.04 | 18 | 8.2 | 0.04 | 0.9 | | | | |
| 10 | 2,000 | 3 | 2,000 | 127 | 10.8 | 0.30 | 69 | 400 | 0.08 | 27 | 10.8 | 0.06 | 0.7 | | | | |
| 15 | 2,800 | 3 | 2,800 | 193 | 9.9 | 0.42 | 94 | 300 | 0.06 | 26 | 8.2 | 0.05 | 0.9 | | | | |
| 3 | 1,000 | 3 | 1,000 | 22 | 31.0 | 0.04 | 69 | 500 | 0.09 | 30 | 10.8 | 0.06 | 0.7 | | | | |
| 15 | 1,500 | 3 | 1,500 | 102 | 9.9 | 0.22 | 70 | 800 | 0.15 | 50 | 10.8 | 0.10 | 0.7 | | | | |
| 3 | 3,000 | 3 | 3,000 | 66 | 31.0 | 0.11 | 69 | 300 | 0.06 | 20 | 10.8 | 0.04 | 0.7 | | | | |
| 10 | 2,000 | 3 | 2,000 | 107 | 10.8 | 0.22 | 10 | 800 | 0.15 | 50 | 10.8 | 0.10 | 0.7 | | | | |
| 3 | 7,400 | 3 | 7,400 | 163 | 31.0 | 0.28 | 6 | 800 | 0.15 | 57 | 9.4 | 0.12 | 0.8 | | | | |
| 21 | 600 | 3 | 600 | 37 | 10.8 | 0.08 | 62 | 6,300 | 1.19 | 382 | 11.2 | 0.71 | 0.6 | | | | |
| 22 | 1,700 | 3 | 1,700 | 116 | 9.9 | 0.26 | 6 | 300 | 0.06 | 23 | 9.4 | 0.05 | 0.8 | | | | |
| 21 | 600 | 3 | 600 | 37 | 10.8 | 0.08 | 15 | 800 | 0.15 | 57 | 9.4 | 0.12 | 0.8 | | | | |
| 22 | 600 | 3 | 600 | 40 | 9.9 | 0.09 | 63 | 400 | 0.08 | 31 | 9.4 | 0.06 | 0.8 | | | | |
| 21 | 600 | 3 | 600 | 37 | 10.8 | 0.08 | 62 | 1,900 | 0.36 | 116 | 11.2 | 0.22 | 0.6 | | | | |
| 22 | 2,400 | 3 | 2,400 | 164 | 9.9 | 0.36 | 63 | 3,800 | 0.72 | 276 | 9.4 | 0.58 | 0.8 | | | | |
| 3 | 2,100 | 3 | 2,100 | 63 | 31.0 | 0.08 | 31 | 4,000 | 0.76 | 88 | 31.0 | 0.15 | 0.2 | | | | |
| 21 | 700 | 3 | 700 | 43 | 10.8 | 0.09 | 80 | 1,000 | 0.19 | 85 | 8.2 | 0.17 | 0.9 | | | | |
| 3 | 9,100 | 3 | 9,100 | 200 | 31.0 | 0.34 | 31 | 4,100 | 0.77 | 89 | 31.0 | 0.15 | 0.2 | | | | |
| 10 | 1,300 | 3 | 1,300 | 83 | 10.8 | 0.18 | 15 | 1,000 | 0.19 | 72 | 9.4 | 0.15 | 0.8 | | | | |
| 15 | 5,000 | 3 | 5,000 | 342 | 9.9 | 0.75 | 10 | 500 | 0.17 | 57 | 10.8 | 0.12 | 0.7 | | | | |
| 3 | 500 | 3 | 500 | 10 | 31.0 | 0.02 | 3 | 1,700 | 0.32 | 37 | 31.0 | 0.06 | 0.2 | | | | |
| 10 | 400 | 3 | 400 | 27 | 10.8 | 0.06 | 16 | 400 | 0.08 | 35 | 8.2 | 0.07 | 0.9 | | | | |
| 3 | 2,500 | 3 | 2,500 | 55 | 31.0 | 0.09 | 15 | 1,600 | 0.30 | 114 | 9.4 | 0.24 | 0.8 | | | | |
| 10 | 200 | 3 | 200 | 13 | 10.8 | 0.03 | 10 | 2,000 | 0.38 | 127 | 10.8 | 0.27 | 0.7 | | | | |
| 3 | 11,200 | 3 | 11,200 | 283 | 31.0 | 0.42 | 15 | 2,800 | 0.53 | 201 | 9.4 | 0.42 | 0.8 | | | | |
| 69 | 1,900 | 3 | 1,900 | 120 | 10.8 | 0.25 | 3 | 1,000 | 0.19 | 22 | 31.0 | 0.04 | 0.2 | | | | |
| 13 | 2,800 | 3 | 2,800 | 94 | 10.8 | 0.38 | 15 | 1,900 | 0.36 | 136 | 9.4 | 0.29 | 0.8 | | | | |
| 10 | 400 | 3 | 400 | 27 | 10.8 | 0.06 | 3 | 3,100 | 0.59 | 69 | 31.0 | 0.12 | 0.2 | | | | |
| 3 | 800 | 3 | 800 | 17 | 31.0 | 0.03 | 10 | 1,000 | 0.19 | 63 | 10.8 | 0.13 | 0.7 | | | | |
| 10 | 1,800 | 3 | 1,800 | 113 | 10.8 | 0.24 | 15 | 800 | 0.15 | 57 | 9.4 | 0.12 | 0.8 | | | | |
| 4 | 1,700 | 3 | 1,700 | 165 | 7.0 | 0.35 | 3 | 4,300 | 0.81 | 94 | 31.0 | 0.16 | 0.2 | | | | |
| 14 | 4,500 | 3 | 4,500 | 471 | 6.5 | 1.02 | 28 | 900 | 0.17 | 20 | 31.0 | 0.03 | 0.2 | | | | |
| 4 | 300 | 3 | 300 | 31 | 7.0 | 0.07 | 3 | 1,900 | 0.36 | 142 | 31.0 | 0.07 | 0.2 | | | | |
| 14 | 1,900 | 3 | 1,900 | 199 | 6.5 | 0.43 | 21 | 600 | 0.11 | 37 | 10.8 | 0.08 | 0.7 | | | | |
| 4 | 1,000 | 3 | 1,000 | 98 | 7.0 | 0.21 | 22 | 1,700 | 0.32 | 121 | 9.4 | 0.26 | 0.8 | | | | |
| 14 | 2,000 | 3 | 2,000 | 210 | 6.5 | 0.46 | 21 | 600 | 0.11 | 37 | 10.8 | 0.08 | 0.7 | | | | |
| 3 | 3,700 | 3 | 3,700 | 81 | 31.0 | 0.14 | 22 | 600 | 0.11 | 142 | 9.4 | 0.09 | 0.8 | | | | |
| 4 | 2,000 | 3 | 2,000 | 199 | 7.0 | 1.42 | 21 | 600 | 0.11 | 37 | 10.8 | 0.08 | 0.7 | | | | |
| 3 | 1,400 | 3 | 1,400 | 30 | 31.0 | 0.05 | 21 | 2,800 | 0.42 | 159 | 9.4 | 0.34 | 0.8 | | | | |
| 4 | 2,200 | 3 | 2,200 | 216 | 7.0 | 0.46 | 3 | 3,400 | 0.64 | 74 | 31.0 | 0.13 | 0.2 | | | | |
| 5 | 100 | 3 | 100 | 3 | 20.7 | 0.01 | 21 | 1,100 | 0.21 | 70 | 10.8 | 0.15 | 0.7 | | | | |
| 3 | 6,200 | 3 | 6,200 | 136 | 31.0 | 0.23 | 3 | 300 | 0.06 | 7 | 31.0 | 0.01 | 0.2 | | | | |
| 4 | 3,000 | 3 | 3,000 | 293 | 7.0 | 0.63 | 21 | 1,400 | 0.26 | 87 | 10.8 | 0.18 | 0.7 | | | | |
| 3 | 400 | 3 | 400 | 9 | 31.0 | 0.02 | 3 | 8,500 | 1.51 | 187 | 31.0 | 0.32 | 0.2 | | | | |
| 2 | 1,000 | 3 | 1,000 | 63 | 10.8 | 0.13 | 10 | 1,300 | 0.25 | 83 | 10.8 | 0.18 | 0.7 | | | | |
| | | | | | | | 15 | 5,000 | 0.94 | 356 | 9.4 | 0.75 | 0.8 | | | | |
| | | | | | | | 3 | 600 | 0.11 | 13 | 31.0 | 0.02 | 0.2 | | | | |
| | | | | | | | 10 | 900 | 0.16 | 20 | 10.8 | 0.04 | 0.7 | | | | |
| | | | | | | | 3 | 2,600 | 0.49 | 57 | 31.0 | 0.10 | 0.2 | | | | |
| | | | | | | | 10 | 300 | 0.06 | 20 | 10.8 | 0.04 | 0.7 | | | | |
| | | | | | | | 3 | 7,500 | 1.49 | 190 | 31.0 | 0.30 | 0.2 | | | | |
| | | | | | | | 15 | 400 | 0.08 | 30 | 9.4 | 0.06 | 0.8 | | | | |
| | | | | | | | 3 | 2,500 | 0.47 | 55 | 31.0 | 0.09 | 0.2 | | | | |
| | | | | | | | 94 | 500 | 0.09 | 40 | 8.2 | 0.08 | 0.9 | | | | |
| | | | | | | | 69 | 1,400 | 0.23 | 77 | 10.8 | 0.16 | 0.7 | | | | |
| | | | | | | | 13 | 2,900 | 0.55 | 9,900 | 0.2 | 3.30 | 6.0 | | | | |

(Continued)

(12 of 32 sheets)

Table 4 (Continued)

| Vehi- cle | Dry Season (60 or 40 RCT) | | | | | | Wet Season (60 or 40 RCT) | | | | | | Wet Season (60 or 35 RCT) | | | | | |
|--------------|---------------------------|------------------|-------------|--------------|----------------------|-------------|---------------------------|------------------|-------------|--------------|----------------------|-------------|---------------------------|------------------|-------------|--------------|----------------------|-------------|
| | Ter- min Type | Distance feet | Time sec | Speed mph | Fuel gal/ mile | Fuel gal | Ter- min Type | Distance feet | Time sec | Speed mph | Fuel gal/ mile | Fuel gal | Ter- min Type | Distance feet | Time sec | Speed mph | Fuel gal/ mile | Fuel gal |
| M61 | 2 | 1,600 | 0.30 | 13.2 | 0.15 | 0.5 | 2 | 1,600 | 0.30 | 13.2 | 0.15 | 0.5 | 2 | 1,600 | 0.30 | 13.2 | 0.15 | 0.5 |
| | 3 | 2,100 | 0.40 | 36 | 40.0 | 0.08 | 3 | 2,100 | 0.40 | 36 | 40.0 | 0.08 | 3 | 2,100 | 0.40 | 36 | 40.0 | 0.08 |
| | 6 | 3,300 | 0.62 | 155 | 14.1 | 0.31 | 6 | 3,300 | 0.62 | 155 | 14.1 | 0.31 | 6 | 3,300 | 0.62 | 155 | 14.1 | 0.31 |
| | 10 | 1,600 | 0.17 | 61 | 3.6 | 0.14 | 10 | 1,600 | 0.17 | 61 | 3.6 | 0.14 | 10 | 1,600 | 0.17 | 61 | 3.6 | 0.14 |
| | 3 | 1,600 | 0.30 | 27 | 40.0 | 0.06 | 3 | 1,600 | 0.30 | 27 | 40.0 | 0.06 | 3 | 1,600 | 0.30 | 27 | 40.0 | 0.06 |
| | 10 | 300 | 0.06 | 22 | 9.6 | 0.05 | 10 | 300 | 0.06 | 22 | 9.6 | 0.05 | 10 | 300 | 0.06 | 22 | 9.6 | 0.05 |
| | 6 | 1,000 | 0.19 | 47 | 14.4 | 0.10 | 6 | 1,000 | 0.19 | 47 | 14.4 | 0.10 | 6 | 1,000 | 0.19 | 47 | 14.4 | 0.10 |
| | 3 | 3,200 | 0.60 | 54 | 40.0 | 0.12 | 3 | 3,200 | 0.60 | 54 | 40.0 | 0.12 | 3 | 3,200 | 0.60 | 54 | 40.0 | 0.12 |
| | 6 | 1,200 | 0.23 | 57 | 14.4 | 0.12 | 6 | 1,200 | 0.23 | 57 | 14.4 | 0.12 | 6 | 1,200 | 0.23 | 57 | 14.4 | 0.12 |
| | 10 | 600 | 0.11 | 41 | 9.6 | 0.09 | 10 | 600 | 0.11 | 41 | 9.6 | 0.09 | 10 | 600 | 0.11 | 41 | 9.6 | 0.09 |
| M61 | 3 | 1,900 | 0.36 | 32 | 40.0 | 0.07 | 3 | 1,900 | 0.36 | 32 | 40.0 | 0.07 | 3 | 1,900 | 0.36 | 32 | 40.0 | 0.07 |
| | 10 | 1,200 | 0.23 | 103 | 9.6 | 0.18 | 10 | 1,200 | 0.23 | 103 | 9.6 | 0.18 | 10 | 1,200 | 0.23 | 103 | 9.6 | 0.18 |
| | 6 | 3,300 | 0.62 | 155 | 14.4 | 0.31 | 6 | 3,300 | 0.62 | 155 | 14.4 | 0.31 | 6 | 3,300 | 0.62 | 155 | 14.4 | 0.31 |
| | 10 | 2,500 | 0.47 | 176 | 9.6 | 0.38 | 10 | 2,500 | 0.47 | 176 | 9.6 | 0.38 | 10 | 2,500 | 0.47 | 176 | 9.6 | 0.38 |
| | 6 | 1,700 | 0.32 | 80 | 14.4 | 0.16 | 6 | 1,700 | 0.32 | 80 | 14.4 | 0.16 | 6 | 1,700 | 0.32 | 80 | 14.4 | 0.16 |
| | 10 | 700 | 0.13 | 49 | 9.6 | 0.10 | 10 | 700 | 0.13 | 49 | 9.6 | 0.10 | 10 | 700 | 0.13 | 49 | 9.6 | 0.10 |
| | 6 | 2,800 | 0.53 | 132 | 14.4 | 0.26 | 6 | 2,800 | 0.53 | 132 | 14.4 | 0.26 | 6 | 2,800 | 0.53 | 132 | 14.4 | 0.26 |
| | 3 | 1,800 | 0.34 | 31 | 40.0 | 0.08 | 3 | 1,800 | 0.34 | 31 | 40.0 | 0.08 | 3 | 1,800 | 0.34 | 31 | 40.0 | 0.08 |
| | 10 | 1,000 | 0.15 | 47 | 13.2 | 0.14 | 10 | 1,000 | 0.15 | 47 | 13.2 | 0.14 | 10 | 1,000 | 0.15 | 47 | 13.2 | 0.14 |
| | 3 | 1,200 | 0.23 | 1221 | 40.0 | 1.35 | 3 | 1,200 | 0.23 | 1221 | 40.0 | 1.35 | 3 | 1,200 | 0.23 | 1221 | 40.0 | 1.35 |
| M61 | 3 | 1,200 | 0.23 | 1240 | 9.6 | 0.51 | 3 | 1,200 | 0.23 | 1240 | 9.6 | 0.51 | 3 | 1,200 | 0.23 | 1240 | 9.6 | 0.51 |
| | 10 | 3,400 | 0.64 | 240 | 9.6 | 0.04 | 10 | 3,400 | 0.64 | 240 | 9.6 | 0.04 | 10 | 3,400 | 0.64 | 240 | 9.6 | 0.04 |
| | 3 | 1,000 | 0.19 | 17 | 40.0 | 0.04 | 3 | 1,000 | 0.19 | 17 | 40.0 | 0.04 | 3 | 1,000 | 0.19 | 17 | 40.0 | 0.04 |
| | 10 | 1,000 | 0.19 | 71 | 9.6 | 0.15 | 10 | 1,000 | 0.19 | 71 | 9.6 | 0.15 | 10 | 1,000 | 0.19 | 71 | 9.6 | 0.15 |
| | 49 | 500 | 0.09 | 20 | 16.3 | 0.04 | 49 | 500 | 0.09 | 20 | 16.3 | 0.04 | 49 | 500 | 0.09 | 20 | 16.3 | 0.04 |
| | Total | | | | | | Total | | | | | | Total | | | | | |
| | 246,900 | | | | | | 53590 | | | | | | 61,527 | | | | | |
| | 46.66 | | | | | | 38.63 | | | | | | 43.85 | | | | | |

(Continued)

(13 of 22 sheets)

Table 4 (Continued)

| Vehi- cle | Dry Season (60 or 10 RCI) | | | | | | | Wet Season (60 or 10 RCI) | | | | | | | |
|--------------|---------------------------|------------------|-------------|---------------------|---------------------|---------------------|---------------------|---------------------------|------------------|-------------|---------------------|---------------------|---------------------|---------------------|-----|
| | Ter- rain Type | Distance feet | Time sec | City Time sec | Avg Speed mph | Fuel gal mile | Fuel gal mile | Ter- rain Type | Distance feet | Time sec | City Time sec | Avg Speed mph | Fuel gal mile | Fuel gal mile | |
| 6 | 4,300 | 0.81 | 202 | 14.4 | 0.40 | 0.5 | | 3 | 1,700 | 0.22 | 69 | 44.2 | 0.06 | 3.6 | |
| 69 | 600 | 0.11 | 49 | 8.1 | 0.10 | 0.9 | | 15 | 900 | 0.17 | 27 | 54.2 | 0.14 | 0.6 | |
| 6 | 1,100 | 0.21 | 52 | 14.4 | 0.10 | 0.5 | | 42 | 600 | 0.17 | 27 | 54.2 | 0.14 | 0.6 | |
| 32 | 800 | 0.15 | 17 | 5.17 | 0.1 | 1.16 | 7.7 | 8 | 4,300 | 0.81 | 202 | 14.4 | 0.40 | 3.6 | |
| 3 | 2,300 | 0.43 | 39 | 40.0 | 0.09 | 0.2 | | 89 | 600 | 0.11 | 49 | 8.1 | 0.10 | 0.5 | |
| 37 | 600 | 0.11 | 10 | 40.0 | 0.02 | 0.2 | | 6 | 1,000 | 0.19 | 48 | 14.4 | 0.10 | 0.4 | |
| 40 | 300 | 0.06 | 25 | 9.8 | 0.05 | 0.8 | | 30 | 500 | 0.09 | 34 | 14.4 | 0.10 | 0.4 | |
| 11 | 1,500 | 0.36 | 147 | 8.8 | 0.29 | 0.8 | | 3 | 2,000 | 0.26 | 51 | 44.2 | 0.08 | 0.2 | |
| 32 | 200 | 0.04 | 1,440 | 0.1 | 0.31 | 7.7 | | 47 | 700 | 0.13 | 5 | 40.2 | 0.02 | 1.2 | |
| 87 | 1,500 | 0.28 | 124 | 8.1 | 0.25 | 0.9 | | 40 | 400 | 0.08 | 33 | 8.8 | 0.06 | 0.3 | |
| 14 | 5,400 | 1.02 | 456 | 7.4 | 1.02 | 1.0 | | 11 | 1,900 | 0.36 | 147 | 8.8 | 0.29 | 0.8 | |
| 21 | 1,000 | 0.19 | 98 | 7.4 | 0.19 | 1.0 | | 32 | 300 | 0.06 | 27 | 54.2 | 0.14 | 0.7 | |
| 14 | 1,400 | 0.08 | 39 | 7.4 | 0.08 | 1.0 | | 87 | 800 | 0.15 | 27 | 54.2 | 0.14 | 0.9 | |
| 10 | 400 | 0.08 | 30 | 9.6 | 1.06 | 0.2 | | 14 | 3,700 | 0.70 | 34 | 7.4 | 0.70 | 1.1 | |
| 3 | 4,200 | 0.23 | 21 | 40.0 | 0.05 | 0.2 | | 10 | 1,200 | 0.23 | 96 | 9.6 | 0.14 | 0.6 | |
| 10 | 900 | 0.17 | 64 | 9.6 | 0.14 | 0.8 | | 14 | 300 | 0.06 | 26 | 7.4 | 0.06 | 0.2 | |
| 3 | 3,200 | 0.60 | 54 | 40.0 | 0.12 | 0.2 | | 15 | 300 | 0.09 | 35 | 9.2 | 0.07 | 0.2 | |
| 10 | 1,600 | 0.30 | 130 | 9.6 | 0.24 | 0.8 | | 82 | 1,500 | 0.36 | 175 | 7.4 | 0.36 | 1.0 | |
| 25 | 1,300 | 0.25 | 25 | 36.5 | 0.05 | 0.2 | | 14 | 300 | 0.06 | 26 | 7.4 | 0.06 | 0.2 | |
| 3 | 900 | 0.17 | 15 | 40.0 | 0.03 | 0.2 | | 15 | 700 | 0.13 | 51 | 9.2 | 0.10 | 0.3 | |
| 27 | 7,600 | 1.44 | 259 | 20.0 | 0.58 | 0.4 | | 3 | 900 | 0.17 | 15 | 40.0 | 0.03 | 0.2 | |
| 32 | 300 | 0.06 | 2,160 | 0.1 | 0.16 | 7.7 | | 15 | 2,600 | 0.53 | 207 | 9.2 | 0.42 | 0.8 | |
| 2 | 900 | 0.17 | 42 | 13.2 | 0.08 | 0.5 | | 10 | 800 | 0.15 | 36 | 9.2 | 0.12 | 0.3 | |
| 16 | 600 | 0.11 | 27 | 14.7 | 0.06 | 0.5 | | 15 | 800 | 0.15 | 36 | 9.2 | 0.12 | 0.3 | |
| 30 | 700 | 0.04 | 1,440 | 0.1 | 0.51 | 7.7 | | 22 | 2,000 | 0.38 | 37 | 36.5 | 0.05 | 0.2 | |
| 3 | 800 | 0.15 | 14 | 40.0 | 0.03 | 0.2 | | 15 | 800 | 0.15 | 36 | 9.2 | 0.12 | 0.3 | |
| 2 | 600 | 0.17 | 50 | 13.2 | 0.05 | 0.5 | | 15 | 7,000 | 1.32 | 232 | 26.0 | 0.53 | 0.4 | |
| 3 | 900 | 0.17 | 15 | 40.0 | 0.03 | 0.2 | | 37 | 300 | 0.06 | 26 | 7.4 | 0.06 | 0.2 | |
| 32 | 1,800 | 0.34 | 1800 | 13.440 | 0.1 | 3.92 | 7.7 | 16 | 500 | 0.09 | 35 | 9.2 | 0.07 | 0.2 | |
| 3 | 600 | 0.11 | 10 | 40.0 | 0.02 | 0.2 | | 35 | 900 | 0.09 | 35 | 9.2 | 0.07 | 0.2 | |
| 2 | 700 | 0.13 | 35 | 13.2 | 0.06 | 0.5 | | 30 | 200 | 0.04 | 1,440 | 0.1 | 0.31 | 7.7 | |
| 3 | 1,900 | 0.36 | 32 | 40.0 | 0.07 | 0.2 | | 3 | 600 | 0.17 | 15 | 40.0 | 0.03 | 0.2 | |
| 5 | 4,400 | 0.83 | 83 | 36.2 | 0.17 | 0.2 | | 2 | 1,100 | 0.21 | 57 | 13.2 | 0.10 | 0.5 | |
| 73 | 1,100 | 0.21 | 65 | 11.6 | 0.13 | 0.6 | | 3 | 400 | 0.08 | 7 | 40.0 | 0.02 | 0.2 | |
| 3 | 7,000 | 1.32 | 119 | 40.0 | 0.26 | 0.2 | | 30 | 1,800 | 0.34 | 1,200 | 13.440 | 0.1 | 3.92 | 7.7 |
| 10 | 1,400 | 0.26 | 97 | 9.6 | 0.21 | 0.8 | | 3 | 400 | 0.08 | 7 | 40.0 | 0.02 | 0.2 | |
| 15 | 800 | 0.15 | 58 | 9.3 | 0.12 | 0.8 | | 2 | 1,500 | 0.28 | 76 | 13.2 | 0.14 | 0.5 | |
| 10 | 2,600 | 0.49 | 184 | 9.6 | 0.39 | 0.8 | | 3 | 1,100 | 0.21 | 57 | 13.2 | 0.10 | 0.5 | |
| 15 | 3,600 | 0.68 | 263 | 9.3 | 0.74 | 0.8 | | 3 | 4,800 | 0.81 | 81 | 36.2 | 0.16 | 0.2 | |
| 10 | 1,100 | 0.21 | 73 | 9.6 | 0.17 | 0.8 | | 73A | 800 | 0.15 | 90 | 10.9 | 0.16 | 0.7 | |
| 57 | 1,200 | 0.23 | 41 | 20.0 | 0.09 | 0.4 | | 3 | 7,000 | 1.32 | 119 | 40.0 | 0.26 | 0.2 | |
| 3 | 2,900 | 0.55 | 50 | 40.0 | 0.11 | 0.2 | | 15 | 1,300 | 0.25 | 98 | 9.2 | 0.20 | 0.8 | |
| 10 | 400 | 0.08 | 30 | 9.2 | 0.06 | 0.8 | | 5 | 400 | 0.08 | 7 | 40.0 | 0.02 | 0.2 | |
| 81 | 5,600 | 1.06 | 265 | 14.4 | 0.53 | 0.5 | | 15 | 300 | 0.06 | 23 | 5.2 | 0.05 | 0.3 | |
| 10 | 2,500 | 0.47 | 176 | 9.6 | 0.38 | 0.8 | | 10 | 700 | 0.13 | 49 | 6.6 | 0.10 | 0.3 | |
| 6 | 700 | 0.13 | 32 | 14.4 | 0.06 | 0.5 | | 15 | 1,400 | 0.26 | 108 | 6.2 | 0.21 | 0.3 | |
| 62 | 5,900 | 1.12 | 247 | 16.3 | 0.45 | 0.4 | | 10 | 400 | 0.08 | 30 | 9.6 | 0.06 | 0.3 | |
| 10 | 800 | 0.15 | 56 | 9.2 | 0.12 | 0.8 | | 15 | 3,400 | 0.64 | 260 | 5.2 | 0.51 | 0.3 | |
| 53 | 400 | 0.06 | 20 | 12.4 | 0.24 | 0.5 | | 10 | 600 | 0.11 | 41 | 9.6 | 0.09 | 0.3 | |
| 22 | 900 | 0.17 | 38 | 16.3 | 0.07 | 0.4 | | 57 | 1,700 | 0.38 | 98 | 20.0 | 0.13 | 0.4 | |

(Continued)

(14 of 32)

Table 4 (Continued)

| Vehi- cle | Ter- rain Type | Dry Season (60 or 40 RCI) | | | | | Wet Season (60 or 40 RCI) | | | | | Wet Season (50 or 35 RCI) | | | | |
|--------------|----------------------|---------------------------|-------------|--------------|----------------------|----------------------|---------------------------|-------------|--------------|----------------------|----------------------|---------------------------|-------------|--------------|----------------------|----------------------|
| | | Distance feet | Time sec | Speed mph | Fuel gal/ mile | Ter- rain Type | Distance feet | Time sec | Speed mph | Fuel gal/ mile | Ter- rain Type | Distance feet | Time sec | Speed mph | Fuel gal/ mile | Ter- rain Type |
| 63 | 3 | 900 | 0.17 | 12 | 14.4 | 0.08 | 0.5 | 14.4 | 0.08 | 0.5 | 15 | 400 | 0.08 | 0.2 | 0.06 | 0.6 |
| 63 | 3 | 1,200 | 0.23 | 51 | 16.3 | 0.09 | 0.4 | 16.3 | 0.09 | 0.4 | 3 | 2,500 | 0.47 | 42 | 0.09 | 0.2 |
| 63 | 3 | 1,200 | 0.79 | 197 | 14.4 | 0.40 | 0.5 | 14.4 | 0.40 | 0.5 | 6 | 400 | 0.06 | 1 | 0.04 | 0.3 |
| 31 | 10 | 8,500 | 1.55 | 140 | 40.0 | 0.31 | 0.2 | 40.0 | 0.31 | 0.2 | 81 | 1,200 | 0.23 | 35 | 14.4 | 0.12 |
| 10 | 10 | 1,800 | 0.34 | 127 | 9.6 | 0.27 | 0.8 | 9.6 | 0.27 | 0.8 | 66 | 500 | 0.09 | 34 | 9.6 | 0.07 |
| 3 | 3 | 1,400 | 0.26 | 23 | 40.0 | 0.09 | 0.2 | 40.0 | 0.09 | 0.2 | 94 | 1,300 | 0.19 | 74 | 9.3 | 0.15 |
| 16 | 3 | 1,500 | 0.09 | 22 | 14.7 | 0.04 | 0.5 | 14.7 | 0.04 | 0.5 | 17 | 1,800 | 0.34 | 31 | 16.3 | 0.07 |
| 15 | 15 | 1,800 | 0.34 | 132 | 9.3 | 0.27 | 0.8 | 9.3 | 0.27 | 0.8 | 94 | 300 | 0.06 | 73 | 9.3 | 0.06 |
| 10 | 10 | 2,000 | 0.38 | 142 | 9.6 | 0.30 | 0.8 | 9.6 | 0.30 | 0.8 | 66 | 400 | 0.08 | 30 | 9.6 | 0.06 |
| 15 | 15 | 2,800 | 0.53 | 205 | 9.3 | 0.42 | 0.8 | 9.3 | 0.42 | 0.8 | 64 | 400 | 0.08 | 31 | 9.3 | 0.06 |
| 3 | 3 | 900 | 0.17 | 15 | 40.0 | 0.03 | 0.2 | 40.0 | 0.03 | 0.2 | 66 | 400 | 0.08 | 31 | 9.3 | 0.06 |
| 15 | 15 | 1,600 | 0.30 | 116 | 9.3 | 0.24 | 0.8 | 9.3 | 0.24 | 0.8 | 70 | 800 | 0.15 | 41 | 13.2 | 0.08 |
| 10 | 10 | 1,100 | 0.21 | 79 | 9.6 | 0.17 | 0.8 | 9.6 | 0.17 | 0.8 | 66 | 400 | 0.08 | 31 | 9.3 | 0.06 |
| 3 | 3 | 4,100 | 0.77 | 69 | 40.0 | 0.15 | 0.2 | 40.0 | 0.15 | 0.2 | 10 | 800 | 0.15 | 56 | 9.6 | 0.12 |
| 10 | 10 | 1,600 | 0.23 | 86 | 9.6 | 0.18 | 0.8 | 9.6 | 0.18 | 0.8 | 6 | 600 | 0.11 | 26 | 14.4 | 0.06 |
| 3 | 3 | 4,900 | 0.93 | 84 | 40.0 | 0.19 | 0.2 | 40.0 | 0.19 | 0.2 | 62 | 6,500 | 1.23 | 272 | 16.3 | 0.19 |
| 21 | 21 | 1,700 | 0.13 | 49 | 9.6 | 0.10 | 0.8 | 9.6 | 0.10 | 0.8 | 6 | 300 | 0.06 | 15 | 14.4 | 0.04 |
| 21 | 21 | 2,600 | 0.53 | 205 | 9.3 | 0.42 | 0.8 | 9.3 | 0.42 | 0.8 | 15 | 500 | 0.15 | 59 | 9.6 | 0.12 |
| 21 | 21 | 1,700 | 0.11 | 41 | 9.6 | 0.09 | 0.8 | 9.6 | 0.09 | 0.8 | 63 | 400 | 0.08 | 20 | 14.4 | 0.04 |
| 22 | 22 | 2,400 | 0.45 | 174 | 9.3 | 0.36 | 0.8 | 9.3 | 0.36 | 0.8 | 62 | 1,500 | 0.36 | 80 | 16.3 | 0.14 |
| 3 | 3 | 12,000 | 2.27 | 221 | 40.0 | 0.45 | 0.2 | 40.0 | 0.45 | 0.2 | 63 | 1,700 | 0.70 | 175 | 14.4 | 0.13 |
| 10 | 10 | 1,400 | 0.26 | 97 | 9.6 | 0.21 | 0.8 | 9.6 | 0.21 | 0.8 | 31 | 1,100 | 0.77 | 66 | 16.0 | 0.15 |
| 15 | 15 | 5,000 | 0.94 | 364 | 9.3 | 0.79 | 0.8 | 9.3 | 0.79 | 0.8 | 80 | 900 | 0.17 | 66 | 9.3 | 0.14 |
| 3 | 3 | 600 | 0.11 | 10 | 40.0 | 0.02 | 0.2 | 40.0 | 0.02 | 0.2 | 31 | 4,000 | 0.76 | 62 | 16.3 | 0.15 |
| 10 | 10 | 300 | 0.06 | 22 | 9.6 | 0.05 | 0.8 | 9.6 | 0.05 | 0.8 | 15 | 1,000 | 0.19 | 74 | 9.6 | 0.15 |
| 3 | 3 | 1,800 | 0.36 | 32 | 40.0 | 0.07 | 0.2 | 40.0 | 0.07 | 0.2 | 10 | 700 | 0.13 | 49 | 9.6 | 0.10 |
| 10 | 10 | 300 | 0.06 | 22 | 9.6 | 0.05 | 0.8 | 9.6 | 0.05 | 0.8 | 3 | 1,500 | 0.28 | 25 | 16.3 | 0.06 |
| 15 | 15 | 300 | 0.06 | 23 | 9.6 | 0.05 | 0.8 | 9.6 | 0.05 | 0.8 | 16 | 500 | 0.09 | 35 | 9.3 | 0.07 |
| 10 | 10 | 200 | 0.04 | 15 | 9.6 | 0.03 | 0.8 | 9.6 | 0.03 | 0.8 | 15 | 1,700 | 0.32 | 125 | 9.6 | 0.08 |
| 3 | 3 | 8,500 | 1.61 | 162 | 40.0 | 0.32 | 0.2 | 40.0 | 0.32 | 0.2 | 10 | 1,500 | 0.36 | 135 | 9.6 | 0.09 |
| 63 | 63 | 1,500 | 0.28 | 105 | 9.6 | 0.22 | 0.8 | 9.6 | 0.22 | 0.8 | 15 | 5,200 | 0.98 | 383 | 9.6 | 0.78 |
| 13 | 13 | 2,900 | 0.55 | 762 | 2.6 | 1.65 | 3.0 | 2.6 | 1.65 | 3.0 | 3 | 5,200 | 0.98 | 88 | 16.0 | 0.20 |
| 10 | 10 | 600 | 0.11 | 41 | 9.6 | 0.09 | 0.8 | 9.6 | 0.09 | 0.8 | 15 | 400 | 0.08 | 31 | 9.6 | 0.06 |
| 3 | 3 | 700 | 0.13 | 12 | 40.0 | 0.03 | 0.2 | 40.0 | 0.03 | 0.2 | 10 | 400 | 0.08 | 30 | 9.6 | 0.06 |
| 10 | 10 | 1,900 | 0.36 | 135 | 9.6 | 0.29 | 0.8 | 9.6 | 0.29 | 0.8 | 15 | 300 | 0.06 | 23 | 9.6 | 0.05 |
| 4 | 4 | 1,800 | 0.34 | 219 | 5.6 | 0.44 | 1.3 | 5.6 | 0.44 | 1.3 | 3 | 2,100 | 0.40 | 36 | 16.3 | 0.08 |
| 14 | 14 | 6,200 | 1.17 | 569 | 7.4 | 1.17 | 1.0 | 7.4 | 1.17 | 1.0 | 26 | 800 | 0.17 | 5 | 16.0 | 0.09 |
| 4 | 4 | 500 | 0.09 | 58 | 5.6 | 0.12 | 1.3 | 5.6 | 0.12 | 1.3 | 3 | 1,800 | 0.36 | 32 | 16.0 | 0.07 |
| 14 | 14 | 1,600 | 0.30 | 146 | 7.4 | 0.30 | 1.0 | 7.4 | 0.30 | 1.0 | 21 | 1,600 | 0.08 | 30 | 9.6 | 0.06 |
| 4 | 4 | 300 | 0.06 | 39 | 5.6 | 0.06 | 1.3 | 5.6 | 0.06 | 1.3 | 24 | 1,700 | 0.32 | 125 | 9.6 | 0.06 |
| 14 | 14 | 1,200 | 0.23 | 112 | 7.4 | 0.23 | 1.0 | 7.4 | 0.23 | 1.0 | 21 | 700 | 0.13 | 49 | 9.6 | 0.10 |
| 3 | 3 | 4,100 | 0.77 | 69 | 40.0 | 0.15 | 0.2 | 40.0 | 0.15 | 0.2 | 22 | 600 | 0.11 | 43 | 9.6 | 0.09 |
| 3 | 3 | 1,200 | 0.23 | 1200 | 1,348 | 5.6 | 1.60 | 1.3 | 5.6 | 1.60 | 22 | 600 | 0.11 | 43 | 9.6 | 0.09 |
| 3 | 3 | 1,400 | 0.26 | 23 | 40.0 | 0.05 | 0.2 | 40.0 | 0.05 | 0.2 | 22 | 2,400 | 0.45 | 176 | 9.6 | 0.08 |
| 4 | 4 | 2,500 | 0.47 | 302 | 5.6 | 0.61 | 1.3 | 5.6 | 0.61 | 1.3 | 3 | 2,100 | 0.40 | 1,236 | 16.0 | 1.38 |
| 5 | 5 | 400 | 0.08 | 8 | 46.2 | 0.02 | 0.2 | 46.2 | 0.02 | 0.2 | 21 | 800 | 0.15 | 96 | 9.6 | 0.12 |
| 3 | 3 | 5,700 | 1.08 | 97 | 40.0 | 0.22 | 0.2 | 40.0 | 0.22 | 0.2 | 3 | 5,600 | 1.06 | 95 | 16.0 | 0.21 |
| 3 | 3 | 3,500 | 0.57 | 366 | 5.6 | 0.74 | 1.3 | 5.6 | 0.74 | 1.3 | 10 | 800 | 0.15 | 96 | 9.6 | 0.12 |
| 3 | 3 | 3,500 | 0.49 | 8 | 40.0 | 0.02 | 0.2 | 40.0 | 0.02 | 0.2 | 3 | 400 | 0.08 | 7 | 16.0 | 0.08 |
| 2 | 2 | 1,000 | 0.19 | 52 | 13.2 | 0.10 | 0.5 | 13.2 | 0.10 | 0.5 | 10 | 300 | 0.06 | 22 | 9.6 | 0.05 |

(Continued)

(15 of 35 sheets)

Table 4 (Continued)

| Vehi- cle | Dry Season (60 or 40 mi) | | | | | Wet Season (60 or 40 mi) | | | | | Wet Season (60 or 40 mi) | | | | |
|--------------|--------------------------|------------------|-------------|--------------|------------------|--------------------------|------------------|-------------|--------------|------------------|--------------------------|------------------|-------------|--------------|------------------|
| | Run- type | Distance feet | Time sec | Speed mph | Fuel gal/mile | Run- type | Distance feet | Time sec | Speed mph | Fuel gal/mile | Run- type | Distance feet | Time sec | Speed mph | Fuel gal/mile |
| M706 | 2 | 1,600 | 0.30 | 13.2 | 0.27 | 2 | 1,600 | 0.30 | 13.2 | 0.27 | 2 | 1,600 | 0.30 | 13.2 | 0.27 |
| | 3 | 1,700 | 0.32 | 12.1 | 0.28 | 3 | 1,700 | 0.32 | 12.1 | 0.28 | 3 | 1,700 | 0.32 | 12.1 | 0.28 |
| | 6 | 2,800 | 0.53 | 9.0 | 0.46 | 6 | 2,800 | 0.53 | 9.0 | 0.46 | 6 | 2,800 | 0.53 | 9.0 | 0.46 |
| | 10 | 1,400 | 0.26 | 18 | 0.19 | 10 | 1,400 | 0.26 | 18 | 0.19 | 10 | 1,400 | 0.26 | 18 | 0.19 |
| | 3 | 1,000 | 0.19 | 21 | 0.14 | 3 | 1,000 | 0.19 | 21 | 0.14 | 3 | 1,000 | 0.19 | 21 | 0.14 |
| | 6 | 1,500 | 0.28 | 13 | 0.21 | 6 | 1,500 | 0.28 | 13 | 0.21 | 6 | 1,500 | 0.28 | 13 | 0.21 |
| | 10 | 3,300 | 0.62 | 5.1 | 0.74 | 10 | 3,300 | 0.62 | 5.1 | 0.74 | 10 | 3,300 | 0.62 | 5.1 | 0.74 |
| | 6 | 2,100 | 0.40 | 9.1 | 0.32 | 6 | 2,100 | 0.40 | 9.1 | 0.32 | 6 | 2,100 | 0.40 | 9.1 | 0.32 |
| | 10 | 1,300 | 0.25 | 15.3 | 0.18 | 10 | 1,300 | 0.25 | 15.3 | 0.18 | 10 | 1,300 | 0.25 | 15.3 | 0.18 |
| | 6 | 500 | 0.09 | 20 | 0.07 | 6 | 500 | 0.09 | 20 | 0.07 | 6 | 500 | 0.09 | 20 | 0.07 |
| | 10 | 800 | 0.15 | 12.1 | 0.10 | 10 | 800 | 0.15 | 12.1 | 0.10 | 10 | 800 | 0.15 | 12.1 | 0.10 |
| | 6 | 2,900 | 0.47 | 10.7 | 0.38 | 6 | 2,900 | 0.47 | 10.7 | 0.38 | 6 | 2,900 | 0.47 | 10.7 | 0.38 |
| | 10 | 3,000 | 0.57 | 9.4 | 0.42 | 10 | 3,000 | 0.57 | 9.4 | 0.42 | 10 | 3,000 | 0.57 | 9.4 | 0.42 |
| | 6 | 1,800 | 0.35 | 13.2 | 0.25 | 6 | 1,800 | 0.35 | 13.2 | 0.25 | 6 | 1,800 | 0.35 | 13.2 | 0.25 |
| | 10 | 1,300 | 0.21 | 18 | 0.17 | 10 | 1,300 | 0.21 | 18 | 0.17 | 10 | 1,300 | 0.21 | 18 | 0.17 |
| M706 | 2 | 1,600 | 0.30 | 13.2 | 0.27 | 2 | 1,600 | 0.30 | 13.2 | 0.27 | 2 | 1,600 | 0.30 | 13.2 | 0.27 |
| | 3 | 1,700 | 0.32 | 12.1 | 0.28 | 3 | 1,700 | 0.32 | 12.1 | 0.28 | 3 | 1,700 | 0.32 | 12.1 | 0.28 |
| | 6 | 2,800 | 0.53 | 9.0 | 0.46 | 6 | 2,800 | 0.53 | 9.0 | 0.46 | 6 | 2,800 | 0.53 | 9.0 | 0.46 |
| | 10 | 1,400 | 0.26 | 18 | 0.19 | 10 | 1,400 | 0.26 | 18 | 0.19 | 10 | 1,400 | 0.26 | 18 | 0.19 |
| | 3 | 1,000 | 0.19 | 21 | 0.14 | 3 | 1,000 | 0.19 | 21 | 0.14 | 3 | 1,000 | 0.19 | 21 | 0.14 |
| | 6 | 1,500 | 0.28 | 13 | 0.21 | 6 | 1,500 | 0.28 | 13 | 0.21 | 6 | 1,500 | 0.28 | 13 | 0.21 |
| | 10 | 3,300 | 0.62 | 5.1 | 0.74 | 10 | 3,300 | 0.62 | 5.1 | 0.74 | 10 | 3,300 | 0.62 | 5.1 | 0.74 |
| | 6 | 2,100 | 0.40 | 9.1 | 0.32 | 6 | 2,100 | 0.40 | 9.1 | 0.32 | 6 | 2,100 | 0.40 | 9.1 | 0.32 |
| | 10 | 1,300 | 0.25 | 15.3 | 0.18 | 10 | 1,300 | 0.25 | 15.3 | 0.18 | 10 | 1,300 | 0.25 | 15.3 | 0.18 |
| | 6 | 500 | 0.09 | 20 | 0.07 | 6 | 500 | 0.09 | 20 | 0.07 | 6 | 500 | 0.09 | 20 | 0.07 |
| | 10 | 800 | 0.15 | 12.1 | 0.10 | 10 | 800 | 0.15 | 12.1 | 0.10 | 10 | 800 | 0.15 | 12.1 | 0.10 |
| | 6 | 2,900 | 0.47 | 10.7 | 0.38 | 6 | 2,900 | 0.47 | 10.7 | 0.38 | 6 | 2,900 | 0.47 | 10.7 | 0.38 |
| | 10 | 3,000 | 0.57 | 9.4 | 0.42 | 10 | 3,000 | 0.57 | 9.4 | 0.42 | 10 | 3,000 | 0.57 | 9.4 | 0.42 |
| | 6 | 1,800 | 0.35 | 13.2 | 0.25 | 6 | 1,800 | 0.35 | 13.2 | 0.25 | 6 | 1,800 | 0.35 | 13.2 | 0.25 |
| | 10 | 1,300 | 0.21 | 18 | 0.17 | 10 | 1,300 | 0.21 | 18 | 0.17 | 10 | 1,300 | 0.21 | 18 | 0.17 |
| Total | | | | | 46.33 | Total | | | | | Total | | | | |
| | | | | | 39,507 | | | | | | | | | | |
| | | | | | 34.99 | | | | | | | | | | |

(Continued)

(16 of 32 sheets)

Table 4 (Continued)

| Vehi- cle | Dry Season (66 or 67) | | | | | | | Wet Season (66 or 67) | | | | | | | Wet Season (66 or 67) | | | | | | | | |
|--------------|-----------------------|-----------------------|---------------------|--------------------------------|----------------|-------------|------|-----------------------|-----------------------|---------------------|--------------------------------|----------------|-------------|------|-----------------------|-----------------------|---------------------|--------------------------------|----------------|-------------|------|------|-----|
| | Re- tain Type | Dis- tance feet | Avg Speed MPH | Per- centage Time SEC | Fuel GAL/MI | Fuel GAL | MPG | Re- tain Type | Dis- tance feet | Avg Speed MPH | Per- centage Time SEC | Fuel GAL/MI | Fuel GAL | MPG | Re- tain Type | Dis- tance feet | Avg Speed MPH | Per- centage Time SEC | Fuel GAL/MI | Fuel GAL | MPG | | |
| 49 | 6 | 7,400 | 1.40 | 2,895 | 10.4 | 5.68 | 1.2 | 6 | 1,500 | 0.28 | 64 | 15.6 | 0.28 | 0.3 | 6 | 1,500 | 0.28 | 64 | 15.6 | 0.28 | 0.3 | | |
| 49 | 10 | 7,400 | 0.19 | 37 | 18.6 | 5.68 | 1.2 | 3 | 2,300 | 0.43 | 46 | 38.3 | 0.13 | 0.3 | 3 | 2,300 | 0.43 | 46 | 38.3 | 0.13 | 0.3 | | |
| 28 | 6 | 7,000 | 0.13 | 30 | 15.8 | 0.10 | 0.8 | 15 | 1,400 | 0.26 | 1,200 | 9.2 | 2.74 | 0.3 | 15 | 1,400 | 0.26 | 1,200 | 9.2 | 2.74 | 0.3 | | |
| 28 | 14 | 1,400 | 0.26 | 31 | 30.4 | 0.10 | 0.4 | 3 | 1,400 | 0.26 | 1,200 | 38.3 | 2.68 | 0.3 | 3 | 1,400 | 0.26 | 1,200 | 38.3 | 2.68 | 0.3 | | |
| 6 | 2,300 | 0.43 | 58 | 15.8 | 0.34 | 0.8 | | 15 | 4,000 | 0.76 | 297 | 9.2 | 0.99 | 1.3 | 15 | 4,000 | 0.76 | 297 | 9.2 | 0.99 | 1.3 | | |
| 89 | 6 | 600 | 0.11 | 42 | 9.4 | 0.14 | 1.3 | 10 | 400 | 0.36 | 28 | 10.4 | 0.10 | 1.2 | 10 | 400 | 0.36 | 28 | 10.4 | 0.10 | 1.2 | | |
| 89 | 6 | 1,000 | 0.19 | 43 | 15.8 | 0.15 | 0.8 | 15 | 700 | 0.13 | 51 | 9.2 | 0.17 | 1.3 | 15 | 700 | 0.13 | 51 | 9.2 | 0.17 | 1.3 | | |
| 32 | 3 | 500 | 0.09 | 3,253 | 0.11 | 1.10 | 12.3 | 10 | 200 | 0.04 | 14 | 10.4 | 0.05 | 1.2 | 10 | 200 | 0.04 | 14 | 10.4 | 0.05 | 1.2 | | |
| 32 | 3 | 2,300 | 0.43 | 30 | 38.3 | 0.13 | 0.3 | 49 | 1,000 | 0.09 | 37 | 18.6 | 0.13 | 0.7 | 49 | 1,000 | 0.09 | 37 | 18.6 | 0.13 | 0.7 | | |
| 37 | 7 | 700 | 0.13 | 12 | 38.3 | 0.04 | 0.3 | 28 | 6 | 700 | 0.13 | 30 | 15.8 | 0.10 | 0.8 | 28 | 6 | 700 | 0.13 | 30 | 15.8 | 0.10 | 0.8 |
| 49 | 300 | 0.06 | 18 | 12.0 | 0.05 | 1.0 | | 6 | 1,400 | 0.26 | 31 | 30.4 | 0.10 | 0.4 | 6 | 1,400 | 0.26 | 31 | 30.4 | 0.10 | 0.4 | | |
| 11 | 2,000 | 0.3 | 124 | 11.0 | 4.67 | 12.3 | | 89 | 700 | 0.13 | 58 | 15.8 | 0.34 | 0.8 | 89 | 700 | 0.13 | 58 | 15.8 | 0.34 | 0.8 | | |
| 87 | 300 | 0.06 | 2,160 | 0.1 | 0.34 | 1.3 | | 6 | 700 | 0.13 | 30 | 15.8 | 0.10 | 0.8 | 6 | 700 | 0.13 | 30 | 15.8 | 0.10 | 0.8 | | |
| 14 | 4,200 | 0.79 | 323 | 8.8 | 1.11 | 1.4 | | 30 | 1,000 | 0.19 | 17 | 6.87 | 0.1 | 2.34 | 30 | 1,000 | 0.19 | 17 | 6.87 | 0.1 | 2.34 | | |
| 82 | 2,300 | 0.43 | 166 | 9.3 | 0.56 | 1.3 | | 3 | 2,200 | 0.42 | 39 | 38.3 | 0.13 | 0.3 | 3 | 2,200 | 0.42 | 39 | 38.3 | 0.13 | 0.3 | | |
| 10 | 300 | 0.06 | 33 | 8.8 | 0.11 | 1.4 | | 37 | 800 | 0.15 | 14 | 38.3 | 0.04 | 0.3 | 37 | 800 | 0.15 | 14 | 38.3 | 0.04 | 0.3 | | |
| 10 | 300 | 0.06 | 21 | 10.4 | 0.07 | 1.2 | | 40 | 500 | 0.09 | 27 | 12.0 | 0.05 | 1.0 | 40 | 500 | 0.09 | 27 | 12.0 | 0.05 | 1.0 | | |
| 3 | 1,100 | 0.21 | 20 | 38.3 | 0.06 | 0.3 | | 11 | 1,500 | 0.36 | 118 | 11.0 | 0.40 | 1.1 | 11 | 1,500 | 0.36 | 118 | 11.0 | 0.40 | 1.1 | | |
| 10 | 800 | 0.15 | 52 | 10.4 | 0.18 | 1.2 | | 32 | 300 | 0.06 | 2,160 | 0.1 | 0.74 | 12.3 | 32 | 300 | 0.06 | 2,160 | 0.1 | 0.74 | 12.3 | | |
| 3 | 1,000 | 0.19 | 18 | 38.3 | 0.06 | 0.3 | | 87 | 1,500 | 0.28 | 107 | 8.4 | 0.36 | 1.3 | 87 | 1,500 | 0.28 | 107 | 8.4 | 0.36 | 1.3 | | |
| 23 | 3,500 | 0.74 | 256 | 10.4 | 0.89 | 1.2 | | 14 | 5,500 | 1.04 | 465 | 8.8 | 1.16 | 1.4 | 14 | 5,500 | 1.04 | 465 | 8.8 | 1.16 | 1.4 | | |
| 57 | 7,800 | 1.47 | 248 | 21.3 | 0.88 | 0.6 | | 14 | 300 | 0.06 | 25 | 8.8 | 0.68 | 1.4 | 14 | 300 | 0.06 | 25 | 8.8 | 0.68 | 1.4 | | |
| 32 | 400 | 0.08 | 2,880 | 0.1 | 0.98 | 12.3 | | 3 | 1,600 | 0.30 | 28.3 | 38.3 | 0.09 | 0.3 | 3 | 1,600 | 0.30 | 28.3 | 38.3 | 0.09 | 0.3 | | |
| 2 | 800 | 0.15 | 41 | 13.2 | 0.14 | 0.9 | | 15 | 700 | 0.13 | 51 | 9.2 | 0.17 | 1.3 | 15 | 700 | 0.13 | 51 | 9.2 | 0.17 | 1.3 | | |
| 16 | 600 | 0.11 | 38 | 10.5 | 0.13 | 1.2 | | 3 | 1,200 | 0.23 | 22 | 38.3 | 0.07 | 0.3 | 3 | 1,200 | 0.23 | 22 | 38.3 | 0.07 | 0.3 | | |
| 30 | 300 | 0.06 | 2,160 | 0.1 | 0.74 | 12.3 | | 15 | 2,500 | 0.47 | 184 | 9.2 | 0.61 | 1.3 | 15 | 2,500 | 0.47 | 184 | 9.2 | 0.61 | 1.3 | | |
| 3 | 600 | 0.21 | 10 | 38.3 | 0.03 | 0.3 | | 10 | 800 | 0.15 | 52 | 10.4 | 0.18 | 1.2 | 10 | 800 | 0.15 | 52 | 10.4 | 0.18 | 1.2 | | |
| 2 | 1,100 | 0.21 | 57 | 13.2 | 0.19 | 0.9 | | 23 | 1,800 | 0.34 | 36 | 33.7 | 0.14 | 0.4 | 23 | 1,800 | 0.34 | 36 | 33.7 | 0.14 | 0.4 | | |
| 32 | 1,400 | 0.36 | 1200 | 14,160 | 0.1 | 6.43 | 12.3 | 15 | 800 | 0.15 | 61 | 8.8 | 0.21 | 1.4 | 15 | 800 | 0.15 | 61 | 8.8 | 0.21 | 1.4 | | |
| 3 | 300 | 0.09 | 8 | 38.3 | 0.03 | 0.3 | | 57 | 7,000 | 1.28 | 223 | 21.3 | 0.75 | 0.6 | 57 | 7,000 | 1.28 | 223 | 21.3 | 0.75 | 0.6 | | |
| 2 | 700 | 0.13 | 35 | 13.2 | 0.12 | 0.9 | | 30 | 400 | 0.08 | 2,880 | 0.1 | 0.68 | 12.3 | 30 | 400 | 0.08 | 2,880 | 0.1 | 0.68 | 12.3 | | |
| 3 | 1,900 | 0.36 | 96 | 10.5 | 0.34 | 1.2 | | 2 | 500 | 0.17 | 46 | 13.2 | 0.15 | 0.9 | 2 | 500 | 0.17 | 46 | 13.2 | 0.15 | 0.9 | | |
| 5 | 3,400 | 0.64 | 34 | 38.3 | 0.11 | 0.3 | | 16 | 500 | 0.09 | 37 | 8.8 | 0.13 | 1.4 | 16 | 500 | 0.09 | 37 | 8.8 | 0.13 | 1.4 | | |
| 73 | 300 | 0.06 | 32 | 38.3 | 0.10 | 0.3 | | 30 | 200 | 0.04 | 1,440 | 0.1 | 0.16 | 12.3 | 30 | 200 | 0.04 | 1,440 | 0.1 | 0.16 | 12.3 | | |
| 22 | 1,000 | 0.19 | 18 | 12.2 | 0.06 | 1.0 | | 3 | 700 | 0.13 | 12 | 12 | 0.15 | 0.9 | 3 | 700 | 0.13 | 12 | 12 | 0.15 | 0.9 | | |
| 16 | 1,500 | 0.28 | 71 | 9.6 | 0.25 | 1.3 | | 2 | 1,000 | 0.21 | 57 | 13.2 | 0.15 | 0.9 | 2 | 1,000 | 0.21 | 57 | 13.2 | 0.15 | 0.9 | | |
| 13 | 3,700 | 0.70 | 96 | 10.5 | 0.34 | 1.2 | | 3 | 500 | 0.09 | 8 | 9.2 | 0.03 | 0.3 | 3 | 500 | 0.09 | 8 | 9.2 | 0.03 | 0.3 | | |
| 13 | 2,000 | 0.23 | 66 | 38.3 | 0.21 | 0.3 | | 30 | 1,800 | 0.34 | 1200 | 13,440 | 0.1 | 5.18 | 30 | 1,800 | 0.34 | 1200 | 13,440 | 0.1 | 5.18 | | |
| 13 | 300 | 0.06 | 80 | 10.4 | 0.28 | 1.2 | | 3 | 500 | 0.09 | 37 | 8.8 | 0.13 | 1.4 | 3 | 500 | 0.09 | 37 | 8.8 | 0.13 | 1.4 | | |
| 13 | 400 | 0.08 | 6 | 38.3 | 0.02 | 0.1 | | 2 | 700 | 0.13 | 37 | 13.2 | 0.12 | 0.9 | 2 | 700 | 0.13 | 37 | 13.2 | 0.12 | 0.9 | | |
| 10 | 2,800 | 0.53 | 183 | 10.4 | 0.64 | 1.2 | | 3 | 1,900 | 0.26 | 34 | 38.3 | 0.11 | 0.3 | 3 | 1,900 | 0.26 | 34 | 38.3 | 0.11 | 0.3 | | |
| 15 | 3,600 | 0.68 | 255 | 9.6 | 0.88 | 1.3 | | 5 | 1,600 | 0.30 | 28 | 38.3 | 0.09 | 0.3 | 5 | 1,600 | 0.30 | 28 | 38.3 | 0.09 | 0.3 | | |
| 10 | 1,100 | 0.21 | 73 | 10.4 | 0.25 | 1.2 | | 73A | 400 | 0.08 | 28 | 10.3 | 0.10 | 1.2 | 73A | 400 | 0.08 | 28 | 10.3 | 0.10 | 1.2 | | |
| 57 | 1,300 | 0.25 | 42 | 21.3 | 0.15 | 0.6 | | 22 | 1,200 | 0.23 | 90 | 9.2 | 0.30 | 1.3 | 22 | 1,200 | 0.23 | 90 | 9.2 | 0.30 | 1.3 | | |
| 3 | 2,800 | 0.53 | 50 | 36.3 | 0.16 | 0.3 | | 16 | 1,700 | 0.32 | 131 | 8.8 | 0.45 | 1.4 | 16 | 1,700 | 0.32 | 131 | 8.8 | 0.45 | 1.4 | | |
| 10 | 400 | 0.08 | 28 | 10.4 | 0.10 | 1.2 | | 3 | 3,200 | 0.60 | 56 | 38.3 | 0.15 | 0.3 | 3 | 3,200 | 0.60 | 56 | 38.3 | 0.15 | 0.3 | | |
| 81 | 3,100 | 0.59 | 134 | 15.8 | 0.47 | 0.8 | | 15 | 1,100 | 0.21 | 82 | 9.2 | 0.27 | 1.2 | 15 | 1,100 | 0.21 | 82 | 9.2 | 0.27 | 1.2 | | |
| 25 | 2,600 | 0.49 | 112 | 15.8 | 0.39 | 0.8 | | 5 | 400 | 0.06 | 6 | 38.3 | 0.02 | 0.3 | 5 | 400 | 0.06 | 6 | 38.3 | 0.02 | 0.3 | | |
| 10 | 2,300 | 0.43 | 149 | 10.4 | 0.52 | 1.2 | | 15 | 600 | 0.11 | 38 | 10.4 | 0.13 | 1.2 | 15 | 600 | 0.11 | 38 | 10.4 | 0.13 | 1.2 | | |
| 6 | 500 | 0.09 | 20 | 15.8 | 0.07 | 0.6 | | 15 | 1,400 | 0.26 | 102 | 5.2 | 0.34 | 1.3 | 15 | 1,400 | 0.26 | 102 | 5.2 | 0.34 | 1.3 | | |

(Continued)

(17 of 32 sheets)

Table 4 (Continued)

| Vehi- cle | Wtr- rein Type | Dry Season (50 or 40 Mph) | | | | | Wet Season (50 or 40 Mph) | | | | | Wet Season (50 or 40 Mph) | | | | | Wet Season (50 or 40 Mph) | | | | | Wet Season (50 or 40 Mph) | | | | | | |
|--------------|----------------------|---------------------------|-------------|---------------------|-----------------------------|---------------------|---------------------------|-------------|---------------------|-----------------------------|---------------------|---------------------------|-------------|---------------------|-----------------------------|---------------------|---------------------------|-------------|---------------------|-----------------------------|---------------------|---------------------------|-------------|---------------------|-----------------------------|---------------------|------|----|
| | | Distance feet | Time sec | City Time sec | Non- city Time sec | Avg Speed mph | Distance feet | Time sec | City Time sec | Non- city Time sec | Avg Speed mph | Distance feet | Time sec | City Time sec | Non- city Time sec | Avg Speed mph | Distance feet | Time sec | City Time sec | Non- city Time sec | Avg Speed mph | Distance feet | Time sec | City Time sec | Non- city Time sec | Avg Speed mph | | |
| 62 | 6 | 6,500 | 1.23 | 238 | 18.6 | 0.86 | 0.7 | 10 | 10 | 10 | 10 | 500 | 0.09 | 31 | 10.4 | 0.11 | 10.4 | 0.11 | 31 | 10.4 | 0.11 | 10.4 | 0.11 | 31 | 10.4 | 0.11 | 10.4 | |
| 6 | 6 | 300 | 0.06 | 14 | 15.8 | 0.05 | 0.8 | 15 | 15 | 15 | 15 | 3,600 | 0.06 | 286 | 9.2 | 0.11 | 9.2 | 0.11 | 286 | 9.2 | 0.11 | 9.2 | 0.11 | 286 | 9.2 | 0.11 | 9.2 | |
| 10 | 10 | 700 | 0.13 | 45 | 10.4 | 0.16 | 1.2 | 17 | 17 | 17 | 17 | 600 | 0.11 | 38 | 10.4 | 0.13 | 10.4 | 0.13 | 38 | 10.4 | 0.13 | 10.4 | 0.13 | 38 | 10.4 | 0.13 | 10.4 | |
| 63 | 63 | 500 | 0.09 | 20 | 15.8 | 0.07 | 0.8 | 17 | 17 | 17 | 17 | 700 | 0.11 | 22 | 11.3 | 0.13 | 11.3 | 0.13 | 22 | 11.3 | 0.13 | 11.3 | 0.13 | 22 | 11.3 | 0.13 | 11.3 | |
| 62 | 62 | 2,300 | 0.43 | 83 | 18.6 | 0.30 | 0.7 | 2 | 2 | 2 | 2 | 400 | 0.06 | 22 | 13.2 | 0.17 | 13.2 | 0.17 | 22 | 13.2 | 0.17 | 13.2 | 0.17 | 22 | 13.2 | 0.17 | 13.2 | |
| 63 | 63 | 3,500 | 0.66 | 150 | 15.8 | 0.53 | 0.8 | 57 | 57 | 57 | 57 | 600 | 0.11 | 19 | 21.3 | 0.07 | 21.3 | 0.07 | 19 | 21.3 | 0.07 | 21.3 | 0.07 | 19 | 21.3 | 0.07 | 21.3 | |
| 31 | 31 | 4,000 | 0.76 | 71 | 38.3 | 0.23 | 0.3 | 16 | 16 | 16 | 16 | 200 | 0.04 | 8 | 9.2 | 0.03 | 9.2 | 0.03 | 8 | 9.2 | 0.03 | 9.2 | 0.03 | 8 | 9.2 | 0.03 | 9.2 | |
| 35 | 35 | 1,400 | 0.19 | 72 | 10.4 | 0.23 | 1.2 | 16 | 16 | 16 | 16 | 200 | 0.04 | 8 | 9.2 | 0.03 | 9.2 | 0.03 | 16 | 16 | 0.04 | 16 | 16 | 0.04 | 16 | 16 | 0.04 | 16 |
| 31 | 31 | 4,100 | 0.77 | 72 | 38.3 | 0.23 | 0.3 | 3 | 3 | 3 | 3 | 2,800 | 0.53 | 50 | 38.3 | 0.16 | 38.3 | 0.16 | 3 | 3 | 0.53 | 3 | 3 | 0.16 | 3 | 3 | 0.16 | 3 |
| 10 | 10 | 1,800 | 0.34 | 118 | 10.4 | 0.41 | 1.2 | 94 | 94 | 94 | 94 | 400 | 0.08 | 27 | 10.5 | 0.10 | 10.5 | 0.10 | 94 | 94 | 0.08 | 94 | 94 | 0.10 | 94 | 94 | 0.10 | 94 |
| 3 | 3 | 800 | 0.15 | 14 | 38.3 | 0.04 | 0.3 | 81 | 81 | 81 | 81 | 1,400 | 0.26 | 59 | 15.8 | 0.21 | 15.8 | 0.21 | 81 | 81 | 0.26 | 81 | 81 | 0.21 | 81 | 81 | 0.21 | 81 |
| 16 | 16 | 500 | 0.09 | 31 | 10.5 | 0.11 | 1.2 | 66 | 66 | 66 | 66 | 300 | 0.06 | 21 | 10.4 | 0.07 | 10.4 | 0.07 | 66 | 66 | 0.06 | 66 | 66 | 0.07 | 66 | 66 | 0.07 | 66 |
| 15 | 15 | 2,300 | 0.43 | 161 | 9.6 | 0.56 | 1.3 | 64 | 64 | 64 | 64 | 300 | 0.15 | 51 | 10.5 | 0.18 | 10.5 | 0.18 | 64 | 64 | 0.15 | 64 | 64 | 0.18 | 64 | 64 | 0.18 | 64 |
| 10 | 10 | 1,500 | 0.36 | 125 | 10.4 | 0.43 | 1.2 | 17 | 17 | 17 | 17 | 500 | 0.09 | 16 | 31.0 | 0.07 | 31.0 | 0.07 | 17 | 17 | 0.09 | 17 | 17 | 0.07 | 17 | 17 | 0.07 | 17 |
| 15 | 15 | 2,300 | 0.43 | 161 | 9.6 | 0.56 | 1.3 | 25 | 25 | 25 | 25 | 3,800 | 0.72 | 164 | 15.8 | 0.58 | 15.8 | 0.58 | 25 | 25 | 0.72 | 25 | 25 | 0.58 | 25 | 25 | 0.58 | 25 |
| 3 | 3 | 800 | 0.15 | 14 | 38.3 | 0.04 | 0.3 | 10 | 10 | 10 | 10 | 1,100 | 0.21 | 73 | 10.4 | 0.25 | 10.4 | 0.25 | 10 | 10 | 0.21 | 10 | 10 | 0.25 | 10 | 10 | 0.25 | 10 |
| 15 | 15 | 1,700 | 0.32 | 120 | 9.6 | 0.42 | 1.3 | 62 | 62 | 62 | 62 | 600 | 0.11 | 25 | 15.8 | 0.09 | 15.8 | 0.09 | 62 | 62 | 0.11 | 62 | 62 | 0.09 | 62 | 62 | 0.09 | 62 |
| 10 | 10 | 1,200 | 0.17 | 80 | 38.3 | 0.26 | 0.3 | 62 | 62 | 62 | 62 | 6,600 | 1.25 | 242 | 18.6 | 0.88 | 18.6 | 0.88 | 62 | 62 | 1.25 | 62 | 62 | 0.88 | 62 | 62 | 0.88 | 62 |
| 3 | 3 | 4,500 | 0.85 | 80 | 38.3 | 0.26 | 0.3 | 15 | 15 | 15 | 15 | 300 | 0.06 | 59 | 9.2 | 0.05 | 9.2 | 0.05 | 15 | 15 | 0.06 | 15 | 15 | 0.05 | 15 | 15 | 0.05 | 15 |
| 10 | 10 | 1,200 | 0.23 | 80 | 10.4 | 0.28 | 1.2 | 65 | 65 | 65 | 65 | 400 | 0.06 | 18 | 15.8 | 0.06 | 15.8 | 0.06 | 65 | 65 | 0.06 | 65 | 65 | 0.06 | 65 | 65 | 0.06 | 65 |
| 3 | 3 | 5,000 | 0.94 | 88 | 38.3 | 0.28 | 0.3 | 62 | 62 | 62 | 62 | 1,900 | 0.36 | 70 | 15.8 | 0.25 | 15.8 | 0.25 | 62 | 62 | 0.36 | 62 | 62 | 0.25 | 62 | 62 | 0.25 | 62 |
| 21 | 21 | 300 | 0.06 | 21 | 10.4 | 0.07 | 1.2 | 62 | 62 | 62 | 62 | 3,700 | 0.70 | 159 | 15.8 | 0.16 | 15.8 | 0.16 | 62 | 62 | 0.70 | 62 | 62 | 0.16 | 62 | 62 | 0.16 | 62 |
| 22 | 22 | 1,700 | 0.32 | 45 | 10.4 | 0.16 | 1.2 | 61 | 61 | 61 | 61 | 3,300 | 0.81 | 76 | 38.3 | 0.24 | 38.3 | 0.24 | 61 | 61 | 0.81 | 61 | 61 | 0.24 | 61 | 61 | 0.24 | 61 |
| 21 | 21 | 700 | 0.13 | 41 | 9.6 | 0.14 | 1.3 | 80 | 80 | 80 | 80 | 800 | 0.15 | 61 | 8.8 | 0.21 | 8.8 | 0.21 | 80 | 80 | 0.15 | 80 | 80 | 0.21 | 80 | 80 | 0.21 | 80 |
| 22 | 22 | 600 | 0.11 | 38 | 10.4 | 0.13 | 1.2 | 31 | 31 | 31 | 31 | 4,100 | 0.77 | 72 | 38.3 | 0.23 | 38.3 | 0.23 | 31 | 31 | 0.77 | 31 | 31 | 0.23 | 31 | 31 | 0.23 | 31 |
| 22 | 22 | 2,400 | 0.45 | 159 | 9.6 | 0.58 | 1.3 | 15 | 15 | 15 | 15 | 900 | 0.27 | 66 | 9.2 | 0.22 | 9.2 | 0.22 | 15 | 15 | 0.27 | 15 | 15 | 0.22 | 15 | 15 | 0.22 | 15 |
| 3 | 3 | 2,000 | 0.36 | 1200 | 38.3 | 2.11 | 0.3 | 10 | 10 | 10 | 10 | 900 | 0.17 | 59 | 10.4 | 0.20 | 10.4 | 0.20 | 10 | 10 | 0.17 | 10 | 10 | 0.20 | 10 | 10 | 0.20 | 10 |
| 21 | 21 | 900 | 0.17 | 59 | 10.4 | 0.20 | 1.2 | 3 | 3 | 3 | 3 | 1,700 | 0.32 | 30 | 38.3 | 0.10 | 38.3 | 0.10 | 3 | 3 | 0.32 | 3 | 3 | 0.10 | 3 | 3 | 0.10 | 3 |
| 3 | 3 | 9,000 | 1.70 | 100 | 38.3 | 0.51 | 0.3 | 16 | 16 | 16 | 16 | 500 | 0.06 | 25 | 8.8 | 0.08 | 8.8 | 0.08 | 16 | 16 | 0.06 | 16 | 16 | 0.08 | 16 | 16 | 0.08 | 16 |
| 10 | 10 | 1,000 | 0.21 | 73 | 10.4 | 0.25 | 1.2 | 15 | 15 | 15 | 15 | 1,600 | 0.30 | 117 | 9.2 | 0.39 | 9.2 | 0.39 | 15 | 15 | 0.30 | 15 | 15 | 0.39 | 15 | 15 | 0.39 | 15 |
| 15 | 15 | 5,000 | 0.94 | 398 | 9.6 | 1.22 | 1.3 | 10 | 10 | 10 | 10 | 1,900 | 0.36 | 125 | 10.4 | 0.43 | 10.4 | 0.43 | 10 | 10 | 0.36 | 10 | 10 | 0.43 | 10 | 10 | 0.43 | 10 |
| 3 | 3 | 500 | 0.09 | 8 | 38.3 | 0.03 | 0.3 | 15 | 15 | 15 | 15 | 2,800 | 0.53 | 207 | 9.2 | 0.69 | 9.2 | 0.69 | 15 | 15 | 0.53 | 15 | 15 | 0.69 | 15 | 15 | 0.69 | 15 |
| 10 | 10 | 400 | 0.08 | 28 | 10.4 | 0.10 | 1.2 | 3 | 3 | 3 | 3 | 800 | 0.15 | 14 | 38.3 | 0.04 | 38.3 | 0.04 | 3 | 3 | 0.15 | 3 | 3 | 0.04 | 3 | 3 | 0.04 | 3 |
| 3 | 3 | 2,500 | 0.47 | 44 | 38.3 | 0.14 | 0.3 | 15 | 15 | 15 | 15 | 1,800 | 0.34 | 133 | 9.2 | 0.14 | 9.2 | 0.14 | 15 | 15 | 0.34 | 15 | 15 | 0.14 | 15 | 15 | 0.14 | 15 |
| 10 | 10 | 200 | 0.04 | 14 | 10.4 | 0.05 | 1.2 | 3 | 3 | 3 | 3 | 5,200 | 0.98 | 62 | 38.3 | 0.25 | 38.3 | 0.25 | 3 | 3 | 0.98 | 3 | 3 | 0.25 | 3 | 3 | 0.25 | 3 |
| 3 | 3 | 11,000 | 2.09 | 213 | 38.3 | 0.63 | 0.3 | 15 | 15 | 15 | 15 | 400 | 0.08 | 31 | 10.4 | 0.11 | 10.4 | 0.11 | 15 | 15 | 0.08 | 15 | 15 | 0.11 | 15 | 15 | 0.11 | 15 |
| 69 | 69 | 1,200 | 0.23 | 80 | 10.4 | 0.28 | 1.2 | 10 | 10 | 10 | 10 | 500 | 0.09 | 31 | 10.4 | 0.11 | 10.4 | 0.11 | 10 | 10 | 0.09 | 10 | 10 | 0.11 | 10 | 10 | 0.11 | 10 |
| 13 | 13 | 2,900 | 0.55 | 94 | 2.1 | 3.19 | 5.8 | 23 | 23 | 23 | 23 | 300 | 0.06 | 23 | 38.3 | 0.08 | 38.3 | 0.08 | 23 | 23 | 0.06 | 23 | 23 | 0.08 | 23 | 23 | 0.08 | 23 |
| 10 | 10 | 600 | 0.11 | 38 | 10.4 | 0.13 | 1.2 | 15 | 15 | 15 | 15 | 2,100 | 0.40 | 38 | 38.3 | 0.12 | 38.3 | 0.12 | 15 | 15 | 0.40 | 15 | 15 | 0.12 | 15 | 15 | 0.12 | 15 |
| 3 | 3 | 700 | 0.13 | 12 | 38.3 | 0.04 | 0.3 | 28 | 28 | 28 | 28 | 900 | 0.17 | 20 | 30.4 | 0.17 | 30.4 | 0.17 | 28 | 28 | 0.17 | 28 | 28 | 0.17 | 28 | 28 | 0.17 | 28 |
| 10 | 10 | 1,500 | 0.36 | 125 | 10.4 | 0.43 | 1.2 | 3 | 3 | 3 | 3 | 1,500 | 0.36 | 34 | 38.3 | 0.11 | 38.3 | 0.11 | 3 | 3 | 0.36 | 3 | 3 | 0.11 | 3 | 3 | 0.11 | 3 |
| 14 | 14 | 1,800 | 0.34 | 191 | 6.4 | 0.65 | 1.9 | 21 | 21 | 21 | 21 | 400 | 0.08 | 28 | 10.4 | 0.10 | 10.4 | 0.10 | 21 | 21 | 0.08 | 21 | 21 | 0.10 | 21 | 21 | 0.10 | 21 |
| 3 | 3 | 2,500 | 0.55 | 50 | 38.3 | 0.16 | 0.3 | 21 | 21 | 21 | 21 | 1,700 | 0.32 | 45 | 10.4 | 0.16 | 10.4 | 0.16 | 21 | 21 | 0.32 | 21 | 21 | 0.16 | 21 | 21 | 0.16 | 21 |
| 4 | 4 | 2,100 | 0.40 | 225 | 6.4 | 0.76 | 1.9 | 22 | 22 | 22 | 22 | 600 | 0.11 | 43 | 9.2 | 0.14 | 9.2 | 0.14 | 22 | 22 | 0.11 | 22 | 22 | 0.14 | 22 | 22 | 0.14 | 22 |
| 3 | 3 | 1,400 | 0.26 | 24 | 38.3 | 0.03 | 0.3 | 21 | 21 | 21 | 21 | 700 | 0.13 | 45 | 10.4 | 0.16 | 10.4 | 0.16 | 21 | 21 | 0.13 | 21 | 21 | 0.16 | 21 | 21 | 0.16 | 21 |
| 5 | 5 | 300 | 0.06 | 7 | 33.0 | 0.02 | 0.4 | 22 | 22 | 22 | 22 | 2,300 | 0.43 | 168 | 9.2 | 0.56 | 9.2 | 0.56 | 22 | 22 | 0.43 | 22 | 22 | 0.56 | 22 | 22 | 0.56 | 22 |
| 3 | 3 | 6,500 | 1.29 | 121 | 38.3 | 0.39 | 0.3 | 3 | 3 | 3 | 3 | 2,100 | 0.40 | 1200 | 38.3 | 2.12 | 38.3 | 2.12 | 3 | 3 | 0.40 | 3 | 3 | 2.12 | 3 | 3 | 2.12 | 3 |
| 4 | 4 | 2,100 | 0.40 | 225 | 6.4 | 0.76 | 1.9 | 21 | 21 | 21 | 21 | 700 | 0.13 | 45 | 10.4 | 0.16 | 10.4 | 0.16 | 21 | 21 | 0.13 | 21 | 21 | 0.16 | 21 | 21 | 0.16 | 21 |
| 2 | 2 | 1,100 | 0.21 | 57 | 13.2 | 0.03 | 0.9 | 15 | 15 | 15 | 15 | 9,000 | 1.70 | 160 | 38.3 | 0.51 | 38.3 | 0.51 | 15 | 15 | 1.70 | 15 | 15 | 0.51 | 15 | 15 | 0.51 | 15 |
| 2 | 2 | 1,100 | 0.21 | 57 | 13.2 | 0.03 | 0.9 | 15 | 15 | 15 | 15 | 1,200 | 0.23 | 86 | 10.4 | 0.28 | 10.4 | 0.28 | 15 | 15 | 0.23 | 15 | | | | | | |

Table 4 (Continued)

| Vehi- cle | Dry Season (60 or 40 BT) | | | | | Wet Season (60 or 40 BT) | | | | | Wet Season (60 or 35 BT) | | | | | Fuel mi- le | | | | |
|--------------|--------------------------|------------------|-------------|---------------------|--------------------|--------------------------|------------------|-------------|---------------------|--------------------|--------------------------|------------------|-------------|---------------------|--------------------|-------------------|-------|--------|-------|-------|
| | Ter- rain Type | Distance feet | Time sec | Avg Speed mph | Fuel gal/ mi | Ter- rain Type | Distance feet | Time sec | Avg Speed mph | Fuel gal/ mi | Ter- rain Type | Distance feet | Time sec | Avg Speed mph | Fuel gal/ mi | | | | | |
| M548 | 2 | 1,100 | 0.21 | 80 | 9.4 | 0.38 | 1.8 | 116 | 9.4 | 0.54 | 1.8 | 2 | 1,600 | 0.30 | 116 | 9.4 | | | | |
| | 10 | 2,200 | 0.42 | 150 | 10.0 | 0.63 | 1.5 | 150 | 10.0 | 0.63 | 1.5 | 10 | 2,200 | 0.42 | 150 | 10.0 | | | | |
| | 52 | 2,600 | 0.11 | 41 | 10.0 | 0.16 | 1.5 | 52 | 10.0 | 0.16 | 1.5 | 52 | 2,600 | 0.11 | 41 | 10.0 | | | | |
| | 10 | 2,600 | 0.38 | 136 | 10.0 | 0.37 | 1.5 | 10 | 1,400 | 0.39 | 1.5 | 10 | 1,400 | 0.36 | 95 | 10.0 | | | | |
| | 13 | 1,100 | 0.21 | 75 | 10.0 | 0.32 | 1.5 | 3 | 300 | 0.09 | 1.5 | 3 | 300 | 0.06 | 20 | 10.0 | | | | |
| | 10 | 1,600 | 0.30 | 109 | 10.0 | 0.45 | 1.5 | 14 | 10.0 | 0.06 | 1.5 | 14 | 200 | 0.04 | 14 | 10.0 | | | | |
| | 6 | 300 | 0.17 | 61 | 10.0 | 0.26 | 1.5 | 75 | 10.0 | 0.32 | 1.5 | 3 | 1,100 | 0.21 | 75 | 10.0 | | | | |
| | 10 | 1,900 | 0.17 | 24 | 8.4 | 0.14 | 2.4 | 82 | 10.0 | 0.34 | 1.5 | 10 | 1,200 | 0.23 | 82 | 10.0 | | | | |
| | 10 | 6,500 | 1.23 | 460 | 10.0 | 1.04 | 1.5 | 37 | 9.2 | 0.17 | 1.5 | 15 | 500 | 0.09 | 44 | 7.8 | | | | |
| | 10 | 1,000 | 0.09 | 68 | 10.0 | 0.22 | 2.4 | 41 | 10.0 | 0.16 | 1.5 | 10 | 600 | 0.11 | 41 | 10.0 | | | | |
| | 10 | 2,000 | 0.19 | 68 | 10.0 | 0.28 | 1.5 | 49 | 8.4 | 0.26 | 2.4 | 6 | 600 | 0.11 | 49 | 8.4 | | | | |
| | 10 | 2,000 | 0.42 | 150 | 10.0 | 0.63 | 1.5 | 135 | 9.2 | 0.89 | 1.9 | 15 | 2,500 | 0.17 | 219 | 7.8 | | | | |
| | 6 | 700 | 0.13 | 57 | 8.4 | 0.31 | 2.4 | 130 | 10.0 | 0.54 | 1.5 | 10 | 1,900 | 0.36 | 130 | 10.0 | | | | |
| | 10 | 3,800 | 0.72 | 259 | 10.0 | 1.08 | 1.5 | 150 | 10.0 | 0.48 | 1.5 | 10 | 1,700 | 0.13 | 57 | 8.4 | | | | |
| | 10 | 1,700 | 0.32 | 116 | 10.0 | 0.48 | 1.5 | 6 | 700 | 0.13 | 2.4 | 6 | 700 | 0.13 | 57 | 8.4 | | | | |
| | 6 | 200 | 0.04 | 16 | 8.4 | 0.10 | 2.4 | 15 | 128 | 9.2 | 0.53 | 1.9 | 15 | 1,500 | 0.28 | 131 | 7.8 | | | |
| | 10 | 1,300 | 0.24 | 89 | 10.0 | 0.36 | 1.5 | 32 | 8.4 | 0.19 | 2.4 | 6 | 400 | 0.08 | 32 | 8.4 | | | | |
| | 10 | 2,200 | 0.42 | 150 | 10.0 | 0.63 | 1.5 | 89 | 9.2 | 0.44 | 1.9 | 15 | 1,200 | 0.23 | 105 | 7.8 | | | | |
| | 3 | 700 | 0.13 | 58 | 10.0 | 0.20 | 1.5 | 116 | 10.0 | 0.48 | 1.5 | 10 | 1,700 | 0.32 | 116 | 10.0 | | | | |
| | 3 | 1,700 | 0.32 | 123 | 9.4 | 0.58 | 1.8 | 14 | 600 | 0.11 | 3.3 | 14 | 1,600 | 0.11 | 60 | 6.8 | | | | |
| | 3 | 200 | 0.04 | 14 | 10.0 | 0.05 | 1.5 | 59 | 9.2 | 0.28 | 1.9 | 15 | 800 | 0.15 | 70 | 7.8 | | | | |
| 10 | 6,500 | 1.23 | 2,400 | 10.0 | 6.40 | 1.5 | 314 | 10.0 | 1.30 | 1.5 | 10 | 4,600 | 0.87 | 311 | 10.0 | | | | | |
| 10 | 700 | 0.13 | 48 | 10.0 | 0.20 | 1.5 | | | | | | | | | 1.5 | | | | | |
| Total | | | | | | | | | | | | | | | | 245,100 | 46.29 | 42,520 | 64.95 | 61.00 |
| | | | | | | | | | | | | | | | | 44,678 | | | | |
| | | | | | | | | | | | | | | | | 46.13 | | | | |
| | | | | | | | | | | | | | | | | 244,400 | | | | |
| | | | | | | | | | | | | | | | | 61.00 | | | | |
| | | | | | | | | | | | | | | | | 61.00 | | | | |
| | | | | | | | | | | | | | | | | 61.00 | | | | |
| | | | | | | | | | | | | | | | | 61.00 | | | | |
| | | | | | | | | | | | | | | | | 61.00 | | | | |
| | | | | | | | | | | | | | | | | 61.00 | | | | |
| | | | | | | | | | | | | | | | | 61.00 | | | | |
| | | | | | | | | | | | | | | | | 61.00 | | | | |
| | | | | | | | | | | | | | | | | 61.00 | | | | |
| | | | | | | | | | | | | | | | | 61.00 | | | | |
| | | | | | | | | | | | | | | | | 61.00 | | | | |
| | | | | | | | | | | | | | | | | 61.00 | | | | |
| | | | | | | | | | | | | | | | | 61.00 | | | | |
| | | | | | | | | | | | | | | | | 61.00 | | | | |
| | | | | | | | | | | | | | | | | 61.00 | | | | |
| | | | | | | | | | | | | | | | | 61.00 | | | | |
| | | | | | | | | | | | | | | | | 61.00 | | | | |
| | | | | | | | | | | | | | | | | 61.00 | | | | |
| | | | | | | | | | | | | | | | | 61.00 | | | | |
| | | | | | | | | | | | | | | | | 61.00 | | | | |
| | | | | | | | | | | | | | | | | 61.00 | | | | |
| | | | | | | | | | | | | | | | | 61.00 | | | | |
| | | | | | | | | | | | | | | | | 61.00 | | | | |
| | | | | | | | | | | | | | | | | 61.00 | | | | |
| | | | | | | | | | | | | | | | | 61.00 | | | | |
| | | | | | | | | | | | | | | | | 61.00 | | | | |
| | | | | | | | | | | | | | | | | 61.00 | | | | |
| | | | | | | | | | | | | | | | | 61.00 | | | | |
| | | | | | | | | | | | | | | | | 61.00 | | | | |
| | | | | | | | | | | | | | | | | 61.00 | | | | |
| | | | | | | | | | | | | | | | | 61.00 | | | | |
| | | | | | | | | | | | | | | | | 61.00 | | | | |
| | | | | | | | | | | | | | | | | 61.00 | | | | |
| | | | | | | | | | | | | | | | | 61.00 | | | | |
| | | | | | | | | | | | | | | | | 61.00 | | | | |
| | | | | | | | | | | | | | | | | 61.00 | | | | |
| | | | | | | | | | | | | | | | | 61.00 | | | | |
| | | | | | | | | | | | | | | | | 61.00 | | | | |
| | | | | | | | | | | | | | | | | 61.00 | | | | |
| | | | | | | | | | | | | | | | | 61.00 | | | | |
| | | | | | | | | | | | | | | | | 61.00 | | | | |
| | | | | | | | | | | | | | | | | 61.00 | | | | |
| | | | | | | | | | | | | | | | | 61.00 | | | | |
| | | | | | | | | | | | | | | | | 61.00 | | | | |
| | | | | | | | | | | | | | | | | 61.00 | | | | |
| | | | | | | | | | | | | | | | | 61.00 | | | | |
| | | | | | | | | | | | | | | | | 61.00 | | | | |
| | | | | | | | | | | | | | | | | 61.00 | | | | |
| | | | | | | | | | | | | | | | | 61.00 | | | | |
| | | | | | | | | | | | | | | | | 61.00 | | | | |
| | | | | | | | | | | | | | | | | 61.00 | | | | |
| | | | | | | | | | | | | | | | | 61.00 | | | | |
| | | | | | | | | | | | | | | | | 61.00 | | | | |
| | | | | | | | | | | | | | | | | 61.00 | | | | |
| | | | | | | | | | | | | | | | | 61.00 | | | | |
| | | | | | | | | | | | | | | | | 61.00 | | | | |
| | | | | | | | | | | | | | | | | 61.00 | | | | |
| | | | | | | | | | | | | | | | | 61.00 | | | | |
| | | | | | | | | | | | | | | | | 61.00 | | | | |
| | | | | | | | | | | | | | | | | 61.00 | | | | |
| | | | | | | | | | | | | | | | | 61.00 | | | | |
| | | | | | | | | | | | | | | | | 61.00 | | | | |
| | | | | | | | | | | | | | | | | 61.00 | | | | |
| | | | | | | | | | | | | | | | | 61.00 | | | | |
| | | | | | | | | | | | | | | | | 61.00 | | | | |
| | | | | | | | | | | | | | | | | 61.00 | | | | |
| | | | | | | | | | | | | | | | | 61.00 | | | | |
| | | | | | | | | | | | | | | | | 61.00 | | | | |
| | | | | | | | | | | | | | | | | 61.00 | | | | |
| | | | | | | | | | | | | | | | | 61.00 | | | | |
| | | | | | | | | | | | | | | | | 61.00 | | | | |
| | | | | | | | | | | | | | | | | 61.00 | | | | |
| | | | | | | | | | | | | | | | | 61.00 | | | | |
| | | | | | | | | | | | | | | | | 61.00 | | | | |
| | | | | | | | | | | | | | | | | 61.00 | | | | |
| | | | | | | | | | | | | | | | | 61.00 | | | | |
| | | | | | | | | | | | | | | | | 61.00 | | | | |
| | | | | | | | | | | | | | | | | 61.00 | | | | |
| | | | | | | | | | | | | | | | | 61.00 | | | | |
| | | | | | | | | | | | | | | | | 61.00 | | | | |
| | | | | | | | | | | | | | | | | 61.00 | | | | |
| | | | | | | | | | | | | | | | | 61.00 | | | | |
| | | | | | | | | | | | | | | | | 61.00 | | | | |
| | | | | | | | | | | | | | | | | 61.00 | | | | |
| | | | | | | | | | | | | | | | | 61.00 | | | | |
| | | | | | | | | | | | | | | | | 61.00 | | | | |
| | | | | | | | | | | | | | | | | 61.00 | | | | |
| | | | | | | | | | | | | | | | | 61.00 | | | | |
| | | | | | | | | | | | | | | | | 61.00 | | | | |
| | | | | | | | | | | | | | | | | 61.00 | | | | |
| | | | | | | | | | | | | | | | | 61.00 | | | | |
| | | | | | | | | | | | | | | | | 61.00 | | | | |
| | | | | | | | | | | | | | | | | 61.00 | | | | |
| | | | | | | | | | | | | | | | | 61.00 | | | | |
| | | | | | | | | | | | | | | | | 61.00 | | | | |
| | | | | | | | | | | | | | | | | 61.00 | | | | |
| | | | | | | | | | | | | | | | | 61.00 | | | | |
| | | | | | | | | | | | | | | | | 61.00 | | | | |
| | | | | | | | | | | | | | | | | 61.00 | | | | |
| | | | | | | | | | | | | | | | | 61.00 | | | | |
| | | | | | | | | | | | | | | | | 61.00 | | | | |
| | | | | | | | | | | | | | | | | 61.00 | | | | |
| | | | | | | | | | | | | | | | | 61.00 | | | | |
| | | | | | | | | | | | | | | | | 61.00 | | | | |
| | | | | | | | | | | | | | | | | 61.00 | | | | |
| | | | | | | | | | | | | | | | | 61.00 | | | | |
| | | | | | | | | | | | | | | | | 61.00 | | | | |
| | | | | | | | | | | | | | | | | 61.00 | | | | |
| | | | | | | | | | | | | | | | | 61.00 | | | | |
| | | | | | | | | | | | | | | | | 61.00 | | | | |
| | | | | | | | | | | | | | | | | 61.00 | | | | |
| | | | | | | | | | | | | | | | | 61.00 | | | | |
| | | | | | | | | | | | | | | | | 61.00 | | | | |
| | | | | | | | | | | | | | | | | 61.00 | | | | |
| | | | | | | | | | | | | | | | | 61.00 | | | | |
| | | | | | | | | | | | | | | | | 61.00 | | | | |
| | | | | | | | | | | | | | | | | | | | | |

Table 4 (Continued)

| Vehi- cle | Dry Season (60 or 60 RT) | | | | | Wet Season (60 or 60 RT) | | | | | Wet Season (60 or 60 RT) | | | | | Wet Season (60 or 60 RT) | | | | |
|--------------|--------------------------|------------------|---------------------|--------------|----------------------|--------------------------|------------------|---------------------|--------------|----------------------|--------------------------|------------------|---------------------|--------------|----------------------|--------------------------|------------------|---------------------|--------------|----------------------|
| | Tr- rein | Distance feet | Time min- sec | Speed mph | Fuel gal/ mile | Tr- rein | Distance feet | Time min- sec | Speed mph | Fuel gal/ mile | Tr- rein | Distance feet | Time min- sec | Speed mph | Fuel gal/ mile | Tr- rein | Distance feet | Time min- sec | Speed mph | Fuel gal/ mile |
| 4 | 6 | 1,000 | 0.19 | 79 | 8.6 | 6 | 1,200 | 0.23 | 97 | 8.2 | 6 | 1,200 | 0.23 | 97 | 8.2 | 6 | 1,200 | 0.23 | 97 | 8.2 |
| 6 | 6 | 700 | 0.13 | 57 | 8.4 | 15 | 3,100 | 0.59 | 230 | 9.2 | 15 | 3,100 | 0.59 | 230 | 9.2 | 15 | 3,100 | 0.59 | 230 | 9.2 |
| 28 | 28 | 1,200 | 0.23 | 27 | 10.0 | 2 | 300 | 0.06 | 20 | 10.0 | 2 | 300 | 0.06 | 20 | 10.0 | 2 | 300 | 0.06 | 20 | 10.0 |
| 3 | 3 | 400 | 0.08 | 252 | 10.0 | 3 | 600 | 0.11 | 44 | 9.4 | 3 | 600 | 0.11 | 44 | 9.4 | 3 | 600 | 0.11 | 44 | 9.4 |
| 32 | 32 | 3,100 | 0.58 | 252 | 8.4 | 15 | 300 | 0.06 | 22 | 3.2 | 15 | 300 | 0.06 | 22 | 3.2 | 15 | 300 | 0.06 | 22 | 3.2 |
| 36 | 36 | 600 | 0.11 | 41 | 9.9 | 3 | 200 | 0.04 | 14 | 10.0 | 3 | 200 | 0.04 | 14 | 10.0 | 3 | 200 | 0.04 | 14 | 10.0 |
| 36 | 36 | 700 | 0.08 | 37 | 8.4 | 21 | 300 | 0.06 | 20 | 10.0 | 21 | 300 | 0.06 | 20 | 10.0 | 21 | 300 | 0.06 | 20 | 10.0 |
| 36 | 36 | 4,300 | 0.61 | 313 | 9.9 | 2 | 500 | 0.09 | 36 | 9.4 | 2 | 500 | 0.09 | 36 | 9.4 | 2 | 500 | 0.09 | 36 | 9.4 |
| 37 | 37 | 1,200 | 0.23 | 78 | 10.0 | 15 | 300 | 0.06 | 2422 | 9.2 | 15 | 300 | 0.06 | 2422 | 9.2 | 15 | 300 | 0.06 | 2422 | 9.2 |
| 37 | 37 | 1,200 | 0.23 | 78 | 10.0 | 15 | 300 | 0.06 | 2400 | | 15 | 300 | 0.06 | 2400 | | 15 | 300 | 0.06 | 2400 | |
| 37 | 37 | 1,000 | 0.19 | 79 | 8.6 | 15 | 5,900 | 1.12 | 515 | 12.2 | 15 | 5,900 | 1.12 | 515 | 12.2 | 15 | 5,900 | 1.12 | 515 | 12.2 |
| 37 | 37 | 1,000 | 0.19 | 79 | 8.6 | 15 | 400 | 0.08 | 27 | 10.0 | 15 | 400 | 0.08 | 27 | 10.0 | 15 | 400 | 0.08 | 27 | 10.0 |
| 14 | 14 | 1,900 | 0.28 | 136 | 6.8 | 15 | 700 | 0.13 | 52 | 9.2 | 15 | 700 | 0.13 | 52 | 9.2 | 15 | 700 | 0.13 | 52 | 9.2 |
| 14 | 14 | 2,000 | 0.38 | 136 | 6.8 | 15 | 300 | 0.06 | 20 | 10.0 | 15 | 300 | 0.06 | 20 | 10.0 | 15 | 300 | 0.06 | 20 | 10.0 |
| 14 | 14 | 400 | 0.08 | 40 | 6.8 | 49 | 900 | 0.17 | 71 | 8.6 | 49 | 900 | 0.17 | 71 | 8.6 | 49 | 900 | 0.17 | 71 | 8.6 |
| 18 | 18 | 400 | 0.08 | 27 | 10.0 | 6 | 800 | 0.15 | 65 | 8.4 | 6 | 800 | 0.15 | 65 | 8.4 | 6 | 800 | 0.15 | 65 | 8.4 |
| 32 | 32 | 1,900 | 0.36 | 191 | 6.8 | 28 | 700 | 0.13 | 48 | 10.0 | 28 | 700 | 0.13 | 48 | 10.0 | 28 | 700 | 0.13 | 48 | 10.0 |
| 32 | 32 | 1,200 | 0.23 | 78 | 10.0 | 6 | 2,900 | 0.55 | 235 | 9.4 | 6 | 2,900 | 0.55 | 235 | 9.4 | 6 | 2,900 | 0.55 | 235 | 9.4 |
| 10 | 10 | 700 | 0.13 | 54 | 10.0 | 89 | 600 | 0.11 | 54 | 7.6 | 89 | 600 | 0.11 | 54 | 7.6 | 89 | 600 | 0.11 | 54 | 7.6 |
| 3 | 3 | 1,200 | 0.23 | 78 | 10.0 | 6 | 500 | 0.09 | 41 | 8.4 | 6 | 500 | 0.09 | 41 | 8.4 | 6 | 500 | 0.09 | 41 | 8.4 |
| 10 | 10 | 200 | 0.04 | 259 | 10.0 | 30 | 1,300 | 0.25 | 121 | 8.5 | 30 | 1,300 | 0.25 | 121 | 8.5 | 30 | 1,300 | 0.25 | 121 | 8.5 |
| 10 | 10 | 3,800 | 0.72 | 116 | 10.4 | 3 | 1,500 | 0.38 | 17 | | 3 | 1,500 | 0.38 | 17 | | 3 | 1,500 | 0.38 | 17 | |
| 23 | 23 | 3,600 | 0.34 | 116 | 10.6 | 30 | 1,000 | 0.19 | 102 | 10.0 | 30 | 1,000 | 0.19 | 102 | 10.0 | 30 | 1,000 | 0.19 | 102 | 10.0 |
| 37 | 37 | 4,700 | 0.69 | 141 | 10.0 | 86 | 500 | 0.09 | 32 | 10.5 | 86 | 500 | 0.09 | 32 | 10.5 | 86 | 500 | 0.09 | 32 | 10.5 |
| 57 | 57 | 3,700 | 0.70 | 255 | 9.9 | 37 | 4,900 | 0.93 | 334 | 10.0 | 37 | 4,900 | 0.93 | 334 | 10.0 | 37 | 4,900 | 0.93 | 334 | 10.0 |
| 32 | 32 | 1,500 | 0.28 | 102 | 10.0 | 82 | 1,000 | 0.19 | 100 | 6.8 | 82 | 1,000 | 0.19 | 100 | 6.8 | 82 | 1,000 | 0.19 | 100 | 6.8 |
| 32 | 32 | 1,000 | 0.19 | 69 | 9.9 | 14 | 1,400 | 0.26 | 140 | 6.0 | 14 | 1,400 | 0.26 | 140 | 6.0 | 14 | 1,400 | 0.26 | 140 | 6.0 |
| 32 | 32 | 3,900 | 0.74 | 120 | 9.9 | 15 | 400 | 0.08 | 30 | 9.2 | 15 | 400 | 0.08 | 30 | 9.2 | 15 | 400 | 0.08 | 30 | 9.2 |
| 3 | 3 | 1,200 | 0.23 | 78 | 10.0 | 10 | 1,600 | 0.30 | 109 | 10.0 | 10 | 1,600 | 0.30 | 109 | 10.0 | 10 | 1,600 | 0.30 | 109 | 10.0 |
| 32 | 32 | 600 | 0.11 | 43 | 8.4 | 14 | 300 | 0.06 | 30 | 6.8 | 14 | 300 | 0.06 | 30 | 6.8 | 14 | 300 | 0.06 | 30 | 6.8 |
| 32 | 32 | 700 | 0.13 | 43 | 9.9 | 15 | 600 | 0.11 | 44 | 9.2 | 15 | 600 | 0.11 | 44 | 9.2 | 15 | 600 | 0.11 | 44 | 9.2 |
| 32 | 32 | 2,500 | 0.47 | 164 | 10.4 | 82 | 1,900 | 0.36 | 191 | 6.8 | 82 | 1,900 | 0.36 | 191 | 6.8 | 82 | 1,900 | 0.36 | 191 | 6.8 |
| 7 | 7 | 300 | 0.06 | 20 | 10.4 | 14 | 200 | 0.04 | 20 | 6.8 | 14 | 200 | 0.04 | 20 | 6.8 | 14 | 200 | 0.04 | 20 | 6.8 |
| 5 | 5 | 1,200 | 0.23 | 82 | 10.0 | 15 | 700 | 0.21 | 52 | 9.2 | 15 | 700 | 0.21 | 52 | 9.2 | 15 | 700 | 0.21 | 52 | 9.2 |
| 32 | 32 | 2,200 | 0.42 | 152 | 9.9 | 3 | 1,100 | 0.21 | 75 | 10.0 | 3 | 1,100 | 0.21 | 75 | 10.0 | 3 | 1,100 | 0.21 | 75 | 10.0 |
| 10 | 10 | 1,200 | 0.23 | 78 | 10.0 | 15 | 4,200 | 0.79 | 311 | 9.2 | 15 | 4,200 | 0.79 | 311 | 9.2 | 15 | 4,200 | 0.79 | 311 | 9.2 |
| 10 | 10 | 1,200 | 0.23 | 78 | 10.0 | 15 | 2,000 | 0.38 | 129 | 10.6 | 15 | 2,000 | 0.38 | 129 | 10.6 | 15 | 2,000 | 0.38 | 129 | 10.6 |
| 15 | 15 | 3,600 | 0.72 | 267 | 9.2 | 16 | 600 | 0.11 | 44 | 9.2 | 16 | 600 | 0.11 | 44 | 9.2 | 16 | 600 | 0.11 | 44 | 9.2 |
| 10 | 10 | 3,800 | 0.73 | 259 | 9.2 | 30 | 3,200 | 0.60 | 463 | 7.8 | 30 | 3,200 | 0.60 | 463 | 7.8 | 30 | 3,200 | 0.60 | 463 | 7.8 |
| 10 | 10 | 700 | 0.13 | 48 | 10.0 | 30 | 3,200 | 0.60 | 257 | 8.5 | 30 | 3,200 | 0.60 | 257 | 8.5 | 30 | 3,200 | 0.60 | 257 | 8.5 |
| 10 | 10 | 1,200 | 0.23 | 78 | 10.0 | 3 | 1,200 | 0.23 | 82 | 10.0 | 3 | 1,200 | 0.23 | 82 | 10.0 | 3 | 1,200 | 0.23 | 82 | 10.0 |
| 10 | 10 | 1,300 | 0.25 | 106 | 8.4 | 30 | 4,500 | 0.85 | 361 | 8.5 | 30 | 4,500 | 0.85 | 361 | 8.5 | 30 | 4,500 | 0.85 | 361 | 8.5 |
| 17 | 17 | 1,400 | 0.34 | 93 | 10.5 | 6 | 1,300 | 0.25 | 1200 | 10.0 | 6 | 1,300 | 0.25 | 1200 | 10.0 | 6 | 1,300 | 0.25 | 1200 | 10.0 |
| 25 | 25 | 1,200 | 0.23 | 78 | 10.0 | 30 | 700 | 0.13 | 56 | 8.5 | 30 | 700 | 0.13 | 56 | 8.5 | 30 | 700 | 0.13 | 56 | 8.5 |
| 60 | 60 | 1,200 | 0.23 | 78 | 10.0 | 5 | 2,700 | 0.51 | 177 | 10.4 | 5 | 2,700 | 0.51 | 177 | 10.4 | 5 | 2,700 | 0.51 | 177 | 10.4 |
| 16 | 16 | 200 | 0.06 | 24 | 8.4 | 3 | 1,700 | 0.32 | 116 | 9.0 | 3 | 1,700 | 0.32 | 116 | 9.0 | 3 | 1,700 | 0.32 | 116 | 9.0 |
| 6 | 6 | 300 | 0.06 | 539 | 8.6 | 15 | 2,100 | 0.40 | 168 | 8.5 | 15 | 2,100 | 0.40 | 168 | 8.5 | 15 | 2,100 | 0.40 | 168 | 8.5 |
| 62 | 62 | 6,800 | 1.29 | 371 | 9.2 | 15 | 5,000 | 0.94 | 371 | 9.2 | 15 | 5,000 | 0.94 | 371 | 9.2 | 15 | 5,000 | 0.94 | 371 | 9.2 |
| 6 | 6 | 400 | 0.08 | 32 | 8.4 | 10 | 500 | 0.09 | 34 | 10.0 | 10 | 500 | 0.09 | 34 | 10.0 | 10 | 500 | 0.09 | 34 | 10.0 |
| 60 | 60 | 700 | 0.13 | 48 | 10.0 | 15 | 3,700 | 0.70 | 274 | 9.2 | 15 | 3,700 | 0.70 | 274 | 9.2 | 15 | 3,700 | 0.70 | 274 | 9.2 |
| 60 | 60 | 200 | 0.11 | 44 | 8.4 | 10 | 4,400 | 0.83 | 300 | 10.0 | 10 | 4,400 | 0.83 | 300 | 10.0 | 10 | 4,400 | 0.83 | 300 | 10.0 |
| 62 | 62 | 600 | 0.11 | 44 | 8.6 | 3 | 1,300 | 0.25 | 89 | 10.0 | 3 | 1,300 | 0.25 | 89 | 10.0 | 3 | 1,300 | 0.25 | 89 | 10.0 |
| 63 | 63 | 4,400 | 0.63 | 357 | 8.4 | 15 | 300 | 0.06 | 22 | 9.2 | 15 | 300 | 0.06 | 22 | 9.2 | 15 | 300 | 0.06 | 22 | 9.2 |

(20 of 32 sheets)

(Continued)

Table 4 (Continued)

| Vehi- cle | Test Type | Dry Season (60 or 40 RCI) | | | | | Wet Season (60 or 40 RCI) | | | | | Wet Season (60 or 40 RCI) | | | | | Wet Season (60 or 40 RCI) | | | | |
|--------------|--------------|---------------------------|------------------|-------------|--------------|----------------------|---------------------------|------------------|-------------|--------------|----------------------|---------------------------|------------------|-------------|--------------|----------------------|---------------------------|------------------|-------------|--------------|----------------------|
| | | Test Type | Distance feet | Time sec | Speed mph | Fuel gal/ mile | Test Type | Distance feet | Time sec | Speed mph | Fuel gal/ mile | Test Type | Distance feet | Time sec | Speed mph | Fuel gal/ mile | Test Type | Distance feet | Time sec | Speed mph | Fuel gal/ mile |
| 31 | 3,000 | 31 | 3,000 | 0.57 | 10.0 | 0.86 | 81 | 1,300 | 0.25 | 106 | 8.4 | 61 | 1,300 | 0.25 | 106 | 8.4 | 61 | 1,300 | 0.25 | 106 | 8.4 |
| 35 | 900 | 69 | 900 | 0.17 | 10.0 | 0.26 | 69 | 900 | 0.06 | 20 | 10.0 | 69 | 900 | 0.06 | 20 | 10.0 | 69 | 900 | 0.06 | 20 | 10.0 |
| 35 | 1,600 | 94 | 1,600 | 0.19 | 10.0 | 0.45 | 94 | 1,600 | 0.19 | 74 | 9.2 | 94 | 1,600 | 0.19 | 74 | 9.2 | 94 | 1,600 | 0.19 | 74 | 9.2 |
| 25 | 700 | 17 | 700 | 0.13 | 10.0 | 0.20 | 17 | 700 | 0.09 | 32 | 10.5 | 25 | 700 | 0.09 | 32 | 10.5 | 25 | 700 | 0.09 | 32 | 10.5 |
| 25 | 1,600 | 25 | 1,600 | 0.34 | 10.0 | 0.51 | 25 | 1,600 | 0.21 | 89 | 8.4 | 25 | 1,600 | 0.21 | 89 | 8.4 | 25 | 1,600 | 0.21 | 89 | 8.4 |
| 35 | 1,600 | 69 | 1,600 | 0.34 | 10.0 | 0.45 | 69 | 1,600 | 0.30 | 109 | 10.0 | 69 | 1,600 | 0.30 | 109 | 10.0 | 69 | 1,600 | 0.30 | 109 | 10.0 |
| 35 | 1,600 | 25 | 1,600 | 0.34 | 10.0 | 0.45 | 25 | 1,600 | 0.17 | 73 | 8.4 | 25 | 1,600 | 0.17 | 73 | 8.4 | 25 | 1,600 | 0.17 | 73 | 8.4 |
| 10 | 1,000 | 10 | 1,000 | 0.19 | 10.0 | 0.28 | 10 | 1,000 | 0.09 | 34 | 10.0 | 10 | 1,000 | 0.09 | 34 | 10.0 | 10 | 1,000 | 0.09 | 34 | 10.0 |
| 10 | 1,000 | 10 | 1,000 | 0.15 | 10.0 | 0.28 | 10 | 1,000 | 0.02 | 9 | 7.8 | 10 | 1,000 | 0.02 | 9 | 7.8 | 10 | 1,000 | 0.02 | 9 | 7.8 |
| 15 | 1,600 | 15 | 1,600 | 0.23 | 10.0 | 0.34 | 15 | 1,600 | 0.06 | 24 | 8.4 | 15 | 1,600 | 0.06 | 24 | 8.4 | 15 | 1,600 | 0.06 | 24 | 8.4 |
| 10 | 1,200 | 10 | 1,200 | 0.13 | 10.0 | 0.20 | 10 | 1,200 | 0.29 | 539 | 8.6 | 10 | 1,200 | 0.29 | 539 | 8.6 | 10 | 1,200 | 0.29 | 539 | 8.6 |
| 15 | 2,800 | 15 | 2,800 | 0.33 | 10.0 | 0.53 | 15 | 2,800 | 0.06 | 24 | 8.4 | 15 | 2,800 | 0.06 | 24 | 8.4 | 15 | 2,800 | 0.06 | 24 | 8.4 |
| 3 | 700 | 3 | 700 | 0.13 | 10.0 | 0.20 | 3 | 700 | 0.15 | 59 | 9.2 | 3 | 700 | 0.15 | 59 | 9.2 | 3 | 700 | 0.15 | 59 | 9.2 |
| 3 | 200 | 3 | 200 | 0.04 | 10.0 | 0.06 | 3 | 200 | 0.08 | 32 | 8.4 | 3 | 200 | 0.08 | 32 | 8.4 | 3 | 200 | 0.08 | 32 | 8.4 |
| 15 | 1,500 | 15 | 1,500 | 0.26 | 10.0 | 0.33 | 15 | 1,500 | 0.19 | 79 | 8.6 | 15 | 1,500 | 0.19 | 79 | 8.6 | 15 | 1,500 | 0.19 | 79 | 8.6 |
| 10 | 1,400 | 10 | 1,400 | 0.26 | 10.0 | 0.39 | 10 | 1,400 | 0.79 | 341 | 8.4 | 10 | 1,400 | 0.79 | 341 | 8.4 | 10 | 1,400 | 0.79 | 341 | 8.4 |
| 3 | 2,400 | 3 | 2,400 | 0.45 | 10.0 | 0.68 | 3 | 2,400 | 0.08 | 27 | 10.0 | 3 | 2,400 | 0.08 | 27 | 10.0 | 3 | 2,400 | 0.08 | 27 | 10.0 |
| 10 | 1,100 | 10 | 1,100 | 0.21 | 10.0 | 0.32 | 10 | 1,100 | 0.13 | 48 | 10.0 | 10 | 1,100 | 0.13 | 48 | 10.0 | 10 | 1,100 | 0.13 | 48 | 10.0 |
| 3 | 700 | 3 | 700 | 0.13 | 10.0 | 0.20 | 3 | 700 | 0.55 | 198 | 10.0 | 3 | 700 | 0.55 | 198 | 10.0 | 3 | 700 | 0.55 | 198 | 10.0 |
| 10 | 1,200 | 10 | 1,200 | 0.23 | 10.0 | 0.34 | 10 | 1,200 | 0.19 | 79 | 8.6 | 10 | 1,200 | 0.19 | 79 | 8.6 | 10 | 1,200 | 0.19 | 79 | 8.6 |
| 3 | 2,800 | 3 | 2,800 | 0.42 | 10.0 | 0.63 | 3 | 2,800 | 0.26 | 132 | 10.0 | 3 | 2,800 | 0.26 | 132 | 10.0 | 3 | 2,800 | 0.26 | 132 | 10.0 |
| 28 | 800 | 28 | 800 | 0.15 | 10.0 | 0.22 | 28 | 800 | 0.64 | 170 | 10.0 | 28 | 800 | 0.64 | 170 | 10.0 | 28 | 800 | 0.64 | 170 | 10.0 |
| 3 | 1,900 | 3 | 1,900 | 0.36 | 10.0 | 0.54 | 3 | 1,900 | 0.47 | 170 | 10.0 | 3 | 1,900 | 0.47 | 170 | 10.0 | 3 | 1,900 | 0.47 | 170 | 10.0 |
| 21 | 500 | 21 | 500 | 0.09 | 10.0 | 0.14 | 21 | 500 | 0.08 | 82 | 10.0 | 21 | 500 | 0.08 | 82 | 10.0 | 21 | 500 | 0.08 | 82 | 10.0 |
| 22 | 1,700 | 22 | 1,700 | 0.32 | 10.0 | 0.61 | 22 | 1,700 | 0.23 | 82 | 10.0 | 22 | 1,700 | 0.23 | 82 | 10.0 | 22 | 1,700 | 0.23 | 82 | 10.0 |
| 21 | 600 | 21 | 600 | 0.11 | 10.0 | 0.16 | 21 | 600 | 0.15 | 55 | 10.0 | 21 | 600 | 0.15 | 55 | 10.0 | 21 | 600 | 0.15 | 55 | 10.0 |
| 22 | 600 | 22 | 600 | 0.11 | 10.0 | 0.16 | 22 | 600 | 0.53 | 191 | 10.0 | 22 | 600 | 0.53 | 191 | 10.0 | 22 | 600 | 0.53 | 191 | 10.0 |
| 22 | 2,500 | 22 | 2,500 | 0.47 | 10.0 | 0.79 | 22 | 2,500 | 0.06 | 20 | 10.0 | 22 | 2,500 | 0.06 | 20 | 10.0 | 22 | 2,500 | 0.06 | 20 | 10.0 |
| 21 | 1,400 | 21 | 1,400 | 0.26 | 10.0 | 0.42 | 21 | 1,400 | 0.19 | 1274 | 9.2 | 21 | 1,400 | 0.19 | 1274 | 9.2 | 21 | 1,400 | 0.19 | 1274 | 9.2 |
| 3 | 600 | 3 | 600 | 0.11 | 10.0 | 0.16 | 3 | 600 | 0.60 | 218 | 10.0 | 3 | 600 | 0.60 | 218 | 10.0 | 3 | 600 | 0.60 | 218 | 10.0 |
| 21 | 2,300 | 21 | 2,300 | 0.43 | 10.0 | 0.64 | 21 | 2,300 | 0.21 | 82 | 9.2 | 21 | 2,300 | 0.21 | 82 | 9.2 | 21 | 2,300 | 0.21 | 82 | 9.2 |
| 21 | 2,300 | 21 | 2,300 | 0.32 | 10.0 | 0.40 | 21 | 2,300 | 0.40 | 143 | 10.0 | 21 | 2,300 | 0.40 | 143 | 10.0 | 21 | 2,300 | 0.40 | 143 | 10.0 |
| 10 | 1,600 | 10 | 1,600 | 0.30 | 10.0 | 0.45 | 10 | 1,600 | 0.09 | 34 | 10.0 | 10 | 1,600 | 0.09 | 34 | 10.0 | 10 | 1,600 | 0.09 | 34 | 10.0 |
| 3 | 500 | 3 | 500 | 0.09 | 10.0 | 0.14 | 3 | 500 | 0.26 | 95 | 10.0 | 3 | 500 | 0.26 | 95 | 10.0 | 3 | 500 | 0.26 | 95 | 10.0 |
| 10 | 500 | 10 | 500 | 0.09 | 10.0 | 0.14 | 10 | 500 | 0.15 | 55 | 10.0 | 10 | 500 | 0.15 | 55 | 10.0 | 10 | 500 | 0.15 | 55 | 10.0 |
| 3 | 1,500 | 3 | 1,500 | 0.28 | 10.0 | 0.42 | 3 | 1,500 | 0.26 | 132 | 10.0 | 3 | 1,500 | 0.26 | 132 | 10.0 | 3 | 1,500 | 0.26 | 132 | 10.0 |
| 3 | 1,500 | 3 | 1,500 | 0.25 | 10.0 | 0.38 | 3 | 1,500 | 0.15 | 55 | 10.0 | 3 | 1,500 | 0.15 | 55 | 10.0 | 3 | 1,500 | 0.15 | 55 | 10.0 |
| 15 | 1,300 | 15 | 1,300 | 0.13 | 10.0 | 0.21 | 15 | 1,300 | 0.11 | 41 | 10.0 | 15 | 1,300 | 0.11 | 41 | 10.0 | 15 | 1,300 | 0.11 | 41 | 10.0 |
| 15 | 4,500 | 15 | 4,500 | 0.85 | 10.0 | 1.54 | 15 | 4,500 | 0.11 | 41 | 10.0 | 15 | 4,500 | 0.11 | 41 | 10.0 | 15 | 4,500 | 0.11 | 41 | 10.0 |
| 3 | 500 | 3 | 500 | 0.09 | 10.0 | 0.14 | 3 | 500 | 0.47 | 185 | 9.2 | 3 | 500 | 0.47 | 185 | 9.2 | 3 | 500 | 0.47 | 185 | 9.2 |
| 10 | 400 | 10 | 400 | 0.08 | 10.0 | 0.12 | 10 | 400 | 0.26 | 1302 | 10.0 | 10 | 400 | 0.26 | 1302 | 10.0 | 10 | 400 | 0.26 | 1302 | 10.0 |
| 3 | 1,800 | 3 | 1,800 | 0.34 | 10.0 | 0.58 | 3 | 1,800 | 0.11 | 41 | 10.0 | 3 | 1,800 | 0.11 | 41 | 10.0 | 3 | 1,800 | 0.11 | 41 | 10.0 |
| 15 | 400 | 15 | 400 | 0.08 | 10.0 | 0.12 | 15 | 400 | 0.11 | 41 | 10.0 | 15 | 400 | 0.11 | 41 | 10.0 | 15 | 400 | 0.11 | 41 | 10.0 |
| 3 | 1,500 | 3 | 1,500 | 0.28 | 10.0 | 0.45 | 3 | 1,500 | 0.23 | 82 | 10.0 | 3 | 1,500 | 0.23 | 82 | 10.0 | 3 | 1,500 | 0.23 | 82 | 10.0 |
| 3 | 1,500 | 3 | 1,500 | 0.28 | 10.0 | 0.45 | 3 | 1,500 | 0.25 | 89 | 10.0 | 3 | 1,500 | 0.25 | 89 | 10.0 | 3 | 1,500 | 0.25 | 89 | 10.0 |
| 69 | 1,200 | 69 | 1,200 | 0.23 | 10.0 | 0.36 | 69 | 1,200 | 0.09 | 34 | 10.0 | 69 | 1,200 | 0.09 | 34 | 10.0 | 69 | 1,200 | 0.09 | 34 | 10.0 |
| 13 | 3,600 | 13 | 3,600 | 0.57 | 10.0 | 1.01 | 13 | 3,600 | 0.11 | 41 | 10.0 | 13 | 3,600 | 0.11 | 41 | 10.0 | 13 | 3,600 | 0.11 | 41 | 10.0 |
| 10 | 2,100 | 10 | 2,100 | 0.40 | 10.0 | 0.60 | 10 | 2,100 | 0.30 | 109 | 10.0 | 10 | 2,100 | 0.30 | 109 | 10.0 | 10 | 2,100 | 0.30 | 109 | 10.0 |
| 10 | 3,600 | 10 | 3,600 | 0.68 | 10.0 | 1.08 | 10 | 3,600 | 0.30 | 82 | 10.0 | 10 | 3,600 | 0.30 | 82 | 10.0 | 10 | 3,600 | 0.30 | 82 | 10.0 |
| 14 | 1,700 | 14 | 1,700 | 0.32 | 10.0 | 0.68 | 14 | 1,700 | 0.3 | 82 | 10.0 | 14 | 1,700 | 0.3 | 82 | 10.0 | 14 | 1,700 | 0.3 | 82 | 10.0 |
| 1 | 1,700 | 1 | 1,700 | 0.32 | 10.0 | 0.68 | 1 | 1,700 | 0.3 | 377 | 10.0 | 1 | 1,700 | 0.3 | 377 | 10.0 | 1 | 1,700 | 0.3 | 377 | 10.0 |
| 4 | 1,300 | 4 | 1,300 | 0.25 | 10.0 | 0.38 | 4 | 1,300 | 0.11 | 41 | 10.0 | 4 | 1,300 | 0.11 | 41 | 10.0 | 4 | 1,300 | 0.11 | 41 | 10.0 |

(Continued)

(21 of 32 sheets)

Table 4 (Continued)

| Vehi- cle | Tr- ain Type | Dry Season (60 or 40 RBT) | | | | | Wet Season (60 or 40 RBT) | | | | | Fuel mi- le | | |
|--------------|--------------------|---------------------------|---------------------|---------------------|--------------------|-------------------|---------------------------|-----------------------|---------------------|---------------------|--------------------|-------------------|-------------------|-----|
| | | Dis- tance feet | Pen- alty sec | Avg Speed mph | Fuel gal/ mi | Fuel mi- le | Tr- ain Type | Dis- tance feet | Pen- alty sec | Avg Speed mph | Fuel gal/ mi | | Fuel mi- le | |
| 4 | 1,400 | 0.26 | 95 | 10.0 | 0.39 | 1.5 | 3 | 1,900 | 0.36 | 130 | 10.0 | 0.54 | 1.5 | 1.5 |
| 4 | 1,500 | 0.28 | 102 | 10.0 | 0.42 | 1.5 | 10 | 400 | 0.08 | 27 | 10.0 | 0.12 | 1.5 | 1.5 |
| 4 | 2,400 | 0.45 | 116 | 10.0 | 0.68 | 1.5 | 15 | 300 | 0.06 | 26 | 7.8 | 0.10 | 1.7 | 1.7 |
| 3 | 1,700 | 0.32 | 82 | 10.0 | 0.48 | 1.5 | 10 | 100 | 0.02 | 7 | 10.0 | 0.03 | 1.5 | 1.5 |
| 3 | 1,200 | 0.23 | 7 | 10.0 | 0.34 | 1.5 | 3 | 2,200 | 0.42 | 1350 | 10.0 | 0.51 | 1.0 | 1.7 |
| 3 | 700 | 0.13 | 48 | 10.0 | 0.80 | 1.5 | 16 | 300 | 0.06 | 26 | 7.8 | 0.10 | 1.7 | 1.7 |
| 3 | 200 | 0.04 | 14 | 10.0 | 0.06 | 1.5 | | | | | | | | |
| 3 | 1,800 | 0.34 | 1,223 | 10.0 | 0.66 | 1.5 | 3 | 2,500 | 0.47 | 170 | 10.3 | 0.70 | 1.5 | 1.5 |
| 3 | 1,400 | 0.28 | 102 | 10.0 | 0.42 | 1.5 | 16 | 600 | 0.11 | 52 | 7.8 | 0.19 | 1.7 | 1.7 |
| 3 | 2,400 | 0.42 | 116 | 10.0 | 0.68 | 1.5 | 3 | 2,500 | 0.47 | 170 | 10.0 | 0.70 | 1.5 | 1.5 |
| 5 | 2,800 | 0.55 | 134 | 10.0 | 0.85 | 1.5 | 94 | 1,200 | 0.23 | 105 | 7.6 | 0.39 | 1.7 | 1.7 |
| 3 | 1,200 | 0.23 | 7 | 10.0 | 0.34 | 1.5 | 13 | 3,000 | 0.57 | 20,454 | 0.1 | 3.36 | 5.9 | 5.9 |
| 3 | 300 | 0.06 | 20 | 10.0 | 0.09 | 1.5 | 5 | 1,900 | 0.74 | 289 | 9.2 | 1.41 | 1.9 | 1.7 |
| 4 | 200 | 0.04 | 14 | 10.0 | 0.06 | 1.5 | 4 | 600 | 0.11 | 60 | 6.8 | 0.36 | 3.3 | 3.3 |
| 4 | 600 | 0.11 | 41 | 10.0 | 0.16 | 1.5 | 0 | 1,000 | 0.19 | 68 | 10.0 | 0.28 | 1.5 | 1.5 |
| 3 | 1,700 | 0.32 | 116 | 10.0 | 0.48 | 1.5 | 0 | 1,900 | 0.35 | 791 | 6.8 | 1.19 | 3.3 | 3.3 |
| 7 | 1,200 | 0.23 | 154 | 5.3 | 0.94 | 4.1 | 1 | 8,500 | 1.61 | 630 | 9.2 | 3.06 | 1.9 | 1.9 |
| 1 | 1,900 | 0.17 | 67 | 9.2 | 0.32 | 1.9 | 3 | 2,700 | 0.51 | 184 | 10.0 | 0.76 | 1.5 | 1.5 |
| | | | | | | | 1 | 3,600 | 0.68 | 1467 | 9.2 | 3.57 | 1.9 | 1.9 |
| | | | | | | | 3 | 2,100 | 0.21 | 75 | 10.0 | 0.32 | 1.5 | 1.5 |
| | | | | | | | 4 | 2,400 | 0.45 | 178 | 9.2 | 0.86 | 1.9 | 1.9 |
| | | | | | | | 5 | 2,600 | 0.38 | 131 | 10.4 | 0.49 | 1.3 | 1.3 |
| | | | | | | | 3 | 1,300 | 0.25 | 89 | 10.0 | 0.38 | 1.5 | 1.5 |
| | | | | | | | 4 | 1,800 | 0.13 | 48 | 9.2 | 0.11 | 1.9 | 1.9 |
| | | | | | | | 4 | 700 | 0.08 | 42 | 10.2 | 0.14 | 1.9 | 1.9 |
| | | | | | | | 3 | 1,500 | 0.23 | 102 | 10.0 | 0.42 | 1.5 | 1.5 |
| | | | | | | | 2 | 1,200 | 0.23 | 82 | 10.0 | 0.34 | 1.5 | 1.5 |
| | | | | | | | 1 | 2,900 | 0.55 | 215 | 9.2 | 1.04 | 1.9 | 1.9 |
| | | | | | | | 2 | 700 | 0.13 | 51 | 9.4 | 0.45 | 1.8 | 1.8 |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | |

022341

1.1

(Continued)

(22 of 32 sheets)

Table 4 (Continued)

| Vehi- cle | Test- run Type | Dry Season (60 or 40 Mph) | | | | | Wet Season (60 or 40 Mph) | | | | | Wet Season (60 or 35 Mph) | | | | | Fuel gal/ mile |
|--------------|----------------------|---------------------------|------------------|-------------|---------------------|----------------------|---------------------------|------------------|-------------|---------------------|----------------------|---------------------------|------------------|-------------|---------------------|----------------------|----------------------|
| | | Test- run Type | Distance feet | Time sec | Avg Speed mph | Fuel gal/ mile | Test- run Type | Distance feet | Time sec | Avg Speed mph | Fuel gal/ mile | Test- run Type | Distance feet | Time sec | Avg Speed mph | Fuel gal/ mile | |
| 3 | 1,300 | 23 | 1,300 | 0.25 | 39.0 | 0.05 | 23 | 1,300 | 0.25 | 39.0 | 0.05 | 6 | 600 | 0.11 | 37 | 10.7 | 1.3 |
| 2 | 1,400 | 77 | 1,400 | 0.26 | 39.0 | 0.01 | 77 | 1,400 | 0.26 | 39.0 | 0.01 | 10 | 800 | 0.15 | 50 | 10.7 | 0.8 |
| 3 | 200 | 4 | 200 | 0.04 | 39.0 | 0.01 | 4 | 200 | 0.04 | 39.0 | 0.01 | 6 | 1,000 | 0.19 | 64 | 10.7 | 0.8 |
| 10 | 6,800 | 2,834 | 6,800 | 1.29 | 10.7 | 5.03 | 2,834 | 6,800 | 1.29 | 10.7 | 5.03 | 15 | 800 | 0.15 | 52 | 10.3 | 0.8 |
| 49 | 1,100 | 44 | 1,100 | 0.21 | 17.3 | 0.19 | 44 | 1,100 | 0.21 | 17.3 | 0.19 | 6 | 1,200 | 0.23 | 77 | 10.7 | 1.3 |
| 6 | 700 | 44 | 700 | 0.13 | 10.7 | 0.17 | 44 | 700 | 0.13 | 10.7 | 0.17 | 15 | 600 | 0.11 | 39 | 10.3 | 0.8 |
| 28 | 1,400 | 184 | 1,400 | 0.26 | 39.0 | 0.05 | 184 | 1,400 | 0.26 | 39.0 | 0.05 | 2 | 1,000 | 0.19 | 17 | 39.0 | 0.04 |
| 6 | 2,300 | 145 | 2,300 | 0.13 | 10.7 | 0.17 | 145 | 2,300 | 0.13 | 10.7 | 0.17 | 83 | 1,200 | 0.28 | 12.1 | 0.31 | 1.1 |
| 6 | 800 | 44 | 800 | 0.13 | 10.7 | 0.17 | 44 | 800 | 0.13 | 10.7 | 0.17 | 12 | 2,000 | 0.04 | 12.2 | 0.05 | 1.1 |
| 32 | 1,000 | 17 | 1,000 | 0.19 | 19.4 | 5.0 | 17 | 1,000 | 0.19 | 19.4 | 5.0 | 240 | 2,791 | 10.3 | 4.90 | 0.8 | |
| 32 | 1,400 | 24 | 1,400 | 0.26 | 39.0 | 0.05 | 24 | 1,400 | 0.26 | 39.0 | 0.05 | 10 | 400 | 0.08 | 27 | 10.7 | 0.6 |
| 37 | 3,500 | 153 | 3,500 | 0.21 | 15.3 | 5.0 | 153 | 3,500 | 0.21 | 15.3 | 5.0 | 15 | 800 | 0.15 | 57 | 10.7 | 0.12 |
| 67 | 600 | 61 | 600 | 0.66 | 39.0 | 0.13 | 61 | 600 | 0.66 | 39.0 | 0.13 | 49 | 1,100 | 0.21 | 44 | 17.3 | 0.19 |
| 14 | 3,300 | 237 | 3,300 | 0.62 | 9.4 | 0.87 | 237 | 3,300 | 0.62 | 9.4 | 0.87 | 6 | 700 | 0.13 | 44 | 10.7 | 0.17 |
| 10 | 1,300 | 121 | 1,300 | 0.36 | 12.1 | 10.7 | 121 | 1,300 | 0.36 | 12.1 | 10.7 | 28 | 1,400 | 0.26 | 24 | 39.0 | 0.05 |
| 14 | 800 | 57 | 800 | 0.15 | 9.4 | 0.21 | 57 | 800 | 0.15 | 9.4 | 0.21 | 6 | 2,300 | 0.43 | 145 | 10.7 | 0.34 |
| 82 | 1,900 | 161 | 1,900 | 0.36 | 9.2 | 0.54 | 161 | 1,900 | 0.36 | 9.2 | 0.54 | 89 | 700 | 0.11 | 46 | 10.2 | 0.17 |
| 14 | 300 | 23 | 300 | 0.06 | 9.4 | 0.08 | 23 | 300 | 0.06 | 9.4 | 0.08 | 6 | 800 | 0.15 | 50 | 10.7 | 0.12 |
| 10 | 700 | 44 | 700 | 0.13 | 10.7 | 0.10 | 44 | 700 | 0.13 | 10.7 | 0.10 | 30 | 1,000 | 0.19 | 140 | 4.9 | 0.28 |
| 3 | 1,100 | 19 | 1,100 | 0.11 | 39.0 | 0.04 | 19 | 1,100 | 0.11 | 39.0 | 0.04 | 3 | 1,400 | 0.26 | 41 | 39.0 | 0.05 |
| 12 | 4,300 | 286 | 4,300 | 0.32 | 10.7 | 0.38 | 286 | 4,300 | 0.32 | 10.7 | 0.38 | 30 | 1,200 | 0.23 | 169 | 4.9 | 0.34 |
| 23 | 1,700 | 94 | 1,700 | 0.32 | 12.2 | 0.35 | 94 | 1,700 | 0.32 | 12.2 | 0.35 | 37 | 3,400 | 0.64 | 58 | 39.0 | 0.13 |
| 3 | 900 | 16 | 900 | 0.17 | 39.0 | 0.03 | 16 | 900 | 0.17 | 39.0 | 0.03 | 87 | 600 | 0.11 | 39 | 10.2 | 0.14 |
| 57 | 6,900 | 433 | 6,900 | 1.30 | 10.8 | 1.69 | 433 | 6,900 | 1.30 | 10.8 | 1.69 | 14 | 2,800 | 0.53 | 214 | 9.4 | 0.74 |
| 32 | 400 | 58 | 400 | 0.08 | 5.0 | 0.11 | 58 | 400 | 0.08 | 5.0 | 0.11 | 10 | 1,900 | 0.36 | 121 | 10.7 | 0.29 |
| 2 | 800 | 45 | 800 | 0.15 | 12.1 | 0.16 | 45 | 800 | 0.15 | 12.1 | 0.16 | 14 | 800 | 0.15 | 57 | 9.4 | 0.21 |
| 16 | 600 | 32 | 600 | 0.11 | 12.2 | 0.12 | 32 | 600 | 0.11 | 12.2 | 0.12 | 82 | 1,900 | 0.36 | 141 | 9.2 | 0.34 |
| 30 | 300 | 44 | 300 | 0.06 | 4.9 | 0.09 | 44 | 300 | 0.06 | 4.9 | 0.09 | 14 | 800 | 0.15 | 23 | 9.4 | 0.08 |
| 3 | 800 | 14 | 800 | 0.15 | 39.0 | 0.03 | 14 | 800 | 0.15 | 39.0 | 0.03 | 15 | 700 | 0.13 | 45 | 10.3 | 0.10 |
| 2 | 1,000 | 57 | 1,000 | 0.19 | 12.1 | 0.21 | 57 | 1,000 | 0.19 | 12.1 | 0.21 | 3 | 1,200 | 0.23 | 21 | 39.0 | 0.05 |
| 3 | 500 | 8 | 500 | 0.09 | 39.0 | 0.02 | 8 | 500 | 0.09 | 39.0 | 0.02 | 15 | 2,400 | 0.49 | 171 | 10.3 | 0.39 |
| 32 | 2,100 | 1,468 | 2,100 | 0.04 | 5.0 | 2.56 | 1,468 | 2,100 | 0.04 | 5.0 | 2.56 | 10 | 800 | 0.15 | 50 | 10.7 | 0.12 |
| 3 | 600 | 10 | 600 | 0.11 | 39.0 | 0.02 | 10 | 600 | 0.11 | 39.0 | 0.02 | 15 | 900 | 0.17 | 50 | 10.3 | 0.14 |
| 2 | 800 | 45 | 800 | 0.15 | 12.1 | 0.16 | 45 | 800 | 0.15 | 12.1 | 0.16 | 16 | 900 | 0.17 | 50 | 12.2 | 0.37 |
| 3 | 1,900 | 28 | 1,900 | 0.28 | 39.0 | 0.06 | 28 | 1,900 | 0.28 | 39.0 | 0.06 | 37 | 6,900 | 1.30 | 433 | 10.8 | 1.69 |
| 6 | 800 | 79 | 800 | 0.15 | 10.7 | 0.20 | 79 | 800 | 0.15 | 10.7 | 0.20 | 30 | 500 | 0.09 | 64 | 4.9 | 0.14 |
| 32 | 600 | 79 | 600 | 0.11 | 5.0 | 0.15 | 79 | 600 | 0.11 | 5.0 | 0.15 | 2 | 1,000 | 0.19 | 57 | 12.1 | 0.21 |
| 5 | 1,700 | 94 | 1,700 | 0.32 | 12.2 | 0.35 | 94 | 1,700 | 0.32 | 12.2 | 0.35 | 16 | 200 | 0.04 | 12 | 12.2 | 0.04 |
| 3 | 1,700 | 30 | 1,700 | 0.32 | 39.0 | 0.06 | 30 | 1,700 | 0.32 | 39.0 | 0.06 | 30 | 700 | 0.13 | 96 | 4.9 | 0.20 |
| 73 | 300 | 18 | 300 | 0.06 | 12.1 | 0.03 | 18 | 300 | 0.06 | 12.1 | 0.03 | 3 | 400 | 0.08 | 7 | 39.0 | 0.02 |
| 22 | 570 | 58 | 570 | 0.17 | 10.5 | 0.14 | 58 | 570 | 0.17 | 10.5 | 0.14 | 2 | 1,100 | 0.21 | 62 | 12.1 | 0.23 |
| 16 | 1,500 | 83 | 1,500 | 0.28 | 12.2 | 0.31 | 83 | 1,500 | 0.28 | 12.2 | 0.31 | 3 | 400 | 0.08 | 7 | 39.0 | 0.02 |
| 3 | 1,000 | 12 | 1,000 | 0.19 | 39.0 | 0.04 | 12 | 1,000 | 0.19 | 39.0 | 0.04 | 30 | 2,300 | 0.43 | 1,516 | 4.9 | 2.64 |
| 32 | 800 | 108 | 800 | 0.15 | 5.0 | 0.21 | 108 | 800 | 0.15 | 5.0 | 0.21 | 2 | 700 | 0.13 | 39 | 12.1 | 0.16 |
| 3 | 400 | 7 | 400 | 0.08 | 39.0 | 0.02 | 7 | 400 | 0.08 | 39.0 | 0.02 | 3 | 1,200 | 0.23 | 21 | 39.0 | 0.05 |
| 10 | 1,600 | 101 | 1,600 | 0.30 | 10.7 | 0.24 | 101 | 1,600 | 0.30 | 10.7 | 0.24 | 6 | 1,000 | 0.19 | 64 | 10.7 | 0.15 |
| 15 | 700 | 45 | 700 | 0.13 | 10.3 | 0.10 | 45 | 700 | 0.13 | 10.3 | 0.10 | 30 | 600 | 0.11 | 81 | 4.9 | 0.16 |
| 10 | 2,800 | 178 | 2,800 | 0.53 | 10.7 | 0.42 | 178 | 2,800 | 0.53 | 10.7 | 0.42 | 5 | 1,200 | 0.23 | 68 | 12.2 | 0.25 |
| 15 | 3,700 | 245 | 3,700 | 0.70 | 10.3 | 0.56 | 245 | 3,700 | 0.70 | 10.3 | 0.56 | | | | | | |
| 10 | 1,100 | 71 | 1,100 | 0.21 | 10.7 | 0.17 | 71 | 1,100 | 0.21 | 10.7 | 0.17 | | | | | | |
| 57 | 1,100 | 70 | 1,100 | 0.21 | 10.8 | 0.27 | 70 | 1,100 | 0.21 | 10.8 | 0.27 | | | | | | |
| 10 | 300 | 20 | 300 | 0.06 | 10.7 | 0.05 | 20 | 300 | 0.06 | 10.7 | 0.05 | | | | | | |
| 3 | 2,700 | 47 | 2,700 | 0.51 | 39.0 | 0.10 | 47 | 2,700 | 0.51 | 39.0 | 0.10 | | | | | | |

(Continued)

(23 of 32 sheets)

Table 4 (Continued)

| Vehi- cle | Dry Season (60 or 40 RT) | | | | | | Wet Season (60 or 40 RT) | | | | | | Wet Season (60 or 35 RT) | | | | | | | |
|--------------|--------------------------|------------------|-------------|---------------------|---------------------|----------------------|--------------------------|------------------|-------------|---------------------|---------------------|----------------------|--------------------------|------------------|-------------|---------------------|---------------------|----------------------|------|-----|
| | Ter- rain Type | Distance feet | Time sec | Pen- alty sec | Avg Speed mph | Fuel gal/ mile | Ter- rain Type | Distance feet | Time sec | Pen- alty sec | Avg Speed mph | Fuel gal/ mile | Ter- rain Type | Distance feet | Time sec | Pen- alty sec | Avg Speed mph | Fuel gal/ mile | | |
| 10 | 81 | 400 | 0.08 | | 27 | 10.7 | 0.06 | 1.3 | | | | | 3 | 1,300 | 0.25 | | 23 | 39.0 | 0.05 | 0.2 |
| 61 | 81 | 1,300 | 0.25 | | 84 | 10.7 | 0.32 | 0.8 | | | | | 13 | 800 | 0.15 | | 415 | 1.3 | 1.38 | 9.2 |
| 69 | 69 | 1,500 | 0.28 | | 94 | 10.7 | 0.22 | 0.8 | | | | | 30 | 3,300 | 0.62 | | 57 | 39.0 | 0.12 | 0.2 |
| 17 | 17 | 1,900 | 0.36 | | 33 | 39.0 | 0.07 | 0.2 | | | | | 30 | 1,200 | 0.23 | | 169 | 4.9 | 0.34 | 1.5 |
| 69 | 69 | 1,400 | 0.26 | | 87 | 10.7 | 0.09 | 0.8 | | | | | 3 | 200 | 0.04 | | 4 | 39.0 | 0.01 | 0.2 |
| 70 | 70 | 900 | 0.17 | | 51 | 12.1 | 0.19 | 1.1 | | | | | 15 | 2,300 | 0.43 | | 150 | 10.3 | 0.34 | 0.8 |
| 69 | 69 | 300 | 0.06 | | 20 | 10.7 | 0.05 | 0.8 | | | | | 15 | 500 | 0.08 | | 30 | 10.7 | 0.07 | 0.8 |
| 10 | 10 | 800 | 0.15 | | 50 | 10.7 | 0.12 | 0.8 | | | | | 15 | 1,700 | 0.32 | | 112 | 10.3 | 0.26 | 0.8 |
| 6 | 6 | 1,000 | 0.19 | | 64 | 10.7 | 0.25 | 1.3 | | | | | 10 | 600 | 0.11 | | 37 | 10.7 | 0.09 | 0.8 |
| 62 | 62 | 6,100 | 1.15 | | 239 | 17.3 | 1.04 | 0.9 | | | | | 15 | 3,700 | 0.70 | | 245 | 10.3 | 0.56 | 0.8 |
| 6 | 6 | 300 | 0.06 | | 20 | 10.7 | 0.08 | 1.3 | | | | | 10 | 2,900 | 0.55 | | 185 | 10.7 | 0.44 | 0.8 |
| 10 | 10 | 800 | 0.15 | | 50 | 10.7 | 0.12 | 0.8 | | | | | 3 | 2,200 | 0.42 | | 39 | 39.0 | 0.08 | 0.2 |
| 63 | 63 | 300 | 0.06 | | 20 | 10.7 | 0.08 | 1.3 | | | | | 15 | 800 | 0.15 | | 52 | 10.3 | 0.12 | 0.8 |
| 62 | 62 | 1,800 | 0.34 | | 71 | 17.3 | 0.31 | 0.9 | | | | | 81 | 800 | 0.15 | | 50 | 10.7 | 0.20 | 1.3 |
| 63 | 63 | 3,500 | 0.74 | | 249 | 10.7 | 0.96 | 1.3 | | | | | 69 | 400 | 0.08 | | 27 | 10.7 | 0.06 | 0.8 |
| 31 | 31 | 4,300 | 0.81 | | 75 | 39.0 | 0.16 | 0.2 | | | | | 94 | 900 | 0.17 | | 50 | 12.2 | 0.19 | 1.1 |
| 55 | 55 | 1,000 | 0.19 | | 64 | 10.7 | 0.15 | 0.8 | | | | | 17 | 500 | 0.09 | | 8 | 39.0 | 0.02 | 0.2 |
| 31 | 31 | 4,100 | 0.77 | | 71 | 39.0 | 0.15 | 0.2 | | | | | 25 | 3,700 | 0.70 | | 236 | 10.7 | 0.91 | 1.3 |
| 10 | 10 | 1,800 | 0.34 | | 114 | 10.7 | 0.27 | 0.8 | | | | | 15 | 1,300 | 0.25 | | 87 | 10.3 | 0.20 | 0.8 |
| 3 | 3 | 1,800 | 0.34 | | 31 | 39.0 | 0.07 | 0.2 | | | | | 6 | 800 | 0.15 | | 50 | 10.7 | 0.12 | 0.8 |
| 16 | 16 | 400 | 0.08 | | 24 | 12.2 | 0.09 | 1.1 | | | | | 62 | 5,600 | 1.06 | | 221 | 17.3 | 0.95 | 0.9 |
| 15 | 15 | 1,500 | 0.28 | | 94 | 10.3 | 0.22 | 0.8 | | | | | 15 | 1,000 | 0.19 | | 66 | 10.3 | 0.15 | 0.8 |
| 10 | 10 | 1,900 | 0.36 | | 121 | 10.7 | 0.29 | 0.8 | | | | | 63 | 500 | 0.09 | | 30 | 10.7 | 0.12 | 1.3 |
| 15 | 15 | 2,800 | 0.55 | | 182 | 10.3 | 0.44 | 0.8 | | | | | 62 | 800 | 0.15 | | 50 | 10.7 | 0.14 | 0.9 |
| 3 | 3 | 800 | 0.15 | | 31 | 39.0 | 0.03 | 0.2 | | | | | 62 | 800 | 0.15 | | 50 | 10.7 | 0.20 | 1.3 |
| 15 | 15 | 1,700 | 0.32 | | 112 | 10.3 | 0.26 | 0.8 | | | | | 63 | 800 | 0.15 | | 50 | 10.7 | 0.20 | 1.3 |
| 10 | 10 | 800 | 0.15 | | 50 | 10.7 | 0.12 | 0.8 | | | | | 62 | 900 | 0.17 | | 35 | 17.3 | 0.15 | 0.9 |
| 3 | 3 | 4,500 | 0.85 | | 71 | 39.0 | 0.17 | 0.2 | | | | | 63 | 4,400 | 0.83 | | 279 | 10.7 | 1.08 | 1.3 |
| 10 | 10 | 1,200 | 0.23 | | 77 | 10.7 | 0.18 | 0.8 | | | | | 80 | 700 | 0.13 | | 38 | 12.2 | 0.14 | 1.1 |
| 3 | 3 | 2,300 | 0.42 | | 39 | 39.0 | 0.08 | 0.2 | | | | | 31 | 1,400 | 0.26 | | 24 | 39.0 | 0.05 | 0.2 |
| 26 | 26 | 800 | 0.15 | | 14 | 39.0 | 0.03 | 0.2 | | | | | 80 | 400 | 0.08 | | 24 | 12.2 | 0.09 | 1.1 |
| 3 | 3 | 1,900 | 0.36 | | 33 | 39.0 | 0.07 | 0.2 | | | | | 31 | 200 | 0.04 | | 4 | 39.0 | 0.01 | 0.2 |
| 21 | 21 | 500 | 0.09 | | 30 | 10.7 | 0.07 | 0.8 | | | | | 80 | 600 | 0.11 | | 32 | 12.2 | 0.12 | 1.1 |
| 22 | 22 | 1,700 | 0.32 | | 112 | 10.3 | 0.26 | 0.8 | | | | | 31 | 3,400 | 0.64 | | 59 | 39.0 | 0.13 | 0.2 |
| 21 | 21 | 600 | 0.11 | | 37 | 10.7 | 0.09 | 0.8 | | | | | 10 | 1,400 | 0.26 | | 87 | 10.7 | 0.21 | 0.8 |
| 22 | 22 | 600 | 0.11 | | 36 | 10.3 | 0.09 | 0.8 | | | | | 15 | 600 | 0.11 | | 38 | 10.3 | 0.12 | 0.8 |
| 22 | 22 | 700 | 0.13 | | 44 | 10.7 | 0.10 | 0.8 | | | | | 31 | 100 | 0.02 | | 8 | 9.0 | 0.01 | 0.2 |
| 22 | 22 | 2,300 | 0.43 | | 190 | 10.3 | 0.34 | 0.8 | | | | | 10 | 1,000 | 0.19 | | 64 | 10.7 | 0.15 | 0.8 |
| 3 | 3 | 2,100 | 0.40 | | 94 | 39.0 | 0.08 | 0.2 | | | | | 3 | 1,400 | 0.26 | | 24 | 39.0 | 0.05 | 0.2 |
| 21 | 21 | 800 | 0.15 | | 50 | 10.7 | 0.12 | 0.8 | | | | | 16 | 400 | 0.08 | | 24 | 12.2 | 0.09 | 1.1 |
| | | | | | | | | | | | | | 15 | 1,700 | 0.32 | | 112 | 10.3 | 0.26 | 0.8 |
| | | | | | | | | | | | | | 10 | 1,900 | 0.36 | | 121 | 10.7 | 0.29 | 0.8 |
| | | | | | | | | | | | | | 15 | 5,500 | 1.04 | | 363 | 10.3 | 0.83 | 0.8 |
| | | | | | | | | | | | | | 15 | 2,300 | 0.43 | | 40 | 39.0 | 0.09 | 0.2 |
| | | | | | | | | | | | | | 10 | 500 | 0.09 | | 30 | 10.7 | 0.07 | 0.8 |
| | | | | | | | | | | | | | 3 | 2,300 | 0.43 | | 40 | 39.0 | 0.09 | 0.2 |
| | | | | | | | | | | | | | 15 | 500 | 0.09 | | 31 | 10.3 | 0.07 | 0.8 |
| | | | | | | | | | | | | | 15 | 400 | 0.08 | | 27 | 10.7 | 0.06 | 0.8 |
| | | | | | | | | | | | | | 15 | 400 | 0.08 | | 28 | 10.3 | 0.08 | 0.8 |
| | | | | | | | | | | | | | 3 | 2,200 | 0.42 | | 39 | 39.0 | 0.08 | 0.2 |
| | | | | | | | | | | | | | 28 | 900 | 0.17 | | 16 | 39.0 | 0.03 | 0.2 |

(Continued)

(24 of 32 sheets)

Table 4 (Continued)

| Vehi- cle | Ter- rain Type | Dry Season (60 or 40 R/L) | | | | | Wet Season (60 or 40 R/L) | | | | | Wet Season (60 or 40 R/L) | | | | | Ter- rain Type | Fuel gal/ mile | Fuel gal/ mile | | |
|--------------|----------------------|---------------------------|-------------------|-------------|---------------------|----------------------|---------------------------|-------------------|-------------|---------------------|----------------------|---------------------------|-------------------|-------------|---------------------|----------------------|----------------------|----------------------|----------------------|--|--|
| | | Distance feet | Distance miles | Time sec | Avg Speed mph | Fuel gal/ mile | Distance feet | Distance miles | Time sec | Avg Speed mph | Fuel gal/ mile | Distance feet | Distance miles | Time sec | Avg Speed mph | Fuel gal/ mile | | | | | |
| 3 | 3 | 3,700 | 0.70 | 1,265 | 39.0 | 2.14 | 0.2 | | | | | 1,900 | 0.36 | 33 | 39.0 | 0.07 | 0.2 | | | | |
| 4 | 4 | 2,000 | 0.38 | 201 | 6.8 | 0.46 | 1.2 | | | | | 15 | 100 | 0.06 | 21 | 10.3 | 0.05 | 0.8 | | | |
| 3 | 3 | 1,400 | 0.26 | 24 | 39.0 | 0.05 | 0.2 | | | | | 22 | 1,700 | 0.22 | 112 | 10.3 | 0.26 | 0.8 | | | |
| 4 | 4 | 2,200 | 0.42 | 222 | 6.8 | 3.50 | 1.2 | | | | | 21 | 800 | 0.15 | 50 | 10.7 | 0.12 | 0.8 | | | |
| 5 | 5 | 200 | 0.04 | 12 | 12.2 | 0.04 | 1.1 | | | | | 22 | 600 | 0.11 | 38 | 10.3 | 0.09 | 0.8 | | | |
| 3 | 3 | 6,100 | 1.15 | 106 | 39.0 | 0.23 | 0.2 | | | | | 21 | 600 | 0.11 | 37 | 10.7 | 0.09 | 0.8 | | | |
| 4 | 4 | 2,900 | 0.55 | 291 | 6.8 | 0.66 | 1.2 | | | | | 22 | 2,400 | 0.45 | 157 | 10.3 | 0.36 | 0.8 | | | |
| 3 | 3 | 500 | 0.09 | 8 | 39.0 | 0.02 | 0.2 | | | | | 3 | 2,100 | 0.40 | 1200 | 1,237 | 39.0 | 2.08 | 0.2 | | |
| 2 | 2 | 1,000 | 0.19 | 57 | 12.1 | 0.21 | 1.1 | | | | | 21 | 800 | 0.15 | 50 | 10.7 | 0.12 | 0.8 | | | |
| | | | | | | | | | | | | 3 | 5,600 | 1.06 | 98 | 39.0 | 0.21 | 0.2 | | | |
| | | | | | | | | | | | | 10 | 1,000 | 0.19 | 64 | 10.7 | 0.15 | 0.8 | | | |
| | | | | | | | | | | | | 3 | 200 | 0.04 | 4 | 39.0 | 0.01 | 0.2 | | | |
| | | | | | | | | | | | | 10 | 600 | 0.11 | 37 | 10.7 | 0.09 | 0.8 | | | |
| | | | | | | | | | | | | 3 | 1,000 | 0.19 | 17 | 39.0 | 0.04 | 0.2 | | | |
| | | | | | | | | | | | | 10 | 1,400 | 0.26 | 87 | 10.7 | 0.21 | 0.8 | | | |
| | | | | | | | | | | | | 15 | 5,000 | 0.94 | 329 | 10.3 | 0.75 | 0.8 | | | |
| | | | | | | | | | | | | 3 | 500 | 0.09 | 8 | 39.0 | 0.02 | 0.2 | | | |
| | | | | | | | | | | | | 10 | 400 | 0.08 | 27 | 10.7 | 0.06 | 0.8 | | | |
| | | | | | | | | | | | | 3 | 2,300 | 0.43 | 40 | 39.0 | 0.09 | 0.2 | | | |
| | | | | | | | | | | | | 10 | 500 | 0.09 | 30 | 10.7 | 0.07 | 0.8 | | | |
| | | | | | | | | | | | | 3 | 300 | 0.06 | 6 | 39.0 | 0.01 | 0.2 | | | |
| | | | | | | | | | | | | 15 | 200 | 0.04 | 14 | 10.3 | 0.03 | 0.8 | | | |
| | | | | | | | | | | | | 3 | 7,600 | 1.44 | 17 | 150 | 39.0 | 0.03 | 0.2 | | |
| | | | | | | | | | | | | 15 | 500 | 0.09 | 31 | 10.3 | 0.07 | 0.8 | | | |
| | | | | | | | | | | | | 16 | 300 | 0.06 | 18 | 12.2 | 0.07 | 1.1 | | | |
| | | | | | | | | | | | | 15 | 1,200 | 0.23 | 80 | 10.3 | 0.18 | 0.8 | | | |
| | | | | | | | | | | | | 13 | 3,200 | 0.60 | 1,642 | 1.3 | 5.52 | 9.2 | | | |
| | | | | | | | | | | | | 15 | 3,900 | 0.74 | 259 | 10.3 | 0.59 | 0.8 | | | |
| | | | | | | | | | | | | 14 | 900 | 0.17 | 85 | 9.4 | 0.24 | 1.4 | | | |
| | | | | | | | | | | | | 4 | 400 | 0.09 | 42 | 6.8 | 0.15 | 1.2 | | | |
| | | | | | | | | | | | | 14 | 10,300 | 1.95 | 747 | 9.4 | 3.32 | 1.4 | | | |
| | | | | | | | | | | | | 3 | 2,900 | 0.55 | 51 | 39.0 | 0.11 | 0.2 | | | |
| | | | | | | | | | | | | 1 | 600 | 0.11 | 59 | 6.7 | 0.13 | 1.2 | | | |
| | | | | | | | | | | | | 4 | 500 | 0.09 | 48 | 6.8 | 0.11 | 1.2 | | | |
| | | | | | | | | | | | | 1 | 1,400 | 0.26 | 1200 | 1,3-0 | 6.7 | 2.31 | 1.2 | | |
| | | | | | | | | | | | | 3 | 1,400 | 0.26 | 24 | 39.0 | 0.05 | 0.2 | | | |
| | | | | | | | | | | | | 1 | 2,500 | 0.47 | 253 | 6.7 | 0.06 | 1.2 | | | |
| | | | | | | | | | | | | 5 | 400 | 0.08 | 24 | 12.2 | 0.09 | 1.1 | | | |
| | | | | | | | | | | | | 3 | 6,800 | 1.29 | 119 | 39.0 | 0.26 | 0.2 | | | |
| | | | | | | | | | | | | 7A | 1,800 | 0.34 | 612 | 2.0 | 1.94 | 2.8 | | | |
| | | | | | | | | | | | | 3 | 900 | 0.17 | 16 | 39.0 | 0.03 | 0.2 | | | |
| | | | | | | | | | | | | 2 | 900 | 0.17 | 51 | 12.1 | 0.19 | 1.1 | | | |
| Total | | 245,200 | 46.26 | 18,655 | | 48.39 | | | | | | 240,700 | 45.42 | | 22,298 | | | 55.60 | | | |

(Continued)

(24 of 32 sheets)

Table 4 (Continued)

| Vehi- cle | Ter- rain Type | Dry Season (60 or 40 RCI) | | | | | | Wet Season (60 or 40 RCI) | | | | | | Wet Season (60 or 35 RCI) | | | | | | Fuel gal/ mile |
|--------------|----------------------|---------------------------|-----------------------|-------------|---------------------|----------------------|----------------------|---------------------------|-----------------------|-------------|---------------------|----------------------|------------------|---------------------------|-------------|---------------------|----------------------|-------|------|----------------------|
| | | Distance feet | Pen- alty miles | Time sec | Avg Speed mph | Fuel gal/ mile | Ter- rain Type | Distance feet | Pen- alty miles | Time sec | Avg Speed mph | Fuel gal/ mile | Distance feet | Pen- alty miles | Time sec | Avg Speed mph | Fuel gal/ mile | | | |
| M116 | 2 | 1,700 | 0.32 | 101 | 11.4 | 0.38 | 1.2 | 2 | 1,600 | 0.30 | 95 | 11.4 | 0.36 | 2 | 1,600 | 0.30 | 95 | 11.4 | 0.36 | 1.2 |
| | 3 | 1,600 | 0.30 | 34 | 32.1 | 0.12 | 0.4 | 3 | 1,700 | 0.32 | 36 | 32.1 | 0.13 | 3 | 1,700 | 0.32 | 36 | 32.1 | 0.13 | 0.4 |
| | 6 | 2,800 | 0.53 | 129 | 14.8 | 0.48 | 0.9 | 6 | 2,700 | 0.51 | 124 | 14.8 | 0.47 | 6 | 2,700 | 0.51 | 124 | 14.8 | 0.47 | 0.9 |
| | 10 | 1,100 | 0.21 | 68 | 11.1 | 0.27 | 1.3 | 15 | 900 | 0.17 | 56 | 10.9 | 0.22 | 15 | 900 | 0.17 | 56 | 10.9 | 0.22 | 1.3 |
| | 3 | 1,300 | 0.25 | 28 | 32.1 | 0.10 | 0.4 | 10 | 800 | 0.15 | 49 | 11.1 | 0.20 | 10 | 800 | 0.15 | 49 | 11.1 | 0.20 | 1.3 |
| | 10 | 1,500 | 0.28 | 61 | 11.1 | 0.36 | 1.3 | 3 | 1,200 | 0.23 | 26 | 32.1 | 0.09 | 3 | 1,200 | 0.23 | 26 | 32.1 | 0.09 | 1.4 |
| | 6 | 1,000 | 0.19 | 146 | 14.8 | 0.17 | 0.9 | 16 | 900 | 0.17 | 19 | 11.1 | 0.08 | 16 | 900 | 0.17 | 19 | 11.1 | 0.08 | 1.3 |
| | 10 | 1,300 | 0.25 | 201 | 11.1 | 0.27 | 1.3 | 15 | 1,300 | 0.25 | 61 | 14.8 | 0.22 | 15 | 1,300 | 0.25 | 61 | 14.8 | 0.22 | 0.9 |
| | 6 | 2,000 | 0.38 | 92 | 14.8 | 0.34 | 0.9 | 15 | 900 | 0.17 | 56 | 10.9 | 0.22 | 15 | 900 | 0.17 | 56 | 10.9 | 0.22 | 1.3 |
| | 10 | 1,200 | 0.23 | 92 | 11.1 | 0.30 | 1.3 | 3 | 1,200 | 0.23 | 26 | 32.1 | 0.09 | 3 | 1,200 | 0.23 | 26 | 32.1 | 0.09 | 0.5 |
| | 6 | 600 | 0.11 | 27 | 14.8 | 0.10 | 0.9 | 15 | 1,400 | 0.27 | 89 | 10.9 | 0.35 | 15 | 1,400 | 0.27 | 89 | 10.9 | 0.35 | 1.3 |
| | 10 | 700 | 0.13 | 42 | 11.1 | 0.17 | 1.3 | 15 | 1,900 | 0.36 | 88 | 14.8 | 0.32 | 15 | 1,900 | 0.36 | 88 | 14.8 | 0.32 | 0.9 |
| | 6 | 2,000 | 0.38 | 92 | 14.8 | 0.34 | 0.9 | 15 | 600 | 0.11 | 36 | 10.9 | 0.14 | 15 | 600 | 0.11 | 36 | 10.9 | 0.14 | 1.3 |
| | 10 | 900 | 0.17 | 55 | 11.1 | 0.22 | 1.3 | 15 | 1,500 | 0.15 | 67 | 10.9 | 0.20 | 15 | 1,500 | 0.15 | 67 | 10.9 | 0.20 | 1.3 |
| | 6 | 4,100 | 0.77 | 187 | 14.8 | 0.69 | 0.9 | 6 | 2,800 | 0.53 | 129 | 14.8 | 0.48 | 6 | 2,800 | 0.53 | 129 | 14.8 | 0.48 | 0.9 |
| | 10 | 1,700 | 0.32 | 104 | 11.1 | 0.42 | 1.3 | 10 | 300 | 0.06 | 19 | 11.1 | 0.08 | 10 | 300 | 0.06 | 19 | 11.1 | 0.08 | 1.3 |
| 3 | 3,800 | 0.72 | 81 | 32.1 | 0.29 | 0.4 | 15 | 1,700 | 0.32 | 78 | 14.8 | 0.29 | 15 | 1,700 | 0.32 | 78 | 14.8 | 0.29 | 0.9 | |
| 10 | 1,000 | 0.19 | 1200 | 11.1 | 2.35 | 1.3 | 15 | 1,100 | 0.21 | 69 | 10.9 | 0.27 | 15 | 1,100 | 0.21 | 69 | 10.9 | 0.27 | 1.3 | |
| 3 | 1,100 | 0.21 | 34 | 32.1 | 0.08 | 0.4 | 10 | 1,200 | 0.23 | 72 | 11.1 | 0.30 | 10 | 1,200 | 0.23 | 72 | 11.1 | 0.30 | 1.3 | |
| 32 | 1,500 | 0.28 | 194 | 5.2 | 0.67 | 2.4 | 6 | 1,400 | 0.27 | 66 | 14.8 | 0.24 | 6 | 1,400 | 0.27 | 66 | 14.8 | 0.24 | 0.9 | |
| 3 | 1,000 | 0.19 | 21 | 32.1 | 0.08 | 0.4 | 15 | 1,600 | 0.30 | 99 | 10.9 | 0.39 | 15 | 1,600 | 0.30 | 99 | 10.9 | 0.39 | 1.3 | |
| 47 | 800 | 0.11 | 76 | 5.2 | 0.26 | 2.4 | 6 | 1,100 | 0.21 | 51 | 14.8 | 0.19 | 6 | 1,100 | 0.21 | 51 | 14.8 | 0.19 | 0.9 | |
| 3 | 2,100 | 0.40 | 45 | 32.1 | 0.16 | 0.4 | 3 | 2,700 | 0.51 | 1200 | 12.57 | 32.1 | 2.30 | 3 | 2,700 | 0.51 | 1200 | 12.57 | 0.4 | |
| 36 | 2,500 | 0.55 | 178 | 11.1 | 0.72 | 1.3 | 15 | 1,000 | 0.19 | 63 | 10.9 | 0.25 | 15 | 1,000 | 0.19 | 63 | 10.9 | 0.25 | 1.3 | |
| 10 | 300 | 0.06 | 19 | 11.1 | 0.08 | 1.3 | 12 | 1,400 | 0.27 | 17 | 204 | 5.2 | 0.65 | 12 | 1,400 | 0.27 | 17 | 204 | 5.2 | 2.4 |
| 6 | 2,400 | 0.45 | 139 | 14.8 | 0.40 | 0.9 | 30 | 2,100 | 0.40 | 17 | 204 | 5.2 | 0.65 | 30 | 2,100 | 0.40 | 17 | 204 | 5.2 | 2.4 |
| 89 | 600 | 0.11 | 42 | 9.4 | 0.16 | 1.5 | 32 | 2,600 | 0.11 | 76 | 5.2 | 0.26 | 32 | 2,600 | 0.11 | 76 | 5.2 | 0.26 | 2.4 | |
| 6 | 800 | 0.15 | 53 | 14.8 | 0.14 | 0.9 | 30 | 800 | 0.15 | 104 | 5.2 | 0.36 | 30 | 800 | 0.15 | 104 | 5.2 | 0.36 | 2.4 | |
| 32 | 900 | 0.17 | 118 | 5.2 | 0.41 | 2.4 | 48 | 900 | 0.17 | 71 | 8.6 | 0.27 | 48 | 900 | 0.17 | 71 | 8.6 | 0.27 | 1.6 | |
| 3 | 1,600 | 0.30 | 34 | 32.1 | 0.12 | 0.4 | 3 | 1,300 | 0.25 | 28 | 32.1 | 0.10 | 3 | 1,300 | 0.25 | 28 | 32.1 | 0.10 | 0.4 | |
| 32 | 1,100 | 0.21 | 145 | 5.2 | 0.30 | 2.4 | 15 | 600 | 0.11 | 36 | 10.9 | 0.14 | 15 | 600 | 0.11 | 36 | 10.9 | 0.14 | 1.3 | |
| 37 | 3,500 | 0.66 | 74 | 32.1 | 0.26 | 0.4 | 10 | 300 | 0.06 | 19 | 11.1 | 0.08 | 10 | 300 | 0.06 | 19 | 11.1 | 0.08 | 1.3 | |
| 87 | 2,600 | 0.11 | 42 | 9.4 | 0.16 | 1.5 | 49 | 800 | 0.15 | 36 | 15.0 | 0.14 | 49 | 800 | 0.15 | 36 | 15.0 | 0.14 | 0.9 | |
| 14 | 2,800 | 0.53 | 222 | 8.6 | 0.85 | 1.6 | 6 | 800 | 0.15 | 36 | 14.8 | 0.14 | 6 | 800 | 0.15 | 36 | 14.8 | 0.14 | 0.9 | |
| 10 | 1,800 | 0.34 | 110 | 11.1 | 0.44 | 1.3 | 28 | 1,400 | 0.27 | 30 | 32.1 | 0.11 | 28 | 1,400 | 0.27 | 30 | 32.1 | 0.11 | 0.1 | |
| 14 | 900 | 0.17 | 71 | 8.6 | 0.27 | 1.6 | 6 | 2,300 | 0.44 | 107 | 14.8 | 0.40 | 6 | 2,300 | 0.44 | 107 | 14.8 | 0.40 | 0.9 | |
| 82 | 1,900 | 0.36 | 151 | 8.6 | 0.58 | 1.6 | 89 | 700 | 0.13 | 50 | 9.4 | 0.20 | 89 | 700 | 0.13 | 50 | 9.4 | 0.20 | 1.5 | |
| 14 | 200 | 0.04 | 17 | 8.6 | 0.06 | 1.6 | 6 | 700 | 0.13 | 32 | 14.8 | 0.12 | 6 | 700 | 0.13 | 32 | 14.8 | 0.12 | 0.9 | |
| 10 | 800 | 0.15 | 49 | 11.1 | 0.20 | 1.3 | 30 | 1,000 | 0.19 | 132 | 5.2 | 0.46 | 30 | 1,000 | 0.19 | 132 | 5.2 | 0.46 | 2.4 | |
| 3 | 1,300 | 0.25 | 28 | 32.1 | 0.10 | 0.4 | 3 | 1,400 | 0.27 | 17 | 32.1 | 0.11 | 3 | 1,400 | 0.27 | 17 | 32.1 | 0.11 | 0.4 | |
| 10 | 4,100 | 0.77 | 250 | 11.1 | 1.00 | 1.3 | 30 | 1,200 | 0.23 | 159 | 5.2 | 0.55 | 30 | 1,200 | 0.23 | 159 | 5.2 | 0.55 | 2.4 | |
| 23 | 1,800 | 0.34 | 41 | 32.1 | 0.17 | 0.5 | 37 | 3,500 | 0.66 | 74 | 32.1 | 0.46 | 37 | 3,500 | 0.66 | 74 | 32.1 | 0.46 | 0.4 | |
| 3 | 1,000 | 0.19 | 21 | 32.1 | 0.08 | 0.4 | 37 | 3,500 | 0.66 | 74 | 32.1 | 0.46 | 37 | 3,500 | 0.66 | 74 | 32.1 | 0.46 | 1.5 | |
| 57 | 6,900 | 1.30 | 867 | 5.4 | 2.99 | 2.3 | 10 | 2,800 | 0.53 | 222 | 8.6 | 0.85 | 10 | 2,800 | 0.53 | 222 | 8.6 | 0.85 | 1.6 | |
| 32 | 400 | 0.08 | 55 | 5.2 | 0.19 | 2.4 | 10 | 1,800 | 0.44 | 110 | 11.1 | 0.44 | 10 | 1,800 | 0.44 | 110 | 11.1 | 0.44 | 1.3 | |
| 2 | 800 | 0.15 | 47 | 11.4 | 0.18 | 1.2 | 14 | 1,000 | 0.19 | 80 | 8.6 | 0.30 | 14 | 1,000 | 0.19 | 80 | 8.6 | 0.30 | 1.6 | |
| 16 | 600 | 0.11 | 23 | 17.2 | 0.09 | 0.8 | 82 | 1,900 | 0.36 | 151 | 8.6 | 0.58 | 82 | 1,900 | 0.36 | 151 | 8.6 | 0.58 | 1.6 | |
| 30 | 200 | 0.04 | 28 | 5.2 | 0.10 | 2.4 | 14 | 200 | 0.04 | 17 | 8.6 | 0.06 | 14 | 200 | 0.04 | 17 | 8.6 | 0.06 | 1.6 | |
| 3 | 700 | 0.13 | 15 | 32.1 | 0.05 | 0.4 | 15 | 800 | 0.15 | 50 | 10.9 | 0.20 | 15 | 800 | 0.15 | 50 | 10.9 | 0.20 | 1.3 | |
| 2 | 1,000 | 0.19 | 60 | 11.4 | 0.23 | 1.2 | 3 | 1,200 | 0.23 | 26 | 32.1 | 0.09 | 3 | 1,200 | 0.23 | 26 | 32.1 | 0.09 | 0.4 | |
| 3 | 500 | 0.09 | 10 | 32.1 | 0.04 | 0.4 | 15 | 2,700 | 0.51 | 168 | 10.9 | 0.66 | 15 | 2,700 | 0.51 | 168 | 10.9 | 0.66 | 1.3 | |
| 32 | 1,800 | 0.34 | 1200 | 1.435 | 5.2 | 2.92 | 10 | 600 | 0.11 | 36 | 11.1 | 0.14 | 10 | 600 | 0.11 | 36 | 11.1 | 0.14 | 1.3 | |
| 2 | 600 | 0.11 | 12 | 32.1 | 0.04 | 0.4 | 15 | 800 | 0.15 | 50 | 10.9 | 0.20 | 15 | 800 | 0.15 | 50 | 10.9 | 0.20 | 1.3 | |
| 2 | 700 | 0.13 | 41 | 11.4 | 0.16 | 1.2 | 23 | 1,900 | 0.36 | 144 | 79.4 | 2.18 | 23 | 1,900 | 0.36 | 144 | 79.4 | 2.18 | 0.5 | |
| 3 | 1,400 | 0.26 | 29 | 32.1 | 0.10 | 0.4 | 16 | 800 | 0.15 | 34 | 15.1 | 0.14 | 16 | 800 | 0.15 | 34 | 15.1 | 0.14 | 0.9 | |

(Continued)

(26 of 32 sheets)

Table 4 (Continued)

| Vehi- cle | Re- tain Type | Dry Season (60 or 40 NCI) | | | | | Wet Season (60 or 40 NCI) | | | | | Wet Season (60 or 35 NCI) | | | | |
|--------------|---------------------|---------------------------|-------------|---------------------|---------------------|----------------------|---------------------------|------------------|-------------|---------------------|---------------------|---------------------------|---------------------|------------------|-------------|---------------------|
| | | Distance feet | Time sec | Pen- alty sec | Avg Speed mph | Fuel gal/ mile | Re- tain Type | Distance feet | Time sec | Pen- alty sec | Avg Speed mph | Fuel gal/ mile | Re- tain Type | Distance feet | Time sec | Pen- alty sec |
| 6 | 6 | 700 | 0.13 | 32 | 14.8 | 0.12 | 0.9 | 57 | 6,700 | 1.27 | 947 | 5.4 | 2.32 | 2.3 | | |
| 32 | 32 | 600 | 0.11 | 76 | 5.2 | 0.26 | 2.4 | 30 | 500 | 0.11 | 76 | 5.2 | 0.26 | 2.4 | | |
| 5 | 5 | 1,700 | 0.32 | 40 | 29.0 | 0.16 | 0.5 | 2 | 900 | 0.17 | 51 | 11.4 | 0.20 | 1.2 | | |
| 73 | 31 | 1,700 | 0.32 | 36 | 32.1 | 0.13 | 0.4 | 16 | 500 | 0.09 | 20 | 15.8 | 0.08 | 0.9 | | |
| 73 | 31 | 400 | 0.08 | 22 | 13.0 | 0.09 | 1.1 | 30 | 500 | 0.09 | 62 | 5.2 | 0.22 | 2.4 | | |
| 22 | 22 | 900 | 0.27 | 56 | 11.0 | 0.22 | 1.3 | 3 | 400 | 0.08 | 9 | 32.1 | 0.03 | 0.4 | | |
| 16 | 16 | 1,100 | 0.21 | 44 | 17.2 | 0.17 | 0.8 | 2 | 1,100 | 0.21 | 26 | 11.4 | 0.25 | 1.2 | | |
| 3 | 3 | 800 | 0.15 | 17 | 32.1 | 0.06 | 0.4 | 3 | 400 | 0.08 | 9 | 32.1 | 0.03 | 0.4 | | |
| 32 | 32 | 1,200 | 0.23 | 159 | 5.2 | 0.55 | 2.4 | 30 | 2,000 | 0.38 | 1,463 | 5.2 | 3.01 | 2.4 | | |
| 3 | 3 | 300 | 0.06 | 7 | 32.1 | 0.02 | 0.4 | 3 | 300 | 0.06 | 7 | 32.1 | 0.02 | 0.4 | | |
| 10 | 10 | 1,500 | 0.28 | 91 | 11.1 | 0.36 | 1.3 | 2 | 700 | 0.13 | 41 | 11.4 | 0.16 | 1.2 | | |
| 3 | 3 | 300 | 0.06 | 7 | 32.1 | 0.02 | 0.4 | 3 | 1,400 | 0.27 | 30 | 32.1 | 0.11 | 0.4 | | |
| 15 | 15 | 500 | 0.09 | 29 | 11.0 | 0.12 | 1.2 | 6 | 800 | 0.15 | 30 | 14.8 | 0.14 | 0.9 | | |
| 10 | 10 | 2,700 | 0.51 | 165 | 11.1 | 0.66 | 1.3 | 30 | 600 | 0.11 | 76 | 5.2 | 0.26 | 2.4 | | |
| 15 | 15 | 3,700 | 0.70 | 229 | 11.0 | 0.91 | 1.3 | 5 | 2,400 | 0.45 | 56 | 23.0 | 0.22 | 0.5 | | |
| 10 | 10 | 2,700 | 0.51 | 165 | 11.1 | 0.66 | 1.3 | 3 | 300 | 0.06 | 7 | 32.1 | 0.02 | 0.4 | | |
| 3 | 3 | 2,300 | 0.43 | 48 | 32.1 | 0.17 | 0.4 | 73A | 300 | 0.04 | 11 | 12.7 | 0.04 | 1.1 | | |
| 10 | 10 | 600 | 0.11 | 36 | 11.1 | 0.4 | 1.3 | 3 | 3,700 | 0.70 | 78 | 32.1 | 0.28 | 0.4 | | |
| 81 | 81 | 1,100 | 0.21 | 51 | 14.8 | 0.19 | 0.9 | 30 | 800 | 0.15 | 104 | 5.2 | 0.36 | 2.4 | | |
| 69 | 69 | 1,900 | 0.28 | 91 | 11.1 | 0.36 | 1.3 | 3 | 500 | 0.09 | 10 | 32.1 | 0.04 | 0.4 | | |
| 17 | 17 | 300 | 0.06 | 7 | 32.1 | 0.02 | 0.4 | 15 | 1,400 | 0.27 | 89 | 10.9 | 0.35 | 1.3 | | |
| 25 | 25 | 3,000 | 0.57 | 199 | 14.8 | 0.51 | 0.9 | 3 | 300 | 0.06 | 7 | 32.1 | 0.02 | 0.4 | | |
| 10 | 10 | 2,400 | 0.45 | 146 | 11.1 | 0.58 | 1.3 | 15 | 300 | 0.06 | 20 | 15.9 | 0.08 | 1.2 | | |
| 6 | 6 | 600 | 0.11 | 27 | 14.8 | 0.10 | 0.9 | 10 | 700 | 0.13 | 42 | 11.3 | 0.17 | 1.3 | | |
| 62 | 62 | 6,300 | 1.19 | 286 | 15.0 | 1.07 | 0.9 | 15 | 1,400 | 0.27 | 89 | 10.9 | 0.35 | 1.3 | | |
| 10 | 10 | 900 | 0.17 | 55 | 11.1 | 0.22 | 1.3 | 10 | 500 | 0.09 | 29 | 11.1 | 0.12 | 1.3 | | |
| 63 | 63 | 400 | 0.08 | 19 | 14.8 | 0.07 | 0.9 | 15 | 3,700 | 0.70 | 231 | 10.9 | 0.91 | 1.3 | | |
| 62 | 62 | 900 | 0.17 | 41 | 15.0 | 0.15 | 0.9 | 10 | 1,300 | 0.25 | 81 | 11.1 | 0.32 | 1.3 | | |
| 63 | 63 | 900 | 0.17 | 41 | 14.8 | 0.15 | 0.9 | 57 | 600 | 0.11 | 73 | 5.4 | 0.25 | 2.3 | | |
| 62 | 62 | 1,200 | 0.23 | 55 | 15.0 | 0.21 | 0.9 | 10 | 1,400 | 0.27 | 88 | 11.1 | 0.35 | 1.3 | | |
| 63 | 63 | 4,300 | 0.81 | 197 | 14.8 | 0.73 | 0.5 | 3 | 1,900 | 0.36 | 40 | 32.1 | 0.14 | 0.4 | | |
| 31 | 31 | 6,200 | 1.17 | 131 | 32.1 | 0.47 | 0.4 | 15 | 1,400 | 0.08 | 26 | 10.9 | 0.10 | 1.3 | | |
| 10 | 10 | 200 | 0.04 | 13 | 11.1 | 0.05 | 1.3 | 81 | 1,300 | 0.25 | 61 | 14.8 | 0.22 | 0.5 | | |
| 31 | 31 | 500 | 0.09 | 10 | 32.1 | 0.04 | 0.4 | 69 | 300 | 0.06 | 19 | 11.1 | 0.08 | 1.3 | | |
| 10 | 10 | 1,900 | 0.36 | 117 | 11.1 | 0.47 | 1.3 | 94 | 1,000 | 0.19 | 43 | 15.8 | 0.17 | 0.9 | | |
| 31 | 31 | 2,300 | 0.45 | 48 | 32.1 | 0.17 | 0.4 | 17 | 300 | 0.06 | 7 | 32.1 | 0.02 | 0.4 | | |
| 10 | 10 | 800 | 0.15 | 49 | 11.1 | 0.20 | 1.3 | 25 | 3,700 | 0.70 | 170 | 14.8 | 0.63 | 0.9 | | |
| 15 | 15 | 2,800 | 0.53 | 173 | 11.0 | 0.69 | 1.3 | 15 | 900 | 0.17 | 56 | 10.9 | 0.22 | 1.3 | | |
| 10 | 10 | 1,400 | 0.26 | 84 | 11.1 | 0.34 | 1.3 | 57 | 2,000 | 0.36 | 99 | 14.8 | 0.34 | 0.9 | | |
| 15 | 15 | 5,400 | 1.02 | 334 | 11.0 | 1.33 | 1.3 | 52 | 4,300 | 0.91 | 218 | 15.0 | 0.82 | 0.9 | | |
| 3 | 3 | 5,000 | 0.84 | 105 | 32.1 | 0.38 | 0.4 | 15 | 700 | 0.13 | 43 | 10.9 | 0.17 | 1.3 | | |
| 10 | 10 | 1,200 | 0.23 | 77 | 11.1 | 0.30 | 1.3 | 63 | 500 | 0.09 | 22 | 14.8 | 0.08 | 0.9 | | |
| 3 | 3 | 4,900 | 0.53 | 106 | 32.1 | 0.37 | 0.4 | 62 | 900 | 0.17 | 41 | 15.0 | 0.15 | 0.9 | | |
| 21 | 21 | 600 | 0.11 | 26 | 11.1 | 0.14 | 1.3 | 63 | 1,400 | 0.15 | 44 | 14.8 | 0.17 | 0.9 | | |
| 22 | 22 | 2,900 | 0.55 | 180 | 11.0 | 0.72 | 1.3 | 62 | 1,200 | 0.23 | 55 | 15.0 | 0.21 | 0.9 | | |
| 21 | 21 | 600 | 0.11 | 36 | 11.1 | 0.14 | 1.3 | 63 | 4,200 | 0.80 | 195 | 14.8 | 0.72 | 0.9 | | |
| 22 | 22 | 3,300 | 0.43 | 141 | 11.0 | 0.56 | 1.3 | 31 | 700 | 0.13 | 15 | 32.1 | 0.05 | 0.4 | | |
| 3 | 3 | 2,100 | 0.40 | 62 | 32.1 | 0.16 | 0.4 | 63 | 1,200 | 0.23 | 77 | 14.8 | 0.21 | 0.9 | | |
| 21 | 21 | 800 | 0.15 | 49 | 11.1 | 0.20 | 1.3 | 31 | 900 | 0.17 | 77 | 32.1 | 0.07 | 0.4 | | |
| 3 | 3 | 5,900 | 1.12 | 126 | 32.1 | 0.45 | 0.4 | 80 | 400 | 0.08 | 15 | 15.8 | 0.07 | 0.9 | | |
| 10 | 10 | 1,000 | 0.19 | 62 | 11.1 | 0.25 | 1.3 | 31 | 2,800 | 0.53 | 59 | 32.1 | 0.21 | 0.4 | | |
| 3 | 3 | 100 | 0.02 | 2 | 32.1 | 0.01 | 0.4 | 80 | 200 | 0.04 | 9 | 15.8 | 0.04 | 0.9 | | |
| 10 | 10 | 800 | 0.15 | 49 | 11.1 | 0.20 | 1.3 | 31 | 600 | 0.11 | 12 | 32.1 | 0.04 | 0.4 | | |
| 3 | 3 | 900 | 0.17 | 19 | 32.1 | 0.07 | 0.4 | 10 | 1,500 | 0.28 | 91 | 11.1 | 0.34 | 1.3 | | |
| 10 | 10 | 1,300 | 0.25 | 81 | 11.1 | 0.32 | 1.3 | 15 | 500 | 0.09 | 30 | 10.9 | 0.12 | 1.3 | | |

(Continued)

(27 of 32 sheets)

Table 4 (Continued)

| Vehi- cle | Ter- min Type | Dry Season (60 or 10 RCT) | | | | | Wet Season (60 or 10 RCT) | | | | | Wet Season (60 or 10 RCT) | | | | | Wet Season (60 or 10 RCT) | | | | | |
|--------------|---------------------|---------------------------|-------------|-------------|--------------|----------------------|---------------------------|-------------|-------------|--------------|----------------------|---------------------------|-------------|-------------|--------------|----------------------|---------------------------|-------------|-------------|--------------|----------------------|-----|
| | | Distance feet | Time min | Rate sec | Speed mph | Fuel gal/ mile | Distance feet | Time min | Rate sec | Speed mph | Fuel gal/ mile | Distance feet | Time min | Rate sec | Speed mph | Fuel gal/ mile | Distance feet | Time min | Rate sec | Speed mph | Fuel gal/ mile | |
| 15 | 5,000 | 0.04 | 308 | 11.0 | 1.22 | 1.3 | 10 | 1,300 | 0.25 | 21 | 11.1 | 0.32 | 1.3 | 10 | 1,300 | 0.25 | 21 | 11.1 | 0.32 | 1.3 | 1.3 | |
| 3 | 600 | 0.11 | 12 | 34.1 | 0.04 | 0.4 | 3 | 1,400 | 0.27 | 13 | 15.8 | 0.37 | 1.3 | 3 | 1,400 | 0.27 | 13 | 15.8 | 0.37 | 1.3 | 0.5 | |
| 10 | 300 | 0.06 | 19 | 11.1 | 0.17 | 0.4 | 15 | 1,600 | 0.30 | 59 | 10.9 | 0.39 | 1.3 | 15 | 1,600 | 0.30 | 59 | 10.9 | 0.39 | 1.3 | 1.3 | |
| 3 | 2,300 | 0.13 | 48 | 32.1 | 0.17 | 0.4 | 10 | 1,700 | 0.32 | 104 | 11.1 | 0.42 | 1.3 | 10 | 1,700 | 0.32 | 104 | 11.1 | 0.42 | 1.3 | 1.3 | |
| 10 | 900 | 0.09 | 29 | 11.1 | 0.12 | 0.3 | 15 | 5,600 | 1.06 | 350 | 10.9 | 1.38 | 1.3 | 15 | 5,600 | 1.06 | 350 | 10.9 | 1.38 | 1.3 | 1.3 | |
| 3 | 4,500 | 0.28 | 31 | 32.1 | 0.11 | 0.4 | 3 | 2,300 | 0.44 | 49 | 32.1 | 0.13 | 0.4 | 3 | 2,300 | 0.44 | 49 | 32.1 | 0.13 | 0.4 | 1.3 | |
| 69 | 1,800 | 0.26 | 51 | 11.1 | 0.36 | 1.3 | 10 | 600 | 0.11 | 36 | 11.1 | 0.11 | 1.3 | 10 | 600 | 0.11 | 36 | 11.1 | 0.11 | 1.3 | 1.3 | |
| 13 | 4,900 | 0.55 | 19,800 | 0.1 | 6.71 | 12.2 | 3 | 2,100 | 0.40 | 45 | 32.1 | 0.16 | 0.4 | 3 | 2,100 | 0.40 | 45 | 32.1 | 0.16 | 0.4 | 0.4 | |
| 10 | 400 | 0.08 | 26 | 11.1 | 0.10 | 1.3 | 15 | 500 | 0.09 | 30 | 10.9 | 0.12 | 1.3 | 15 | 500 | 0.09 | 30 | 10.9 | 0.12 | 1.3 | 1.3 | |
| 3 | 800 | 0.15 | 17 | 32.1 | 0.46 | 0.4 | 10 | 400 | 0.08 | 26 | 11.1 | 0.10 | 1.3 | 10 | 400 | 0.08 | 26 | 11.1 | 0.10 | 1.3 | 1.3 | |
| 10 | 1,900 | 0.36 | 117 | 11.1 | 0.61 | 1.7 | 15 | 400 | 0.08 | 26 | 11.1 | 0.10 | 1.3 | 15 | 400 | 0.08 | 26 | 11.1 | 0.10 | 1.3 | 1.3 | |
| 4 | 1,900 | 0.36 | 117 | 11.1 | 0.61 | 1.7 | 22 | 2,100 | 0.40 | 45 | 32.1 | 0.16 | 0.4 | 22 | 2,100 | 0.40 | 45 | 32.1 | 0.16 | 0.4 | 0.4 | |
| 14 | 5,600 | 1.31 | 158 | 7.0 | 2.96 | 1.6 | 28 | 900 | 0.17 | 19 | 32.1 | 0.07 | 0.4 | 28 | 900 | 0.17 | 19 | 32.1 | 0.07 | 0.4 | 0.4 | |
| 3 | 3,700 | 0.70 | 1200 | 1.273 | 32.1 | 2.38 | 0.4 | 3 | 1,900 | 0.36 | 40 | 32.1 | 0.14 | 0.4 | 3 | 1,900 | 0.36 | 40 | 32.1 | 0.14 | 0.4 | 0.4 |
| 4 | 2,000 | 0.39 | 195 | 7.0 | 0.65 | 1.7 | 15 | 500 | 0.08 | 26 | 10.9 | 0.10 | 1.3 | 15 | 500 | 0.08 | 26 | 10.9 | 0.10 | 1.3 | 1.3 | |
| 3 | 1,400 | 0.26 | 29 | 32.1 | 0.10 | 0.4 | 22 | 1,600 | 0.30 | 95 | 10.9 | 0.39 | 1.3 | 22 | 1,600 | 0.30 | 95 | 10.9 | 0.39 | 1.3 | 1.3 | |
| 4 | 2,300 | 0.43 | 221 | 7.0 | 0.73 | 1.7 | 21 | 800 | 0.15 | 49 | 11.1 | 0.20 | 1.3 | 21 | 800 | 0.15 | 49 | 11.1 | 0.20 | 1.3 | 1.3 | |
| 5 | 100 | 0.02 | 2 | 29.0 | 0.01 | 0.5 | 22 | 600 | 0.11 | 36 | 10.9 | 0.14 | 1.3 | 22 | 600 | 0.11 | 36 | 10.9 | 0.14 | 1.3 | 1.3 | |
| 3 | 2,200 | 1.17 | 131 | 32.1 | 0.47 | 0.4 | 21 | 600 | 0.11 | 36 | 11.1 | 0.14 | 1.3 | 21 | 600 | 0.11 | 36 | 11.1 | 0.14 | 1.3 | 1.3 | |
| 4 | 3,100 | 0.59 | 303 | 7.0 | 1.00 | 1.7 | 10 | 1,000 | 0.19 | 21 | 32.1 | 0.08 | 0.4 | 10 | 1,000 | 0.19 | 21 | 32.1 | 0.08 | 0.4 | 0.4 | |
| 2 | 1,200 | 0.23 | 73 | 11.4 | 0.28 | 1.2 | 10 | 1,400 | 0.27 | 88 | 11.1 | 0.35 | 1.3 | 10 | 1,400 | 0.27 | 88 | 11.1 | 0.35 | 1.3 | 1.3 | |
| | | | | | | | 15 | 5,000 | 0.95 | 314 | 10.9 | 1.24 | 1.3 | 15 | 5,000 | 0.95 | 314 | 10.9 | 1.24 | 1.3 | 1.3 | |
| | | | | | | | 10 | 500 | 0.09 | 10 | 32.1 | 0.12 | 1.3 | 10 | 500 | 0.09 | 10 | 32.1 | 0.12 | 1.3 | 1.3 | |
| | | | | | | | 15 | 300 | 0.06 | 15 | 11.1 | 0.08 | 1.3 | 15 | 300 | 0.06 | 15 | 11.1 | 0.08 | 1.3 | 1.3 | |
| | | | | | | | 3 | 2,300 | 0.44 | 49 | 32.1 | 0.13 | 0.4 | 3 | 2,300 | 0.44 | 49 | 32.1 | 0.13 | 0.4 | 0.4 | |
| | | | | | | | 10 | 500 | 0.09 | 29 | 11.1 | 0.12 | 1.3 | 10 | 500 | 0.09 | 29 | 11.1 | 0.12 | 1.3 | 1.3 | |
| | | | | | | | 3 | 8,300 | 1.57 | 193 | 32.1 | 0.63 | 0.4 | 3 | 8,300 | 1.57 | 193 | 32.1 | 0.63 | 0.4 | 0.4 | |
| | | | | | | | 15 | 600 | 0.11 | 36 | 10.9 | 0.14 | 1.3 | 15 | 600 | 0.11 | 36 | 10.9 | 0.14 | 1.3 | 1.3 | |
| | | | | | | | 16 | 200 | 0.04 | 9 | 15.8 | 0.04 | 0.9 | 16 | 200 | 0.04 | 9 | 15.8 | 0.04 | 0.9 | 0.9 | |
| | | | | | | | 5 | 1,200 | 0.23 | 76 | 10.9 | 0.30 | 1.3 | 5 | 1,200 | 0.23 | 76 | 10.9 | 0.30 | 1.3 | 1.3 | |
| | | | | | | | 13 | 3,200 | 0.61 | 21,960 | 0.1 | 7.44 | 12.2 | 13 | 3,200 | 0.61 | 21,960 | 0.1 | 7.44 | 12.2 | 12.2 | |
| | | | | | | | 15 | 4,000 | 0.76 | 251 | 10.9 | 0.99 | 1.3 | 15 | 4,000 | 0.76 | 251 | 10.9 | 0.99 | 1.3 | 1.3 | |
| | | | | | | | 4 | 900 | 0.17 | 17 | 8.6 | 0.27 | 1.6 | 4 | 900 | 0.17 | 17 | 8.6 | 0.27 | 1.6 | 1.6 | |
| | | | | | | | 4 | 400 | 0.08 | 41 | 7.0 | 0.14 | 1.7 | 4 | 400 | 0.08 | 41 | 7.0 | 0.14 | 1.7 | 1.7 | |
| | | | | | | | 14 | 7,500 | 1.42 | 594 | 6.6 | 2.27 | 1.6 | 14 | 7,500 | 1.42 | 594 | 6.6 | 2.27 | 1.6 | 1.6 | |
| | | | | | | | 4 | 700 | 0.13 | 67 | 7.0 | 0.22 | 1.7 | 4 | 700 | 0.13 | 67 | 7.0 | 0.22 | 1.7 | 1.7 | |
| | | | | | | | 14 | 2,100 | 0.40 | 167 | 8.6 | 0.54 | 1.6 | 14 | 2,100 | 0.40 | 167 | 8.6 | 0.54 | 1.6 | 1.6 | |
| | | | | | | | 3 | 2,800 | 0.53 | 59 | 32.1 | 0.21 | 0.4 | 3 | 2,800 | 0.53 | 59 | 32.1 | 0.21 | 0.4 | 0.4 | |
| | | | | | | | 16 | 500 | 0.11 | 25 | 15.8 | 0.10 | 0.9 | 16 | 500 | 0.11 | 25 | 15.8 | 0.10 | 0.9 | 0.9 | |
| | | | | | | | 4 | 300 | 0.06 | 31 | 7.0 | 0.10 | 1.7 | 4 | 300 | 0.06 | 31 | 7.0 | 0.10 | 1.7 | 1.7 | |
| | | | | | | | 3 | 300 | 0.06 | 7 | 32.1 | 0.02 | 0.4 | 3 | 300 | 0.06 | 7 | 32.1 | 0.02 | 0.4 | 0.4 | |
| | | | | | | | 1 | 1,300 | 0.25 | 129 | 7.0 | 0.42 | 1.7 | 1 | 1,300 | 0.25 | 129 | 7.0 | 0.42 | 1.7 | 1.7 | |
| | | | | | | | 3 | 1,300 | 0.25 | 28 | 32.1 | 0.10 | 0.4 | 3 | 1,300 | 0.25 | 28 | 32.1 | 0.10 | 0.4 | 0.4 | |
| | | | | | | | 1 | 2,600 | 0.49 | 269 | 7.0 | 0.83 | 1.7 | 1 | 2,600 | 0.49 | 269 | 7.0 | 0.83 | 1.7 | 1.7 | |
| | | | | | | | 5 | 100 | 0.02 | 2 | 29.0 | 0.01 | 0.5 | 5 | 100 | 0.02 | 2 | 29.0 | 0.01 | 0.5 | 0.5 | |
| | | | | | | | 3 | 7,100 | 1.34 | 150 | 32.1 | 0.51 | 0.4 | 3 | 7,100 | 1.34 | 150 | 32.1 | 0.51 | 0.4 | 0.4 | |

(Continued)

(28 of 32 sheets)

(Continued)

| Vehi- cle | dry Season (60 or 40 MCI) | | | | | Wet Season (60 or 40 MCI) | | | | | Wet Season (60 or 35 MCI) | | | | | Fuel gal mile |
|--------------|---------------------------|-----------------------|-------------|---------------------|----------------------|---------------------------|-----------------------|-------------|---------------------|----------------------|---------------------------|-----------------------|-------------|---------------------|----------------------|---------------------|
| | Ter- rain TYPE | Dis- tance feet | Time sec | Avg Speed mph | Fuel gal/ mile | Ter- rain TYPE | Dis- tance feet | Time sec | Avg Speed mph | Fuel gal/ mile | Ter- rain TYPE | Dis- tance feet | Time sec | Avg Speed mph | Fuel gal/ mile | |
| Total | | 242,600 | 45.79 | 35,909 | 99.23 | | | | | | | 241,900 | 45.87 | 36,890 | 62.19 | |
| M71 | 2 | 1,700 | 0.32 | 56 | 12.0 | 0.16 | 0.5 | | | | 2 | 1,600 | 0.30 | 90 | 12.0 | 0.15 |
| | 3 | 1,400 | 0.26 | 34 | 27.4 | 0.45 | 0.2 | | | | 3 | 1,500 | 0.28 | 37 | 27.4 | 0.46 |
| | 10 | 4,300 | 0.81 | 295 | 9.9 | 0.19 | 0.6 | | | | 15 | 4,000 | 0.76 | 232 | 9.7 | 0.40 |
| | 12 | 1,700 | 0.32 | 64 | 27.4 | 0.06 | 0.6 | | | | 10 | 300 | 0.11 | 22 | 27.4 | 0.04 |
| | 3 | 1,200 | 0.23 | 64 | 9.9 | 0.14 | 0.6 | | | | 3 | 1,700 | 0.32 | 42 | 27.4 | 0.06 |
| | 3 | 900 | 0.09 | 12 | 27.4 | 0.02 | 0.2 | | | | 10 | 1,100 | 0.21 | 76 | 9.9 | 0.13 |
| | 10 | 800 | 0.15 | 12 | 27.4 | 0.09 | 0.6 | | | | 3 | 600 | 0.11 | 14 | 27.4 | 0.02 |
| | 3 | 1,700 | 0.32 | 12 | 27.4 | 0.06 | 0.2 | | | | 15 | 600 | 0.11 | 41 | 9.7 | 0.07 |
| | 10 | 2,000 | 0.38 | 138 | 9.9 | 0.23 | 0.6 | | | | 3 | 1,600 | 0.30 | 39 | 27.4 | 0.06 |
| | 3 | 1,500 | 0.28 | 37 | 27.4 | 0.06 | 0.2 | | | | 15 | 1,400 | 0.26 | 56 | 9.7 | 0.16 |
| | 10 | 3,000 | 0.57 | 224 | 9.9 | 0.34 | 1.1 | | | | 6 | 1,400 | 0.26 | 167 | 5.6 | 0.29 |
| | 6 | 800 | 0.15 | 96 | 5.6 | 0.17 | 1.1 | | | | 15 | 1,700 | 0.32 | 136 | 9.7 | 0.19 |
| | 10 | 5,300 | 1.00 | 364 | 9.9 | 0.60 | 0.6 | | | | 6 | 500 | 0.09 | 58 | 5.6 | 0.10 |
| | 6 | 200 | 0.04 | 26 | 5.6 | 0.04 | 1.1 | | | | 15 | 800 | 0.15 | 56 | 9.7 | 0.09 |
| | 10 | 3,600 | 0.68 | 247 | 9.9 | 0.41 | 0.6 | | | | 6 | 2,900 | 0.47 | 302 | 5.6 | 0.32 |
| | 3 | 2,600 | 0.49 | 64 | 27.4 | 0.10 | 0.2 | | | | 15 | 1,200 | 0.23 | 85 | 9.7 | 0.14 |
| | 10 | 2,000 | 0.38 | 1,338 | 9.9 | 1.33 | 0.6 | | | | 10 | 1,800 | 0.26 | 131 | 9.7 | 0.22 |
| | 3 | 1,000 | 0.19 | 17 | 42 | 0.16 | 0.2 | | | | 6 | 800 | 0.15 | 96 | 5.6 | 0.16 |
| | 10 | 2,800 | 0.15 | 17 | 167 | 4.1 | 0.28 | 1.5 | | | 15 | 1,300 | 0.25 | 51 | 9.7 | 0.15 |
| | 47 | 1,000 | 0.19 | 167 | 4.1 | 0.28 | 1.5 | | | | 6 | 1,200 | 0.23 | 148 | 5.6 | 0.29 |
| | 3 | 1,000 | 0.19 | 25 | 27.4 | 0.04 | 0.2 | | | | 15 | 1,200 | 0.23 | 35 | 9.7 | 0.14 |
| | 47 | 700 | 0.13 | 114 | 4.1 | 0.20 | 1.5 | | | | 3 | 2,200 | 0.42 | 155 | 27.4 | 0.08 |
| | 3 | 2,100 | 0.40 | 53 | 27.4 | 0.08 | 0.2 | | | | 15 | 2,100 | 0.42 | 145 | 9.7 | 0.24 |
| | 36 | 2,800 | 0.53 | 193 | 9.9 | 0.32 | 0.6 | | | | 12 | 1,400 | 0.26 | 224 | 4.0 | 0.39 |
| | 10 | 900 | 0.17 | 62 | 9.9 | 0.10 | 0.6 | | | | 30 | 1,700 | 0.32 | 232 | 4.0 | 0.48 |
| | 6 | 1,900 | 0.36 | 231 | 5.6 | 0.40 | 1.1 | | | | 3 | 800 | 0.15 | 20 | 27.4 | 0.03 |
| | 89 | 600 | 0.11 | 71 | 5.6 | 0.12 | 1.1 | | | | 47 | 700 | 0.13 | 114 | 4.1 | 0.20 |
| | 6 | 1,200 | 0.23 | 168 | 5.6 | 0.25 | 1.1 | | | | 364 | 1,300 | 0.25 | 53 | 27.4 | 0.08 |
| | 32 | 900 | 0.17 | 166 | 4.1 | 0.26 | 1.5 | | | | 36 | 1,800 | 0.34 | 124 | 9.9 | 0.20 |
| | 3 | 1,700 | 0.32 | 42 | 27.4 | 0.06 | 0.2 | | | | 15 | 1,100 | 0.21 | 78 | 9.7 | 0.13 |
| | 32 | 1,000 | 0.19 | 167 | 4.1 | 0.28 | 1.5 | | | | 6 | 1,700 | 0.32 | 208 | 5.6 | 0.39 |
| | 86 | 200 | 0.04 | 27 | 5.4 | 0.04 | 1.1 | | | | 69 | 600 | 0.11 | 71 | 5.6 | 0.12 |
| | 37 | 1,400 | 0.25 | 34 | 27.4 | 0.05 | 0.2 | | | | 6 | 1,200 | 0.23 | 148 | 5.6 | 0.29 |
| | 3 | 800 | 0.15 | 20 | 27.4 | 0.03 | 0.2 | | | | 30 | 900 | 0.17 | 170 | 4.0 | 0.28 |
| | 37 | 300 | 0.06 | 3 | 27.4 | 0.01 | 0.2 | | | | 17 | 17 | 17 | 17 | 17 | 17 |
| | 83 | 600 | 0.11 | 71 | 5.6 | 0.12 | 1.1 | | | | 3 | 1,700 | 0.32 | 142 | 27.4 | 0.06 |
| | 87 | 600 | 0.11 | 71 | 5.6 | 0.12 | 1.1 | | | | 30 | 1,200 | 0.23 | 207 | 4.0 | 0.34 |
| | 14 | 5,300 | 1.00 | 643 | 5.6 | 1.10 | 1.1 | | | | 37 | 3,400 | 0.64 | 84 | 27.4 | 0.13 |
| | 82 | 600 | 0.11 | 71 | 5.6 | 0.12 | 1.1 | | | | 87 | 700 | 0.13 | 84 | 5.6 | 0.14 |
| | 14 | 300 | 0.06 | 39 | 5.6 | 0.07 | 1.1 | | | | 14 | 2,800 | 0.53 | 341 | 5.6 | 0.14 |
| | 3 | 1,700 | 0.32 | 142 | 27.4 | 0.06 | 0.2 | | | | 10 | 1,900 | 0.36 | 131 | 9.9 | 0.22 |
| | 10 | 700 | 0.13 | 47 | 9.7 | 0.08 | 0.6 | | | | 14 | 400 | 0.08 | 21 | 5.6 | 0.09 |
| | 3 | 1,300 | 0.25 | 33 | 27.4 | 0.05 | 0.2 | | | | 15 | 500 | 0.09 | 33 | 9.7 | 0.09 |
| | 10 | 3,700 | 0.70 | 225 | 9.9 | 0.42 | 0.6 | | | | 82 | 1,900 | 0.36 | 234 | 5.6 | 0.40 |
| | 23 | 1,200 | 0.23 | 53 | 15.5 | 0.09 | 0.4 | | | | 14 | 500 | 0.06 | 39 | 5.6 | 0.07 |
| | 2 | 800 | 0.15 | 20 | 27.4 | 0.03 | 0.2 | | | | 15 | 700 | 0.13 | 148 | 9.7 | 0.03 |
| | 57 | 7,000 | 1.32 | 720 | 6.6 | 1.19 | 0.9 | | | | 3 | 900 | 0.17 | 22 | 27.4 | 0.02 |
| | 32 | 500 | 0.09 | 79 | 4.1 | 0.14 | 1.5 | | | | 15 | 2,200 | 0.42 | 156 | 9.7 | 0.25 |
| | 2 | 900 | 0.17 | 51 | 12.0 | 0.08 | 0.5 | | | | 10 | 700 | 0.13 | 47 | 9.9 | 0.08 |
| | 16 | 500 | 0.09 | 29 | 11.2 | 0.04 | 0.5 | | | | 15 | 700 | 0.13 | 48 | 9.7 | 0.08 |

29 of 32 sheets

(Continued)

Table 4 (Continued)

| Vehi- cle | Ter- rain Type | Dry Season (60 or 40 RCI) | | | | | Wet Season (60 or 40 RCI) | | | | | Wet Season (60 or 35 RCI) | | | | | Fuel mi/gal |
|--------------|----------------------|---------------------------|------------------|-------------|--------------|--------------------|---------------------------|------------------|-------------|--------------|--------------------|---------------------------|------------------|-------------|--------------|--------------------|----------------|
| | | Ter- rain Type | Distance feet | Time sec | Speed mph | Fuel gal/ mi | Ter- rain Type | Distance feet | Time sec | Speed mph | Fuel gal/ mi | Ter- rain Type | Distance feet | Time sec | Speed mph | Fuel gal/ mi | |
| 30 | 200 | 36 | 200 | 0.04 | 4.0 | 0.06 | 1.5 | 23 | 1,900 | 0.36 | 84 | 15.5 | 0.14 | 0.4 | 0.4 | 0.4 | 0.4 |
| 3 | 700 | 17 | 700 | 0.13 | 27.4 | 0.03 | 0.2 | 16 | 500 | 0.17 | 51 | 10.8 | 0.17 | 0.6 | 0.6 | 0.6 | 0.6 |
| 2 | 1,100 | 6 | 1,100 | 0.21 | 12.1 | 0.10 | 0.2 | 57 | 6,900 | 1.30 | 799 | 6.3 | 1.1 | 0.9 | 0.9 | 0.9 | 0.9 |
| 3 | 1,400 | 11 | 1,400 | 0.08 | 27.4 | 0.02 | 0.2 | 30 | 400 | 0.08 | 72 | 4.0 | 0.12 | 1.5 | 1.5 | 1.5 | 1.5 |
| 32 | 2,800 | 1,499 | 2,800 | 0.34 | 4.1 | 1.61 | 1.5 | 2 | 900 | 0.17 | 51 | 12.0 | 0.58 | 0.5 | 0.5 | 0.5 | 0.5 |
| 3 | 600 | 14 | 600 | 0.11 | 27.4 | 0.02 | 0.2 | 16 | 500 | 0.09 | 30 | 10.8 | 0.09 | 0.6 | 0.6 | 0.6 | 0.6 |
| 2 | 800 | 45 | 800 | 0.15 | 12.0 | 0.08 | 0.5 | 30 | 200 | 0.04 | 36 | 4.0 | 0.36 | 1.5 | 1.5 | 1.5 | 1.5 |
| 3 | 1,900 | 47 | 1,900 | 0.36 | 27.4 | 0.07 | 0.2 | 3 | 700 | 0.13 | 17 | 27.4 | 0.03 | 0.2 | 0.2 | 0.2 | 0.2 |
| 5 | 3,200 | 138 | 3,200 | 0.60 | 12.6 | 0.2 | 0.4 | 2 | 1,000 | 0.19 | 57 | 12.0 | 0.10 | 0.5 | 0.5 | 0.5 | 0.5 |
| 3 | 1,700 | 42 | 1,700 | 0.32 | 27.4 | 0.06 | 1.2 | 3 | 500 | 0.09 | 12 | 27.4 | 0.02 | 0.2 | 0.2 | 0.2 | 0.2 |
| 73 | 300 | 19 | 300 | 0.06 | 11.5 | 0.03 | 0.5 | 30 | 1,800 | 0.34 | 1,966 | 4.0 | 1.61 | 1.5 | 1.5 | 1.5 | 1.5 |
| 22 | 1,000 | 70 | 1,000 | 0.19 | 9.8 | 0.11 | 0.6 | 3 | 900 | 0.09 | 12 | 27.4 | 0.02 | 0.2 | 0.2 | 0.2 | 0.2 |
| 16 | 1,600 | 96 | 1,600 | 0.30 | 11.2 | 0.15 | 0.5 | 3 | 800 | 0.15 | 45 | 12.0 | 0.08 | 0.5 | 0.5 | 0.5 | 0.5 |
| 3 | 3,400 | 84 | 3,400 | 0.64 | 27.4 | 0.13 | 0.2 | 3 | 1,800 | 0.34 | 145 | 27.4 | 0.07 | 0.2 | 0.2 | 0.2 | 0.2 |
| 10 | 1,200 | 84 | 1,200 | 0.23 | 9.9 | 0.14 | 0.6 | 3 | 3,300 | 0.62 | 145 | 15.6 | 0.05 | 0.4 | 0.4 | 0.4 | 0.4 |
| 3 | 300 | 8 | 300 | 0.06 | 27.4 | 0.01 | 0.2 | 3 | 1,700 | 0.32 | 142 | 27.4 | 0.06 | 0.2 | 0.2 | 0.2 | 0.2 |
| 15 | 600 | 40 | 600 | 0.11 | 9.8 | 0.07 | 0.6 | 73 | 300 | 0.06 | 15 | 11.5 | 0.03 | 0.5 | 0.5 | 0.5 | 0.5 |
| 10 | 2,700 | 105 | 2,700 | 0.51 | 9.9 | 0.31 | 0.6 | 16 | 1,100 | 0.21 | 70 | 10.8 | 0.13 | 0.6 | 0.6 | 0.6 | 0.6 |
| 15 | 3,300 | 228 | 3,300 | 0.62 | 9.8 | 0.37 | 0.6 | 22 | 1,600 | 0.30 | 111 | 9.7 | 0.15 | 0.6 | 0.6 | 0.6 | 0.6 |
| 10 | 1,200 | 84 | 1,200 | 0.23 | 9.9 | 0.14 | 0.6 | 3 | 3,400 | 0.64 | 84 | 27.4 | 0.13 | 0.2 | 0.2 | 0.2 | 0.2 |
| 2 | 1,200 | 69 | 1,200 | 0.23 | 12.0 | 0.12 | 0.5 | 15 | 1,900 | 0.36 | 134 | 9.7 | 0.22 | 0.6 | 0.6 | 0.6 | 0.6 |
| 3 | 3,200 | 79 | 3,200 | 0.60 | 27.4 | 0.12 | 0.2 | 3 | 900 | 0.09 | 12 | 27.4 | 0.02 | 0.2 | 0.2 | 0.2 | 0.2 |
| 10 | 400 | 29 | 400 | 0.08 | 9.9 | 0.05 | 0.6 | 15 | 300 | 0.06 | 22 | 9.7 | 0.04 | 0.6 | 0.6 | 0.6 | 0.6 |
| 81 | 1,200 | 148 | 1,200 | 0.23 | 5.6 | 0.25 | 1.1 | 10 | 700 | 0.13 | 47 | 9.9 | 0.08 | 0.6 | 0.6 | 0.6 | 0.6 |
| 69 | 1,400 | 95 | 1,400 | 0.26 | 9.9 | 0.16 | 0.6 | 15 | 1,300 | 0.25 | 93 | 9.7 | 0.15 | 0.6 | 0.6 | 0.6 | 0.6 |
| 17 | 1,900 | 47 | 1,900 | 0.36 | 27.4 | 0.07 | 0.2 | 10 | 600 | 0.11 | 40 | 9.9 | 0.07 | 0.6 | 0.6 | 0.6 | 0.6 |
| 69 | 1,400 | 95 | 1,400 | 0.26 | 9.9 | 0.16 | 0.6 | 15 | 3,500 | 0.66 | 245 | 9.7 | 0.40 | 0.6 | 0.6 | 0.6 | 0.6 |
| 70 | 800 | 45 | 800 | 0.15 | 12.0 | 0.08 | 0.5 | 10 | 600 | 0.11 | 40 | 9.9 | 0.07 | 0.6 | 0.6 | 0.6 | 0.6 |
| 69 | 1,400 | 95 | 1,400 | 0.26 | 9.9 | 0.16 | 0.6 | 57 | 600 | 0.11 | 60 | 6.6 | 0.10 | 0.9 | 0.9 | 0.9 | 0.9 |
| 10 | 800 | 55 | 800 | 0.15 | 5.9 | 0.09 | 0.6 | 2 | 1,000 | 0.19 | 57 | 12.0 | 0.10 | 0.5 | 0.5 | 0.5 | 0.5 |
| 6 | 1,000 | 122 | 1,000 | 0.19 | 5.6 | 0.21 | 1.1 | 16 | 800 | 0.15 | 50 | 10.8 | 0.09 | 0.6 | 0.6 | 0.6 | 0.6 |
| 62 | 6,100 | 739 | 6,100 | 1.25 | 5.6 | 1.26 | 1.1 | 16 | 800 | 0.15 | 50 | 10.8 | 0.09 | 0.6 | 0.6 | 0.6 | 0.6 |
| 6 | 300 | 39 | 300 | 0.06 | 5.6 | 0.07 | 1.1 | 16 | 800 | 0.15 | 50 | 10.8 | 0.09 | 0.6 | 0.6 | 0.6 | 0.6 |
| 10 | 800 | 55 | 800 | 0.15 | 5.9 | 0.09 | 0.6 | 16 | 800 | 0.15 | 50 | 10.8 | 0.09 | 0.6 | 0.6 | 0.6 | 0.6 |
| 63 | 400 | 51 | 400 | 0.08 | 5.6 | 0.09 | 1.1 | 81 | 1,200 | 0.23 | 148 | 5.6 | 0.25 | 1.1 | 1.1 | 1.1 | 1.1 |
| 62 | 1,700 | 206 | 1,700 | 0.32 | 5.6 | 0.35 | 1.1 | 69 | 300 | 0.09 | 33 | 9.9 | 0.05 | 0.6 | 0.6 | 0.6 | 0.6 |
| 63 | 3,900 | 476 | 3,900 | 0.74 | 5.6 | 0.81 | 1.1 | 94 | 1,000 | 0.19 | 63 | 10.8 | 0.11 | 0.6 | 0.6 | 0.6 | 0.6 |
| 3 | 4,100 | 101 | 4,100 | 0.77 | 27.4 | 0.15 | 0.2 | 17 | 1,800 | 0.34 | 45 | 27.4 | 0.07 | 0.2 | 0.2 | 0.2 | 0.2 |
| 55 | 1,000 | 69 | 1,000 | 0.19 | 9.9 | 0.11 | 0.6 | 94 | 200 | 0.04 | 13 | 10.8 | 0.02 | 0.6 | 0.6 | 0.6 | 0.6 |
| 31 | 4,200 | 104 | 4,200 | 0.79 | 27.4 | 0.16 | 0.2 | 69 | 500 | 0.09 | 34 | 5.9 | 0.25 | 0.6 | 0.6 | 0.6 | 0.6 |
| 10 | 1,000 | 131 | 1,000 | 0.36 | 9.9 | 0.22 | 0.6 | 94 | 300 | 0.06 | 20 | 10.8 | 0.04 | 0.6 | 0.6 | 0.6 | 0.6 |
| 15 | 1,800 | 45 | 1,800 | 0.34 | 27.4 | 0.07 | 0.2 | 69 | 400 | 0.08 | 29 | 9.9 | 0.05 | 0.6 | 0.6 | 0.6 | 0.6 |
| 15 | 1,400 | 29 | 1,400 | 0.26 | 11.2 | 0.07 | 0.2 | 70 | 800 | 0.15 | 45 | 12.0 | 0.08 | 0.5 | 0.5 | 0.5 | 0.5 |
| 15 | 1,400 | 103 | 1,400 | 0.26 | 9.8 | 0.17 | 0.6 | 69 | 400 | 0.08 | 29 | 9.9 | 0.05 | 0.6 | 0.6 | 0.6 | 0.6 |
| 10 | 1,700 | 116 | 1,700 | 0.32 | 9.9 | 0.19 | 0.6 | 10 | 800 | 0.15 | 55 | 9.9 | 0.09 | 0.6 | 0.6 | 0.6 | 0.6 |
| 15 | 3,000 | 209 | 3,000 | 0.57 | 9.8 | 0.34 | 0.6 | 6 | 1,100 | 0.21 | 135 | 5.6 | 0.23 | 1.1 | 1.1 | 1.1 | 1.1 |
| 3 | 900 | 22 | 900 | 0.17 | 27.4 | 0.03 | 0.2 | 62 | 5,900 | 1.12 | 720 | 5.6 | 1.23 | 1.1 | 1.1 | 1.1 | 1.1 |
| 15 | 1,900 | 132 | 1,900 | 0.36 | 9.8 | 0.22 | 0.6 | 6 | 400 | 0.08 | 21 | 3.6 | 0.09 | 0.6 | 0.6 | 0.6 | 0.6 |
| 3 | 5,300 | 131 | 5,300 | 1.00 | 27.4 | 0.20 | 0.2 | 15 | 800 | 0.15 | 24 | 5.6 | 0.09 | 0.6 | 0.6 | 0.6 | 0.6 |
| 10 | 1,200 | 84 | 1,200 | 0.23 | 9.9 | 0.14 | 0.6 | 62 | 1,600 | 0.30 | 193 | 3.6 | 0.33 | 1.1 | 1.1 | 1.1 | 1.1 |
| 3 | 5,000 | 124 | 5,000 | 0.94 | 27.4 | 0.19 | 0.2 | 63 | 4,100 | 0.77 | 495 | 5.6 | 0.95 | 1.1 | 1.1 | 1.1 | 1.1 |
| 21 | 300 | 22 | 300 | 0.06 | 9.9 | 0.14 | 0.6 | 31 | 4,200 | 0.79 | 134 | 27.4 | 0.16 | 0.2 | 0.2 | 0.2 | 0.2 |
| 21 | 1,700 | 118 | 1,700 | 0.32 | 9.8 | 0.19 | 0.6 | 80 | 900 | 0.17 | 57 | 10.8 | 0.10 | 0.6 | 0.6 | 0.6 | 0.6 |
| 21 | 800 | 55 | 800 | 0.15 | 9.9 | 0.09 | 0.6 | 31 | 4,000 | 0.76 | 100 | 27.4 | 0.15 | 0.2 | 0.2 | 0.2 | 0.2 |
| 22 | 500 | 33 | 500 | 0.09 | 9.8 | 0.05 | 0.6 | 15 | 1,000 | 0.19 | 70 | 9.7 | 0.11 | 0.6 | 0.6 | 0.6 | 0.6 |

(Continued)

(30 of 32 sheets)

Table 4 (Continued)


| Vehi- cle | Type | Dry Season (50 or 40 MI) | | | | | | Wet Season (50 or 40 MI) | | | | | | Wet Season (50 or 40 MI) | | | | | |
|--------------|------|--------------------------|------------------------|-------------|-------------|---------------------|----------------------|--------------------------|------------------------|-------------|-------------|---------------------|----------------------|--------------------------|------------------------|-------------|-------------|---------------------|----------------------|
| | | Dist- ance feet | Dist- ance miles | Time sec | Time min | Avg Speed mph | Fuel gal/ mile | Dist- ance feet | Dist- ance miles | Time sec | Time min | Avg Speed mph | Fuel gal/ mile | Dist- ance feet | Dist- ance miles | Time sec | Time min | Avg Speed mph | Fuel gal/ mile |
| 21 | 21 | 600 | 0.11 | 40 | 9.9 | 0.07 | 0.6 | 10 | 800 | 0.15 | 55 | 9.9 | 0.06 | 10 | 800 | 0.15 | 55 | 9.9 | 0.06 |
| 22 | 22 | 2,500 | 0.47 | 173 | 27.4 | 0.28 | 0.6 | 15 | 1,500 | 0.26 | 37 | 27.4 | 0.06 | 15 | 1,500 | 0.26 | 37 | 27.4 | 0.06 |
| 3 | 3 | 1,600 | 0.30 | 17 | 9.9 | 0.06 | 0.2 | 16 | 600 | 0.11 | 37 | 10.8 | 0.07 | 16 | 600 | 0.11 | 37 | 10.8 | 0.07 |
| 21 | 21 | 1,300 | 0.25 | 91 | 9.9 | 0.15 | 0.6 | 15 | 1,400 | 0.26 | 96 | 9.7 | 0.16 | 15 | 1,400 | 0.26 | 96 | 9.7 | 0.16 |
| 3 | 3 | 8,800 | 1.66 | 218 | 27.4 | 0.33 | 0.2 | 10 | 1,900 | 0.36 | 131 | 9.9 | 0.22 | 10 | 1,900 | 0.36 | 131 | 9.9 | 0.22 |
| 10 | 10 | 1,200 | 0.23 | 84 | 9.9 | 0.14 | 0.6 | 15 | 3,000 | 0.57 | 212 | 9.7 | 0.34 | 15 | 3,000 | 0.57 | 212 | 9.7 | 0.34 |
| 15 | 15 | 5,100 | 0.96 | 353 | 27.4 | 0.22 | 0.6 | 25 | 1,000 | 0.19 | 25 | 27.4 | 0.19 | 25 | 1,000 | 0.19 | 25 | 27.4 | 0.19 |
| 3 | 3 | 600 | 0.11 | 14 | 27.4 | 0.02 | 0.2 | 15 | 1,900 | 0.36 | 134 | 9.7 | 0.22 | 15 | 1,900 | 0.36 | 134 | 9.7 | 0.22 |
| 10 | 10 | 300 | 0.06 | 22 | 9.9 | 0.04 | 0.6 | 3 | 5,200 | 0.98 | 129 | 27.4 | 0.20 | 3 | 5,200 | 0.98 | 129 | 27.4 | 0.20 |
| 3 | 3 | 2,300 | 0.43 | 56 | 27.4 | 0.09 | 0.2 | 15 | 400 | 0.08 | 30 | 9.7 | 0.05 | 15 | 400 | 0.08 | 30 | 9.7 | 0.05 |
| 10 | 10 | 300 | 0.06 | 22 | 9.9 | 0.04 | 0.6 | 10 | 400 | 0.08 | 29 | 9.9 | 0.05 | 10 | 400 | 0.08 | 29 | 9.9 | 0.05 |
| 3 | 3 | 7,700 | 1.46 | 17 | 27.4 | 0.20 | 0.2 | 15 | 300 | 0.06 | 22 | 2.7 | 0.04 | 15 | 300 | 0.06 | 22 | 2.7 | 0.04 |
| 69 | 69 | 1,700 | 0.32 | 116 | 9.9 | 0.19 | 0.6 | 22 | 2,100 | 0.40 | 53 | 27.4 | 0.08 | 22 | 2,100 | 0.40 | 53 | 27.4 | 0.08 |
| 10 | 10 | 400 | 0.08 | 29 | 9.9 | 0.05 | 0.6 | 28 | 300 | 0.17 | 45 | 27.4 | 0.07 | 28 | 300 | 0.17 | 45 | 27.4 | 0.07 |
| 3 | 3 | 1,800 | 0.34 | 3 | 27.4 | 0.03 | 0.6 | 21 | 600 | 0.11 | 40 | 9.9 | 0.07 | 21 | 600 | 0.11 | 40 | 9.9 | 0.07 |
| 21 | 21 | 600 | 0.11 | 20 | 27.4 | 0.03 | 0.2 | 22 | 1,700 | 0.32 | 119 | 9.7 | 0.19 | 22 | 1,700 | 0.32 | 119 | 9.7 | 0.19 |
| 21 | 21 | 1,900 | 0.36 | 209 | 27.4 | 0.22 | 0.6 | 21 | 600 | 0.11 | 40 | 9.9 | 0.07 | 21 | 600 | 0.11 | 40 | 9.9 | 0.07 |
| 14 | 14 | 6,100 | 1.15 | 779 | 5.6 | 1.28 | 1.1 | 22 | 600 | 0.11 | 41 | 9.7 | 0.07 | 22 | 600 | 0.11 | 41 | 9.7 | 0.07 |
| 4 | 4 | 400 | 0.08 | 46 | 6.2 | 0.08 | 1.0 | 21 | 600 | 0.11 | 40 | 9.9 | 0.07 | 21 | 600 | 0.11 | 40 | 9.9 | 0.07 |
| 14 | 14 | 3,000 | 0.57 | 366 | 5.6 | 0.63 | 1.1 | 22 | 2,400 | 0.45 | 167 | 9.7 | 0.27 | 22 | 2,400 | 0.45 | 167 | 9.7 | 0.27 |
| 3 | 3 | 3,700 | 0.70 | 109 | 27.4 | 0.14 | 0.2 | 21 | 1,300 | 0.26 | 1,237 | 27.4 | 1.16 | 21 | 1,300 | 0.26 | 1,237 | 27.4 | 1.16 |
| 3 | 3 | 2,000 | 0.38 | 221 | 6.2 | 0.38 | 1.0 | 21 | 1,400 | 0.26 | 99 | 9.9 | 0.16 | 21 | 1,400 | 0.26 | 99 | 9.9 | 0.16 |
| 3 | 3 | 1,400 | 0.26 | 34 | 27.4 | 0.05 | 0.2 | 3 | 9,000 | 1.70 | 223 | 27.4 | 0.34 | 3 | 9,000 | 1.70 | 223 | 27.4 | 0.34 |
| 4 | 4 | 2,300 | 0.43 | 250 | 6.2 | 0.43 | 1.0 | 10 | 1,300 | 0.25 | 91 | 9.9 | 0.15 | 10 | 1,300 | 0.25 | 91 | 9.9 | 0.15 |
| 5 | 5 | 300 | 0.06 | 14 | 15.6 | 0.02 | 0.4 | 15 | 5,000 | 0.94 | 349 | 9.7 | 0.56 | 15 | 5,000 | 0.94 | 349 | 9.7 | 0.56 |
| 2 | 2 | 6,000 | 1.13 | 148 | 27.4 | 0.23 | 0.2 | 3 | 300 | 0.09 | 12 | 27.4 | 0.02 | 3 | 300 | 0.09 | 12 | 27.4 | 0.02 |
| 3 | 3 | 2,800 | 0.53 | 368 | 6.2 | 0.53 | 1.0 | 10 | 1,400 | 0.26 | 99 | 9.9 | 0.15 | 10 | 1,400 | 0.26 | 99 | 9.9 | 0.15 |
| 3 | 3 | 300 | 0.09 | 12 | 27.4 | 0.02 | 0.2 | 3 | 2,600 | 0.49 | 64 | 27.4 | 0.10 | 3 | 2,600 | 0.49 | 64 | 27.4 | 0.10 |
| 2 | 2 | 1,000 | 0.19 | 57 | 12.0 | 0.10 | 0.5 | 10 | 300 | 0.06 | 22 | 9.9 | 0.04 | 10 | 300 | 0.06 | 22 | 9.9 | 0.04 |
| | | | | | | | | 3 | 8,000 | 1.51 | 215 | 27.4 | 0.30 | 3 | 8,000 | 1.51 | 215 | 27.4 | 0.30 |
| | | | | | | | | 16 | 400 | 0.08 | 17 | 10.8 | 0.05 | 16 | 400 | 0.08 | 17 | 10.8 | 0.05 |
| | | | | | | | | 3 | 2,400 | 0.45 | 59 | 27.4 | 0.09 | 3 | 2,400 | 0.45 | 59 | 27.4 | 0.09 |
| | | | | | | | | 94 | 600 | 0.11 | 37 | 10.8 | 0.07 | 94 | 600 | 0.11 | 37 | 10.8 | 0.07 |
| | | | | | | | | 69 | 1,200 | 0.23 | 84 | 9.9 | 0.14 | 69 | 1,200 | 0.23 | 84 | 9.9 | 0.14 |
| | | | | | | | | 13 | 2,800 | 0.53 | 867 | 2.2 | 1.59 | 13 | 2,800 | 0.53 | 867 | 2.2 | 1.59 |
| | | | | | | | | 10 | 600 | 0.11 | 40 | 9.9 | 0.07 | 10 | 600 | 0.11 | 40 | 9.9 | 0.07 |
| | | | | | | | | 15 | 700 | 0.13 | 17 | 27.4 | 0.03 | 15 | 700 | 0.13 | 17 | 27.4 | 0.03 |
| | | | | | | | | 15 | 1,900 | 0.36 | 134 | 9.7 | 0.22 | 15 | 1,900 | 0.36 | 134 | 9.7 | 0.22 |
| | | | | | | | | 1 | 1,700 | 0.32 | 186 | 6.2 | 0.32 | 1 | 1,700 | 0.32 | 186 | 6.2 | 0.32 |
| | | | | | | | | 14 | 3,900 | 0.74 | 476 | 5.6 | 0.81 | 14 | 3,900 | 0.74 | 476 | 5.6 | 0.81 |
| | | | | | | | | 1 | 800 | 0.15 | 87 | 6.2 | 0.15 | 1 | 800 | 0.15 | 87 | 6.2 | 0.15 |
| | | | | | | | | 14 | 2,100 | 0.40 | 257 | 5.6 | 0.44 | 14 | 2,100 | 0.40 | 257 | 5.6 | 0.44 |
| | | | | | | | | 4 | 900 | 0.17 | 99 | 6.2 | 0.17 | 4 | 900 | 0.17 | 99 | 6.2 | 0.17 |
| | | | | | | | | 14 | 2,100 | 0.40 | 257 | 5.6 | 0.44 | 14 | 2,100 | 0.40 | 257 | 5.6 | 0.44 |
| | | | | | | | | 3 | 2,800 | 0.53 | 70 | 27.4 | 0.11 | 3 | 2,800 | 0.53 | 70 | 27.4 | 0.11 |
| | | | | | | | | 16 | 700 | 0.13 | 63 | 10.8 | 0.08 | 16 | 700 | 0.13 | 63 | 10.8 | 0.08 |
| | | | | | | | | 3 | 300 | 0.06 | 8 | 27.4 | 0.01 | 3 | 300 | 0.06 | 8 | 27.4 | 0.01 |
| | | | | | | | | 1 | 1,900 | 0.36 | 209 | 6.2 | 0.36 | 1 | 1,900 | 0.36 | 209 | 6.2 | 0.36 |
| | | | | | | | | 3 | 1,400 | 0.26 | 34 | 27.4 | 0.05 | 3 | 1,400 | 0.26 | 34 | 27.4 | 0.05 |

(Continued)

(31 of 32 sheets)


Table 4 (Continued)

[illegible]



NOTE: NUMERICAL DESIGNATIONS INDICATE COMBINATIONS OF STRUCTURE GEOMETRY, SURFACE COMPOSITION, AND VEGETATION FACTORS. FOR CLASS LIMITS OF EACH FACTOR OCCURRING IN A PARTICULAR TERRAIN COMBINATION. SEE TABLE I.

SEQUENCES IN WHICH FACTORS OCCUR FROM LEFT TO RIGHT IN TABULATION ARE NOT INTENDED TO INDICATE A HIERARCHY OF EFFECT ON VEHICLE PERFORMANCE.



| TER- RAIN TYPE NO | Surface Geometry | | | | Surface Composition- Vegetation Combination No. |
|----------------------------|------------------|---------------------------------------|--------------------------|-----------------------|---|
| | Slope deg | Vertical Obstacle Spacing ft | Approach Angle deg | Step Height in. | |
| 1 | 0-1.5 | >12-50 | 125-2150 | >10-15 | 19 |
| 2 | 0-1.5 | >150 | 165-180 | 0-4 | 2 |
| 3 | 0-1.5 | >150 | 165-180 | 0-4 | 3 |
| 4 | 0-1.5 | >12-50 | 125-150 | >10-18 | 3 |
| 5 | 0-1.5 | >150 | 165-180 | 0-4 | 6 |
| 6 | 0-1.5 | >150 | 165-180 | 0-4 | 1 |
| 7 | 0-1.5 | >12-50 | 125-150 | >18-30 | 3 |
| 8 | 0-1.5 | >150 | 165-180 | 0-4 | 12 |
| 9 | 0-1.5 | >150 | 165-180 | 0-4 | 5 |
| 10 | 0-1.5 | >50-150 | 125-150 | >10-18 | 3 |
| 11 | 0-1.5 | >150 | 165-180 | 0-4 | 15 |
| 12 | 0-1.5 | >50-150 | 100-125 | >18-30 | 19 |
| 13 | 0-1.5 | >150 | 165-180 | 0-4 | 7 |
| 14 | 0-1.5 | >150 | 165-180 | 0-4 | 4 |
| 15 | 0-1.5 | >50-150 | 125-150 | >10-18 | 19 |
| 16 | 0-1.5 | >150 | 165-180 | 0-4 | 19 |
| 17 | >1.5-4.5 | >150 | 165-180 | >4-10 | 3 |
| 18 | 0-1.5 | >50-150 | 125-150 | >10-18 | 2 |
| 19 | 0-1.5 | >50-150 | 125-150 | >10-18 | 12 |
| 20 | 0-1.5 | >150 | 165-180 | 0-4 | 18 |
| 21 | 0-1.5 | >50-150 | 100-125 | >10-18 | 3 |
| 22 | 0-1.5 | >50-150 | 100-125 | >10-18 | 19 |
| 23 | 0-1.5 | >150 | 165-180 | 0-4 | 9 |
| 24 | 0-1.5 | >50-150 | 125-150 | >10-18 | 4 |
| 25 | 0-1.5 | >50-150 | 125-150 | >10-18 | 1 |
| 26 | 0-1.5 | >50-150 | 165-180 | >4-10 | 3 |
| 27 | 0-1.5 | >50-150 | 165-180 | >4-10 | 19 |
| 28 | 0-1.5 | >50-150 | 125-150 | >4-10 | 3 |
| 29 | 0-1.5 | >50-150 | 125-150 | >4-10 | 19 |
| 30 | 0-1.5 | >50-150 | 125-150 | >18-30 | 19 |
| 31 | 0-1.5 | >150 | 165-180 | >4-10 | 3 |
| 32 | 0-1.5 | >50-150 | 125-150 | >18-30 | 3 |
| 33 | 0-1.5 | >50-150 | 100-125 | >10-18 | 6 |
| 34 | 0-1.5 | >50-150 | 125-150 | >18-30 | 2 |
| 35 | 0-1.5 | >50-150 | 100-125 | >4-10 | 3 |
| 36 | >1.5-4.5 | >50-150 | 125-150 | >10-18 | 3 |
| 37 | >1.5-4.5 | >150 | 165-180 | 0-4 | 3 |
| 38 | >1.5-4.5 | >50-150 | 100-125 | >4-10 | 3 |
| 39 | >1.5-4.5 | >150 | 165-180 | 0-4 | 6 |
| 40 | >1.5-4.5 | >150 | 165-180 | 0-4 | 15 |
| 41 | >1.5-4.5 | >150 | 165-180 | 0-4 | 5 |
| 42 | >4.5-9 | >150 | 125-150 | >10-18 | 14 |
| 43 | >4.5-9 | >150 | 125-150 | >10-18 | 5 |
| 44 | >18-30 | >150 | 125-150 | >10-18 | 14 |
| 45 | >18-30 | >150 | 125-150 | >10-18 | 5 |
| 46 | 0-1.5 | >150 | 125-150 | >10-18 | 5 |
| 47 | 0-1.5 | >50-150 | 100-125 | >18-30 | 3 |
| 48 | 0-1.5 | >150 | 165-180 | 0-4 | 13 |
| 49 | >1.5-4.5 | >150 | 165-180 | 0-4 | 1 |

**KHON KAEN CROSS-COUNTRY
MOBILITY ROUTE
SURFACE GEOMETRY, SURFACE
AND VEGETATION FACTORS**

SCALE




Table 1

Terrain Factor Types (Surface Geometry, Surface Composition, Vegetation Structure)


[illegible]

KHON KAEN CROSS-COUNTRY MOBILITY ROUTES


SURFACE GEOMETRY, SURFACE COMPOSITION AND VEGETATION FACTORS

SCALE

0 1 2 3 4 MILES



| Elev Height in. | Surface Composition- Vegetation Combination No. | Surface Composi- tion Rating Cone Index | Vegetation Structure | | | | | | | |
|-----------------------|---|--|---|--------|--------|--------|---|--------|--------|--------|
| | | | Stems of Diameter Equal to or Less Than | | | | Stems of Diameter Equal to or More Than | | | |
| | | | 2 in. | 5 in. | 9 in. | 30 in. | 1 in. | 3 in. | 6 in. | 10 in. |
| 0-4 | 1 | >60 | 0-5 | 0-5 | 0-5 | 0-5 | 0-5 | >10-30 | >30 | >30 |
| 0-4 | 1 | >60 | 0-5 | 0-5 | 0-5 | 0-5 | 0-5 | >10-30 | >30 | >30 |
| 0-4 | 3 | >60 | 0-5 | 0-5 | 0-5 | 0-5 | 0-5 | >30 | >30 | >30 |
| 0-4 | 2 | >60 | >30 | >30 | >10-30 | >10-30 | >10-30 | >10-30 | >10-30 | >30 |
| >10-18 | 6 | >60 | >5-10 | >5-10 | >5-10 | >5-10 | >5-10 | >10-30 | >30 | >30 |
| >10-18 | 3 | >60 | 0-5 | 0-5 | 0-5 | 0-5 | 0-5 | >30 | >30 | >30 |
| >10-18 | 1 | >60 | 0-5 | 0-5 | 0-5 | 0-5 | 0-5 | >10-30 | >30 | >30 |
| 0-4 | 17 | >60 | >5-10 | >5-10 | >5-10 | >5-10 | >5-10 | >10-30 | >10-30 | >30 |
| 0-4 | 11 | >60 | >30 | >10-30 | >10-30 | >10-30 | >10-30 | >10-30 | >30 | >30 |
| >10-18 | 3 | >60 | 0-5 | 0-5 | 0-5 | 0-5 | 0-5 | >30 | >30 | >30 |
| 0-4 | 3 | >60 | 0-5 | 0-5 | 0-5 | 0-5 | 0-5 | >30 | >30 | >30 |
| 0-4 | 3 | >60 | 0-5 | 0-5 | 0-5 | 0-5 | 0-5 | >30 | >30 | >30 |
| >10-18 | 1 | >60 | 0-5 | 0-5 | 0-5 | 0-5 | 0-5 | >10-30 | >30 | >30 |
| 0-4 | 1 | >60 | >10-30 | >10-30 | >10-30 | >10-30 | >10-30 | >10-30 | >30 | >30 |
| >10-18 | 2 | >60 | >30 | >30 | >10-30 | >10-30 | >10-30 | >10-30 | >30 | >30 |
| >10-18 | 19 | 25-60 | 0-5 | 0-5 | 0-5 | 0-5 | 0-5 | >30 | >30 | >30 |
| >10-18 | 4 | >60 | >5-10 | 0-5 | 0-5 | 0-5 | 0-5 | >5-10 | >30 | >30 |
| 0-4 | 7 | >60 | 0-5 | 0-5 | 0-5 | 0-5 | 0-5 | >10-30 | >10-30 | >30 |
| >10-18 | 3 | >60 | 0-5 | 0-5 | 0-5 | 0-5 | 0-5 | >30 | >30 | >30 |
| >10-18 | 2 | >60 | >30 | >30 | >10-30 | >10-30 | >10-30 | >10-30 | >10-30 | >30 |
| >10-18 | 2 | >60 | >30 | >30 | >10-30 | >10-30 | >10-30 | >10-30 | >10-30 | >30 |
| 0-4 | 7 | >60 | 0-5 | 0-5 | 0-5 | 0-5 | 0-5 | >10-30 | >30 | >30 |
| >10-18 | 3 | >60 | 0-5 | 0-5 | 0-5 | 0-5 | 0-5 | >30 | >30 | >30 |
| 0-4 | 5 | >60 | >5-10 | 0-5 | 0-5 | 0-5 | 0-5 | >10-30 | >10-30 | >30 |
| 0-4 | 5 | >60 | >5-10 | 0-5 | 0-5 | 0-5 | 0-5 | >10-30 | >10-30 | >30 |
| >10-18 | 5 | >60 | >5-10 | 0-5 | 0-5 | 0-5 | 0-5 | >10-30 | >10-30 | >30 |
| 0-4 | 5 | >60 | >5-10 | 0-5 | 0-5 | 0-5 | 0-5 | >10-30 | >10-30 | >30 |
| >10-18 | 4 | >60 | >5-10 | 0-5 | 0-5 | 0-5 | 0-5 | >5-10 | >30 | >30 |
| >10-18 | 1 | >60 | 0-5 | 0-5 | 0-5 | 0-5 | 0-5 | >10-30 | >30 | >30 |
| >10-18 | 19 | 25-60 | 0-5 | 0-5 | 0-5 | 0-5 | 0-5 | >30 | >30 | >30 |
| >10-18 | 1 | >60 | 0-5 | 0-5 | 0-5 | 0-5 | 0-5 | >10-30 | >30 | >30 |
| 0-4 | 4 | >60 | >5-10 | 0-5 | 0-5 | 0-5 | 0-5 | >5-10 | >30 | >30 |
| 0-4 | 16 | >60 | 0-5 | 0-5 | 0-5 | 0-5 | 0-5 | >5-10 | >10-30 | >30 |
| 0-4 | 10 | >60 | >30 | >30 | >10-30 | >10-30 | >10-30 | >10-30 | >30 | >30 |
| >10-18 | 11 | >60 | >30 | >10-30 | >10-30 | >10-30 | >10-30 | >10-30 | >30 | >30 |
| >10-18 | 3 | >60 | 0-5 | 0-5 | 0-5 | 0-5 | 0-5 | >30 | >30 | >30 |
| >10-18 | 16 | >60 | 0-5 | 0-5 | 0-5 | 0-5 | 0-5 | >5-10 | >10-30 | >30 |
| >10-18 | 3 | >60 | 0-5 | 0-5 | 0-5 | 0-5 | 0-5 | >30 | >30 | >30 |
| 0-4 | 14 | >60 | >5-10 | 0-5 | 0-5 | 0-5 | 0-5 | >5-10 | >10-30 | >30 |
| >10-18 | 10 | >60 | >30 | >30 | >10-30 | >10-30 | >10-30 | >10-30 | >30 | >30 |
| 0-4 | 19 | 25-60 | 0-5 | 0-5 | 0-5 | 0-5 | 0-5 | >30 | >30 | >30 |
| 0-4 | 18 | 25-60 | >30 | >30 | >30 | >30 | >30 | >30 | >30 | >30 |
| >10-18 | 7 | >60 | 0-5 | 0-5 | 0-5 | 0-5 | 0-5 | >10-30 | >10-30 | >30 |
| >10-18 | 19 | 25-60 | 0-5 | 0-5 | 0-5 | 0-5 | 0-5 | >30 | >30 | >30 |
| 0-4 | 15 | >60 | >5-10 | >5-10 | >5-10 | >5-10 | >5-10 | >10-30 | >30 | >30 |
| >10-18 | 3 | >60 | 0-5 | 0-5 | 0-5 | 0-5 | 0-5 | >30 | >30 | >30 |
| >10-18 | 3 | >60 | 0-5 | 0-5 | 0-5 | 0-5 | 0-5 | >30 | >30 | >30 |
| 0-4 | 8 | >60 | >10-30 | >10-30 | >10-30 | >10-30 | >10-30 | >10-30 | >10-30 | >30 |



LEGEND

- FEATURES WITH WATER DEPTH < 3 FT.
- - - FEATURES WITH WATER DEPTH > 3 FT.
- 20/10
20/10
UNIT DESIGNATIONS FOR STREAM SEGMENTS ARE BOUNDED BY TICK MARKS WITH EACH BANK IDENTIFIED SEPARATELY. NUMBER COMBINATIONS IN NUMERATOR OF FRACTION REFER TO HYDROLOGIC GEOMETRY UNITS APPEARING IN EITHER TABLE 1 OR 2. NUMBERS IN DENOMINATOR REFER TO SURFACE COMPOSITION-VEGETATION STRUCTURE FACTOR COMBINATIONS APPEARING IN TABLE 3.

Dashed line areas ① through ⑥ indicate aerial photographic coverage shown in figs. 2-7.




Table 1
Hydrologic Geometry Factor Computed
Water Depth < 3 Feet*

| Unit | Terrain Approach Angle | |
|------|----------------------------------|----------------------------|
| | Convex Angle at Top of Step, deg | Concave Angle of Step, deg |
| 1 | 180-200 | 165-180 |
| 2 | 180-200 | 165-180 |
| 3 | 180-200 | 165-180 |
| 4 | 180-200 | 150-165 |
| 5 | 180-200 | 150-165 |
| 6 | 200-210 | 165-180 |
| 7 | 200-210 | 150-165 |
| 8 | 200-210 | 150-165 |
| 9 | 200-210 | 150-165 |
| 10 | 200-210 | 150-165 |
| 11 | 200-210 | 150-165 |
| 12 | 200-210 | 125-140 |
| 13 | 200-210 | 125-140 |
| 14 | 210-220 | <100 |
| 15 | 210-220 | 100-115 |
| 16 | 210-220 | 100-115 |
| 17 | 210-220 | 100-115 |
| 18 | 210-220 | 125-140 |
| 19 | 210-220 | 125-140 |
| 20 | 210-220 | 125-140 |
| 21 | 210-220 | 150-165 |
| 22 | 210-220 | 150-165 |
| 23 | 210-220 | 150-165 |
| 24 | >220 | <100 |
| 25 | >220 | <100 |
| 26 | >220 | 100-115 |
| 27 | >220 | 100-115 |
| 28 | >220 | 125-140 |
| 29 | >220 | 125-140 |
| 30 | >220 | 125-140 |
| 31 | >220 | 125-140 |
| 32 | >220 | 125-140 |

* Hydrologic features < 3 ft are described using this classification.

KHON KAEN CROSS MOBILITY ROAD HYDROLOGIC GEOMETRY, SURFACE COMPOSITION, AND VEGETATION

SCALE




Table 1

Hydrologic Geometry Factor Combinations
Water Depth <3 Feet*

| Terrain Approach Angle | | Step Height in. |
|-------------------------------------|---------------------------------------|--------------------|
| Convex Angle at Top of Step, deg | Concave Angle at Base of Step, deg | |
| 180-200 | 165-180 | >18-30 |
| 180-200 | 165-180 | >30-48 |
| 180-200 | 165-180 | >66-84 |
| 180-200 | 150-165 | >18-30 |
| 180-200 | 150-165 | >30-48 |
| 200-210 | 165-180 | >18-30 |
| 200-210 | 150-165 | >30-48 |
| 200-210 | 150-165 | >66-84 |
| 200-210 | 150-165 | >84 |
| 200-210 | 125-150 | >30-48 |
| 200-210 | 125-150 | >66-84 |
| 210-220 | 100-125 | >30-48 |
| 210-220 | 100-125 | >66-84 |
| 210-220 | 125-150 | >30-48 |
| 210-220 | 125-150 | >66-84 |
| 210-220 | 150-165 | >30-48 |
| 210-220 | 150-165 | >66-84 |
| 210-220 | 150-165 | >84 |
| >220 | <100 | >30-48 |
| >220 | <100 | >66-84 |
| >220 | 100-125 | >66-84 |
| >220 | 125-150 | >30-48 |
| >220 | 125-150 | >66-84 |
| >220 | 125-150 | >84 |

Table 2

Hydrologic Geometry Factor Combinations
Water Depth >3 Feet

| Unit | Contact Approach Angle, deg | Step Height in. | Position of Step Base (Inches Above Water Level or Below Water Level) | Water Depth ft |
|------|--------------------------------|--------------------|---|-------------------|
| | | | | |
| 1 | <145 | -- | -- | 3-4.5 |
| 2 | <145 | -- | -- | >4.5 |
| 3 | 145-155 | -- | -- | 3-4.5 |
| 4 | 145-155 | -- | -- | >4.5 |
| 5 | >155-165 | -- | -- | 3-4.5 |
| 6 | >155-165 | -- | -- | >4.5 |
| 7 | >165-180 | -- | -- | 3-4.5 |
| 8 | >165-180 | -- | -- | >4.5 |
| 9 | 145-155 | 24-36 | 1-18 bwl* | >4.5 |
| 10 | 145-155 | 24-36 | At water level | 3-4.5 |
| 11 | 145-155 | 24-36 | 1-12 awl** | >4.5 |
| 12 | 145-155 | 24-36 | >12-30 awl | 3-4.5 |
| 13 | 145-155 | 36-48 | >12-30 awl | >4.5 |
| 14 | 145-155 | >48 | >48 awl | >4.5 |
| 15 | >155-165 | 12-24 | 1-18 bwl | 3-4.5 |
| 16 | >155-165 | 12-24 | >30-48 awl | 3-4.5 |
| 17 | >155-165 | 24-36 | 1-18 bwl | >4.5 |
| 18 | >155-165 | 24-36 | 1-12 awl | 3-4.5 |
| 19 | >155-165 | 36-48 | 36-48 bwl | >4.5 |
| 20 | >155-165 | 36-48 | At water level | 3-4.5 |
| 21 | >165-180 | 12-24 | 1-18 bwl | 3-4.5 |
| 22 | >165-180 | 12-24 | At water level | 3-4.5 |
| 23 | >165-180 | 12-24 | 1-12 awl | >4.5 |
| 24 | >165-180 | 24-36 | 36-48 bwl | >4.5 |
| 25 | >165-180 | 24-36 | 1-18 bwl | 3-4.5 |
| 26 | >165-180 | 36-48 | 1-18 bwl | 3-4.5 |
| 27 | >165-180 | 36-48 | At water level | 3-4.5 |

Table 3

Surface Composition-Vegetation Structure Factor Combinations

| Combination No. | Surface Composition NCI | Vegetation Structure Spacing of Stems | | | | |
|--------------------|-------------------------------|--|--|--|--|--|
| | | Stems of Diameter Equal To or Less Than | Stems of Diameter Equal To or Less Than | Stems of Diameter Equal To or Less Than | Stems of Diameter Equal To or Less Than | Stems of Diameter Equal To or Less Than |
| | | 1 in. | 2 in. | 3 in. | 4 in. | 5 in. |
| 1 | 25-60 | 0-5 | 0-5 | 0-5 | 0-5 | 0-5 |
| 2 | 25-60 | >5 | >5 | >5 | >5 | >5 |
| 3 | >60 | 0-5 | 0-5 | 0-5 | 0-5 | 0-5 |
| 4 | >60 | 0-5 | 0-5 | 0-5 | 0-5 | 0-5 |
| 5 | >60 | 0-5 | 0-5 | 0-5 | 0-5 | 0-5 |
| 6 | >60 | 0-5 | 0-5 | 0-5 | 0-5 | 0-5 |
| 7 | >60 | 0-5 | 0-5 | 0-5 | 0-5 | 0-5 |
| 8 | >60 | >5-10 | 0-5 | 0-5 | 0-5 | 0-5 |
| 9 | >60 | >5-10 | 0-5 | 0-5 | 0-5 | 0-5 |
| 10 | >60 | >5-10 | 0-5 | 0-5 | 0-5 | 0-5 |
| 11 | >60 | >5-10 | >5-10 | >5-10 | >5-10 | >5-10 |
| 12 | >60 | >5-10 | >5-10 | >5-10 | >5-10 | >5-10 |
| 13 | >60 | >5-10 | >5-10 | >5-10 | >5-10 | >5-10 |
| 14 | >60 | >10-30 | >10-30 | >10-30 | >10-30 | >10-30 |
| 15 | >60 | >10-30 | >10-30 | >10-30 | >10-30 | >10-30 |
| 16 | >60 | >30 | >10-30 | >10-30 | >10-30 | >10-30 |
| 17 | >60 | >30 | >30 | >10-30 | >10-30 | >10-30 |
| 18 | >60 | >30 | >30 | >10-30 | >10-30 | >10-30 |
| 19 | >60 | >30 | >30 | >30 | >30 | >30 |

* Below water level.
** Above water level.

Hydrologic features <3 ft are described using surface geometry classification.

KHON KAEN CROSS-COUNTRY MOBILITY ROUTES HYDROLOGIC GEOMETRY, SURFACE COMPOSITION AND VEGETATION FACTORS

SCALE






Table 3

Surface Composition-Vegetation Structure Factor Combinations

| Combination No. | Surface Composition RCI | Vegetation Structure Spacing of Stems, ft | | | | | | | |
|-----------------|-------------------------|---|--------|--------|--------|---|--------|--------|--------|
| | | Stems of Diameter Equal To or Less Than | | | | Stems of Diameter Equal To or More Than | | | |
| | | 1 in. | 2 in. | 3 in. | 50 in. | 1 in. | 2 in. | 3 in. | 10 in. |
| 1 | >60 | 0-5 | 0-5 | 0-5 | 0-5 | 0-5 | >30 | >30 | >30 |
| 2 | >60 | >30 | >30 | >30 | >30 | >30 | >30 | >30 | >30 |
| 3 | >60 | 0-5 | 0-5 | 0-5 | 0-5 | 0-5 | >5-10 | >10-30 | >30 |
| 4 | >60 | 0-5 | 0-5 | 0-5 | 0-5 | 0-5 | >5-10 | >30 | >30 |
| 5 | >60 | 0-5 | 0-5 | 0-5 | 0-5 | 0-5 | >10-30 | >10-30 | >30 |
| 6 | >60 | 0-5 | 0-5 | 0-5 | 0-5 | 0-5 | >10-30 | >30 | >30 |
| 7 | >60 | 0-5 | 0-5 | 0-5 | 0-5 | 0-5 | >30 | >30 | >30 |
| 8 | >60 | >5-10 | 0-5 | 0-5 | 0-5 | 0-5 | >5-10 | >10-30 | >30 |
| 9 | >60 | >5-10 | 0-5 | 0-5 | 0-5 | 0-5 | >5-10 | >30 | >30 |
| 10 | >60 | 10 | 0-5 | 0-5 | 0-5 | 0-5 | >10-30 | >10-30 | >30 |
| 11 | >60 | 5-10 | >5-10 | >5-10 | >5-10 | >5-10 | >5-10 | >10-30 | >30 |
| 12 | >60 | 5-10 | >5-10 | >5-10 | >5-10 | >5-10 | >10-30 | >10-30 | >30 |
| 13 | >60 | >5-10 | >5-10 | >5-10 | >5-10 | >5-10 | >10-30 | >30 | >30 |
| 14 | >60 | 5-10 | >10-30 | >10-30 | >10-30 | >10-30 | >10-30 | >10-30 | >30 |
| 15 | >60 | >10-30 | >10-30 | >10-30 | >10-30 | >10-30 | >10-30 | >30 | >30 |
| 16 | >60 | >30 | >10-30 | >10-30 | >10-30 | >10-30 | >10-30 | >30 | >30 |
| 17 | >60 | >30 | >30 | >10-30 | >10-30 | >10-30 | >10-30 | >10-30 | >30 |
| 18 | >60 | >30 | >30 | >10-30 | >10-30 | >10-30 | >10-30 | >30 | >30 |
| 19 | >60 | >30 | >30 | >30 | >30 | >30 | >30 | >30 | >30 |



21



| Terrain Type No. | Slope deg | Surface Geometry | | | Surf Comp Veg/As Comb |
|---------------------|--------------|---------------------------------------|----------------------------------|----------------------|--------------------------------|
| | | Vertical Obstacle Spacing ft | 180° Approach Angr: deg | Stop Height in | |
| 1 | 0-1.5 | >12-50 | 125-150 | >18-18 | 19 |
| 2 | 0-1.5 | >150 | 165-180 | 0-4 | 8 |
| 3 | 0-1.5 | >150 | 165-180 | 0-4 | 3 |
| 4 | 0-1.5 | >12-50 | 125-150 | >10-18 | 3 |
| 5 | 0-1.5 | >150 | 165-180 | 0-4 | 3 |
| 6A | 0-1.5 | >150 | 165-180 | 0-4 | 20 |
| 7 | 0-1.5 | >12-50 | 125-150 | >18-30 | 3 |
| 7A | 0-1.5 | >12-50 | 125-150 | >18-30 | 19 |
| 8 | 0-1.5 | >150 | 165-180 | 0-4 | 18 |
| 9 | 0-1.5 | >150 | 165-180 | 0-4 | 3 |
| 10 | 0-1.5 | >90-150 | 125-150 | >10-18 | 3 |
| 11 | 0-1.5 | >150 | 165-180 | 0-4 | 13 |
| 12 | 0-1.5 | >90-150 | 100-125 | >18-30 | 19 |
| 13 | 0-1.5 | >150 | 165-180 | 0-4 | 7 |
| 14 | 0-1.5 | >150 | 165-180 | 0-4 | 3 |
| 14A | 0-1.5 | >150 | 165-180 | 0-4 | 21 |
| 15 | 0-1.5 | >90-150 | 125-150 | >10-18 | 19 |
| 16 | 0-1.5 | >150 | 165-180 | 0-4 | 19 |
| 17 | >1.5-4.5 | >150 | 165-180 | >10-18 | 3 |
| 18 | 0-1.5 | >90-150 | 125-150 | >10-18 | 8 |
| 19 | 0-1.5 | >90-150 | 125-150 | >10-18 | 18 |
| 20 | 0-1.5 | >150 | 165-180 | 0-4 | 18 |
| 21 | 0-1.5 | >90-150 | 100-125 | >10-18 | 3 |
| 22 | 0-1.5 | >90-150 | 100-125 | >10-18 | 19 |
| 23 | 0-1.5 | >150 | 165-180 | 0-4 | 3 |
| 24 | 0-1.5 | >90-150 | 125-150 | >10-18 | 4 |
| 25 | 0-1.5 | >90-150 | 125-150 | >10-18 | 1 |
| 26 | 0-1.5 | >90-150 | 165-180 | >10-18 | 3 |
| 27 | 0-1.5 | >90-150 | 165-180 | >10-18 | 19 |
| 28 | 0-1.5 | >90-150 | 125-150 | >10-18 | 3 |
| 29 | 0-1.5 | >90-150 | 125-150 | >10-18 | 19 |
| 30 | 0-1.5 | >90-150 | 175-150 | >18-30 | 19 |
| 31 | 0-1.5 | >150 | 165-180 | >10-18 | 3 |
| 32 | 0-1.5 | >90-150 | 125-150 | >18-30 | 3 |
| 33 | 0-1.5 | >90-150 | 100-125 | >10-18 | 8 |
| 34 | 0-1.5 | >90-150 | 125-150 | >18-30 | 8 |
| 35 | 0-1.5 | >90-150 | 100-125 | >10-18 | 3 |
| 36 | >1.5-4.5 | >90-150 | 125-150 | >10-18 | 19 |
| 36A | >1.5-4.5 | >90-150 | 125-150 | >10-18 | 19 |
| 37 | >1.5-4.5 | >150 | 165-180 | 0-4 | 3 |
| 38 | >1.5-4.5 | >90-150 | 100-125 | >10-18 | 3 |
| 39 | >1.5-4.5 | >150 | 165-180 | 0-4 | 6 |
| 40 | >1.5-4.5 | >150 | 165-180 | 0-4 | 13 |
| 41 | >1.5-4.5 | >150 | 165-180 | 0-4 | 5 |
| 42 | >1.5-9 | >150 | 125-150 | >10-18 | 14 |
| 43 | >1.5-9 | >150 | 125-150 | >10-18 | 14 |
| 44 | >18-30 | >150 | 125-150 | >10-18 | 14 |
| 45 | >18-30 | >150 | 125-150 | >10-18 | 5 |
| 46 | 0-1.5 | >150 | 125-150 | >10-18 | 5 |
| 47 | 0-1.5 | >90-150 | 100-125 | >18-30 | 3 |
| 48 | 0-1.5 | >150 | 165-180 | 0-4 | 13 |
| 49 | >1.5-4.5 | >150 | 165-180 | 0-4 | 1 |
| 50 | >1.5-4.5 | >150 | 125-150 | 0-4 | 1 |
| 51 | >1.5-9 | >150 | 165-180 | 0-4 | 1 |

18° 20'

Ban Nong Hi



SCAL

Table 1


[illegible]

Wet Season Areal Terrain Types

A horizontal scale bar with markings at 0, 1, 2, 3, and 4 miles.



| Step Angle | Step Height in. | Surface Combination No. | Surface Combos. Index | Vegetation Structure Species of <i>Pinus</i> , % | | | | | | | |
|---------------|-----------------------|-------------------------------|-----------------------------|---|--------|--------|--------|--|--------|--------|--------|
| | | | | Stems of Diameter Equal to or Less Than | | | | Stems of Diameter Equal to or Greater Than | | | |
| | | | | 8 in. | 12 in. | 16 in. | 20 in. | 1 in. | 16 in. | 20 in. | 24 in. |
| 125-180 | 0-4 | 3 | >60 | 0-5 | 0-5 | 0-5 | 0-5 | 0-5 | >30 | >30 | >30 |
| 125-180 | 0-4 | 2 | >60 | >30 | >30 | >10-30 | >10-30 | >10-30 | >10-30 | >10-30 | >30 |
| 125-180 | >10-18 | 6 | >60 | 0-5 | >10 | >10-30 | >10-30 | >10-30 | >10-30 | >10-30 | >30 |
| 125-180 | >10-18 | 3 | >60 | 0-5 | 0-5 | 0-5 | 0-5 | 0-5 | >30 | >30 | >30 |
| 125-180 | >10-18 | 20 | >60 | 0-5 | 0-5 | 0-5 | 0-5 | 0-5 | >10-30 | >30 | >30 |
| 125-180 | >10-18 | 20 | 25-60 | 0-5 | 0-5 | 0-5 | 0-5 | 0-5 | >10-30 | >10-30 | >30 |
| 125-180 | 0-4 | 17 | >60 | >10 | >10 | >10 | >10 | >10 | >10-30 | >10-30 | >30 |
| 125-180 | 0-4 | 11 | >60 | >30 | >10-30 | >10-30 | >10-30 | >10-30 | >10-30 | >30 | >30 |
| 125-180 | >10-48 | 3 | >60 | 0-5 | 0-5 | 0-5 | 0-5 | 0-5 | >30 | >30 | >30 |
| 125-180 | 0-4 | 3 | >60 | 0-5 | 0-5 | 0-5 | 0-5 | 0-5 | >30 | >30 | >30 |
| 125-180 | 0-4 | 3 | >60 | 0-5 | 0-5 | 0-5 | 0-5 | 0-5 | >30 | >30 | >30 |
| 125-180 | >4-10 | 1 | >60 | 0-5 | 0-5 | 0-5 | 0-5 | 0-5 | >10-30 | >30 | >30 |
| 125-180 | >4-10 | 9 | >60 | 0-5 | 0-5 | 0-5 | 0-5 | 0-5 | >10-30 | >30 | >30 |
| 125-180 | 0-4 | 2 | >60 | >30 | >30 | >10-30 | >10-30 | >10-30 | >10-30 | >10-30 | >30 |
| 125-180 | >4-10 | 19 | 25-60 | 0-5 | 0-5 | 0-5 | 0-5 | 0-5 | >30 | >30 | >30 |
| 125-180 | >4-10 | 4 | >60 | >10 | 0-5 | 0-5 | 0-5 | 0-5 | >10-30 | >30 | >30 |
| 125-180 | 0-4 | 7 | >60 | 0-5 | 0-5 | 0-5 | 0-5 | 0-5 | >10-30 | >10-30 | >30 |
| 125-180 | >10-18 | 3 | >60 | 0-5 | 0-5 | 0-5 | 0-5 | 0-5 | >30 | >30 | >30 |
| 125-180 | >10-18 | 2 | >60 | >30 | >30 | >10-30 | >10-30 | >10-30 | >10-30 | >10-30 | >30 |
| 125-180 | >10-18 | 2 | >60 | >30 | >30 | >10-30 | >10-30 | >10-30 | >10-30 | >10-30 | >30 |
| 125-180 | >10-18 | 22 | 25-60 | >30 | >30 | >10-30 | >10-30 | >10-30 | >10-30 | >10-30 | >30 |
| 125-180 | 0-4 | 7 | >60 | 0-5 | 0-5 | 0-5 | 0-5 | 0-5 | >10-30 | >10-30 | >30 |
| 125-180 | >10-18 | 3 | >60 | 0-5 | 0-5 | 0-5 | 0-5 | 0-5 | >30 | >30 | >30 |
| 125-180 | >10-18 | 19 | 25-60 | 0-5 | 0-5 | 0-5 | 0-5 | 0-5 | >30 | >30 | >30 |
| 125-180 | 0-4 | 5 | >60 | >10 | 0-5 | 0-5 | 0-5 | 0-5 | >10-30 | >10-30 | >30 |
| 125-180 | 0-4 | 5 | >60 | >10 | 0-5 | 0-5 | 0-5 | 0-5 | >10-30 | >10-30 | >30 |
| 125-180 | >10-18 | 5 | >60 | >10 | 0-5 | 0-5 | 0-5 | 0-5 | >10-30 | >10-30 | >30 |
| 125-180 | 0-4 | 5 | >60 | >10 | 0-5 | 0-5 | 0-5 | 0-5 | >10-30 | >10-30 | >30 |
| 125-180 | >4-10 | 4 | >60 | >10 | 0-5 | 0-5 | 0-5 | 0-5 | >10-30 | >10-30 | >30 |
| 125-180 | >4-10 | 1 | >60 | 0-5 | 0-5 | 0-5 | 0-5 | 0-5 | >30 | >30 | >30 |
| 125-180 | >10-18 | 19 | 25-60 | 0-5 | 0-5 | 0-5 | 0-5 | 0-5 | >30 | >30 | >30 |
| 125-180 | >10-18 | 1 | >60 | 0-5 | 0-5 | 0-5 | 0-5 | 0-5 | >30 | >30 | >30 |
| 125-180 | 0-4 | 1 | >60 | >10 | 0-5 | 0-5 | 0-5 | 0-5 | >10-30 | >30 | >30 |
| 125-180 | 0-4 | 16 | >60 | 0-5 | 0-5 | 0-5 | 0-5 | 0-5 | >10-30 | >10-30 | >30 |
| 125-180 | 0-4 | 10 | >60 | >30 | >30 | >10-30 | >10-30 | >10-30 | >10-30 | >30 | >30 |
| 125-180 | >10-18 | 11 | >60 | >30 | >10-30 | >10-30 | >10-30 | >10-30 | >10-30 | >30 | >30 |
| 125-180 | >18-30 | 3 | >60 | 0-5 | 0-5 | 0-5 | 0-5 | 0-5 | >30 | >30 | >30 |
| 125-180 | >18-30 | 19 | 25-60 | 0-5 | 0-5 | 0-5 | 0-5 | 0-5 | >30 | >30 | >30 |
| 125-180 | >18-30 | 16 | >60 | 0-5 | 0-5 | 0-5 | 0-5 | 0-5 | >30 | >30 | >30 |
| 125-180 | >4-10 | 3 | >60 | 0-5 | 0-5 | 0-5 | 0-5 | 0-5 | >30 | >30 | >30 |
| 125-180 | >4-10 | 19 | 25-60 | 0-5 | 0-5 | 0-5 | 0-5 | 0-5 | >30 | >30 | >30 |
| 125-180 | >4-10 | 14 | >60 | >10 | 0-5 | 0-5 | 0-5 | 0-5 | >10-30 | >30 | >30 |
| 125-180 | >4-10 | 10 | >60 | >30 | >30 | >10-30 | >10-30 | >10-30 | >10-30 | >30 | >30 |
| 125-180 | 0-4 | 19 | 25-60 | 0-5 | 0-5 | 0-5 | 0-5 | 0-5 | >30 | >30 | >30 |
| 125-180 | 0-4 | 18 | 25-60 | >30 | >30 | >30 | >30 | >30 | >30 | >30 | >30 |
| 125-180 | >10-18 | 7 | >60 | 0-5 | 0-5 | 0-5 | 0-5 | 0-5 | >10-30 | >10-30 | >30 |
| 125-180 | >10-18 | 19 | 25-60 | 0-5 | 0-5 | 0-5 | 0-5 | 0-5 | >30 | >30 | >30 |
| 125-180 | 0-4 | 15 | >60 | >10 | >10 | >10 | >10 | >10 | >10-30 | >10-30 | >30 |
| 125-180 | >10-18 | 3 | >60 | 0-5 | 0-5 | 0-5 | 0-5 | 0-5 | >30 | >30 | >30 |
| 125-180 | >10-18 | 19 | 25-60 | 0-5 | 0-5 | 0-5 | 0-5 | 0-5 | >30 | >30 | >30 |
| 125-180 | >4-10 | 3 | >60 | 0-5 | 0-5 | 0-5 | 0-5 | 0-5 | >30 | >30 | >30 |
| 125-180 | >4-10 | 19 | 25-60 | 0-5 | 0-5 | 0-5 | 0-5 | 0-5 | >30 | >30 | >30 |
| 125-180 | 0-4 | 8 | >60 | >10-30 | >10-30 | >10-30 | >10-30 | >10-30 | >10-30 | >10-30 | >30 |



2




Table 1
Hydrologic Geometry Factor Combinations
Water Depth < 3 Feet*

| Unit | West Bank | | | East Bank | | | Dry Water |
|------|------------------|-----------------|-----------------|------------------|-----------------|-----------------|-----------|
| | Angle at Base of | Angle at Top of | Step Height in. | Angle at Base of | Angle at Top of | Step Height in. | |
| 649 | 150-165 | 180-200 | ~18-30 | 150-165 | 180-200 | ~18-30 | 1 |
| 676 | 165-180 | 180-200 | ~18-30 | 150-165 | 180-200 | ~18-30 | 1 |
| 679 | 165-180 | 180-200 | ~18-30 | 165-180 | 180-200 | ~18-30 | 1 |
| 684 | 165-180 | 190-200 | ~30-48 | 165-180 | 180-200 | ~30-48 | 1 |
| 705 | 125-150 | 200-210 | ~30-48 | 125-150 | 200-210 | ~30-48 | 10 |
| 752 | 150-165 | 200-210 | ~30-48 | 125-150 | 210-220 | ~30-48 | 10 |
| 755 | 150-165 | 200-210 | ~30-48 | 150-165 | 200-210 | ~30-48 | 8, 10, 12 |
| 835 | 125-150 | 210-220 | ~30-48 | 125-150 | 210-220 | ~30-48 | 10 |
| 836 | 125-150 | 210-220 | ~30-48 | 125-150 | 220 | ~30-48 | 10 |
| 836 | 125-150 | 210-220 | ~30-48 | 150-165 | 210-220 | ~30-48 | 10 |
| 844 | 125-150 | 210-220 | ~48-66 | 125-150 | 210-220 | ~48-66 | 10 |
| 847 | 125-150 | 210-220 | ~48-66 | 150-165 | 200-210 | ~48-66 | 10 |

* Hydrologic features < 3 ft are described using surface geometry classification.

KHON KAEN MOBILITY

Wet Season Line




Table 2
Hydrologic Geometry Factor Combinations
Water Depth > 3 Feet

| West Bank | East Bank |
|---------------------|---------------------|
| Approach Angle | Approach Angle |
| Top of Step, deg | Top of Step, deg |
| Step Height, in. | Step Height, in. |
| Dry Season Map Unit | Dry Season Map Unit |
| Water Depth < 3 ft | Water Depth < 3 ft |
| Water Depth > 3 ft | Water Depth > 3 ft |
| 1 | 1 |
| 2 | 2 |
| 3 | 3 |
| 4 | 4 |
| 5 | 5 |
| 6 | 6 |
| 7 | 7 |
| 8 | 8 |
| 9 | 9 |
| 10 | 10 |
| 11 | 11 |
| 12 | 12 |
| 13 | 13 |
| 14 | 14 |
| 15 | 15 |
| 16 | 16 |
| 17 | 17 |
| 18 | 18 |
| 19 | 19 |
| 20 | 20 |
| 21 | 21 |
| 22 | 22 |
| 23 | 23 |
| 24 | 24 |
| 25 | 25 |
| 26 | 26 |
| 27 | 27 |
| 28 | 28 |
| 29 | 29 |
| 30 | 30 |
| 31 | 31 |
| 32 | 32 |
| 33 | 33 |
| 34 | 34 |
| 35 | 35 |
| 36 | 36 |
| 37 | 37 |
| 38 | 38 |
| 39 | 39 |
| 40 | 40 |
| 41 | 41 |
| 42 | 42 |
| 43 | 43 |
| 44 | 44 |
| 45 | 45 |
| 46 | 46 |
| 47 | 47 |
| 48 | 48 |
| 49 | 49 |
| 50 | 50 |
| 51 | 51 |
| 52 | 52 |
| 53 | 53 |
| 54 | 54 |
| 55 | 55 |
| 56 | 56 |
| 57 | 57 |
| 58 | 58 |
| 59 | 59 |
| 60 | 60 |
| 61 | 61 |
| 62 | 62 |
| 63 | 63 |
| 64 | 64 |
| 65 | 65 |
| 66 | 66 |
| 67 | 67 |
| 68 | 68 |
| 69 | 69 |
| 70 | 70 |
| 71 | 71 |
| 72 | 72 |
| 73 | 73 |
| 74 | 74 |
| 75 | 75 |
| 76 | 76 |
| 77 | 77 |
| 78 | 78 |
| 79 | 79 |
| 80 | 80 |
| 81 | 81 |
| 82 | 82 |
| 83 | 83 |
| 84 | 84 |
| 85 | 85 |
| 86 | 86 |
| 87 | 87 |
| 88 | 88 |
| 89 | 89 |
| 90 | 90 |
| 91 | 91 |
| 92 | 92 |
| 93 | 93 |
| 94 | 94 |
| 95 | 95 |
| 96 | 96 |
| 97 | 97 |
| 98 | 98 |
| 99 | 99 |
| 100 | 100 |

| West Bank | East Bank |
|----------------------------|----------------------------|
| Contact Approach Angle | Contact Approach Angle |
| Step Height, in. | Step Height, in. |
| Position of Step Base, in. | Position of Step Base, in. |
| Water Depth < 3 ft | Water Depth < 3 ft |
| Water Depth > 3 ft | Water Depth > 3 ft |
| 1 | 1 |
| 2 | 2 |
| 3 | 3 |
| 4 | 4 |
| 5 | 5 |
| 6 | 6 |
| 7 | 7 |
| 8 | 8 |
| 9 | 9 |
| 10 | 10 |
| 11 | 11 |
| 12 | 12 |
| 13 | 13 |
| 14 | 14 |
| 15 | 15 |
| 16 | 16 |
| 17 | 17 |
| 18 | 18 |
| 19 | 19 |
| 20 | 20 |
| 21 | 21 |
| 22 | 22 |
| 23 | 23 |
| 24 | 24 |
| 25 | 25 |
| 26 | 26 |
| 27 | 27 |
| 28 | 28 |
| 29 | 29 |
| 30 | 30 |
| 31 | 31 |
| 32 | 32 |
| 33 | 33 |
| 34 | 34 |
| 35 | 35 |
| 36 | 36 |
| 37 | 37 |
| 38 | 38 |
| 39 | 39 |
| 40 | 40 |
| 41 | 41 |
| 42 | 42 |
| 43 | 43 |
| 44 | 44 |
| 45 | 45 |
| 46 | 46 |
| 47 | 47 |
| 48 | 48 |
| 49 | 49 |
| 50 | 50 |
| 51 | 51 |
| 52 | 52 |
| 53 | 53 |
| 54 | 54 |
| 55 | 55 |
| 56 | 56 |
| 57 | 57 |
| 58 | 58 |
| 59 | 59 |
| 60 | 60 |
| 61 | 61 |
| 62 | 62 |
| 63 | 63 |
| 64 | 64 |
| 65 | 65 |
| 66 | 66 |
| 67 | 67 |
| 68 | 68 |
| 69 | 69 |
| 70 | 70 |
| 71 | 71 |
| 72 | 72 |
| 73 | 73 |
| 74 | 74 |
| 75 | 75 |
| 76 | 76 |
| 77 | 77 |
| 78 | 78 |
| 79 | 79 |
| 80 | 80 |
| 81 | 81 |
| 82 | 82 |
| 83 | 83 |
| 84 | 84 |
| 85 | 85 |
| 86 | 86 |
| 87 | 87 |
| 88 | 88 |
| 89 | 89 |
| 90 | 90 |
| 91 | 91 |
| 92 | 92 |
| 93 | 93 |
| 94 | 94 |
| 95 | 95 |
| 96 | 96 |
| 97 | 97 |
| 98 | 98 |
| 99 | 99 |
| 100 | 100 |

Table 3
Surface Composition-Vegetation

| Combination No. | Surface Composition | Stems of Diameter Equal to or |
|-----------------|---------------------|-------------------------------|
| | | 2 in. |
| 1 | 25-60 | 0-5 |
| 2 | 25-60 | 0-5 |
| 3 | 25-60 | 0-5 |
| 4 | 25-60 | 0-5 |
| 5 | 25-60 | 0-5 |
| 6 | 25-60 | 0-5 |
| 7 | 25-60 | 0-5 |
| 8 | 25-60 | 0-5 |
| 9 | 25-60 | 0-5 |
| 10 | 25-60 | 0-5 |
| 11 | 25-60 | 0-5 |
| 12 | 25-60 | 0-5 |
| 13 | 25-60 | 0-5 |
| 14 | 25-60 | 0-5 |
| 15 | 25-60 | 0-5 |
| 16 | 25-60 | 0-5 |
| 17 | 25-60 | 0-5 |
| 18 | 25-60 | 0-5 |
| 19 | 25-60 | 0-5 |
| 20 | 25-60 | 0-5 |
| 21 | 25-60 | 0-5 |
| 22 | 25-60 | 0-5 |
| 23 | 25-60 | 0-5 |
| 24 | 25-60 | 0-5 |
| 25 | 25-60 | 0-5 |
| 26 | 25-60 | 0-5 |
| 27 | 25-60 | 0-5 |
| 28 | 25-60 | 0-5 |
| 29 | 25-60 | 0-5 |
| 30 | 25-60 | 0-5 |
| 31 | 25-60 | 0-5 |
| 32 | 25-60 | 0-5 |
| 33 | 25-60 | 0-5 |
| 34 | 25-60 | 0-5 |
| 35 | 25-60 | 0-5 |
| 36 | 25-60 | 0-5 |
| 37 | 25-60 | 0-5 |
| 38 | 25-60 | 0-5 |
| 39 | 25-60 | 0-5 |
| 40 | 25-60 | 0-5 |
| 41 | 25-60 | 0-5 |
| 42 | 25-60 | 0-5 |
| 43 | 25-60 | 0-5 |
| 44 | 25-60 | 0-5 |
| 45 | 25-60 | 0-5 |
| 46 | 25-60 | 0-5 |
| 47 | 25-60 | 0-5 |
| 48 | 25-60 | 0-5 |
| 49 | 25-60 | 0-5 |
| 50 | 25-60 | 0-5 |
| 51 | 25-60 | 0-5 |
| 52 | 25-60 | 0-5 |
| 53 | 25-60 | 0-5 |
| 54 | 25-60 | 0-5 |
| 55 | 25-60 | 0-5 |
| 56 | 25-60 | 0-5 |
| 57 | 25-60 | 0-5 |
| 58 | 25-60 | 0-5 |
| 59 | 25-60 | 0-5 |
| 60 | 25-60 | 0-5 |
| 61 | 25-60 | 0-5 |
| 62 | 25-60 | 0-5 |
| 63 | 25-60 | 0-5 |
| 64 | 25-60 | 0-5 |
| 65 | 25-60 | 0-5 |
| 66 | 25-60 | 0-5 |
| 67 | 25-60 | 0-5 |
| 68 | 25-60 | 0-5 |
| 69 | 25-60 | 0-5 |
| 70 | 25-60 | 0-5 |
| 71 | 25-60 | 0-5 |
| 72 | 25-60 | 0-5 |
| 73 | 25-60 | 0-5 |
| 74 | 25-60 | 0-5 |
| 75 | 25-60 | 0-5 |
| 76 | 25-60 | 0-5 |
| 77 | 25-60 | 0-5 |
| 78 | 25-60 | 0-5 |
| 79 | 25-60 | 0-5 |
| 80 | 25-60 | 0-5 |
| 81 | 25-60 | 0-5 |
| 82 | 25-60 | 0-5 |
| 83 | 25-60 | 0-5 |
| 84 | 25-60 | 0-5 |
| 85 | 25-60 | 0-5 |
| 86 | 25-60 | 0-5 |
| 87 | 25-60 | 0-5 |
| 88 | 25-60 | 0-5 |
| 89 | 25-60 | 0-5 |
| 90 | 25-60 | 0-5 |
| 91 | 25-60 | 0-5 |
| 92 | 25-60 | 0-5 |
| 93 | 25-60 | 0-5 |
| 94 | 25-60 | 0-5 |
| 95 | 25-60 | 0-5 |
| 96 | 25-60 | 0-5 |
| 97 | 25-60 | 0-5 |
| 98 | 25-60 | 0-5 |
| 99 | 25-60 | 0-5 |
| 100 | 25-60 | 0-5 |

* Above water level.
** Below water level.

KHON KAEN CROSS-COUNTRY MOBILITY ROUTES

Wet Season Linear Terrain Types






Table 3

Surface Composition-Vegetation Structure Factor Combinations

| Combination No. | Surface Composition MCI | Vegetation Structure Spacing of Stems, ft | | | | | | | |
|-----------------|-------------------------|---|-------|-------|--------|---|-------|-------|--------|
| | | Stems of Diameter Equal to or Less Than | | | | Stems of Diameter Equal to or More Than | | | |
| | | 2 in. | 3 in. | 4 in. | 50 in. | 1 in. | 3 in. | 6 in. | 10 in. |
| 1 | 25-60 | 0-5 | 0-5 | 0-5 | 0-5 | 0-5 | >30 | >30 | >30 |
| 1A | >60 | 0-5 | 0-5 | 0-5 | 0-5 | 0-5 | >30 | >30 | >30 |
| 2 | 25-60 | >30 | >30 | >30 | >30 | >30 | >30 | >30 | >30 |
| 3 | >60 | 0-5 | 0-5 | 0-5 | 0-5 | 0-5 | >30 | >30 | >30 |
| 3A | 25-60 | 0-5 | 0-5 | 0-5 | 0-5 | 0-5 | >30 | >30 | >30 |
| 4 | >60 | 0-5 | 0-5 | 0-5 | 0-5 | 0-5 | >30 | >30 | >30 |
| 5 | >60 | 0-5 | 0-5 | 0-5 | 0-5 | 0-5 | >30 | >30 | >30 |
| 6 | >60 | 0-5 | 0-5 | 0-5 | 0-5 | 0-5 | >30 | >30 | >30 |
| 7 | >60 | 0-5 | 0-5 | 0-5 | 0-5 | 0-5 | >30 | >30 | >30 |
| 8 | >60 | >30 | 0-5 | 0-5 | 0-5 | 0-5 | >30 | >30 | >30 |
| 9 | >60 | >30 | 0-5 | 0-5 | 0-5 | 0-5 | >30 | >30 | >30 |
| 10 | >60 | >30 | 0-5 | 0-5 | 0-5 | 0-5 | >30 | >30 | >30 |
| 11 | >60 | >30 | >30 | >30 | >30 | >30 | >30 | >30 | >30 |
| 11A | 25-60 | >30 | >30 | >30 | >30 | >30 | >30 | >30 | >30 |
| 12 | >60 | >30 | >30 | >30 | >30 | >30 | >30 | >30 | >30 |
| 13 | >60 | >30 | >30 | >30 | >30 | >30 | >30 | >30 | >30 |
| 14 | >60 | >30 | >30 | >30 | >30 | >30 | >30 | >30 | >30 |
| 15 | >60 | >30 | >30 | >30 | >30 | >30 | >30 | >30 | >30 |
| 16 | >60 | >30 | >30 | >30 | >30 | >30 | >30 | >30 | >30 |
| 17 | >60 | >30 | >30 | >30 | >30 | >30 | >30 | >30 | >30 |
| 18 | >60 | >30 | >30 | >30 | >30 | >30 | >30 | >30 | >30 |
| 19 | >60 | >30 | >30 | >30 | >30 | >30 | >30 | >30 | >30 |



ROUTE 1

ROUTE 2

ROUTE 3

SHADED AREAS DENOTE TERRAIN WHERE SOIL STRENGTH CHANGED FROM DRY SEASON TO 25-40 DURING WET SEASON

Ban Nong Hi

10° 30'

10° 20'



100° 40'

3

KHON KAEN CROSS MOBILITY ROAD


Soil Strength Map (Denotes Terrain Types in which Changes of Soil Strength from Dry Season to Wet Season)

SCALE




SHADED AREAS DENOTE TERRAIN TYPES IN WHICH SOIL STRENGTH CHANGED FROM >60 DURING DRY SEASON TO 25-60 DURING WET SEASON.






2




3

KHON KAEN CROSS- MOBILITY ROUTE


Soil Strength Map (Wet)



SCALE



AREAS DENOTE ALL TERRAIN TYPES IN
THE SOIL STRENGTH IS 25-60 RCI.




4

KHON KAEN CROSS-COUNTRY MOBILITY ROUTES

Soil Strength Map (Wet Season)


SCALE

0 1 2 3 4 MILES



Ban Saeng Kaeo

10° 20'
103° 00'






Ban Nong Hi


3

KHON KAEN CROSS-COUNTRY MOBILITY ROUTES


M356
Dry Season

SCALE





SCALE



16° 20'

4


KHON KAEN CROSS-COUNTRY MOBILITY ROUTES


M656 TRAVERSE

WET SEASON SOIL STRENGTH
60 AND 40 RCI

SCALE

0 1 2 3 4 MILES





LEGEND

OPTIMUM PATH SELECTED WITHIN THE BOUNDARIES OF
ROUTE : BETWEEN BAN MENG AND BAN SANG KAE0.
NUMBER INDICATES VEHICLE SPEED IN MPH WITHIN EACH
TERRAIN TYPE.

8.0




LAKE

Ban Nong Hi

3

KHON KAEN CROSS-
MOBILITY ROUTE
VEHICLE M656 TRA
WET SEASON SOIL S
60 AND 35 R



SCALE



4

G


SCALE



Ban Sang Kaeo

103°00'

16°20'



LEGEND

- OPTIMUM PATH SELECTED WITHIN THE BOUNDARIES OF ROUTE 1 BETWEEN SAN MENG AND BAN SANG KAEO.
- 7.2 NUMBER INDICATES VE ICLE SPEED IN MPH WITHIN EACH TERRAIN TYPE.
- LAKE

10° 30'

[illegible]

ROUTE 3



Ban Nong Hi

Ban Nong Hi

KHON KAEN CROSS-COUNTY
MOBILITY ROUTES

M54A2
Dry Season

SCALE





4

KHON KAEN CROSS-COUNTRY MOBILITY ROUTES

M54A2
Dry Season

SCALE





LEGEND



OPTIMUM PATH SELECTED WITHIN THE BOUNDARIES OF
ROUTE 1 BETWEEN BAN MENG AND BAN SANG KAEO.
NUMBER INDICATES VEHICLE SPEED IN MPH WITHIN EACH
TERRAIN TYPE.
LAKE

7.8



10° 30'

21





3

KHON KAEN CRO MOBILITY R

M54A2 TRAV
WET SEASON SOIL
60 AND 40

SCALE





10° 20'


4

KHON KAEN CROSS-COUNTRY MOBILITY ROUTES

M54A2 TRAVERSE
WET SEASON SOIL STRENGTH
60 AND 40 RCI

SCALE






LEGEND

- OPTIMUM PATH SELECTED WITHIN THE BOUNDARIES OF ROUTE 1 BETWEEN BAN MENG AND BAN SANG KAEO.
- 10.0 NUMBER INDICATES VEHICLE SPEED IN MPH WITHIN EACH TERRAIN TYPE.
- LAKE



21



3 1

KHON KAEN C
MOBILITY
VEHICLE M5
WET SEASON
60 AND

SC




4


KHON KAEN CROSS-COUNTRY MOBILITY ROUTES


VEHICLE M54A2 TRAVERSE
WET SEASON SOIL STRENGTH
60 AND 35 RCI

SCALE



Ban Sang Nueo







The map displays three distinct routes through a mountainous terrain. Route 1 is the uppermost, Route 2 is the middle, and Route 3 is the lowermost. The map includes contour lines, elevation markers, and a scale bar. The location 'Ban Nong Hi' is marked at the bottom right.

3

KHON KAEN CROSS-COUNTRY MOBILITY ROUTES

M520
Dry Season


SCALE



4


Dry Season

A horizontal scale bar with markings at 1, 2, 3, and 4 miles.



Ben Say Koo

Plate 13






100° 30'

10° 20'

LEGEND

- OPTIMUM PATH SELECTED WITHIN THE BOUNDARIES OF ROUTE 1 BETWEEN BAN MENG AND BAN SANG KAEO.
- 72 NUMBER INDICATES VEHICLE SPEED IN MPH WITHIN EACH TERRAIN TYPE.
- LAKE






KHON KAEN CROSS-COUNTRY MOBILITY ROUTES


M520 TRAVERSE


WET SEASON SOIL STRENGTH
60 AND 40 RCI

SCALE



Ban Sang Kaeo







ROUTE 3

Ban Nong Hi

Ban Nong Hi

WET SEASON SOIL STR
60 AND 35 RCI





21

ROUTE 1


ROUTE 2

ROUTE 3

10° 30'

10° 30'


Ban Hong Hi



3

DRY SEASON

SCALE



4


KHON KAEN CROSS-COUNTRY MOBILITY ROUTES


M548

DRY SEASON

SCALE

0 1 2 3 4 MILES





LEGEND

- OPTIMUM PATH SELECTED WITHIN THE BOUNDARIES OF ROUTE 1 BETWEEN BAN MENG AND BAN SANG KAO.
- 10.0 NUMBER INDICATES VEHICLE SPEED IN MPH WITHIN EACH TERRAIN TYPE.
- LAKE




KHON KAEN CROSS-COUNTRY MOBILITY ROUTES


M548 TRAVERSE
WET SEASON SOIL STRENGTH
60 AND 40 RCI

SCALE

0 1 2 3 4 MILES



10° 20' 100° 50'



10.0



10.0

21

ROUTE 1


10°20'

ROUTE 2


ROUTE 3

Ban Nong Hi

10°20'
100°45'






3




KHON KAEN CROSS-COUNTRY MOBILITY ROUTES

VEHICLE M48 TRAVERSE
WET SEASON SOIL STRENGTH
60 AND 35 RCI

SCALE





21

ROUTE 1

16°30'


ROUTE 2

ROUTE 3

Ban Nong Hi

16°20'


103°40'






3

KHON KAEN CROSS-COUNTRY MOBILITY ROUTES

M113A1 TRAVERSE
DRY SEASON SOIL STRENGTH
60 AND 40 RCI



SCALE



APPENDIX A: WES ANALYTICAL MODEL FOR PREDICTING
OFF-ROAD GROUND VEHICLE PERFORMANCE

1. The WES analytical model for predicting cross-country performance is described in detail in WES Technical Report No. 3-783, "An Analytical Model for Predicting Cross-Country Vehicle Performance," which is now in preparation. This model uses as input data terrain characteristics, vehicle characteristics and performance, and terrain-vehicle performance relations to predict performance in terms of speed, fuel consumption, and delivery rate.

2. The portion of the WES analytical model that pertains to vehicle performance predictions (speed and delivery rate) in areal terrain factor complexes composed of any combination of factors of surface composition, surface geometry, and vegetation was used in this study and is identified in fig.A1 as program 1. Brief discussions of the basic relations used and the application of the WES model are presented in tables A1 and A2, respectively.





Fig. A1. WES analytical model for predicting vehicle performance




P_1 = AVAILABLE PROPELLING FORCE
 R_s = MOTION RESISTANCE DUE TO SOIL
 F_g = FORCE DUE TO GRAVITY
 F_{om} = AVERAGE FORCE REQUIRED TO CROSS MULTIPLE OBSTACLES
 F_o = AVERAGE FORCE REQUIRED TO OVERRIDE MULTIPLE STEMS
 S_D = SPEED ACROSS OBSTACLE CONTROLLED BY DYNAMIC RESPONSE

for predicting vehicle performance

SURFACE GEOMORPHOLOGY


Slopes

The effect of macroslopes (slopes long on vehicle speed is taken into account in to compute the forces due to gravity as shown



Large scale linear obstacles


For such obstacles as ditches, dikes, vehicle-terrain model is constructed to determine and if not to determine the maximum vehicle the vehicle attempts to negotiate the obstacle following sketches.



Although vehicles rarely attain the maximum speed permitted by the surface they are crossing,³ the above relation may be considered as the baseline of the WbS model. On the tractive force axis are entered the other resisting forces; on the speed axis are entered speed limits imposed by surface roughness, visibility and the effects of water crossings (swimming, fording, and entrances and exits from streams).

Large scale nonlinear obstacles

Boulders, mounds, craters, and other. If the vehicle may override (vertical obstacles) are evaluated in the same manner as the large obstacle is concerned. For those which may be determined by the area denied-speed relation or predicted relation which indicates the area denied is within the limits of 10 percent or less than 10 percent, there is no effect. If more than 10 percent, the area is impassable. This is shown in the sketch below.



1, 2 Raised numbers refer to the List of References at the end of this paper.


2

Table A1

BASIC RELATIONS USED IN THE WES MODEL


SURFACE GEOMETRY

cross-slopes (slopes longer than wheelbase or track length) taken into account in the model by use of classic formulas due to gravity as shown in the following sketch.



Obstacles

As ditches, dikes, etc., a two-dimensional geometric model is constructed to determine if interference will occur, and the maximum vehicle attitude angle that will occur as the vehicle negotiates the obstacle. Examples are shown in the



Maximum Attitude Angle, α

For the vehicle to negotiate the maximum vehicle attitude angle, the maximum force required due to the abrupt irregularity.

Obstacles



Craters, and other large-scale nonlinear obstacles which require (vertical obstacles) or may avoid (lateral obstacles) in the same manner as the large-scale linear obstacles insofar as they are avoided. For those which may be avoided, the effect on speed is a denied-speed relation.⁴ This is an empirically established relation which indicates the effect maneuvering has on speed when the area denied is within the limits of 10 percent and 60 percent. When area denied is greater than 60 percent, there is no effect on speed; when area denied is greater than 10 percent and less than 60 percent, the area is impassable. The general form of the relation is shown below.

Maximum speed of vehicle

Area Denied, %

Small scale obstacles

Small scale obstacles (surface roughness) which cause vibration or vertical acceleration of the vehicle, may be linear or non-linear and may or may not be avoidable. For those which are unavoidable, the average force-speed-obstacle height relations¹ are used to determine the average force required for override and the speed-obstacle height-vertical acceleration relation² is used to limit the speed on the basis of driver tolerance to vertical acceleration. Examples of these relations are shown in the sketches below:




The effect on vehicle speed of small scale irregularities which are avoided is determined by the area denied-speed relations cited above.

VEGETATION

Override

The effect of overriding vegetation on speed is considered by the model in terms of force required to override multiple trees. Established relations⁶ of stem diameter-spacing - work required to override and maximum bending stress for speeds of 0.1 to 17.0 mph at a range of pushbar heights are used to derive the relation of average force required to override multiple trees and stem diameters overridden. An example of the derived relation is shown below:



The force required to fall a single tree of each size is compared to the force the leading edge of the vehicle can withstand to determine the maximum size tree that can be overridden and is also used to determine longitudinal acceleration of the vehicle in a further check that limits the size tree overridden to one that will not produce a longitudinal acceleration greater than the driver's tolerance (2.0 g).


*Except when otherwise indicated, stem diameter refers to maximum size overridden, hence all smaller stems are overridden and all larger stems are avoided.

Maneuvering

The effect of maneuvering (avoiding trees) on vehicle speed is determined by the area denied - speed relations in a manner analogous to that for non-linear obstacles.

Visibility

The constraint placed upon speed by visibility is considered to be a function of the distance at which a driver can recognize an obstacle he wishes to avoid. While the recognition distance-speed relation is not well-defined at the present time, some work has been done in this area⁷, and the general form of the relation has been established as indicated in the following sketch:



HYDROLOGIC GEOMETRY

Although vehicle performance in features such as streams and channels is a part of the WES model, predictions for these features are generally made separately. Consideration is given to whether or not the vehicle can negotiate the obstacle, and if so, the time required is determined, based on an arbitrary speed for entry and exit, and for fording. The rated water speed is used to compute the time required for swimming. The results of certain work to date involving stream crossings in tropical and temperate areas and the hydrologic feature - vehicle relations will be presented in a report⁸ now under preparation at WES. From the knowledge gained in these studies, the entry and exit speed and fording speed is considered to be 2.0 mph.

FUEL CONSUMPTION

Fuel consumption rate-speed relations for full-load and no-load conditions are used in the model to develop average fuel consumption rates for the vehicle when the engine is producing maximum power and when the engine is idling.

When the speed is limited by traction the average rate for full-load condition (maximum power) is used.

When the vehicle is going down slope and the effect of gravity exceeds the resisting force, the average rate for no-load condition is used.


When the predicted speed is limited by factors other than traction available, e.g., dynamic response, visibility, the ratio of the force required to propel the vehicle to the maximum tractive force available at the predicted speed is used to linearly interpolate between the average fuel consumption rates for no-load and full-load conditions.

AREAL TERRAIN UNITS

The method by which performance is predicted for a specific areal terrain unit is outlined briefly in the following seven steps.


Step 1. Determine the tractive force (T_f) - speed relation considering the effects of soil strength, motion resistance, R_s , and resisting force due to gravity, F_g .

Step 2. Determine the average force, F_{om} , required to override vertical obstacles and subtract from tractive force available at all speeds as indicated on the following sketch.




The above relation is not computed for vertical obstacles determined to be impassable due to obstacle-vehicle geometry interference, insufficient traction or exceeding the driver tolerance to vertical acceleration.

Step 3. Determine the average force, F_o , required to override multiple tree stems up to and including the maximum stem size a vehicle can override, and determine a speed based on the summation of the resisting forces R_s , F_g , and F_o . The procedure is illustrated graphically below.




The computations of F_o and the corresponding speeds are terminated when the maximum stem size a vehicle can override is determined as a result of consideration of traction available, vehicle damage, or driver tolerance to horizontal acceleration.


Step 4. Using the relations of to be overridden, and vertical obstacle height illustrated in the figure, the relation of speed (as controlled by maneuvering) to obstacle height is illustrated in the figure.




Step 5. Using the relations of force, F_r , required to accelerate a vehicle, determine (a) the acceleration area denied, determine (b) the acceleration area denied, and F_r as a function of stem diameter, and F_r as a function of total resisting force, and speed as a function of stem diameter. The procedure is shown in the following figure.



ing the relations of percent area denied, stem diameter and vertical obstacle height to be overridden, develop speed (as controlled by maneuvering), stem diameter, and illustrated in the following sketch.



Step 6. Predict speed S_t on the basis of trade-off between overriding obstacles as illustrated in the following sketch.



Step 7. Predict a speed, S_v , on the basis of the recognition distance maximum distance at which a driver can recognize an obstacle he must avoid the lower of S_t or S_v as the predicted speed for the terrain complex. speed, the fuel consumption relation and the cargo capacity, determine ion rate and the delivery rate.

LINEAR TERRAIN UNITS

Predictions of the time required to cross streams, rivers, etc. are determining if the vehicle can cross the feature unassisted. Determination follows:

For all vehicles. Will bank configuration cause interference?
Are water entry and exit angles acceptable?
Is sufficient traction available?
Is stream velocity acceptable?

For fording vehicles. Is fording depth exceeded?

For deep fording vehicles. Is submersible time exceeded?

If the vehicle can cross unassisted the time required is predicted.

For fording vehicles. Entry and exit distance divided by average speed and exit, plus fording distance divided by fording speed, plus time required for fording kit.

For amphibious vehicles. Entry and exit distance divided by average speed plus swimming distance divided by swimming speed.

If the vehicle cannot cross unassisted the application of engine winching, towing, bridging, etc., is considered and a time penalty determination in hydrologic geometry features is predicted using the same method as to areal terrain units with the following special considerations:



Entry and exit. Full-load fuel consumption rate is used for entry and no-load fuel consumption rate is used for one-half the time.

Fording. Fuel consumption rate is interpolated by ratio of tractive force to tractive force available at fording speed.


Swimming. No-load fuel consumption rate is used.

Penalty time. No-load fuel consumption rate is used for one-half the time and no fuel is considered used during the other half of penalty time.

Delivery rate in hydrologic geometry features is predicted by distance across the feature by the total time to arrive at an average speed at this speed by the cargo capacity of the vehicle.



Speed S_t on the basis of trade-off between overriding and avoided in the following sketch.



Speed, S_v , on the basis of the recognition distance, i.e. the distance which a driver can recognize an obstacle he must avoid; and select the predicted speed for the terrain complex. Using the selected speed and the cargo capacity, determine the fuel consumption rate.

LINEAR TERRAIN UNITS

The time required to cross streams, rivers, etc. are made by first determining the time a vehicle can cross the feature unassisted. Determinations are made as follows:

- For trucks. Will bank configuration cause interference?
- Are water entry and exit angles acceptable?
- Is sufficient traction available?
- Is stream velocity acceptable?

For amphibious vehicles. Is fording depth exceeded?

For diving vehicles. Is submersible time exceeded?

When crossing unassisted the time required is predicted as follows:

For trucks. Entry and exit distance divided by average speed for entry and exit distance divided by fording speed, plus time required to install and remove equipment.

For amphibious vehicles. Entry and exit distance divided by entry and exit speed, plus time required to enter and exit water, divided by swimming speed.

When crossing unassisted the application of engineering effort, such as bridging, etc., is considered and a time penalty determined. Fuel consumption for hydrologic geometry features is predicted using the same techniques applicable to terrain features with the following special considerations:

- a. Full-load fuel consumption rate is used for one-half the time, no-load rate is used for one-half the time.
- b. Fuel consumption rate is interpolated by ratio of tractive force used to full-load rate at fording speed.
- c. No-load fuel consumption rate is used.
- d. No-load fuel consumption rate is used for one-half the penalty time, full-load rate is used during the other half of penalty time.
- e. Fuel consumption for hydrologic geometry features is predicted by dividing the total distance by the total time to arrive at an average speed and multiplying by the cargo capacity of the vehicle.

Literature Cited

1. Rula, A. A., et al., "Evaluation of the Relative Off-Road Mobility of the MBT-70 and M60 Tanks in Selected Terrains in West Germany (U)," (in preparation), U. S. Army Engineer Waterways Experiment Station, CE, Vicksburg, Miss. CONFIDENTIAL.
2. Freitag, D. R., "A Dimensional Analysis of the Performance of Pneumatic Tires on Soft Soils," Technical Report No. 3-688, Aug 1965, U. S. Army Engineer Waterways Experiment Station, CE, Vicksburg, Miss.
3. Shockley, W. G., "Bumps and Grinds: Studies in Body Motion," Miscellaneous Paper No. 4-893, May 1967, U. S. Army Engineer Waterways Experiment Station, CE, Vicksburg, Miss.
4. Blackmon, C. A. and Stoll, J. K., "An Analytical Model for Predicting Cross-Country Vehicle Performance; Appendix B: Vehicle Performance in Lateral and Longitudinal Obstacles (Vegetation); Vol I: Lateral Obstacles," Technical Report No. 3-783, Dec 1968, U. S. Army Engineer Waterways Experiment Station, CE, Vicksburg, Miss.
5. FMC Corporation, Ordnance Engineering Division, San Jose, Calif., "A Computer Analysis of Vehicle Dynamics While Traversing Hard Surface Terrain Profiles," Contract Report 3-155, Feb 1966, U. S. Army Engineer Waterways Experiment Station, CE, Vicksburg, Miss.
6. Blackmon, C. A. and Randolph, D. D., "An Analytical Model for Predicting Cross-Country Vehicle Performance; Appendix B: Vehicle Performance in Lateral and Longitudinal Obstacles (Vegetation); Vol II: Longitudinal Obstacles," Technical Report No. 3-783, Jul 1968, U. S. Army Engineer Waterways Experiment Station, CE, Vicksburg, Miss.
7. U. S. Army Engineer Waterways Experiment Station, CE, "An Analytical Model for Predicting Cross-Country Vehicle Performance; Appendix E: Quantification of the Screening Effects of Vegetation on Driver's Vision and Vehicle Speed," Technical Report No. 3-783 (in preparation), Vicksburg, Miss.
8. _____, "An Analytical Model for Predicting Cross-Country Vehicle Performance; Appendix D: Performance of Amphibious Vehicles in the Water-Land Interface (Hydrologic Geometry)," Technical Report No. 3-783, (in preparation), Vicksburg, Miss.

APPENDIX B: EVALUATION OF DYNAMIC RESPONSE OF M706

Input Parameters Used

| <u>Symbol</u> | <u>Description</u> | <u>Value</u> |
|-------------------|--|--------------|
| n | Number of axles----- | 2 |
| $\bar{x}_{1,2}$ | Height of axle C.G. above ground at full load, in. | 22.60 |
| \bar{x} | Height of body C.G. above ground at full load, in. | 41.87 |
| W | Sprung weight, lb----- | 11,962 |
| LL_1 | Axle to body C.G. distance, in.----- | 57.75 |
| LL_2 | Axle to body C.G. distance, in.----- | 47.25 |
| $L_{1,2,3,4}$ | Suspension to body C.G. distance, in.----- | 16.83 |
| $LL_{1,2,3,4}$ | Suspension to axle C.G. distance, in.----- | 16.83 |
| $L_{1,2,3,4}$ | Tire-to-axle C.G. distance, in.----- | 36.5 |
| W_1 | Unsprung weight of axle, lb----- | 2236 |
| W_2 | Unsprung weight of axle, lb----- | 2052 |
| $S_{1,2}$ | Springs suspension reference distance----- | 17.69 |
| $S_{3,4}$ | Springs suspension reference distance----- | 17.44 |
| $R_{1,2,3,4}$ | Tire reference distance (undeflected wheel radius) ----- | 24.95 |
| \bar{I}_y | Body pitch inertia in.-lb/sec ² ----- | 129,888 |
| \bar{I}_z | Body roll inertia in.-lb/sec ² ----- | -- |
| $\bar{I}_{1,2,z}$ | Axle roll inertia in.-lb/sec ² ----- | -- |

| Symbol | Description | Value |
|-----------------|--|------------|
| D | Driver's position to body C.G. (long. distance), in.----- | 60.75 |
| D ₂ | Driver's position to body C.G. (vert. distance), in.----- | 12.0 |
| D ₃ | Driver's position to body C.G. (lat. distance), in.----- | 12.0 |
| k _j | Spring deflection versus suspension spring force----- | Fig. A2 |
| c _j | Suspension deflection velocity versus suspension force----- | Fig. A3 |
| KK _j | Tire spring rate of segmented wheel - 12 seg @ 10°, lb/in. ----- | 980 lb/in. |
| cc _j | Tire damping rate lb-sec/in.----- | 0 |

NOTE: See fig. B1 for identification sketch.




Fig. B1. Schematic drawing of input data for the M706 dynamic response mathematical model





Fig. B2. Spring deflection versus suspension force
for the M706




Fig. B3. Shock absorber velocity versus suspension force for the M706

APPENDIX C: EFFECT OF SOIL STRENGTH ON VEHICLE PERFORMANCE

1. At the conclusion of the wet-season analysis during the first phase of the study reported herein (see paragraph 3 of main text), additional general analyses were made of the effects of soil strength on vehicle performance, in an attempt to provide a more comprehensive treatment of this subject than was possible in the limited study. The performances of only four vehicles--M656, M54A2, M520, and M548--were analyzed. Speed, delivery rate, one-pass vehicle cone index (VCI_1), and overall trafficability in the United States and Thailand were investigated and are discussed in the following paragraphs.

Maximum speed performance

2. To give an indication of the relative effects of soil strength on speed performance of the four vehicles, maximum speeds were determined over a range of soil strengths from the minimum required to complete one pass a cone index of 300 for a clay of uniform strength and for a pavement. The maximum speed values were determined according to procedures described in WES Technical Report No. 3-783, "An Analytical Model for Predicting Cross-Country Vehicle Performance," now in preparation. These data are plotted in fig. C1. The value of the abscissa of each curve at $Y = 0$ in fig. C1 is the minimum soil strength required to permit one very slow pass of the vehicle (VCI_1). The computed VCI_1 values for the four vehicles are:

| <u>Vehicle</u> | <u>VCI_1</u> |
|----------------|---------------------------|
| M656 | 23 |
| M54A2 | 27 |
| M520 | 30 |
| M548 | 25 |

3. The VCI_1 determination was made for the M548 by using the WES mobility index equation for tracked vehicles.* Once the mobility index was computed, the 50-pass vehicle cone index (VCI_{50}) was determined from data shown in table C1. The VCI_1 for the M548 is approximately 50 percent of the VCI_{50} .

*Knight, S. J., "Trafficability of Soils, A Summary of Trafficability Studies Through 1955," Technical Memorandum No. 3-240, 14th Supplement, Dec 1956, U. S. Army Engineer Waterways Experiment Station, CE, Vicksburg, Miss.




Fig. C1. Comparative speed performance on smooth, level clay soil of uniform strength

Delivery rate

4. A comparison of the performance of the four vehicles on the basis of delivery rate in ton-miles/hr as a function of soil strength is illustrated in fig. C2. (Delivery rate was obtained by multiplying speed and cargo capacity.) The M520 performance is much closer to the performance of the other wheeled vehicles (M656 and M54A2) than to that of the M548, as opposed to the speed performance shown in fig. C1, because the rate cargo capacity of the M520 is 8 tons, that of the M548 is 6 tons, and those of the M656 and the M54A2 are 5 tons each. Note that the delivery rates shown in fig. C2 are considerably higher than those listed in paragraph 91 of the main text, which are delivery rates established by considering the combined effects of all terrain factors. For example, the average delivery rate for the M520 between 60 and 40 cone index determined from fig. C2 is 90 ton-miles/hr, compared to 38.4 listed in paragraph 91 for the wet-season soil strength combination of 60 or 40 RCI.

Trafficable areas in the United States and Thailand

5. The performance data illustrated in figs. C1 and C2 should be interpreted in terms of mission requirements or, in the absence of this type of information, knowledge of the frequency of occurrence of various soil strengths within the operational area of interest. The type of information of value in making basic decisions in all phases pertinent to ground vehicle mobility is shown in fig. C3*. When something is known about the frequency of occurrence and topographic position of soil strengths in an area, the importance of this factor can be evaluated in relation to others that are present; for example, in selecting vehicles to meet operational mission requirements.

6. Comparative data taken from fig. C3 and based on the individual VCI_1 values are summarized below.

| <u>Vehicle</u> | <u>Percentage of Areas Trafficable</u> | | | |
|----------------|--|--------------------------------|-----------------------------|--------------------------------|
| | <u>Thailand.</u> | | <u>U. S.</u> | |
| | <u>Wet</u> <u>Season</u> | <u>High</u> <u>Moisture</u> | <u>Wet</u> <u>Season</u> | <u>High</u> <u>Moisture</u> |
| M656 | 96.0 | 93.0 | 99.0 | 92.0 |
| M54A2 | 95.0 | 90.0 | 98.7 | 87.5 |
| M520 | 94.5 | 87.5 | 97.5 | 84.8 |
| M548 | 95.5 | 91.5 | 98.8 | 89.7 |





Fig. C2. Comparative performance on smooth, level, clay soil of uniform strength



NOTE: Wet-season condition is for high- and low-topography areas; high-moisture condition is for low-topography areas only.

Fig. C3. Cumulative frequency of rating cone indexes in United States and Thailand (Fine-grained soils, 6- to 12-in. layer)

— The wet-season category is based on high and low topographic positions, while the high-moisture category is only for low topographic positions. Because the data in fig. C3 are biased toward wetter-than-average conditions, estimates of percentages of trafficable areas made from the curves will be smaller than actual, i.e. on the conservative side. Environments having soil strengths less than 25 RCI, such as marshes and swamps, are particularly troublesome to ground vehicles. Consequently, special vehicle configurations, such as the marginal terrain vehicle, have been built to provide some degree of mobility in these environments. Such environments are beyond the operational context intended for conventional cargo vehicles.

Table C1.

MOBILITY INDEX VS VEHICLE CONE INDEX

| <u>MI</u> | <u>VCI</u> | <u>MI</u> | <u>VCI</u> | <u>MI</u> | <u>VCI</u> | <u>MI</u> | <u>VCI</u> | <u>MI</u> | <u>VCI</u> |
|-----------|------------|-----------|------------|-----------|------------|-----------|------------|-----------|------------|
| 0 | 3.0 | 31 | 39.2 | 67 | 55.6 | 103 | 72.0 | 139 | 88.3 |
| 0.25 | 5.5 | 32 | 39.7 | 68 | 56.1 | 104 | 72.4 | 140 | 88.8 |
| 0.50 | 7.0 | 33 | 40.1 | 69 | 56.5 | 105 | 72.9 | 141 | 89.2 |
| 0.75 | 8.3 | 34 | 40.6 | 70 | 57.0 | 106 | 73.3 | 142 | 89.7 |
| 1.00 | 9.0 | 35 | 41.0 | 71 | 57.4 | 107 | 73.8 | 143 | 90.1 |
| 1.50 | 10.8 | 36 | 41.5 | 72 | 57.9 | 108 | 74.2 | 144 | 90.6 |
| 2.00 | 12.5 | 37 | 42.0 | 73 | 58.3 | 109 | 74.7 | 145 | 91.0 |
| 2.50 | 13.8 | 38 | 42.4 | 74 | 58.8 | 110 | 75.1 | 146 | 91.5 |
| 3 | 15.1 | 39 | 42.9 | 75 | 59.2 | 111 | 75.6 | 147 | 91.9 |
| 4 | 17.5 | 40* | 43.4* | 76 | 59.7 | 112 | 76.0 | 148 | 92.4 |
| 5 | 19.7 | 41 | 43.8 | 77 | 60.2 | 113 | 76.5 | 149 | 92.8 |
| 6 | 21.5 | 42 | 44.3 | 78 | 60.6 | 114 | 77.0 | 150 | 93.3 |
| 7 | 23.0 | 43 | 44.7 | 79 | 61.1 | 115 | 77.4 | 151 | 93.8 |
| 8 | 24.2 | 44 | 45.2 | 80 | 61.5 | 116 | 77.9 | 152 | 94.2 |
| 9 | 25.3 | 45 | 45.6 | 81 | 62.0 | 117 | 78.3 | 153 | 94.7 |
| 10 | 26.4 | 46 | 46.1 | 82 | 62.4 | 118 | 78.8 | 154 | 95.1 |
| 11 | 27.3 | 47 | 46.5 | 83 | 62.9 | 119 | 79.2 | 155 | 95.6 |
| 12 | 28.1 | 48 | 47.0 | 84 | 63.3 | 120 | 79.7 | 156 | 96.0 |
| 13 | 28.9 | 49 | 47.4 | 85 | 63.8 | 121 | 80.1 | 157 | 96.5 |
| 14 | 29.6 | 50 | 47.9 | 86 | 64.2 | 122 | 80.6 | 158 | 96.9 |
| 15 | 30.4 | 51 | 48.4 | 87 | 64.7 | 123 | 81.0 | 159 | 97.4 |
| 16 | 31.0 | 52 | 48.8 | 88 | 65.2 | 124 | 81.5 | 160 | 97.8 |
| 17 | 31.7 | 53 | 49.3 | 89 | 65.6 | 125 | 82.0 | 161 | 98.3 |
| 18 | 32.3 | 54 | 49.7 | 90 | 66.1 | 126 | 82.4 | 162 | 98.7 |
| 19 | 32.9 | 55 | 50.2 | 91 | 66.5 | 127 | 82.8 | 163 | 99.2 |
| 20 | 33.5 | 56 | 50.6 | 92 | 67.0 | 128 | 83.3 | 164 | 99.6 |
| 21 | 34.1 | 57 | 51.1 | 93 | 67.4 | 129 | 83.8 | 165 | 100.1 |
| 22 | 34.6 | 58 | 51.5 | 94 | 67.9 | 130 | 84.2 | 166 | 100.6 |
| 23 | 35.2 | 59 | 52.0 | 95 | 68.3 | 131 | 84.7 | 167 | 101.0 |
| 24 | 35.8 | 60 | 52.4 | 96 | 68.8 | 132 | 85.1 | 168 | 101.5 |
| 25 | 36.3 | 61 | 52.9 | 97 | 69.2 | 133 | 85.6 | 169 | 101.9 |
| 26 | 36.8 | 62 | 53.3 | 98 | 69.7 | 134 | 86.0 | 170 | 102.4 |
| 27 | 37.3 | 63 | 53.8 | 99 | 70.1 | 135 | 86.5 | 171 | 102.8 |
| 28 | 37.8 | 64 | 54.2 | 100 | 70.6 | 136 | 86.9 | 172 | 103.3 |
| 29 | 38.3 | 65 | 54.7 | 101 | 71.1 | 137 | 87.4 | 173 | 103.7 |
| 30 | 38.7 | 66 | 55.2 | 102 | 71.5 | 138 | 87.8 | 174 | 104.2 |

* For MI above approximately 40, VCI obtained from equation:

$$VCI = 25.2 + 0.454 \times MI$$

Unclassified

Security Classification

DOCUMENT CONTROL DATA - R & D

(Security classification of title, body of abstract and indexing annotation must be entered when the overall report is classified)

| | | | |
|--|--|--|-----------------|
| 1. ORIGINATING ACTIVITY (Corporate author) | | 1a. REPORT SECURITY CLASSIFICATION | |
| U. S. Army Engineer Waterways Experiment Station Vicksburg, Mississippi | | Unclassified | |
| 2. REPORT TITLE | | 1b. GROUP | |
| RELATIVE OFF-ROAD MOBILITY PERFORMANCE OF SIX WHEELED AND FOUR TRACKED VEHICLES IN SELECTED TERRAIN | | | |
| 3. DESCRIPTIVE NOTES (Type of report and inclusive dates) | | | |
| Final Report | | | |
| 4. AUTHOR(S) (First name, middle initial, last name) | | | |
| Jack K. Stoll Donald D. Randolph Adam A. Rula | | | |
| 5. REPORT DATE | | 7a. TOTAL NO. OF PAGES | 7b. NO. OF REFS |
| March 1970 | | 156 | 15 |
| 6a. CONTRACT OR GRANT NO. | | 6b. ORIGINATOR'S REPORT NUMBER(S) | |
| a. PROJECT NO. | | Technical Report M-70-4 | |
| c. | | 8a. OTHER REPORT NO(S) (Any other numbers that may be assigned this report) | |
| d. | | | |
| 10. DISTRIBUTION STATEMENT | | | |
| | | | |
| 11. SUPPLEMENTARY NOTES | | 12. SPONSORING MILITARY ACTIVITY | |
| | | U. S. Army Materiel Command Washington, D. C. | |
| 13. ABSTRACT | | | |
| <p>The U. S. Army Engineer Waterways Experiment Station analytical model for predicting off-road ground mobility was used to evaluate the performance of six wheeled vehicles (M556, M54A2, M520, M37B1, M561, and M706) and four tracked vehicles (M548, M113A1, M116, and M571) over a selected traverse in Thailand. Maps were prepared to exhibit the terrain in terms of surface composition (soil consistency), surface geometry (slopes, rice-field dikes, etc.), vegetation, and hydrologic geometry (rivers and streams). The performance of each vehicle was evaluated in terms of average speed over the traverse and the center line, average fuel consumed over the traverse, and center-line cargo delivery rate. The vehicles were "run" over the traverse under dry-season conditions (60 or 40 rating cone index) and wet-season conditions (60 or 35 rating cone index). Four of the vehicles (M556, M54A2, M520, and M548) were tested also under wet-season conditions of 60 or 40 rating cone index. Wet-season conditions usually reduced vehicle performance. However, soil strength was not as significant as other terrain factors in evaluating the vehicles over the selected traverse because the soil strengths used were higher than the vehicle cone indexes of all the vehicles; so no vehicles were immobilized because of soft soils. No one vehicle provided optimum mobility for all the terrain conditions encountered on the traverse over which predictions were made. Further, neither wheels nor tracks appeared to consistently give better performance. The M113A1 had the highest average traverse and center-line speeds in the dry season, and the M571 had the highest speeds in the wet. The M54A2 had the lowest traverse and center-line speeds in both seasons. The M571 consumed less fuel on the average in the dry season, and the M561 and M571</p> | | | |

(continued on back)

DD FORM 1473

REPLACES DD FORM 1473, 1 JAN 64, WHICH IS
OBSOLETE FOR ARMY USE.

Unclassified

Security Classification

~~Unclassified~~
~~Security Classification~~

[illegible]

~~Unclassified~~
~~Security Classification~~